### **Higher National Diploma in Information Technology**


Second Year, First Semester Examination - 2017

# HNDIT 2321/IT3201: Advanced Database Management System Marking Schemes

### **Question 1**

- I. The three-tier architecture is commonly used to implement a database driven web application.
  - a. Draw a diagram to illustrate this architecture.

(4 marks)



b. Describe the role of each tier.

(3 marks)

**External level:** The users' view of the database. This level describes that part of the database that is relevant to each user.


**Conceptual level**: The community view of the database. This level describes what data is stored in the database and the relationships among the data.

**Internal level:** The physical representation of the database on the computer. This level describes how the data is stored in the database.

II. Database development life cycle contains following eleven main stages.


Name A to M in the above Diagram from the given list.

(13 Marks)



## Question 2

I. (12 Marks)



## **Question 3**

I. (8 Marks)

**SELECT** – select records from a table

INSERT - insert new records

**UPDATE** – update/Modify existing records

**DELETE** – delete existing records

```
SELECT p.pname FROM Parts AS p
          WHERE EXISTS (
          SELECT * FROM Catalog AS c
          WHERE c.pid = p.pid)
ii)
      SELECT DISTINCT P.pname
             FROM Parts P, Catalog C
             WHERE P.pid = C.pid;
iii)
      SELECT DISTINCT c1.sid AS SID
           FROM Parts AS p1, Catalog AS c1
           WHERE p1.pid = c1.pid AND p1.color = 'green')
           INTERSECT (
           SELECT DISTINCT c2.sid AS SID
           FROM Parts AS p2, Catalog AS c2
           WHERE p2.pid = c2.pid AND p2.color = 'red')
           SELECT DISTINCT c.sid
           FROM Catalog c, Parts p
           WHERE c.pid = p.pid and p.color = 'red'
           INTERSECT
           SELECT DISTINCT c.sid
           FROM Catalog c, Parts p
           WHERE c.pid = p.pid and p.color = 'green'
iv)
      SELECT s.sid, s.sname
          FROM Suppliers AS s, Catalog AS c, Parts AS p
          WHERE s.sid = c.sid
          AND p.pid = c.pid AND p.color = 'red'
          GROUP BY s.sid, s.sname
          HAVING COUNT(*) = (SELECT COUNT(*) FROM Parts AS p1
                                                                     (12 Marks)
          WHERE p1.color='red')
```

#### **Question 4**

I.

i) (3 marks)

The table violates 2nd Normal Form (1 mark) because there are two partial dependencies: StudentID → StudentName (1 mark) and ModuleID → ModuleName (1 mark)

ii) Normalize the table up to the normal form identified in question i). (5 marks)

(1.5)

Student(StudentID, StudentName)

Module(ModuleID, ModuleName) (1.5)

Results(StudentID\*, ModuleID\*, Grade) (2)

II.

## Query 1

(12 marks)

Mname	budget
Ashforce	NULL
Bass	675.00
Mission	250.00
Vallance	348.00

(4 row(s) affected)

#### Query 2

Totalk	oudget	Mname	
	NULL	Ashfo	 rce
, 2 m2 3	150.00		
5.75		Missi Valla	

#### Query 3

EmployeeID	EmployeeID	membership
organismos de la companione de la compa		
<u>ಒ</u>	<b>5</b> 3	DGSS

### **Question 5**

- (i) A *transaction* is a *unit* of program execution that accesses and possibly updates various data items. (2 marks)
- (ii) To ensure integrity of data, the database system must maintain:

<u>Atomicity -</u> Either all operations of the transaction are properly reflected in the database.

<u>Consistency -</u> Execution of a transaction in isolation preserves the consistency of the database.

<u>Isolation</u> - Although multiple transactions may execute concurrently, each transaction must be unaware of other concurrently executing transactions.

<u>Durability</u> - After a transaction completes successfully, the changes it has made to the database persist, even if there are system failures. (8 marks)

(iii)

Active, the initial state; the transaction stays in this state while it is executing Partially committed, after the final statement has been executed.

Failed, after the discovery that normal execution can no longer proceed.

**Aborted,** after the transaction has been rolled back and the database restored to its state prior to the start of the transaction. Restart the transaction – only if no internal logical error or kill the transaction

Committed, after successful completion.

(10 marks)

#### **Question 6**

I.

The DOM defines a standard for accessing and manipulating documents:

"Document Object Model (DOM) is a platform and language-neutral interface that allows programs and scripts to dynamically access and update the content, structure, and style of a document."

The XML DOM defines a standard way for accessing and manipulating XML documents. It presents an XML document as a tree-structure.

(2 marks)

- II. An XML document cannot be valid until it is well-formed. Well-formed XML is syntactically correct (it can be parsed), while valid XML is semantically correct (it can be matched to a known vocabulary and grammar (4 marks)
- III. DTD defines the structure of the content of an XML document, and hence allows storing data in a consistent format. The DTD is a set of rules that defines an element, element attribute, attribute values, and the relationship between elements in the document. When an XML document is processed, it is compared to its associated DTD to ensure it is structured correctly and all tags are used correctly. Two types: Internal DTD External DTD (4 marks)
   IV. (10 marks)

XML Tree Structure Root element: <bookstore> Child Element: Attribute: Attribute: "lang" <book> 'category' Element: Element: <author> <year> Siblings Text Text: veryday Italian Giada De Laurentiis