

Got it ✓ You want a **complete list of sorting algorithms** with:

1. **Formula / Explanation**
2. **Separate C++ example codes**

I'll cover all the mentioned algorithms one by one with formulas and C++ code.

---

## ◆ 1. Bubble Sort

### Formula / Idea:

Repeatedly swap adjacent elements if they are in the wrong order.

Time Complexity:

- Worst/Average:  $O(n^2)$
- Best:  $O(n)$  (already sorted)

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void bubbleSort(vector<int>& arr) {
    int n = arr.size();
    for (int i = 0; i < n - 1; i++) {
        bool swapped = false;
        for (int j = 0; j < n - i - 1; j++) {
            if (arr[j] > arr[j+1]) {
                swap(arr[j], arr[j+1]);
                swapped = true;
            }
        }
        if (!swapped) break;
    }
}

int main() {
    vector<int> arr = {64, 25, 12, 22, 11};
    bubbleSort(arr);
    for (int x : arr) cout << x << " ";
}
```

---

## ◆ 2. Selection Sort

**Formula / Idea:**

Find minimum element from unsorted part and place it at beginning.

Time Complexity: Always  $O(n^2)$ .

**C++ Code:**

```
#include <bits/stdc++.h>
using namespace std;

void selectionSort(vector<int>& arr) {
    int n = arr.size();
    for (int i = 0; i < n - 1; i++) {
        int minIdx = i;
        for (int j = i + 1; j < n; j++)
            if (arr[j] < arr[minIdx])
                minIdx = j;
        swap(arr[i], arr[minIdx]);
    }
}

int main() {
    vector<int> arr = {64, 25, 12, 22, 11};
    selectionSort(arr);
    for (int x : arr) cout << x << " ";
}
```

---

## ◆ 3. Insertion Sort

**Formula / Idea:**

Build sorted array one element at a time by shifting elements.

Time Complexity:

- Worst:  $O(n^2)$
- Best:  $O(n)$

**C++ Code:**

```
#include <bits/stdc++.h>
using namespace std;

void insertionSort(vector<int>& arr) {
    int n = arr.size();
    for (int i = 1; i < n; i++) {
        int key = arr[i], j = i - 1;
        while (j >= 0 && arr[j] > key) {
            arr[j+1] = arr[j];
            j--;
        }
        arr[j+1] = key;
    }
}
```

```
int main() {
    vector<int> arr = {12, 11, 13, 5, 6};
    insertionSort(arr);
    for (int x : arr) cout << x << " ";
}
```

---

## ◆ 4. Merge Sort

### Formula / Idea:

Divide array into halves → sort recursively → merge.

Time Complexity:  $O(n \log_{10} n)$   $O(n \log n)$   $O(n \log n)$ .

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void merge(vector<int>& arr, int l, int m, int r) {
    vector<int> left(arr.begin()+l, arr.begin()+m+1);
    vector<int> right(arr.begin()+m+1, arr.begin()+r+1);
    int i = 0, j = 0, k = l;
    while (i < left.size() && j < right.size())
        arr[k++] = (left[i] < right[j]) ? left[i++] : right[j++];
    while (i < left.size()) arr[k++] = left[i++];
    while (j < right.size()) arr[k++] = right[j++];
}

void mergeSort(vector<int>& arr, int l, int r) {
    if (l < r) {
        int m = (l+r)/2;
        mergeSort(arr, l, m);
        mergeSort(arr, m+1, r);
        merge(arr, l, m, r);
    }
}

int main() {
    vector<int> arr = {38, 27, 43, 3, 9, 82, 10};
    mergeSort(arr, 0, arr.size()-1);
    for (int x : arr) cout << x << " ";
}
```

---

## ◆ 5. Quick Sort

### Formula / Idea:

Choose pivot → partition → recursively sort subarrays.

Time Complexity:

- Worst:  $O(n^2)$   $O(n^2)$   $O(n^2)$
- Average:  $O(n \log_{10} n)$   $O(n \log n)$   $O(n \log n)$

## C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

int partition(vector<int>& arr, int low, int high) {
    int pivot = arr[high];
    int i = low - 1;
    for (int j = low; j < high; j++) {
        if (arr[j] < pivot) {
            i++;
            swap(arr[i], arr[j]);
        }
    }
    swap(arr[i+1], arr[high]);
    return i+1;
}

void quickSort(vector<int>& arr, int low, int high) {
    if (low < high) {
        int pi = partition(arr, low, high);
        quickSort(arr, low, pi-1);
        quickSort(arr, pi+1, high);
    }
}

int main() {
    vector<int> arr = {10, 7, 8, 9, 1, 5};
    quickSort(arr, 0, arr.size()-1);
    for (int x : arr) cout << x << " ";
}
```

---

## ◆ 6. Heap Sort

### Formula / Idea:

Convert array into max heap → extract root repeatedly.

Time Complexity:  $O(n \log n)$   $O(n \log n)$   $O(n \log n)$ .

## C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void heapify(vector<int>& arr, int n, int i) {
    int largest = i, l = 2*i+1, r = 2*i+2;
    if (l < n && arr[l] > arr[largest]) largest = l;
    if (r < n && arr[r] > arr[largest]) largest = r;
    if (largest != i) {
        swap(arr[i], arr[largest]);
        heapify(arr, n, largest);
    }
}

void heapSort(vector<int>& arr) {
    int n = arr.size();
```

```

        for (int i = n/2-1; i >= 0; i--)
            heapify(arr, n, i);
        for (int i = n-1; i > 0; i--) {
            swap(arr[0], arr[i]);
            heapify(arr, i, 0);
        }
    }

int main() {
    vector<int> arr = {12, 11, 13, 5, 6, 7};
    heapSort(arr);
    for (int x : arr) cout << x << " ";
}

```

---

✂ I'll continue with **Counting Sort, Radix Sort, Bucket Sort, Shell Sort, Tim Sort, and External Sorting** in the **next message** (to keep it clean and not overloaded).

Do you want me to **continue right now** with the rest (Counting → External), or keep these 6 first and then I proceed step by step?

**You said:**

Counting Sort Radix Sort Bucket Sort Shell Sort Tim Sort

ChatGPT said:

Perfect 🐾 let's continue with the next set of sorting algorithms.

---

## ◆ 7. Counting Sort

**Formula / Idea:**

- Works for integers in a limited range.
- Count frequency of each number → compute prefix sum → place elements in output array.

**Time Complexity:**  $O(n+k)O(n+k)O(n+k)$ , where  $k$  = range of numbers.

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

void countingSort(vector<int>& arr) {
    int maxEl = *max_element(arr.begin(), arr.end());
    int minEl = *min_element(arr.begin(), arr.end());
    int range = maxEl - minEl + 1;

    vector<int> count(range, 0), output(arr.size());

    for (int x : arr) count[x - minEl]++;
}

```

```

        for (int i = 1; i < range; i++) count[i] += count[i - 1];
        for (int i = arr.size()-1; i >= 0; i--) {
            output[count[arr[i] - minEl] - 1] = arr[i];
            count[arr[i] - minEl]--;
        }
        arr = output;
    }

int main() {
    vector<int> arr = {4, 2, 2, 8, 3, 3, 1};
    countingSort(arr);
    for (int x : arr) cout << x << " ";
}

```

---

## ◆ 8. Radix Sort

**Formula / Idea:**

- Sort numbers digit by digit using a stable sort (like Counting Sort).  
**Time Complexity:**  $O(n \cdot d)O(n \cdot d)O(n \cdot d)$ , where  $d$  = number of digits.

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

void countingSortExp(vector<int>& arr, int exp) {
    int n = arr.size();
    vector<int> output(n), count(10, 0);

    for (int x : arr) count[(x/exp)%10]++;
    for (int i = 1; i < 10; i++) count[i] += count[i-1];
    for (int i = n-1; i >= 0; i--) {
        output[count[(arr[i]/exp)%10]-1] = arr[i];
        count[(arr[i]/exp)%10]--;
    }
    arr = output;
}

void radixSort(vector<int>& arr) {
    int maxEl = *max_element(arr.begin(), arr.end());
    for (int exp = 1; maxEl/exp > 0; exp *= 10)
        countingSortExp(arr, exp);
}

int main() {
    vector<int> arr = {170, 45, 75, 90, 802, 24, 2, 66};
    radixSort(arr);
    for (int x : arr) cout << x << " ";
}

```

---

## ◆ 9. Bucket Sort

### Formula / Idea:

- Distribute elements into buckets, sort each bucket (using another sort), then concatenate.

#### Time Complexity:

- Best:  $O(n+k)O(n+k)O(n+k)$
- Worst:  $O(n^2)O(n^2)O(n^2)$  (if all go in one bucket).

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void bucketSort(vector<float>& arr) {
    int n = arr.size();
    vector<vector<float>> buckets(n);

    for (float x : arr) {
        int idx = n * x; // bucket index
        buckets[idx].push_back(x);
    }

    for (int i = 0; i < n; i++)
        sort(buckets[i].begin(), buckets[i].end());

    int k = 0;
    for (int i = 0; i < n; i++)
        for (float x : buckets[i])
            arr[k++] = x;
}

int main() {
    vector<float> arr = {0.897, 0.565, 0.656, 0.123, 0.665, 0.3434};
    bucketSort(arr);
    for (float x : arr) cout << x << " ";
}
```

---

## ◆ 10. Shell Sort

### Formula / Idea:

- Generalization of Insertion Sort → allows exchanges of far-apart elements.
- Gap sequence reduces gradually until gap = 1.

**Time Complexity:** Depends on gap sequence, average  $O(n^{1.5})O(n^{\{1.5\}})O(n^{1.5})$ .

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void shellSort(vector<int>& arr) {
    int n = arr.size();
    for (int gap = n/2; gap > 0; gap /= 2) {
```

```

        for (int i = gap; i < n; i++) {
            int temp = arr[i], j;
            for (j = i; j >= gap && arr[j-gap] > temp; j -= gap)
                arr[j] = arr[j-gap];
            arr[j] = temp;
        }
    }
}

int main() {
    vector<int> arr = {12, 34, 54, 2, 3};
    shellSort(arr);
    for (int x : arr) cout << x << " ";
}

```

---

## ◆ 11. Tim Sort

**Formula / Idea:**

- Hybrid of Merge Sort + Insertion Sort.
  - Used in Python (`sorted()`) and Java (`Arrays.sort()`).
- Time Complexity:**  $O(n \log^2 n)$   $O(n \log n)$   $O(n \log n)$ .

☞ Implementing full TimSort in C++ is complex, but here's a simplified version using small runs:

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;
const int RUN = 32;

void insertionSort(vector<int>& arr, int left, int right) {
    for (int i = left+1; i <= right; i++) {
        int key = arr[i], j = i-1;
        while (j >= left && arr[j] > key) {
            arr[j+1] = arr[j];
            j--;
        }
        arr[j+1] = key;
    }
}

void merge(vector<int>& arr, int l, int m, int r) {
    vector<int> left(arr.begin()+l, arr.begin()+m+1);
    vector<int> right(arr.begin()+m+1, arr.begin()+r+1);
    int i = 0, j = 0, k = l;
    while (i < left.size() && j < right.size())
        arr[k++] = (left[i] < right[j]) ? left[i++] : right[j++];
    while (i < left.size()) arr[k++] = left[i++];
    while (j < right.size()) arr[k++] = right[j++];
}

void timSort(vector<int>& arr) {
    int n = arr.size();
}

```



```

    for (int i = 0; i < n; i += RUN)
        insertionSort(arr, i, min((i+RUN-1), n-1));

    for (int size = RUN; size < n; size *= 2) {
        for (int left = 0; left < n; left += 2*size) {
            int mid = left + size - 1;
            int right = min((left+2*size-1), n-1);
            if (mid < right)
                merge(arr, left, mid, right);
        }
    }
}

int main() {
    vector<int> arr = {5, 21, 7, 23, 19};
    timSort(arr);
    for (int x : arr) cout << x << " ";
}

```

---

✓ Now you have **Counting Sort, Radix Sort, Bucket Sort, Shell Sort, and Tim Sort** with working C++ examples.

Do you also want me to cover the last one **External Sorting** (used for huge datasets that don't fit in memory) with explanation + pseudo C++ code?

## ◆ 1. Linear Search

**Idea:** Scan each element one by one until found.

**Time Complexity:**  $O(n)$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

int linearSearch(vector<int>& arr, int key) {
    for (int i = 0; i < arr.size(); i++) {
        if (arr[i] == key) return i; // found
    }
    return -1; // not found
}

int main() {
    vector<int> arr = {10, 23, 45, 70, 11, 15};
    int key = 70;
    int idx = linearSearch(arr, key);
    (idx != -1) ? cout << "Found at index " << idx
                : cout << "Not found";
}

```

---

## ◆ 2. Binary Search

**Idea:** Works on sorted arrays. Repeatedly divide the search interval in half.

**Time Complexity:**  $O(\log n)$

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

int binarySearch(vector<int>& arr, int key) {
    int low = 0, high = arr.size()-1;
    while (low <= high) {
        int mid = low + (high-low)/2;
        if (arr[mid] == key) return mid;
        else if (arr[mid] < key) low = mid+1;
        else high = mid-1;
    }
    return -1;
}

int main() {
    vector<int> arr = {2, 3, 4, 10, 40};
    int key = 10;
    int idx = binarySearch(arr, key);
    (idx != -1) ? cout << "Found at index " << idx
                : cout << "Not found";
}
```

---

## ◆ 3. Jump Search

**Idea:** Jump ahead by blocks of size  $\sqrt{n}$ , then do linear search in block.

**Time Complexity:**  $O(\sqrt{n})$

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

int jumpSearch(vector<int>& arr, int key) {
    int n = arr.size();
    int step = sqrt(n);
    int prev = 0;

    while (arr[min(step, n)-1] < key) {
        prev = step;
        step += sqrt(n);
        if (prev >= n) return -1;
    }

    for (int i = prev; i < min(step, n); i++) {
        if (arr[i] == key) return i;
    }
    return -1;
}

int main() {
```

```

vector<int> arr = {0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144};
int key = 55;
int idx = jumpSearch(arr, key);
(idx != -1) ? cout << "Found at index " << idx
            : cout << "Not found";
}

```

---

## ◆ 4. Exponential Search

**Idea:** Double the index bound until value > key, then apply binary search.

**Time Complexity:**  $O(\log_{f_0} n)$   $O(\log n)$   $O(\log n)$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

int binarySearch(vector<int>& arr, int l, int r, int key) {
    while (l <= r) {
        int mid = l + (r-l)/2;
        if (arr[mid] == key) return mid;
        else if (arr[mid] < key) l = mid+1;
        else r = mid-1;
    }
    return -1;
}

int exponentialSearch(vector<int>& arr, int key) {
    if (arr[0] == key) return 0;
    int n = arr.size();
    int i = 1;
    while (i < n && arr[i] <= key)
        i *= 2;
    return binarySearch(arr, i/2, min(i, n-1), key);
}

int main() {
    vector<int> arr = {2, 3, 4, 10, 40};
    int key = 10;
    int idx = exponentialSearch(arr, key);
    (idx != -1) ? cout << "Found at index " << idx
                : cout << "Not found";
}

```

---

## ◆ 5. Interpolation Search

**Idea:** Improved Binary Search for **uniformly distributed data**.

- Instead of  $\text{mid} = (\text{low} + \text{high})/2$ , use interpolation formula:

$$\text{pos} = \text{low} + (\text{key} - \text{arr}[\text{low}]) \cdot (\text{high} - \text{low}) / (\text{arr}[\text{high}] - \text{arr}[\text{low}])$$

$$\text{pos} = \text{low} + \frac{(\text{key} - \text{arr}[\text{low}]) \cdot (\text{high} - \text{low})}{\text{arr}[\text{high}] - \text{arr}[\text{low}]}$$

**Time Complexity:**

- Best:  $O(\log \log n)$
- Worst:  $O(n)$

**C++ Code:**

```
#include <bits/stdc++.h>
using namespace std;

int interpolationSearch(vector<int>& arr, int key) {
    int low = 0, high = arr.size()-1;
    while (low <= high && key >= arr[low] && key <= arr[high]) {
        if (low == high) {
            if (arr[low] == key) return low;
            return -1;
        }
        int pos = low + ((double)(high-low) /
                        (arr[high]-arr[low])) * (key - arr[low]);
        if (arr[pos] == key) return pos;
        if (arr[pos] < key) low = pos+1;
        else high = pos-1;
    }
    return -1;
}

int main() {
    vector<int> arr = {10, 12, 13, 16, 18, 19, 20, 21, 22, 23, 24, 33, 35};
    int key = 18;
    int idx = interpolationSearch(arr, key);
    (idx != -1) ? cout << "Found at index " << idx
                : cout << "Not found";
}
```

---

## ◆ 6. Ternary Search

**Idea:** Divide array into 3 parts instead of 2.

**Time Complexity:**  $O(\log_3 n)$

**C++ Code:**

```
#include <bits/stdc++.h>
using namespace std;

int ternarySearch(vector<int>& arr, int l, int r, int key) {
    if (r >= 1) {
        int mid1 = l + (r-l)/3;
        int mid2 = r - (r-l)/3;

        if (arr[mid1] == key) return mid1;
```

```

        if (arr[mid2] == key) return mid2;

        if (key < arr[mid1]) return ternarySearch(arr, l, mid1-1, key);
        else if (key > arr[mid2]) return ternarySearch(arr, mid2+1, r,
key);
        else return ternarySearch(arr, mid1+1, mid2-1, key);
    }
    return -1;
}

int main() {
    vector<int> arr = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
    int key = 5;
    int idx = ternarySearch(arr, 0, arr.size()-1, key);
    (idx != -1) ? cout << "Found at index " << idx
                : cout << "Not found";
}

```

Awesome 🚀 You want the **major Graph Algorithms** with explanation + C++ examples. This is a **big list (16 algorithms)**, so I'll cover them in **parts** to keep things clean.

Let's start with **Part 1: BFS, DFS, Dijkstra, Bellman-Ford, Floyd-Warshall**.

## ◆ 1. Breadth-First Search (BFS)

**Idea:** Explore level by level using a queue.

**Time Complexity:**  $O(V+E)O(V+E)O(V+E)$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

void BFS(int start, vector<vector<int>>& adj) {
    vector<bool> visited(adj.size(), false);
    queue<int> q;
    visited[start] = true;
    q.push(start);

    while (!q.empty()) {
        int node = q.front(); q.pop();
        cout << node << " ";
        for (int neigh : adj[node]) {
            if (!visited[neigh]) {
                visited[neigh] = true;
                q.push(neigh);
            }
        }
    }
}

int main() {

```

```

int V = 5;
vector<vector<int>> adj(V);
adj[0] = {1, 2};
adj[1] = {0, 3};
adj[2] = {0, 4};
adj[3] = {1};
adj[4] = {2};

BFS(0, adj);
}

```

---

## ◆ 2. Depth-First Search (DFS)

**Idea:** Explore as deep as possible using recursion/stack.

**Time Complexity:**  $O(V+E)O(V+E)O(V+E)$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

void DFSUtil(int node, vector<vector<int>>& adj, vector<bool>& visited) {
    visited[node] = true;
    cout << node << " ";
    for (int neigh : adj[node]) {
        if (!visited[neigh])
            DFSUtil(neigh, adj, visited);
    }
}

void DFS(int start, vector<vector<int>>& adj) {
    vector<bool> visited(adj.size(), false);
    DFSUtil(start, adj, visited);
}

int main() {
    int V = 5;
    vector<vector<int>> adj(V);
    adj[0] = {1, 2};
    adj[1] = {0, 3};
    adj[2] = {0, 4};
    adj[3] = {1};
    adj[4] = {2};

    DFS(0, adj);
}

```

---

## ◆ 3. Dijkstra's Algorithm

**Idea:** Find shortest paths from a source in weighted graph (non-negative weights).

**Time Complexity:**  $O((V+E)\log V)O((V+E)\log V)O((V+E)\log V)$  with priority queue.

## C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void dijkstra(int V, vector<vector<pair<int,int>>>& adj, int src) {
    vector<int> dist(V, INT_MAX);
    dist[src] = 0;
    priority_queue<pair<int,int>, vector<pair<int,int>>, greater<>> pq;
    pq.push({0, src});

    while (!pq.empty()) {
        int u = pq.top().second;
        pq.pop();
        for (auto [v, w] : adj[u]) {
            if (dist[u] + w < dist[v]) {
                dist[v] = dist[u] + w;
                pq.push({dist[v], v});
            }
        }
    }

    for (int i = 0; i < V; i++)
        cout << "Dist to " << i << " = " << dist[i] << endl;
}

int main() {
    int V = 5;
    vector<vector<pair<int,int>>> adj(V);
    adj[0].push_back({1, 9});
    adj[0].push_back({2, 6});
    adj[0].push_back({3, 5});
    adj[0].push_back({4, 3});
    adj[2].push_back({1, 2});
    adj[2].push_back({3, 4});

    dijkstra(V, adj, 0);
}
```

---

## ◆ 4. Bellman-Ford Algorithm

**Idea:** Handles negative weights, detects negative cycles.

**Time Complexity:**  $O(V \cdot E)$   $O(V \cdot E)$   $O(V \cdot E)$

## C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

struct Edge { int u, v, w; };

void bellmanFord(int V, vector<Edge>& edges, int src) {
    vector<int> dist(V, INT_MAX);
    dist[src] = 0;

    for (int i = 1; i < V; i++) {
```

```

        for (auto e : edges) {
            if (dist[e.u] != INT_MAX && dist[e.u] + e.w < dist[e.v])
                dist[e.v] = dist[e.u] + e.w;
        }
    }

    // Check for negative cycle
    for (auto e : edges) {
        if (dist[e.u] != INT_MAX && dist[e.u] + e.w < dist[e.v]) {
            cout << "Graph contains negative cycle\n";
            return;
        }
    }

    for (int i = 0; i < V; i++)
        cout << "Dist to " << i << " = " << dist[i] << endl;
}

int main() {
    int V = 5;
    vector<Edge> edges = {
        {0,1,-1},{0,2,4},{1,2,3},{1,3,2},{1,4,2},{3,2,5},{3,1,1},{4,3,-3}
    };

    bellmanFord(V, edges, 0);
}

```

---

## ◆ 5. Floyd-Warshall Algorithm

**Idea:** All-pairs shortest paths (DP). Works with negative weights (but no negative cycles).

**Time Complexity:**  $O(V^3)$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

void floydWarshall(vector<vector<int>>& graph, int V) {
    vector<vector<int>> dist = graph;

    for (int k = 0; k < V; k++) {
        for (int i = 0; i < V; i++) {
            for (int j = 0; j < V; j++) {
                if (dist[i][k] != INT_MAX && dist[k][j] != INT_MAX)
                    dist[i][j] = min(dist[i][j], dist[i][k] + dist[k][j]);
            }
        }
    }

    for (int i = 0; i < V; i++) {
        for (int j = 0; j < V; j++) {
            if (dist[i][j] == INT_MAX) cout << "INF ";
            else cout << dist[i][j] << " ";
        }
        cout << endl;
    }
}

```



```

    }
}

int main() {
    int V = 4;
    vector<vector<int>> graph = {
        {0, 5, INF, 10},
        {INF, 0, 3, INF},
        {INF, INF, 0, 1},
        {INF, INF, INF, 0}
    };

    floydWarshall(graph, V);
}

(INF = INT_MAX/2 can be used to avoid overflow).

```

---

✓ That covers **Part 1: BFS, DFS, Dijkstra, Bellman-Ford, Floyd-Warshall**.

☞ Next, I can continue with *Johnson's Algorithm, A Search, Kruskal, Prim, Borůvka, Topological Sort\** (Part 2).  
Do you want me to proceed with **Part 2 right now**?

**You said:**

A\* Search Algorithm Kruskal's Algorithm (MST) Prim's Algorithm (MST) Borůvka's Algorithm (MST)  
Topological Sort Kosaraju's Algorithm (SCC) Tarjan's Algorithm (SCC, Bridges, Articulation Points)  
Edmonds-Karp (Maximum Flow) Dinic's Algorithm (Maximum Flow) Push-Relabel Algorithm  
Hungarian Algorithm (Assignment Problem)

ChatGPT said:

Great 🐼 Let's continue with detailed explanations, formulas, and **C++ implementations** of the advanced **Graph Algorithms** you listed.

---

## ◆ 3. Graph Algorithms (Part 2)

---

### 1. A Search Algorithm\*

☞ A pathfinding algorithm (used in AI, maps, games).  
It combines Dijkstra's Algorithm with a heuristic (like Manhattan distance).

- **Formula:**
- $f(n) = g(n) + h(n)$

where

$g(n)$  = cost to reach node  $n$

$h(n)$  = estimated cost from  $n$  to target (heuristic).

✓ *Code (C++ A Search Example)\**

```
#include <bits/stdc++.h>
using namespace std;

struct Node {
    int x, y;
    double f, g, h;
    Node* parent;
    bool operator>(const Node& other) const { return f > other.f; }
};

double heuristic(pair<int,int> a, pair<int,int> b) {
    return abs(a.first - b.first) + abs(a.second - b.second); // Manhattan
}

int main() {
    pair<int,int> start = {0,0}, goal = {2,2};
    priority_queue<Node, vector<Node>, greater<Node>> pq;
    Node s = {0,0,0,0,0,NULL};
    pq.push(s);

    while(!pq.empty()) {
        Node current = pq.top(); pq.pop();
        if(current.x == goal.first && current.y == goal.second) {
            cout << "Reached goal!" << endl;
            break;
        }
        vector<pair<int,int>> moves = {{1,0},{-1,0},{0,1},{0,-1}};
        for(auto m : moves) {
            int nx = current.x + m.first, ny = current.y + m.second;
            Node neighbor;
            neighbor.x = nx; neighbor.y = ny;
            neighbor.g = current.g + 1;
            neighbor.h = heuristic({nx,ny}, goal);
            neighbor.f = neighbor.g + neighbor.h;
            neighbor.parent = new Node(current);
            pq.push(neighbor);
        }
    }
}
```

---

## 2. Kruskal's Algorithm (MST)

☞ Greedy algorithm to build MST using **Disjoint Set (Union-Find)**.

- Sort edges by weight.
- Add smallest edge that doesn't form a cycle.

✓ **Code (C++ Kruskal)**

```
#include <bits/stdc++.h>
```

```

using namespace std;

struct Edge {
    int u, v, w;
    bool operator<(Edge const& other) { return w < other.w; }
};

int find(vector<int>& parent, int v) {
    if(v == parent[v]) return v;
    return parent[v] = find(parent, parent[v]);
}

void unite(vector<int>& parent, vector<int>& rank, int a, int b) {
    a = find(parent, a); b = find(parent, b);
    if(a != b) {
        if(rank[a] < rank[b]) swap(a, b);
        parent[b] = a;
        if(rank[a] == rank[b]) rank[a]++;
    }
}

int main() {
    int n = 4;
    vector<Edge> edges = {{0,1,10},{0,2,6},{0,3,5},{1,3,15},{2,3,4}};
    sort(edges.begin(), edges.end());

    vector<int> parent(n), rank(n,0);
    iota(parent.begin(), parent.end(), 0);

    int mst = 0;
    for(auto e : edges) {
        if(find(parent,e.u) != find(parent,e.v)) {
            mst += e.w;
            unite(parent, rank, e.u, e.v);
        }
    }
    cout << "MST Weight = " << mst << endl;
}

```

---

### 3. Prim's Algorithm (MST)

☞ Greedy algorithm growing MST one edge at a time.

✓ Code (C++ Prim's using Priority Queue)

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    int n = 5;
    vector<pair<int,int>> adj[5] = {
        {{1,2},{3,6}}, {{0,2},{2,3},{3,8},{4,5}},
        {{1,3},{4,7}}, {{0,6},{1,8}}, {{1,5},{2,7}}
    };

    vector<int> key(n, INT_MAX), parent(n,-1);
    vector<bool> inMST(n,false);
    key[0] = 0;

```

```

priority_queue<pair<int,int>, vector<pair<int,int>>, greater<>> pq;
pq.push({0,0});

int mst=0;
while(!pq.empty()) {
    int u = pq.top().second; pq.pop();
    if(inMST[u]) continue;
    inMST[u] = true;
    mst += key[u];
    for(auto [v,w]: adj[u]) {
        if(!inMST[v] && w < key[v]) {
            key[v] = w; parent[v] = u;
            pq.push({key[v], v});
        }
    }
}
cout << "MST Weight = " << mst << endl;
}

```

---

#### 4. Borůvka's Algorithm (MST)

☞ MST algorithm using cheapest edge from each component.

✓ Code (C++ Borůvka)

```

#include <bits/stdc++.h>
using namespace std;

struct Edge { int u,v,w; };

int find(vector<int>& parent, int x) {
    return parent[x]==x ? x : parent[x]=find(parent,parent[x]);
}

int main() {
    int V=4;
    vector<Edge> edges = {{0,1,10},{0,2,6},{0,3,5},{1,3,15},{2,3,4}};
    vector<int> parent(V);
    iota(parent.begin(), parent.end(), 0);

    int mstWeight=0, comp=V;
    while(comp > 1) {
        vector<int> cheapest(V,-1);
        for(int i=0;i<edges.size();i++) {
            int u=find(parent,edges[i].u), v=find(parent,edges[i].v);
            if(u==v) continue;
            if(cheapest[u]==-1 || edges[i].w < edges[cheapest[u]].w)
                cheapest[u]=i;
            if(cheapest[v]==-1 || edges[i].w < edges[cheapest[v]].w)
                cheapest[v]=i;
        }
        for(int i=0;i<V;i++) {
            if(cheapest[i]!=-1) {
                int u=find(parent,edges[cheapest[i]].u),
                v=find(parent,edges[cheapest[i]].v);
                if(u!=v) {
                    parent[u]=v;

```

```

        mstWeight+=edges[cheapest[i]].w;
        comp--;
    }
}
}
}
cout<<"MST Weight = "<<mstWeight<<endl;
}

```

---

## 5. Topological Sort (DAG Only)

☞ Linear ordering of vertices such that  $u \rightarrow v \Rightarrow u$  appears before  $v$ .

### ✓ Code (C++ using Kahn's Algorithm)

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    int n=6;
    vector<vector<int>> adj={{},{3},{3,4},{5},{5},{}};
    vector<int> indegree(n,0);

    for(int u=0;u<n;u++) for(int v:adj[u]) indegree[v]++;
    queue<int> q;
    for(int i=0;i<n;i++) if(indegree[i]==0) q.push(i);

    vector<int> topo;
    while(!q.empty()) {
        int u=q.front();q.pop();
        topo.push_back(u);
        for(int v:adj[u]) if(--indegree[v]==0) q.push(v);
    }

    cout<<"Topological Order: ";
    for(int x:topo) cout<<x<<" ";
}

```

---

✂ This is already huge, so I'll split.

Next batch will cover:

- **Kosaraju's Algorithm (SCC)**
  - **Tarjan's Algorithm (SCC, Bridges, Articulation Points)**
  - **Edmonds-Karp (Max Flow)**
  - **Dinic's Algorithm (Max Flow)**
  - **Push-Relabel Algorithm**
  - **Hungarian Algorithm (Assignment Problem)**
- 

☞ Do you want me to continue with **Kosaraju + Tarjan + Max Flow algorithms** now?

**You said:**

Kosaraju's Algorithm (SCC) Tarjan's Algorithm (SCC, Bridges, Articulation Points) Edmonds-Karp (Max Flow) Dinic's Algorithm (Max Flow) Push-Relabel Algorithm Hungarian Algorithm (Assignment Problem)

ChatGPT said:

Great, Sahil 🐣 Let's now go through these **advanced graph algorithms** one by one with **concept + formula/intuition + C++ code**.

---

## ◆ 1. Kosaraju's Algorithm (Strongly Connected Components - SCC)

✓ Finds SCCs in a directed graph.

- Step 1: Do DFS and push nodes in stack (by finish time).
- Step 2: Reverse the graph.
- Step 3: Pop nodes from stack, do DFS in reversed graph → each DFS = one SCC.

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

void dfs1(int v, vector<vector<int>>& g, vector<bool>& vis, stack<int>& st)
{
    vis[v] = true;
    for (int u : g[v]) if (!vis[u]) dfs1(u, g, vis, st);
    st.push(v);
}

void dfs2(int v, vector<vector<int>>& rg, vector<bool>& vis) {
    vis[v] = true;
    cout << v << " ";
    for (int u : rg[v]) if (!vis[u]) dfs2(u, rg, vis);
}

int main() {
    int n = 5;
    vector<vector<int>> g(n), rg(n);
    g[0] = {2, 3}; g[1] = {0}; g[2] = {1}; g[3] = {4};

    // Build reverse graph
    for(int v=0; v<n; v++) for(int u: g[v]) rg[u].push_back(v);

    vector<bool> vis(n,false);
    stack<int> st;

    // Step 1
    for(int i=0;i<n;i++) if(!vis[i]) dfs1(i,g,vis,st);

    fill(vis.begin(), vis.end(), false);
```

```

// Step 2 + 3
while(!st.empty()){
    int v=st.top(); st.pop();
    if(!vis[v]) {
        dfs2(v,rg,vis);
        cout << endl;
    }
}
}

```

---

## ◆ 2. Tarjan's Algorithm (SCC, Bridges, Articulation Points)

✓ Uses DFS + low-link values.

- `disc[v]` → discovery time of node `v`.
- `low[v]` → lowest discovery time reachable.
- SCC when `disc[v] == low[v]`.

**C++ Code (SCC part):**

```

#include <bits/stdc++.h>
using namespace std;

int timer = 0;
vector<int> disc, low, st;
vector<bool> inStack;
vector<vector<int>>> adj;

void dfs(int v) {
    disc[v] = low[v] = ++timer;
    st.push_back(v);
    inStack[v] = true;

    for (int u : adj[v]) {
        if (!disc[u]) {
            dfs(u);
            low[v] = min(low[v], low[u]);
        } else if (inStack[u]) {
            low[v] = min(low[v], disc[u]);
        }
    }

    if (low[v] == disc[v]) {
        while (true) {
            int u = st.back(); st.pop_back();
            inStack[u] = false;
            cout << u << " ";
            if (u == v) break;
        }
        cout << endl;
    }
}

```

```
int main() {
    int n = 5;
    adj = {{1}, {2}, {0,3}, {4}, {}};
    disc.assign(n,0); low.assign(n,0); inStack.assign(n,false);

    for(int i=0;i<n;i++) if(!disc[i]) dfs(i);
}
```

---

## ◆ 3. Edmonds-Karp (Maximum Flow)

✓ BFS-based implementation of **Ford-Fulkerson**.

- Finds augmenting paths using BFS.
- Complexity:  $O(VE^2)$ .

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

bool bfs(int s, int t, vector<vector<int>>& rGraph, vector<int>& parent) {
    fill(parent.begin(), parent.end(), -1);
    parent[s] = s;
    queue<int> q; q.push(s);

    while(!q.empty()) {
        int u = q.front(); q.pop();
        for(int v=0; v<rGraph.size(); v++) {
            if(parent[v]==-1 && rGraph[u][v]>0) {
                parent[v]=u;
                if(v==t) return true;
                q.push(v);
            }
        }
    }
    return false;
}

int edmondsKarp(vector<vector<int>>& graph, int s, int t) {
    int n=graph.size();
    vector<vector<int>> rGraph=graph;
    vector<int> parent(n);
    int maxFlow=0;

    while(bfs(s,t,rGraph,parent)) {
        int path_flow=INT_MAX;
        for(int v=t;v!=s;v=parent[v])
            path_flow=min(path_flow,rGraph[parent[v]][v]);

        for(int v=t;v!=s;v=parent[v]) {
            int u=parent[v];
            rGraph[u][v]-=path_flow;
            rGraph[v][u]+=path_flow;
        }
        maxFlow+=path_flow;
    }
}
```



```

    }
    return maxFlow;
}

int main() {
    vector<vector<int>> graph={{0,16,13,0,0,0},
                               {0,0,10,12,0,0},
                               {0,4,0,0,14,0},
                               {0,0,9,0,0,20},
                               {0,0,0,7,0,4},
                               {0,0,0,0,0,0}};

    cout << "Max Flow = " << edmondsKarp(graph,0,5);
}

```

---

## ◆ 4. Dinic's Algorithm (Maximum Flow)

✓ Uses level graph + blocking flow.

- Faster than Edmonds-Karp:  $O(V^2E)$ .

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

struct Edge { int v, cap, rev; };
vector<vector<Edge>> adj;

void addEdge(int u, int v, int cap) {
    adj[u].push_back({v, cap, (int)adj[v].size()});
    adj[v].push_back({u, 0, (int)adj[u].size()-1});
}

bool bfs(int s, int t, vector<int>& level) {
    fill(level.begin(), level.end(), -1);
    level[s]=0;
    queue<int> q; q.push(s);
    while(!q.empty()) {
        int u=q.front(); q.pop();
        for(auto &e:adj[u]) if(level[e.v]<0 && e.cap>0) {
            level[e.v]=level[u]+1;
            q.push(e.v);
        }
    }
    return level[t]>=0;
}

int dfs(int u, int t, int flow, vector<int>& level, vector<int>& start) {
    if(u==t) return flow;
    for(int &i=start[u]; i<adj[u].size(); i++) {
        Edge &e=adj[u][i];
        if(e.cap>0 && level[e.v]==level[u]+1) {
            int cur_flow=dfs(e.v, t, min(flow, e.cap), level, start);
            if(cur_flow>0) {
                e.cap-=cur_flow;
                adj[e.v][e.rev].cap+=cur_flow;
            }
        }
    }
    return 0;
}

```

```

        return cur_flow;
    }
}
return 0;
}

int dinic(int s, int t, int n) {
    int maxFlow=0;
    vector<int> level(n), start(n);
    while(bfs(s,t,level)) {
        fill(start.begin(),start.end(),0);
        while(int flow=dfs(s,t,INT_MAX,level,start)) maxFlow+=flow;
    }
    return maxFlow;
}

int main() {
    int n=6; adj.assign(n,{});
    addEdge(0,1,16); addEdge(0,2,13); addEdge(1,2,10);
    addEdge(1,3,12); addEdge(2,1,4); addEdge(2,4,14);
    addEdge(3,2,9); addEdge(3,5,20); addEdge(4,3,7); addEdge(4,5,4);
    cout<<"Max Flow = "<<dinic(0,5,n);
}

```

---

## ◆ 5. Push-Relabel Algorithm (Maximum Flow)

✓ Maintains **preflow** + pushes excess flow until max-flow is achieved.

- Complexity:  $O(V^3)$ .

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

struct Edge { int v, flow, cap, rev; };
vector<vector<Edge>> adj;

void addEdge(int u, int v, int cap) {
    adj[u].push_back({v,0,cap,(int)adj[v].size()});
    adj[v].push_back({u,0,0,(int)adj[u].size()-1});
}

void push(vector<int>& excess, vector<int>& height, int u, Edge &e) {
    int flow=min(excess[u], e.cap-e.flow);
    if(height[u]==height[e.v]+1 && flow>0) {
        e.flow+=flow;
        adj[e.v][e.rev].flow-=flow;
        excess[u]-=flow;
        excess[e.v]+=flow;
    }
}

```

```

void relabel(vector<int>& height, int u) {
    int mn=INT_MAX;
    for(auto &e:adj[u]) if(e.cap-e.flow>0) mn=min(mn,height[e.v]);
    if(mn<INT_MAX) height[u]=mn+1;
}

int pushRelabel(int s, int t, int n) {
    vector<int> height(n,0), excess(n,0);
    height[s]=n;
    for(auto &e:adj[s]) {
        e.flow=e.cap;
        adj[e.v][e.rev].flow=-e.cap;
        excess[e.v]+=e.cap;
    }

    queue<int> q;
    for(int i=0;i<n;i++) if(i!=s && i!=t && excess[i]>0) q.push(i);

    while(!q.empty()) {
        int u=q.front(); q.pop();
        bool pushed=false;
        for(auto &e:adj[u]) {
            int oldEx=excess[u];
            push(excess,height,u,e);
            if(excess[u]<oldEx && e.v!=s && e.v!=t && excess[e.v]==e.cap)
                q.push(e.v);
        }
        if(excess[u]>0) { relabel(height,u); q.push(u); }
    }
    return excess[t];
}

int main() {
    int n=6; adj.assign(n,{});
    addEdge(0,1,16); addEdge(0,2,13); addEdge(1,2,10);
    addEdge(1,3,12); addEdge(2,1,4); addEdge(2,4,14);
    addEdge(3,2,9); addEdge(3,5,20); addEdge(4,3,7); addEdge(4,5,4);
    cout<<"Max Flow = "<<pushRelabel(0,5,n);
}

```

---

## ◆ 6. Hungarian Algorithm (Assignment Problem)

✓ Solves **minimum cost bipartite matching**.

- Given  $n \times n$  cost matrix.
- Finds assignment with minimum cost in  $O(n^3)$ .

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

```

```

const int INF=1e9;

int hungarian(const vector<vector<int>>& cost) {
    int n=cost.size();
    vector<int> u(n+1), v(n+1), p(n+1), way(n+1);
    for(int i=1;i<=n;i++) {
        p[0]=i;
        int j0=0;
        vector<int> minv(n+1,INF);
        vector<bool> used(n+1,false);
        do {
            used[j0]=true;
            int i0=p[j0], delta=INF, j1=0;
            for(int j=1;j<=n;j++) if(!used[j]) {
                int cur=cost[i0-1][j-1]-u[i0]-v[j];
                if(cur<minv[j]) { minv[j]=cur; way[j]=j0; }
                if(minv[j]<delta) { delta=minv[j]; j1=j; }
            }
            for(int j=0;j<=n;j++) {
                if(used[j]) { u[p[j]]+=delta; v[j]-=delta; }
                else minv[j]-=delta;
            }
            j0=j1;
        } while(p[j0]!=0);
        do {
            int j1=way[j0];
            p[j0]=p[j1];
            j0=j1;
        } while(j0);
    }
    return -v[0];
}


int main() {
    vector<vector<int>> cost={{9,2,7,8},
                             {6,4,3,7},
                             {5,8,1,8},
                             {7,6,9,4}};
    cout<<"Minimum Cost = "<<hungarian(cost);
}

```

---

✓ Now you have **all advanced graph algorithms with formulas + C++ implementations**.

Do you want me to also prepare **short complexity + use-case notes (like cheatsheet form)** for all of them?



## ◆ Johnson's Algorithm (All-Pairs Shortest Paths)

### Purpose:

Find the shortest paths between all pairs of vertices in a **sparse weighted directed graph** (can have negative edge weights but **no negative weight cycles**).

It combines **Bellman-Ford** and **Dijkstra's algorithm**.

---

### ✓ Steps of Johnson's Algorithm:

1. **Add a new vertex  $q$**  and connect it with **0-weight edges** to all vertices.
2. **Run Bellman-Ford** from  $q$  to detect negative weight cycles and compute  $h[v]$ , the potential (minimum distance from  $q$  to each vertex  $v$ ).
  - If a negative cycle exists  $\rightarrow$  stop.

3. **Reweight edges:**

For every edge  $(u, v, w)$ , set

$$w'(u,v) = w(u,v) + h[u] - h[v]$$

This ensures **all edge weights are non-negative**.

4. **Run Dijkstra's Algorithm** from each vertex using reweighted edges.
5. **Recover original distances:**

For each shortest path  $dist'[u][v]$  found in step 4:

$$dist[u][v] = dist'[u][v] - h[u] + h[v]$$

---

### ✓ Time Complexity:

- Bellman-Ford:  $O(VE)$
  - Dijkstra (with min-heap):  $O(VE \log V)$
  - Total:  $O(VE \log V) \rightarrow$  efficient for **sparse graphs**.
- 

### ✓ C++ Implementation

```
#include <bits/stdc++.h>
using namespace std;
const int INF = 1e9;

struct Edge {
    int u, v, w;
};
```

```

void johnson(int V, vector<Edge>& edges) {
    // Step 1: Add new vertex q
    int newV = V + 1;
    vector<Edge> newEdges = edges;
    for (int i = 0; i < V; i++) {
        newEdges.push_back({V, i, 0}); // q -> i with weight 0
    }

    // Step 2: Run Bellman-Ford from q
    vector<int> h(newV, INF);
    h[V] = 0;
    for (int i = 0; i < newV - 1; i++) {
        for (auto &e : newEdges) {
            if (h[e.u] != INF && h[e.u] + e.w < h[e.v]) {
                h[e.v] = h[e.u] + e.w;
            }
        }
    }

    // Check for negative cycle
    for (auto &e : newEdges) {
        if (h[e.u] != INF && h[e.u] + e.w < h[e.v]) {
            cout << "Graph contains negative weight cycle\n";
            return;
        }
    }

    // Step 3: Reweight edges
    vector<vector<pair<int,int>>> adj(V);
    for (auto &e : edges) {
        int w_prime = e.w + h[e.u] - h[e.v];
        adj[e.u].push_back({e.v, w_prime});
    }

    // Step 4: Run Dijkstra from each vertex
    for (int src = 0; src < V; src++) {
        vector<int> dist(V, INF);
        dist[src] = 0;

        priority_queue<pair<int,int>, vector<pair<int,int>>, greater<>> pq;
        pq.push({0, src});

        while (!pq.empty()) {
            auto [d, u] = pq.top(); pq.pop();
            if (d > dist[u]) continue;
            for (auto [v, w] : adj[u]) {
                if (dist[u] + w < dist[v]) {
                    dist[v] = dist[u] + w;
                    pq.push({dist[v], v});
                }
            }
        }

        // Step 5: Recover original distances
        cout << "From vertex " << src << ": ";
        for (int v = 0; v < V; v++) {
            if (dist[v] == INF) cout << "INF ";
            else cout << dist[v] - h[src] + h[v] << " ";
        }
        cout << "\n";
    }
}

```

```

}

int main() {
    int V = 5;
    vector<Edge> edges = {
        {0, 1, 3}, {0, 2, 8}, {0, 4, -4},
        {1, 3, 1}, {1, 4, 7},
        {2, 1, 4},
        {3, 0, 2}, {3, 2, -5},
        {4, 3, 6}
    };

    johnson(V, edges);

    return 0;
}

```

---

## ✓ Example Output

For the above graph:

```

From vertex 0: 0 1 -3 2 -4
From vertex 1: 3 0 -4 1 -1
From vertex 2: 7 4 0 5 3
From vertex 3: 2 -1 -5 0 -2
From vertex 4: 8 5 1 6 0

```

---

Do you want me to also make a step-by-step dry run on a small graph (say 4 vertices) so you can clearly see how reweighting removes negative edges?

I'll give you **explanations, formulas, and C++ implementations** for each, keeping examples separate (like we did earlier).

---

# ◆ 4. Dynamic Programming (DP) Algorithms

---

## 1. Fibonacci (DP version)

📖 **Idea:** Avoid recomputation by storing results in a table (bottom-up).

★ **Recurrence:**

$F(n) = F(n-1) + F(n-2)$ ,  $F(0) = 0$ ,  $F(1) = 1$   $F(n) = F(n-1) + F(n-2)$ ,  $\quad F(0) = 0$ ,  
 $F(1) = 1$   $F(n) = F(n-1) + F(n-2)$ ,  $F(0) = 0$ ,  $F(1) = 1$

```
#include <bits/stdc++.h>
using namespace std;

int fibonacci(int n) {
    vector<int> dp(n+1, 0);
    dp[0] = 0, dp[1] = 1;
    for(int i=2; i<=n; i++)
        dp[i] = dp[i-1] + dp[i-2];
    return dp[n];
}

int main() {
    int n=10;
    cout << "Fibonacci(" << n << ") = " << fibonacci(n);
}
```

---

## 2. Longest Common Subsequence (LCS)

### Recurrence:

$$LCS(i,j) = \begin{cases} 1 + LCS(i-1, j-1) & \text{if } X[i] = Y[j] \\ \max(LCS(i-1, j), LCS(i, j-1)) & \text{otherwise} \end{cases}$$

```
#include <bits/stdc++.h>
using namespace std;

int LCS(string X, string Y) {
    int n=X.size(), m=Y.size();
    vector<vector<int>> dp(n+1, vector<int>(m+1,0));
    for(int i=1; i<=n; i++)
        for(int j=1; j<=m; j++)
            if(X[i-1]==Y[j-1]) dp[i][j]=1+dp[i-1][j-1];
            else dp[i][j]=max(dp[i-1][j], dp[i][j-1]);
    return dp[n][m];
}

int main() {
    cout<<"LCS = "<<LCS("AGGTAB", "GXTXAYB");
}
```

---

## 3. Longest Increasing Subsequence (LIS)

### Recurrence:

$$LIS(i) = 1 + \max_{j < i, arr[j] < arr[i]} LIS(j)$$

```
#include <bits/stdc++.h>
using namespace std;

int LIS(vector<int>& a) {
    int n=a.size();
```



```

vector<int> dp(n,1);
int ans=1;
for(int i=1;i<n;i++)
    for(int j=0;j<i;j++)
        if(a[i]>a[j]) dp[i]=max(dp[i],dp[j]+1);
return *max_element(dp.begin(),dp.end());
}

int main() {
vector<int> arr={10,22,9,33,21,50,41,60};
cout<<"LIS = "<<LIS(arr);
}

```

---

## 4. Edit Distance

### Recurrence:

$$dp[i][j] = \begin{cases} dp[i-1][j-1] & \text{if } s1[i] = s2[j] \\ 1 + \min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1]) & \text{otherwise} \end{cases}$$

```

#include <bits/stdc++.h>
using namespace std;

int editDistance(string s1, string s2) {
    int n=s1.size(), m=s2.size();
    vector<vector<int>> dp(n+1, vector<int>(m+1));
    for(int i=0;i<=n;i++) dp[i][0]=i;
    for(int j=0;j<=m;j++) dp[0][j]=j;

    for(int i=1;i<=n;i++)
        for(int j=1;j<=m;j++)
            if(s1[i-1]==s2[j-1]) dp[i][j]=dp[i-1][j-1];
            else dp[i][j]=1+min({dp[i-1][j], dp[i][j-1], dp[i-1][j-1]});
    return dp[n][m];
}

int main(){
    cout<<"Edit Distance = "<<editDistance("kitten","sitting");
}

```

---

## 5. Matrix Chain Multiplication

### Recurrence:

$$dp[i][j] = \min_{k=i-1}^{j-1} (dp[i][k] + dp[k+1][j] + p_{i-1}p_kp_j)$$

```

#include <bits/stdc++.h>
using namespace std;

int matrixChain(vector<int>& p) {
    int n=p.size()-1;

```

```

vector<vector<int>> dp(n, vector<int>(n, 0));
for(int len=2; len<=n; len++){
    for(int i=0; i<n-len+1; i++){
        int j=i+len-1;
        dp[i][j]=INT_MAX;
        for(int k=i; k<j; k++){
            dp[i][j]=min(dp[i][j],
                dp[i][k]+dp[k+1][j]+p[i]*p[k+1]*p[j+1]);
        }
    }
    return dp[0][n-1];
}

int main(){
    vector<int> p={1,2,3,4};
    cout<<"Min cost = "<<matrixChain(p);
}

```

---

## 6. Knapsack Problem (0/1)

☰ Recurrence:

$$dp[i][w] = \max(dp[i-1][w], val[i-1] + dp[i-1][w - wt[i-1]])$$

$$dp[i][w] = \max(dp[i-1][w], val[i-1] + dp[i-1][w - wt[i-1]])$$

```

#include <bits/stdc++.h>
using namespace std;

int knapsack(vector<int>& wt, vector<int>& val, int W) {
    int n=wt.size();
    vector<vector<int>> dp(n+1, vector<int>(W+1,0));
    for(int i=1; i<=n; i++){
        for(int w=0; w<=W; w++){
            if(wt[i-1]<=w) dp[i][w]=max(dp[i-1][w], val[i-1]+dp[i-1][w-wt[i-1]]);
            else dp[i][w]=dp[i-1][w];
        }
    }
    return dp[n][W];
}

int main(){
    vector<int> wt={1,3,4,5}, val={1,4,5,7};
    cout<<"Max value = "<<knapsack(wt, val, 7);
}

```

---

✂ The rest (Coin Change, Subset Sum, Partition Problem, OBST, DP on Trees, Bitmask DP, Monotonic Queue DP, Convex Hull Trick, SOS DP) are **advanced** — I'll give them **step-by-step** with C++ code like above.

☞ Do you want me to continue with **Coin Change** → **SOS DP** in the same style?

## 8) Subset Sum Problem (0/1)

**Recurrence:**  $dp[i][s] = dp[i-1][s] \ || \ dp[i-1][s-a[i-1]]$

**Space-optimized 1D:**

```
#include <bits/stdc++.h>
using namespace std;

bool subsetSum(vector<int> a, int S){
    vector<char> dp(S+1,false); dp[0]=true;
    for(int x: a) for(int s=S; s>=x; --s)
        dp[s] = dp[s] || dp[s-x];
    return dp[S];
}

int main(){
    cout<<(subsetSum({3,34,4,12,5,2}, 9)?"YES":"NO");
}
```

---

## 9) Partition Problem (equal sum)

**Just check subset sum for  $s = \text{total}/2$ .**

```
#include <bits/stdc++.h>
using namespace std;

bool canPartition(vector<int> a){
    int sum=accumulate(a.begin(),a.end(),0);
    if(sum%2) return false;
    int S=sum/2;
    vector<char> dp(S+1,false); dp[0]=true;
    for(int x:a) for(int s=S; s>=x; --s)
        dp[s]=dp[s]||dp[s-x];
    return dp[S];
}

int main(){ cout<<(canPartition({1,5,11,5})?"YES":"NO"); }
```

---

## 10) Optimal Binary Search Tree (OBST)

**Given keys  $k_1 < k_2 < \dots < k_n$  and search frequencies  $f[i]$ .**

**DP:**

$dp[i][j] = \min_k ( dp[i][k-1] + dp[k+1][j] ) + \text{sumFreq}(i..j)$

```
#include <bits/stdc++.h>
using namespace std;

int obst(vector<int> f){
    int n=f.size();
    vector<int> pref(n+1,0);
    for(int i=0;i<n;i++) pref[i+1]=pref[i]+f[i];
    auto sumF=[&](int l,int r){return pref[r+1]-pref[l];};
```

```

const int INF=1e9;
vector<vector<int>>> dp(n, vector<int>(n,0));
for(int len=2; len<=n; ++len){
    for(int i=0;i+len-1<n;i++){
        int j=i+len-1; dp[i][j]=INF;
        for(int k=i;k<=j;k++){
            int left= (k>i)? dp[i][k-1]:0;
            int right= (k<j)? dp[k+1][j]:0;
            dp[i][j]=min(dp[i][j], left+right+sumF(i,j));
        }
    }
}
return dp[0][n-1];
}

int main(){ cout<<obst({3,1,2,5}); }

```

---

## 11) DP on Trees (example: Maximum Weighted Independent Set in a tree)

Pick nodes with max total weight, no two adjacent chosen.

**DP:**  $dp[u][0] = \text{sum}(\max(dp[v][0], dp[v][1]))$   
 $dp[u][1] = w[u] + \text{sum}(dp[v][0])$

```

#include <bits/stdc++.h>
using namespace std;

vector<vector<int>>> g;
vector<int> w;
vector<array<long long,2>> dp;

void dfs(int u, int p){
    dp[u]={0, w[u]};
    for(int v: g[u]) if(v!=p){
        dfs(v,u);
        dp[u][0]+=max(dp[v][0], dp[v][1]);
        dp[u][1]+=dp[v][0];
    }
}

int main(){
    int n=5; g.assign(n,{}); w={5,1,2,10,6};
    g[0]={1,2}; g[1]={0,3,4}; g[2]={0}; g[3]={1}; g[4]={1};
    dp.assign(n,{0,0});
    dfs(0,-1);
    cout<<max(dp[0][0],dp[0][1]); // 21
}

```

---

## 12) DP with Bitmasking (TSP)

$dp[mask][i] = \text{min cost to visit set } mask \text{ and end at } i.$

**Transition:** try next  $j$  not in  $mask$ .

```

#include <bits/stdc++.h>
using namespace std;

int main(){
    const int INF=1e9;
    int n=4;
    int cost[4][4]={{0,10,15,20},{10,0,35,25},{15,35,0,30},{20,25,30,0}};
    int N=1<<n;
    vector<vector<int>> dp(N, vector<int>(n, INF));
    dp[1][0]=0; // start at 0

    for(int mask=1; mask<N; ++mask){
        for(int i=0;i<n;i++) if(dp[mask][i]<INF){
            for(int j=0;j<n;j++) if(!(mask&(1<<j)))
                dp[mask|1<<j][j]=min(dp[mask|1<<j][j],
dp[mask][i]+cost[i][j]);
        }
    }
    int ans=INF;
    for(int i=0;i<n;i++) ans=min(ans, dp[N-1][i]+cost[i][0]);
    cout<<ans; // optimal tour
}

```

---

## 13) DP with Monotonic Queue (Deque Optimization)

Form:  $dp[i] = a[i] + \min(dp[i-1], dp[i-2], \dots, dp[i-k])$ .  
 Use deque to keep candidates with increasing  $dp$ .

```

#include <bits/stdc++.h>
using namespace std;

long long solve(vector<int> a, int k){
    int n=a.size();
    vector<long long> dp(n,0);
    deque<int> dq; dq.push_back(0);
    dp[0]=a[0];
    for(int i=1;i<n;i++){
        while(!dq.empty() && dq.front()<i-k) dq.pop_front();
        dp[i]=a[i]+dp[dq.front()];
        while(!dq.empty() && dp[dq.back()]>=dp[i]) dq.pop_back();
        dq.push_back(i);
    }
    return dp.back();
}

int main(){
    cout<<solve({5,1,2,10,2,3}, 2);
}

```

---

## 14) Convex Hull Trick (CHT) for DP

Form:  $dp[i] = \min_j (m_j * x_i + b_j)$  with slopes  $m_j$  monotonic and  $x_i$  queried in order.

```

#include <bits/stdc++.h>

```

```

using namespace std;

struct Line{
    long long m,b;
    double x;
    bool operator<(const Line& o) const { return x<o.x; }
};

struct CHT{
    deque<Line> dq;
    double interX(const Line& l1, const Line& l2){
        return double(l2.b - l1.b) / double(l1.m - l2.m);
    }
    void add(long long m, long long b){ // add in decreasing m
        Line l={m,b,0};
        while(dq.size()>=2 && interX(dq[dq.size()-2], dq.back()) >=
interX(dq.back(), l))
            dq.pop_back();
        if(!dq.empty()) l.x=interX(dq.back(), l);
        dq.push_back(l);
    }
    long long query(long long x){ // x non-decreasing
        while(dq.size()>=2 && dq[1].x<=x) dq.pop_front();
        return dq.front().m*x + dq.front().b;
    }
};

int main(){
    // Example dp: m_j and b_j derived elsewhere
    CHT cht;
    cht.add(-1, 5);
    cht.add(-2, 10);
    cout<<cht.query(3)<<"\n";
}

```

---

## 15) SOS DP (Sum Over Subsets)

Given  $F[\text{mask}] = \text{sum of } A[\text{sub}] \text{ over all } \text{sub} \subseteq \text{mask}$ .  
 Bit DP over all masks and bits:

```

#include <bits/stdc++.h>
using namespace std;

int main(){
    int n=3; // up to 2^n masks
    int N=1<<n;
    vector<long long> A(N), F(N);
    // Example values:
    A[0]=1; A[1]=2; A[2]=3; A[3]=4; A[4]=5; A[5]=6; A[6]=7; A[7]=8;
    F=A;
    for(int b=0;b<n;b++)
        for(int mask=0; mask<N; mask++)
            if(mask&(1<<b)) F[mask]+=F[mask^(1<<b)];
    // Now F[mask] = sum_{sub ⊆ mask} A[sub]
    for(int m=0;m<N;m++) cout<<F[m]<<" ";
}

```

---

## (Bonus) Knapsack variants to complete the set

### Unbounded Knapsack (max value, unlimited items):

$dp[w] = \max(dp[w], dp[w - wt[i]] + val[i])$

```
#include <bits/stdc++.h>
using namespace std;


int unboundedKnapsack(vector<int> wt, vector<int> val, int W){
    vector<int> dp(W+1,0);
    for(int i=0;i<wt.size();i++)
        for(int w=wt[i]; w<=W; ++w)
            dp[w]=max(dp[w], dp[w-wt[i]]+val[i]);
    return dp[W];
}

int main(){ cout<<unboundedKnapsack({2,3,4},{4,5,7}, 7); }
```

**Fractional Knapsack = Greedy (not DP):** sort by value/weight and take fractions.

---

want me to bundle these into a **one-page cheatsheet (complexities + when to use which)**, or generate a **.cpp pack** with all files separated?



## ◆ 5. Greedy Algorithms

---

### 1. Activity Selection Problem

☞ Select the maximum number of non-overlapping activities.

**Formula / Idea:**

- Sort activities by **finish time**.
- Always pick the activity that finishes earliest (and is compatible).

**C++ Example:**

```
#include <bits/stdc++.h>
using namespace std;

struct Activity {
    int start, finish;
};
```

```

bool cmp(Activity a, Activity b) {
    return a.finish < b.finish;
}

int main() {
    vector<Activity> activities = {{1, 3}, {2, 5}, {0, 6}, {8, 9}, {5, 7},
{5, 9}};
    sort(activities.begin(), activities.end(), cmp);

    int lastFinish = -1, count = 0;
    cout << "Selected Activities: ";
    for (auto act : activities) {
        if (act.start >= lastFinish) {
            cout << "(" << act.start << ", " << act.finish << ") ";
            lastFinish = act.finish;
            count++;
        }
    }
    cout << "\nMaximum Activities = " << count << endl;
    return 0;
}

```

---

## 2. Huffman Coding

☞ Lossless data compression technique.

### Formula / Idea:

- Build a **min-heap** of characters with frequency.
- Merge two smallest frequencies until one tree remains.

### C++ Example:

```

#include <bits/stdc++.h>
using namespace std;

struct Node {
    char ch;
    int freq;
    Node *left, *right;
    Node(char c, int f) : ch(c), freq(f), left(NULL), right(NULL) {}
};

struct cmp {
    bool operator()(Node* a, Node* b) {
        return a->freq > b->freq;
    }
};

void printCodes(Node* root, string str) {
    if (!root) return;
    if (!root->left && !root->right) cout << root->ch << ": " << str <<
endl;
    printCodes(root->left, str + "0");
    printCodes(root->right, str + "1");
}

```



```

int main() {
    vector<char> chars = {'a','b','c','d','e','f'};
    vector<int> freq = {5,9,12,13,16,45};

    priority_queue<Node*, vector<Node*>, cmp> pq;
    for (int i=0; i<chars.size(); i++) pq.push(new Node(chars[i],
freq[i]));

    while (pq.size() > 1) {
        Node* left = pq.top(); pq.pop();
        Node* right = pq.top(); pq.pop();
        Node* merged = new Node('$', left->freq + right->freq);
        merged->left = left;
        merged->right = right;
        pq.push(merged);
    }

    cout << "Huffman Codes:\n";
    printCodes(pq.top(), "");
}

```

---

### 3. Fractional Knapsack

☞ Maximize value with capacity constraint, items divisible.

**Formula / Idea:**

- Sort items by **value/weight ratio**.
- Pick items until capacity is full.

**C++ Example:**

```

#include <bits/stdc++.h>
using namespace std;

struct Item {
    int value, weight;
};

bool cmp(Item a, Item b) {
    return (double)a.value/a.weight > (double)b.value/b.weight;
}

int main() {
    vector<Item> items = {{60,10}, {100,20}, {120,30}};
    int W = 50;

    sort(items.begin(), items.end(), cmp);
    double totalValue = 0.0;

    for (auto it : items) {
        if (W >= it.weight) {
            W -= it.weight;
            totalValue += it.value;
        } else {
            totalValue += it.value * ((double)W / it.weight);
            break;
        }
    }
}

```

```

    }
}
cout << "Maximum Value = " << totalValue << endl;
}

```

---

## 4. Job Scheduling Problem

☞ Schedule jobs with deadlines & profits.

**Formula / Idea:**

- Sort jobs by profit.
- Assign jobs to latest free slot before deadline.

**C++ Example:**

```

#include <bits/stdc++.h>
using namespace std;

struct Job {
    int id, deadline, profit;
};

bool cmp(Job a, Job b) { return a.profit > b.profit; }

int main() {
    vector<Job> jobs = {{1,4,20}, {2,1,10}, {3,1,40}, {4,1,30}};
    sort(jobs.begin(), jobs.end(), cmp);

    int maxDeadline = 0;
    for (auto j : jobs) maxDeadline = max(maxDeadline, j.deadline);

    vector<int> slot(maxDeadline+1, -1);
    int totalProfit = 0;

    for (auto j : jobs) {
        for (int d = j.deadline; d > 0; d--) {
            if (slot[d] == -1) {
                slot[d] = j.id;
                totalProfit += j.profit;
                break;
            }
        }
    }

    cout << "Scheduled Jobs: ";
    for (int i=1; i<=maxDeadline; i++) if(slot[i]!=-1) cout<<slot[i]<<" ";
    cout << "\nTotal Profit = " << totalProfit << endl;
}

```

---

## 5. Interval Scheduling (Weighted)

☞ Maximize non-overlapping intervals (possibly with weights).

**Formula / Idea:**

- Sort intervals by finish time.
- Use **Greedy** (if unweighted) or DP (if weighted).

### C++ Example (unweighted):

```
#include <bits/stdc++.h>
using namespace std;

struct Interval {
    int start, finish;
};

bool cmp(Interval a, Interval b) {
    return a.finish < b.finish;
}

int main() {
    vector<Interval> intervals = {{1,2},{3,4},{0,6},{5,7},{8,9},{5,9}};
    sort(intervals.begin(), intervals.end(), cmp);

    int lastFinish = -1, count=0;
    cout << "Selected Intervals: ";
    for (auto in : intervals) {
        if (in.start >= lastFinish) {
            cout << "("<<in.start<<","<<in.finish<<") ";
            lastFinish = in.finish;
            count++;
        }
    }
    cout << "\nMaximum intervals = " << count << endl;
}
```

---

## 6 & 7. Kruskal's & Prim's Algorithm

☞ Already covered under **Graph Algorithms** (both greedy MST).

---

✓ Now you have **all main Greedy Algorithms** with C++ examples.

Do you want me to also include **formulas/derivations** (time complexity & correctness **proofs**) for each greedy algorithm?

# ◆ Common Backtracking Algorithms

## 1. N-Queens Problem

Place **N queens** on an  $N \times N$  chessboard so that no two queens attack each other.

### C++ Code:

```
#include <bits/stdc++.h>
```

```

using namespace std;

bool isSafe(vector<string> &board, int row, int col, int n) {
    // Check column
    for (int i = 0; i < row; i++)
        if (board[i][col] == 'Q') return false;

    // Check upper left diagonal
    for (int i = row - 1, j = col - 1; i >= 0 && j >= 0; i--, j--)
        if (board[i][j] == 'Q') return false;

    // Check upper right diagonal
    for (int i = row - 1, j = col + 1; i >= 0 && j < n; i--, j++)
        if (board[i][j] == 'Q') return false;

    return true;
}

void solveNQueens(vector<string> &board, int row, int n) {
    if (row == n) {
        for (auto r : board) cout << r << endl;
        cout << endl;
        return;
    }
    for (int col = 0; col < n; col++) {
        if (isSafe(board, row, col, n)) {
            board[row][col] = 'Q';
            solveNQueens(board, row + 1, n);
            board[row][col] = '.'; // Backtrack
        }
    }
}

int main() {
    int n = 4;
    vector<string> board(n, string(n, '.'));
    solveNQueens(board, 0, n);
}

```

---

## 2. Sudoku Solver

Fill a **9×9 Sudoku board** so that every row, column, and 3×3 sub-grid has digits 1-9.

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

bool isValid(vector<vector<int>> &board, int row, int col, int num) {
    for (int i = 0; i < 9; i++) {
        if (board[row][i] == num || board[i][col] == num) return false;
        if (board[3*(row/3)+i/3][3*(col/3)+i%3] == num) return false;
    }
    return true;
}

bool solveSudoku(vector<vector<int>> &board) {
    for (int row = 0; row < 9; row++) {

```

```

        for (int col = 0; col < 9; col++) {
            if (board[row][col] == 0) {
                for (int num = 1; num <= 9; num++) {
                    if (isValid(board, row, col, num)) {
                        board[row][col] = num;
                        if (solveSudoku(board)) return true;
                        board[row][col] = 0; // Backtrack
                    }
                }
                return false;
            }
        }
    }
    return true;
}

int main() {
    vector<vector<int>> board = {
        {5,3,0,0,7,0,0,0,0},
        {6,0,0,1,9,5,0,0,0},
        {0,9,8,0,0,0,0,6,0},
        {8,0,0,0,6,0,0,0,3},
        {4,0,0,8,0,3,0,0,1},
        {7,0,0,0,2,0,0,0,6},
        {0,6,0,0,0,0,2,8,0},
        {0,0,0,4,1,9,0,0,5},
        {0,0,0,0,8,0,0,7,9}
    };
    solveSudoku(board);

    for (auto &row : board) {
        for (int num : row) cout << num << " ";
        cout << endl;
    }
}

```

---

### 3. Rat in a Maze

Find a path from (0,0) to (N-1,N-1) in a maze represented by a grid.

#### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

int n;
int maze[10][10];
int sol[10][10];

bool isSafe(int x, int y) {
    return (x >= 0 && x < n && y >= 0 && y < n && maze[x][y] == 1);
}

bool solveMazeUtil(int x, int y) {
    if (x == n-1 && y == n-1) {
        sol[x][y] = 1;
        return true;
    }
}

```

```

        if (isSafe(x, y)) {
            sol[x][y] = 1;
            if (solveMazeUtil(x+1, y)) return true;
            if (solveMazeUtil(x, y+1)) return true;
            sol[x][y] = 0; // backtrack
            return false;
        }
        return false;
    }

void solveMaze() {
    if (!solveMazeUtil(0, 0)) {
        cout << "No solution\n";
        return;
    }
    for (int i=0; i<n; i++) {
        for (int j=0; j<n; j++)
            cout << sol[i][j] << " ";
        cout << endl;
    }
}

int main() {
    n = 4;
    int m[4][4] = {{1,0,0,0},
                   {1,1,0,1},
                   {0,1,0,0},
                   {1,1,1,1}};
    memcpy(maze, m, sizeof(m));
    memset(sol, 0, sizeof(sol));
    solveMaze();
}

```

---

## 4. Hamiltonian Cycle

Find a cycle that visits each vertex exactly once.

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

#define V 5
int path[V];

bool isSafe(int v, bool graph[V][V], int pos) {
    if (graph[path[pos-1]][v] == 0) return false;
    for (int i = 0; i < pos; i++)
        if (path[i] == v) return false;
    return true;
}

bool hamiltonianCycleUtil(bool graph[V][V], int pos) {
    if (pos == V) return graph[path[pos-1]][path[0]] == 1;
    for (int v = 1; v < V; v++) {
        if (isSafe(v, graph, pos)) {
            path[pos] = v;
            if (hamiltonianCycleUtil(graph, pos+1)) return true;
        }
    }
    return false;
}

```

```

        path[pos] = -1;
    }
}
return false;
}

void hamiltonianCycle(bool graph[V][V]) {
    for (int i = 0; i < V; i++) path[i] = -1;
    path[0] = 0;
    if (!hamiltonianCycleUtil(graph, 1)) {
        cout << "No Hamiltonian Cycle exists\n";
        return;
    }
    for (int i = 0; i < V; i++) cout << path[i] << " ";
    cout << path[0] << endl;
}

int main() {
    bool graph[V][V] = {{0,1,0,1,0},
                        {1,0,1,1,1},
                        {0,1,0,0,1},
                        {1,1,0,0,1},
                        {0,1,1,1,0}};


    hamiltonianCycle(graph);
}

```

---

✓ So far, I've covered **N-Queens**, **Sudoku Solver**, **Rat in a Maze**, **Hamiltonian Cycle** with **C++ codes**.

Would you like me to also add **Word Search (backtracking in grids)** and **M-Coloring Problem (graph coloring)** as bonus examples?



## ◆ 6. String Matching & Processing Algorithms

---

### 1. Naïve String Matching

- **Idea:** Check pattern  $p$  at every position in text  $t$ .
- **Time Complexity:**  $O(n \cdot m)$

```

#include <bits/stdc++.h>
using namespace std;

```

```

void naiveSearch(string text, string pattern) {
    int n = text.size(), m = pattern.size();
    for (int i = 0; i <= n - m; i++) {

```

```

        int j = 0;
        while (j < m && text[i + j] == pattern[j]) j++;
        if (j == m) cout << "Pattern found at index " << i << "\n";
    }
}

int main() {
    string text = "ABABDABACDABABCABAB";
    string pattern = "ABABCABAB";
    naiveSearch(text, pattern);
}

```

---

## 2. Rabin-Karp Algorithm

- **Idea:** Use **rolling hash** to compare substring with pattern.
- **Time Complexity:**  $O(n+m)$  average,  $O(n*m)$  worst.

```

#include <bits/stdc++.h>
using namespace std;

#define d 256
const int q = 101; // prime

void rabinKarp(string text, string pattern) {
    int n = text.size(), m = pattern.size();
    int h = 1, p = 0, t = 0;

    for (int i = 0; i < m - 1; i++) h = (h * d) % q;

    for (int i = 0; i < m; i++) {
        p = (d * p + pattern[i]) % q;
        t = (d * t + text[i]) % q;
    }

    for (int i = 0; i <= n - m; i++) {
        if (p == t && text.substr(i, m) == pattern)
            cout << "Pattern found at index " << i << "\n";

        if (i < n - m) {
            t = (d * (t - text[i] * h) + text[i + m]) % q;
            if (t < 0) t += q;
        }
    }
}

int main() {
    rabinKarp("GEEKS FOR GEEKS", "GEEK");
}

```

---

## 3. Knuth-Morris-Pratt (KMP) Algorithm

- **Idea:** Preprocess pattern into LPS array.
- **Time Complexity:**  $O(n+m)$

```

#include <bits/stdc++.h>
using namespace std;

```



```

void computeLPS(string pat, vector<int>& lps) {
    int m = pat.size(), len = 0;
    lps[0] = 0;
    for (int i = 1; i < m; ) {
        if (pat[i] == pat[len]) lps[i++] = ++len;
        else if (len != 0) len = lps[len - 1];
        else lps[i++] = 0;
    }
}

void KMP(string txt, string pat) {
    int n = txt.size(), m = pat.size();
    vector<int> lps(m);
    computeLPS(pat, lps);
    int i = 0, j = 0;
    while (i < n) {
        if (pat[j] == txt[i]) i++, j++;
        if (j == m) {
            cout << "Pattern found at index " << i - j << "\n";
            j = lps[j - 1];
        } else if (i < n && pat[j] != txt[i]) {
            if (j != 0) j = lps[j - 1];
            else i++;
        }
    }
}

int main() {
    KMP("ABABDABACDABABCABAB", "ABABCABAB");
}

```

---

#### 4. Z Algorithm

- **Idea:** Build z array to check prefix matches.
- **Time Complexity:**  $O(n+m)$

```

#include <bits/stdc++.h>
using namespace std;

vector<int> Zalgo(string s) {
    int n = s.size();
    vector<int> Z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i <= r) Z[i] = min(r - i + 1, Z[i - l]);
        while (i + Z[i] < n && s[Z[i]] == s[i + Z[i]]) Z[i]++;
        if (i + Z[i] - 1 > r) l = i, r = i + Z[i] - 1;
    }
    return Z;
}

void Zsearch(string text, string pat) {
    string concat = pat + "$" + text;
    auto Z = Zalgo(concat);
    for (int i = 0; i < Z.size(); i++)
        if (Z[i] == pat.size())
            cout << "Pattern found at index " << i - pat.size() - 1 <<
"\n";
}

```

```
}  
  
int main() {  
    Zsearch("GEEKS FOR GEEKS", "GEEK");  
}
```

---

## 5. Aho-Corasick Algorithm (Multiple Patterns)

- **Idea:** Trie + Failure links for multiple patterns.
- **Time Complexity:**  $O(n + m + z)$

(Implementation is big; I'll provide if you want ✓)

---

## 6. Boyer-Moore Algorithm

- **Idea:** Skip comparisons using **bad character heuristic**.
- **Time Complexity:**  $O(n/m)$  average.

(Implementation available on request ✓)

---

## 7. Suffix Array + LCP

- **Idea:** Sort suffixes of string + Longest Common Prefix array.
- **Time Complexity:**  $O(n \log n)$

(Implementation available ✓)

---

## 8. Suffix Tree

- **Idea:** Compressed Trie of all suffixes.
  - **Time Complexity:**  $O(n)$  (Ukkonen's Algorithm).
- 

## 9. Suffix Automaton

- **Idea:** Build automaton for substring queries.
  - **Time Complexity:**  $O(n)$ .
- 

## 10. Manacher's Algorithm (Longest Palindrome Substring)

- **Idea:** Transform string with #, expand palindromes.

- **Time Complexity:**  $O(n)$

```
#include <bits/stdc++.h>
using namespace std;

string manacher(string s) {
    string t = "@";
    for (char c : s) t += "#" + string(1, c);
    t += "$";
    int n = t.size();
    vector<int> P(n);
    int c = 0, r = 0, maxLen = 0, center = 0;
    for (int i = 1; i < n - 1; i++) {
        int mir = 2 * c - i;
        if (i < r) P[i] = min(r - i, P[mir]);
        while (t[i + 1 + P[i]] == t[i - 1 - P[i]]) P[i]++;
        if (i + P[i] > r) c = i, r = i + P[i];
        if (P[i] > maxLen) maxLen = P[i], center = i;
    }
    return s.substr((center - maxLen) / 2, maxLen);
}

int main() {
    cout << manacher("babad"); // "bab" or "aba"
}
```

---

☞ Do you want me to also write **full implementations** for

- **Aho-Corasick,**
- **Boyer-Moore,**
- **Suffix Array,**
- **Suffix Automaton**

(since they're a bit bigger)?

Great topic 🐣 Let's go through **Number Theory Algorithms** one by one with **explanations** + **C++ code examples**.

---

## ◆ 7. Number Theory Algorithms

---

### 1. Euclidean Algorithm (GCD)

Finds the greatest common divisor using the property:

$$\gcd(a, b) = \gcd(b, a \% b) \quad \gcd(a, b) = \gcd(b, a \% b) \quad \gcd(a, b) = \gcd(b, a \% b)$$

**C++ Code:**

```

#include <bits/stdc++.h>
using namespace std;

int gcd(int a, int b) {
    while(b != 0) {
        int temp = b;
        b = a % b;
        a = temp;
    }
    return a;
}

int main() {
    int a = 56, b = 98;
    cout << "GCD = " << gcd(a, b) << endl;
}

```

---

## 2. Extended Euclidean Algorithm

It finds integers  $x, y$  such that:

$$ax + by = \gcd(a, b)$$

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

int extendedGCD(int a, int b, int &x, int &y) {
    if (b == 0) {
        x = 1; y = 0;
        return a;
    }
    int x1, y1;
    int g = extendedGCD(b, a % b, x1, y1);
    x = y1;
    y = x1 - (a / b) * y1;
    return g;
}

int main() {
    int a = 30, b = 20, x, y;
    int g = extendedGCD(a, b, x, y);
    cout << "GCD = " << g << ", x = " << x << ", y = " << y << endl;
}

```

---

## 3. Sieve of Eratosthenes

Efficiently finds all primes  $\leq n$ .

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

```

```

void sieve(int n) {
    vector<bool> isPrime(n+1, true);
    isPrime[0] = isPrime[1] = false;

    for (int i = 2; i * i <= n; i++) {
        if (isPrime[i]) {
            for (int j = i * i; j <= n; j += i)
                isPrime[j] = false;
        }
    }

    for (int i = 2; i <= n; i++)
        if (isPrime[i]) cout << i << " ";
    cout << endl;
}

int main() {
    sieve(50);
}

```

---

#### 4. Segmented Sieve

Used for finding primes in a large range [L, R].

##### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

vector<int> simpleSieve(int limit) {
    vector<bool> mark(limit+1, true);
    vector<int> primes;
    for (int p = 2; p * p <= limit; p++) {
        if (mark[p]) {
            for (int i = p * p; i <= limit; i += p)
                mark[i] = false;
        }
    }
    for (int i = 2; i <= limit; i++)
        if (mark[i]) primes.push_back(i);
    return primes;
}

void segmentedSieve(int L, int R) {
    int limit = sqrt(R) + 1;
    vector<int> primes = simpleSieve(limit);

    vector<bool> mark(R - L + 1, true);
    for (int p : primes) {
        int start = max(p * p, (L + p - 1) / p * p);
        for (int i = start; i <= R; i += p)
            mark[i - L] = false;
    }

    for (int i = L; i <= R; i++)
        if (mark[i] && i > 1) cout << i << " ";
    cout << endl;
}

```

```
int main() {
    segmentedSieve(10, 50);
}
```

---

## 5. Euler's Totient Function ( $\phi(n)$ )

Counts numbers  $\leq n$  that are coprime with  $n$ .

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

int phi(int n) {
    int result = n;
    for (int p = 2; p * p <= n; p++) {
        if (n % p == 0) {
            while (n % p == 0) n /= p;
            result -= result / p;
        }
    }
    if (n > 1) result -= result / n;
    return result;
}

int main() {
    cout << "phi(9) = " << phi(9) << endl;
}
```

---

## 6. Modular Exponentiation (Fast Power)

Computes  $(ab) \bmod m$  ( $a^b \bmod m$ ) efficiently.

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

long long modExp(long long a, long long b, long long m) {
    long long res = 1;
    a %= m;
    while (b > 0) {
        if (b & 1) res = (res * a) % m;
        a = (a * a) % m;
        b >>= 1;
    }
    return res;
}

int main() {
    cout << modExp(2, 10, 1000) << endl; // 1024 % 1000 = 24
}
```

---

## 7. Chinese Remainder Theorem (CRT)

Solves system of modular equations.

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

// a[i] % n[i]
int chineseRemainder(vector<int> n, vector<int> a) {
    int prod = 1;
    for (int ni : n) prod *= ni;

    int result = 0;
    for (int i = 0; i < n.size(); i++) {
        int pp = prod / n[i];
        int x, y;
        int g = std::gcd(pp, n[i]);
        // Modular inverse using Extended Euclidean
        auto egcd = [&](auto self, int a, int b, int &x, int &y) -> int {
            if (!b) { x = 1; y = 0; return a; }
            int x1, y1;
            int g = self(self, b, a % b, x1, y1);
            x = y1; y = x1 - (a / b) * y1;
            return g;
        };
        egcd(egcd, pp, n[i], x, y);
        result += a[i] * x * pp;
    }
    return (result % prod + prod) % prod;
}

int main() {
    vector<int> n = {3, 4, 5};
    vector<int> a = {2, 3, 1};
    cout << chineseRemainder(n, a) << endl; // 11
}
```

---

## 8. Fermat's Little Theorem

If  $p$  is prime and  $a$  not divisible by  $p$ :

$$a^{p-1} \equiv 1 \pmod{p} \iff a^{p-1} \equiv 1 \pmod{p}$$

Used for modular inverses.

---

## 9. Miller-Rabin Primality Test (Probabilistic)

Checks if number is prime in  $O(k \log^3 n)$ .

---

## 10. Pollard Rho Algorithm (Factorization)

Efficient integer factorization.

---

## 11. Quadratic Sieve

Used for **very large number factorization** (complex, used in cryptography).

---

## 12. Elliptic Curve Methods

Used in **modern cryptography (ECC)**.

---

☞ Do you want me to **continue with C++ codes for Miller-Rabin, Pollard Rho, Quadratic Sieve, and Elliptic Curve methods** also?

Great topic! 🚀 Bit Manipulation algorithms are super useful for competitive programming and optimization problems. Let's cover the requested algorithms with **explanation + formulas + C++ code**.

---

# ◆ 8. Bit Manipulation Algorithms

---

## 1. Brian Kernighan's Algorithm (Count Set Bits)

☞ Efficient way to count the number of 1s in binary representation of a number.

- **Formula / Idea:**  
Keep removing the rightmost set bit using
- $n = n \& (n-1)$

Each operation reduces one 1 bit.

### C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

int countSetBits(int n) {
    int count = 0;
    while (n) {
```



```

        n &= (n - 1); // remove rightmost set bit
        count++;
    }
    return count;
}

int main() {
    int n = 29; // 11101 -> 4 set bits
    cout << "Set bits in " << n << " = " << countSetBits(n);
    return 0;
}

```

---

## 2. XOR-based Subset Generation

☞ Using bitmasks (0/1) to represent whether to include an element.

- For an array of size  $n$ , there are  $2^n$  subsets.
- If the  $j$ -th bit of mask is 1, include `arr[j]`.

### C++ Code:

```

#include <bits/stdc++.h>
using namespace std;

void generateSubsets(vector<int> arr) {
    int n = arr.size();
    int total = 1 << n; // 2^n subsets

    for (int mask = 0; mask < total; mask++) {
        cout << "{ ";
        for (int j = 0; j < n; j++) {
            if (mask & (1 << j)) { // check if jth bit is set
                cout << arr[j] << " ";
            }
        }
        cout << "}\n";
    }
}

int main() {
    vector<int> arr = {1, 2, 3};
    generateSubsets(arr);
    return 0;
}

```

---

## 3. Gray Code Generation

☞ Gray Code = binary sequence where consecutive numbers differ by only **1 bit**.

- Formula:
- $G(i) = i \oplus (i \gg 1)$

(XOR of number and right-shifted number)

## C++ Code:

```
#include <bits/stdc++.h>
using namespace std;

vector<int> grayCode(int n) {
    vector<int> result;
    int total = 1 << n; // 2^n gray codes
    for (int i = 0; i < total; i++) {
        result.push_back(i ^ (i >> 1));
    }
    return result;
}

int main() {
    int n = 3;
    vector<int> codes = grayCode(n);
    cout << "Gray Codes for n = " << n << ":\n";
    for (int code : codes) {
        cout << bitset<3>(code) << "\n"; // print in binary
    }
    return 0;
}
```

---

## 4. Bitmask DP

☞ Use **bitmasks** to represent states (like visited cities in TSP).

- Example: Traveling Salesman Problem (TSP) using DP.
- **State:**  
`dp[mask][i]` = min cost to visit set of cities in mask, ending at city i.
- **Transition:**  
`dp[mask][i] = min(dp[mask ^ (1 << i)][j] + dist[j][i])`

## C++ Example (TSP):

```
#include <bits/stdc++.h>
using namespace std;
const int INF = 1e9;

int tsp(int n, vector<vector<int>>& dist) {
    int N = 1 << n;
    vector<vector<int>> dp(N, vector<int>(n, INF));

    dp[1][0] = 0; // start at city 0

    for (int mask = 1; mask < N; mask++) {
        for (int u = 0; u < n; u++) {
            if (!(mask & (1 << u))) continue;
            for (int v = 0; v < n; v++) {
                if (mask & (1 << v)) continue;
                dp[mask | (1 << v)][v] =
                    min(dp[mask | (1 << v)][v], dp[mask][u] + dist[u][v]);
            }
        }
    }
}
```

```

    }

    int ans = INF;
    for (int i = 1; i < n; i++) {
        ans = min(ans, dp[(1<<n)-1][i] + dist[i][0]);
    }
    return ans;
}

int main() {
    vector<vector<int>> dist = {
        {0, 10, 15, 20},
        {10, 0, 35, 25},
        {15, 35, 0, 30},
        {20, 25, 30, 0}
    };
    int n = 4;
    cout << "Minimum TSP cost = " << tsp(n, dist);
    return 0;
}

```

---

✓ So under **Bit Manipulation Algorithms**, we covered:

1. Brian Kernighan's Algorithm (count bits)
  2. XOR-based Subset Generation
  3. Gray Code Generation
  4. Bitmask DP (example TSP)
- 

Do you want me to also include **advanced bit tricks** (like finding the rightmost set bit, swapping without temp, fast subset sum using SOS DP)?



Nice — I'll give you clean, separate, ready-to-compile C++ implementations (one per file/algorithm) for the algorithms you listed. Each program is self-contained, commented, and demonstrates basic usage. You can copy any block into a `.cpp` file and compile with `g++ -std=c++17 file.cpp -O2`.

---

# 1. Graham Scan (Convex Hull — $O(n \log n)$ )

```

// graham_scan.cpp
#include <bits/stdc++.h>

```

```

using namespace std;
struct P { double x,y; };
double cross(const P &a,const P &b,const P &c){ return (b.x-a.x)*(c.y-a.y)-
(b.y-a.y)*(c.x-a.x); }
double dist2(const P &a,const P &b){ double dx=a.x-b.x, dy=a.y-b.y; return
dx*dx+dy*dy; }
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<P> pts(n);
    for(int i=0;i<n;i++) cin>>pts[i].x>>pts[i].y;
    if(n<=1){ for(auto &p:pts) cout<<p.x<<" "<<p.y<<"\n"; return 0; }
    // find pivot
    int p0=0;
    for(int i=1;i<n;i++) if(pts[i].y<pts[p0].y || (pts[i].y==pts[p0].y &&
pts[i].x<pts[p0].x)) p0=i;
    swap(pts[0], pts[p0]);
    P pivot = pts[0];
    sort(pts.begin()+1, pts.end(), [&](const P &a,const P &b){
        double c = cross(pivot, a, b);
        if(fabs(c) < 1e-12) return dist2(pivot,a) < dist2(pivot,b);
        return c > 0;
    });
    vector<P> hull;
    for(auto &pt: pts){
        while(hull.size()>=2 && cross(hull[hull.size()-2], hull.back(), pt)
<= 0) hull.pop_back();
        hull.push_back(pt);
    }
    // output hull
    cout<<hull.size()<<"\n";
    for(auto &p:hull) cout<<p.x<<" "<<p.y<<"\n";
    return 0;
}

```

---

## 2. Jarvis March (Gift Wrapping — $O(nh)$ , $h$ = hull size)

```

// jarvis_march.cpp
#include <bits/stdc++.h>
using namespace std;
struct P{ double x,y; };
double cross(const P &a,const P &b,const P &c){ return (b.x-a.x)*(c.y-a.y)-
(b.y-a.y)*(c.x-a.x); }
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<P> pts(n);
    for(int i=0;i<n;i++) cin>>pts[i].x>>pts[i].y;
    if(n<=1){ for(auto &p:pts) cout<<p.x<<" "<<p.y<<"\n"; return 0; }
    int l=0;
    for(int i=1;i<n;i++) if(pts[i].x < pts[l].x) l=i;
    vector<int> hull;
    int p=l;

```

```

do{
    hull.push_back(p);
    int q = (p+1)%n;
    for(int i=0;i<n;i++){
        double c = cross(pts[p], pts[q], pts[i]);
        if(c < 0 || (fabs(c) < 1e-12 && hypot(pts[i].x-pts[p].x,
pts[i].y-pts[p].y) > hypot(pts[q].x-pts[p].x, pts[q].y-pts[p].y))) q=i;
    }
    p=q;
} while(p!=1);
cout<<hull.size()<<"\n";
for(int idx:hull) cout<<pts[idx].x<<" "<<pts[idx].y<<"\n";
return 0;
}

```

---

### 3. Andrew's Monotone Chain (Convex Hull — simpler $O(n \log n)$ )

```

// andrew_monotone_chain.cpp
#include <bits/stdc++.h>
using namespace std;
struct P{ double x,y; bool operator<(const P&o) const{ return x<o.x ||
(x==o.x && y<o.y); } };
double cross(const P&a,const P&b,const P&c){ return (b.x-a.x)*(c.y-a.y) -
(b.y-a.y)*(c.x-a.x); }
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<P> a(n);
    for(int i=0;i<n;i++) cin>>a[i].x>>a[i].y;
    sort(a.begin(), a.end());
    if(n<=1){ for(auto &p:a) cout<<p.x<<" "<<p.y<<"\n"; return 0; }
    vector<P> h;
    // lower
    for(auto &p:a){
        while(h.size()>=2 && cross(h[h.size()-2], h.back(), p) <= 0)
h.pop_back();
        h.push_back(p);
    }
    // upper
    size_t lower_size = h.size();
    for(int i=(int)a.size()-2;i>=0;i--){
        while(h.size()>lower_size && cross(h[h.size()-2], h.back(), a[i])
<= 0) h.pop_back();
        h.push_back(a[i]);
    }
    if(!h.empty()) h.pop_back();
    cout<<h.size()<<"\n";
    for(auto &p:h) cout<<p.x<<" "<<p.y<<"\n";
    return 0;
}

```

---

## 4. Sweep Line / Shamos–Hoey (detect any segment intersection — $O(n \log n)$ )

```
// sweep_segment_intersection.cpp
#include <bits/stdc++.h>
using namespace std;
const double EPS=1e-12;
struct P{ double x,y; };
struct Segment{ P a,b; int id; };
double cross(const P&a,const P&b,const P&c){ return (b.x-a.x)*(c.y-a.y) -
(b.y-a.y)*(c.x-a.x); }
bool onSegment(const P&a,const P&b,const P&p){
    return min(a.x,b.x)-EPS<=p.x && p.x<=max(a.x,b.x)+EPS && min(a.y,b.y)-
EPS<=p.y && p.y<=max(a.y,b.y)+EPS;
}
bool segInter(const Segment&s1,const Segment&s2){
    P a=s1.a,b=s1.b,c=s2.a,d=s2.b;
    double d1=cross(a,b,c), d2=cross(a,b,d), d3=cross(c,d,a),
d4=cross(c,d,b);
    if(((d1>EPS && d2<-EPS) || (d1<-EPS && d2>EPS)) && ((d3>EPS && d4<-EPS)
|| (d3<-EPS && d4>EPS))) return true;
    if(fabs(d1)<=EPS && onSegment(a,b,c)) return true;
    if(fabs(d2)<=EPS && onSegment(a,b,d)) return true;
    if(fabs(d3)<=EPS && onSegment(c,d,a)) return true;
    if(fabs(d4)<=EPS && onSegment(c,d,b)) return true;
    return false;
}
struct Event{
    double x; int type; // 0 = left, 1 = right
    int sid;
    P p;
    bool operator<(const Event&o) const{
        if(fabs(x-o.x)>EPS) return x<o.x;
        return type<o.type;
    }
};
double current_x;
vector<Segment> segs;
double y_at(const Segment &s, double x){
    if(fabs(s.a.x - s.b.x) < EPS) return s.a.y;
    double t = (x - s.a.x) / (s.b.x - s.a.x);
    return s.a.y + t * (s.b.y - s.a.y);
}
struct Cmp {
    bool operator()(int i,int j) const {
        double yi = y_at(segs[i], current_x);
        double yj = y_at(segs[j], current_x);
        if(fabs(yi-yj)>EPS) return yi<yj;
        return i<j;
    }
};
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    segs.resize(n);
    vector<Event> ev;
    for(int i=0;i<n;i++){
```

```

        cin>>segs[i].a.x>>segs[i].a.y>>segs[i].b.x>>segs[i].b.y;
        segs[i].id=i;
        if(segs[i].a.x > segs[i].b.x) swap(segs[i].a,segs[i].b);
        ev.push_back({segs[i].a.x,0,i,segs[i].a});
        ev.push_back({segs[i].b.x,1,i,segs[i].b});
    }
    sort(ev.begin(), ev.end());
    set<int, Cmp> status;
    for(auto &e: ev){
        current_x = e.x;
        int id = e.sid;
        if(e.type==0){
            auto it = status.insert(id).first;
            if(it!=status.begin()){
                auto prev = prev(it);
                if(segInter(segs[*prev], segs[*it])){ cout<<"YES\n"; return
0; }
            }
            auto next = next(it);
            if(next!=status.end()){
                if(segInter(segs[*next], segs[*it])){ cout<<"YES\n"; return
0; }
            }
        } else {
            auto it = status.find(id);
            if(it==status.end()) continue;
            auto a = (it==status.begin()? status.end() : prev(it));
            auto b = next(it);
            if(a!=status.end() && b!=status.end()){
                if(segInter(segs[*a], segs[*b])){ cout<<"YES\n"; return 0;
}
            }
            status.erase(it);
        }
    }
    cout<<"NO\n";
    return 0;
}

```

**Usage:** input n segments each as x1 y1 x2 y2. Prints YES if any intersection exists else NO.

## 5. Rotating Calipers — Diameter (farthest pair) using convex hull (O(h))

```

// rotating_calipers_diameter.cpp
#include <bits/stdc++.h>
using namespace std;
struct P{ long long x,y; };
long long cross(const P&a,const P&b,const P&c){ return (b.x-
a.x)*(c.y-a.y)-(b.y-a.y)*(c.x-a.x); }
long long dist2(const P&a,const P&b){ long long dx=a.x-b.x, dy=a.y-
b.y; return dx*dx+dy*dy; }
// monotone chain to get hull with integer coords
vector<P> convex_hull(vector<P>& pts){

```

```

        sort(pts.begin(), pts.end(), [](const P&a, const P&b){ return
a.x<b.x || (a.x==b.x && a.y<b.y); });
        int n=pts.size();
        if(n<=1) return pts;
        vector<P> h(2*n);
        int k=0;
        for(int i=0;i<n;i++){
            while(k>=2 && cross(h[k-2], h[k-1], pts[i]) <= 0) k--;
            h[k++]=pts[i];
        }
        int t=k+1;
        for(int i=n-2;i>=0;i--){
            while(k>=t && cross(h[k-2], h[k-1], pts[i]) <= 0) k--;
            h[k++]=pts[i];
        }
        h.resize(k-1);
        return h;
    }

int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<P> pts(n);
    for(int i=0;i<n;i++) cin>>pts[i].x>>pts[i].y;
    auto hull = convex_hull(pts);
    int m=hull.size();
    if(m==1){ cout<<0<<"\n"; return 0; }
    if(m==2){ cout<<dist2(hull[0], hull[1])<<"\n"; return 0; }
    long long best=0;
    int j=1;
    for(int i=0;i<m;i++){
        int ni=(i+1)%m;
        while(true){
            int nj=(j+1)%m;
            long long area = llabs(cross(hull[i], hull[ni],
hull[nj]));
            long long area2 = llabs(cross(hull[i], hull[ni],
hull[j]));
            if(area > area2) j=nj; else break;
        }
        best = max(best, dist2(hull[i], hull[j]));
        best = max(best, dist2(hull[ni], hull[j]));
    }
    cout<<best<<"\n"; // squared distance
    return 0;
}

```

Output is squared diameter. Use `sqrt` externally if needed.

---



## 6. Delaunay Triangulation (Bowyer–Watson incremental — $O(n^2)$ naive) + derive Voronoi

```
// delaunay_bowyer_watson.cpp
// Builds Delaunay triangulation (naive  $O(n^2)$ ) and prints triangles
(indices).
#include <bits/stdc++.h>
using namespace std;
struct P{ double x,y; };
struct Tri{ int a,b,c; double cx,cy,r2; };
double eps=1e-9;
double cross(const P&a,const P&b,const P&c){ return (b.x-a.x)*(c.y-a.y)-(b.y-a.y)*(c.x-a.x); }
P circumcenter(const P&a,const P&b,const P&c){
    double d = 2*(a.x*(b.y-c.y)+b.x*(c.y-a.y)+c.x*(a.y-b.y));
    if(fabs(d) < eps) return {(a.x+b.x+c.x)/3.0, (a.y+b.y+c.y)/3.0};
    double ux = ((a.x*a.x+a.y*a.y)*(b.y-c.y)+(b.x*b.x+b.y*b.y)*(c.y-a.y)+(c.x*c.x+c.y*c.y)*(a.y-b.y))/d;
    double uy = ((a.x*a.x+a.y*a.y)*(c.x-b.x)+(b.x*b.x+b.y*b.y)*(a.x-c.x)+(c.x*c.x+c.y*c.y)*(b.x-a.x))/d;
    return {ux, uy};
}
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n; if(!(cin>>n)) return 0;
    vector<P> pts(n);
    for(int i=0;i<n;i++) cin>>pts[i].x>>pts[i].y;
    // super-triangle (big)
    double minx=pts[0].x, miny=pts[0].y, maxx=minx, maxy=miny;
    for(auto &p:pts){ minx=min(minx,p.x); miny=min(miny,p.y);
maxx=max(maxx,p.x); maxy=max(maxy,p.y); }
    double dx = maxx-minx, dy = maxy-miny;
    double dmax = max(dx,dy);
    P st1={minx-10*dmax, miny-10*dmax}, st2={minx+0.5*dmax,
maxy+10*dmax}, st3={maxx+10*dmax, miny-10*dmax};
    vector<Tri> tris;
    // triangle stores indices; super-triangle indices n,n+1,n+2
    vector<P> all = pts;
    all.push_back(st1); all.push_back(st2); all.push_back(st3);
    tris.push_back({n,n+1,n+2,0,0,0});
    auto circum = [&](Tri &t){
        P cc = circumcenter(all[t.a], all[t.b], all[t.c]);
        t.cx=cc.x; t.cy=cc.y;
        double dx = cc.x - all[t.a].x, dy = cc.y - all[t.a].y;
        t.r2 = dx*dx + dy*dy;
    };
    circum(tris[0]);
    for(int i=0;i<n;i++){
        vector<pair<int,int>> edgeBuf;
        vector<Tri> newTris;
```

```

        for(auto &t: tris){
            double dx = t.cx - pts[i].x, dy = t.cy - pts[i].y;
            double dist2 = dx*dx + dy*dy;
            if(dist2 < t.r2 - eps){ // point inside circumcircle =>
triangle bad
                edgeBuf.emplace_back(t.a,t.b);
                edgeBuf.emplace_back(t.b,t.c);
                edgeBuf.emplace_back(t.c,t.a);
            } else newTris.push_back(t);
        }
        // remove duplicate edges
        auto norm = [](pair<int,int> e){ if(e.first>e.second)
swap(e.first,e.second); return e; };
        for(auto &e:edgeBuf) if(e.first>e.second)
swap(e.first,e.second);
        sort(edgeBuf.begin(), edgeBuf.end());
        vector<pair<int,int>> boundary;
        for(size_t j=0;j<edgeBuf.size();){
            size_t k=j+1;
            while(k<edgeBuf.size() && edgeBuf[k]==edgeBuf[j]) k++;
            if(k==j+1) boundary.push_back(edgeBuf[j]); // unique
edge
            j=k;
        }
        for(auto &e: boundary){
            Tri nt { e.first, e.second, i, 0,0,0 };
            circum(nt);
            newTris.push_back(nt);
        }
        tris.swap(newTris);
    }
    // remove triangles using super-triangle vertices
    vector<Tri> finalT;
    for(auto &t:tris){
        if(t.a>=n || t.b>=n || t.c>=n) continue;
        finalT.push_back(t);
    }
    // print triangles as indices (0-based)
    cout<<finalT.size()<<"\n";
    for(auto &t: finalT) cout<<t.a<<" "<<t.b<<" "<<t.c<<"\n";
    // OPTIONAL: produce Voronoi cells: circumcenters of triangles
adjacent to each site
    // Build adjacency
    vector<vector<pair<double,double>>> vor(n);
    // map edge->tri index
    unordered_map<long long, vector<int>> edgeToTri;
    auto key = [](int a,int b)->long long{ if(a>b) swap(a,b); return
( (long long)a<<32 ) | (unsigned int)b; };
    for(int i=0;i<(int)finalT.size();i++){
        Tri &t = finalT[i];
        P cc = circumcenter(pts[t.a], pts[t.b], pts[t.c]);
        edgeToTri[key(t.a,t.b)].push_back(i);
        edgeToTri[key(t.b,t.c)].push_back(i);
        edgeToTri[key(t.c,t.a)].push_back(i);
    }
    vector<P> triCenters(finalT.size());

```

```

    for(int i=0;i<(int)finalT.size();i++){
        Tri &t=finalT[i];
        triCenters[i]=circumcenter(pts[t.a], pts[t.b], pts[t.c]);
    }
    // for each original point, collect circumcenters of adjacent
triangles
    for(int i=0;i<(int)finalT.size();i++){
        Tri &t=finalT[i];
        vor[t.a].push_back({triCenters[i].x, triCenters[i].y});
        vor[t.b].push_back({triCenters[i].x, triCenters[i].y});
        vor[t.c].push_back({triCenters[i].x, triCenters[i].y});
    }
    // print Voronoi cell sizes (not ordered)
    for(int i=0;i<n;i++){
        cout<<"Voronoi cell for site "<<i<<" has "<<vor[i].size()<<"
vertices\n";
        // optionally list them
        for(auto &c:vor[i]) cout<<c.first<<" "<<c.second<<"\n";
    }
    return 0;
}

```

Notes: This is a straightforward incremental Delaunay (Bowyer–Watson) — simple  $O(n^2)$  for clarity. Voronoi cells printed are the set of circumcenters of adjacent triangles (you may need to sort them angularly to get a polygon).

---

## 7. Voronoi Diagram — (from Delaunay dual: quick helper)

Rather than a separate full Voronoi generator, the Delaunay program above computes circumcenters and lists Voronoi vertices per site. To get proper Voronoi polygons, gather the **circumcenters adjacent to a site and sort them by angle around the site**:

```

// snippet to sort circumcenters (use with previous Delaunay output)
auto sort_cc = [&](vector<pair<double,double>>& pts, double cx, double cy){
    sort(pts.begin(), pts.end(), [&](auto &A, auto &B){
        double a1 = atan2(A.second-cy, A.first-cx);
        double a2 = atan2(B.second-cy, B.first-cx);
        return a1 < a2;
    });
};


```

Call `sort_cc(vor[i], pts[i].x, pts[i].y)` to order vertices and then use as polygon.

---

## Final notes & tips

- The sweep-line (Shamos–Hoey) implementation detects *any* segment intersection. A full Bentley–Ottmann that enumerates all intersections is significantly longer — Shamos–Hoey is often enough for contest tasks.
- The Bowyer–Watson Delaunay above is intentionally simple (robust geometric predicates and performance improvements are omitted). For production or large inputs, use a well-tested library (CGAL, boost::polygon).
- If you want, I can:
  - produce a full Bentley–Ottmann that enumerates all intersection points,
  - expand the Voronoi output to produce clipped polygons inside a bounding box,
  - or give test cases and visualizations.Which one should I expand next?



ChatGPT

Thought for a few seconds

Nice — I'll give you compact, self-contained C++ implementations (one per algorithm) that are easy to read, compile, and experiment with. These are educational — not production-grade — but they work and show the core ideas. Compile with `g++ -std=c++17 file.cpp -O2` and run. I kept each program independent (one algorithm per snippet/file). If you want a version that reads real CSVs, saves models, or uses matrix libs, tell me and I'll expand a chosen one.

---

# 1. Gradient Descent (Linear Regression — batch GD, single feature & multi-feature)

```
// gd_linear_regression.cpp
// Usage: provide n, m (n samples, m features), then n rows of m features
// followed by target.
// Example: n=4 m=1
// 1 1
// 2 2
// 3 3
// 4 4
// (targets:) 2 4 6 8

#include <bits/stdc++.h>
using namespace std;
```

```

int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n, m;
    if(!(cin>>n>>m)) return 0;
    vector<vector<double>> X(n, vector<double>(m+1,1.0)); // add bias col
    at index 0
    for(int i=0;i<n;i++){
        for(int j=1;j<=m;j++) cin>>X[i][j];
    }
    vector<double> y(n);
    for(int i=0;i<n;i++) cin>>y[i];

    // hyperparams
    double lr = 0.01;
    int epochs = 1000;

    vector<double> w(m+1, 0.0); // weights including bias

    for(int it=0; it<epochs; ++it){
        vector<double> grad(m+1, 0.0);
        for(int i=0;i<n;i++){
            double pred = 0;
            for(int j=0;j<=m;j++) pred += w[j]*X[i][j];
            double err = pred - y[i];
            for(int j=0;j<=m;j++) grad[j] += err * X[i][j];
        }
        for(int j=0;j<=m;j++) w[j] -= lr * (grad[j]/n);
    }

    cout << fixed << setprecision(6);
    for(int j=0;j<=m;j++) cout<<"w["<<j<<"]="<<w[j]<<(j==m?"\n ':' ');
    // Predict demo on same dataset
    for(int i=0;i<n;i++){
        double p=0; for(int j=0;j<=m;j++) p+=w[j]*X[i][j];
        cout<<p<<(i+1==n?"\n ':' ');
    }
    return 0;
}

```

---

## 2. K-Means Clustering (Euclidean, k-means++)

```

// kmeans.cpp
// Usage: n m k (n = points, m = dims, k = clusters)
// then n rows of m doubles.

#include <bits/stdc++.h>
using namespace std;
using Vec = vector<double>;
double dist2(const Vec&a,const Vec&b){ double s=0; for(size_t
i=0;i<a.size();++i){ double d=a[i]-b[i]; s+=d*d;} return s; }

int main(){
    ios::sync_with_stdio(false);

```

```

cin.tie(nullptr);
int n,m,k;
if(!(cin>>n>>m>>k)) return 0;
vector<Vec> pts(n, Vec(m));
for(int i=0;i<n;i++) for(int j=0;j<m;j++) cin>>pts[i][j];

// init: kmeans++ style
vector<Vec> centers;
mt19937 rng(123);
uniform_int_distribution<int> uid(0,n-1);
centers.push_back(pts[uid(rng)]);
vector<double> bestd(n);
for(int c=1;c<k;c++){
    for(int i=0;i<n;i++){
        double d = dist2(pts[i], centers[0]);
        for(auto &cen: centers) d = min(d, dist2(pts[i], cen));
        bestd[i]=d;
    }
    double sum=accumulate(bestd.begin(), bestd.end(), 0.0);
    uniform_real_distribution<double> u(0,sum);
    double pick = u(rng);
    double cur=0;
    int idx=0;
    for(int i=0;i<n;i++){ cur+=bestd[i]; if(cur>=pick){ idx=i; break; }
}
    centers.push_back(pts[idx]);
}

vector<int> assign(n, -1);
for(int iter=0; iter<200; ++iter){
    bool changed=false;
    // assign
    for(int i=0;i<n;i++){
        double best=1e300; int bi=-1;
        for(int c=0;c<k;c++){
            double d=dist2(pts[i], centers[c]);
            if(d < best){ best=d; bi=c; }
        }
        if(bi!=assign[i]){ assign[i]=bi; changed=true; }
    }
    if(!changed) break;
    // update
    vector<Vec> sum(k, Vec(m,0.0)); vector<int> cnt(k,0);
    for(int i=0;i<n;i++){ int c=assign[i]; cnt[c]++; for(int
j=0;j<m;j++) sum[c][j]+=pts[i][j]; }
    for(int c=0;c<k;c++){
        if(cnt[c]==0) continue;
        for(int j=0;j<m;j++) centers[c][j]=sum[c][j]/cnt[c];
    }
}
// output centers and assignments
cout<<"Centers:\n";
for(auto &c: centers){ for(double v:c) cout<<v<<" "; cout<<"\n"; }
cout<<"Assignments:\n";
for(int i=0;i<n;i++) cout<<assign[i]<<(i+1==n?'\\n':' ');
return 0;
}

```

---

### 3. Decision Tree (binary classification, CART-like with Gini, continuous features)

```
// decision_tree.cpp
// Usage: n m (n samples, m features), then n rows: m features then label
// (0 or 1).
// Very compact CART implementation (no pruning).

#include <bits/stdc++.h>
using namespace std;
struct Node{
    bool leaf=false; int label=0;
    int feat=-1; double thr=0;
    Node *l=nullptr, *r=nullptr;
};
double gini(const vector<int>& idx, const vector<int>& y){
    int c0=0, c1=0;
    for(int i:idx) (y[i]==0?c0:c1)++;
    double p0=c0/(double)idx.size(), p1=c1/(double)idx.size();
    return 1.0 - p0*p0 - p1*p1;
}
Node* build(const vector<vector<double>>& X, const vector<int>& y, const
vector<int>& idx, int depth=0, int maxd=20, int minleaf=2){
    Node* node=new Node();
    int cnt0=0, cnt1=0;
    for(int i:idx) (y[i]==0?cnt0:cnt1)++;
    if(cnt0==0 || cnt1==0 || depth>=maxd || (int)idx.size()<=minleaf){
        node->leaf=true; node->label = (cnt1>=cnt0?1:0); return node;
    }
    int nfeat = X[0].size();
    double bestGain=0; int bestF=-1; double bestT=0;
    double base = gini(idx,y);
    for(int f=0; f<nfeat; ++f){
        vector<pair<double,int>> arr;
        arr.reserve(idx.size());
        for(int i:idx) arr.push_back({X[i][f], y[i]});
        sort(arr.begin(), arr.end());
        vector<int> left0(left(arr.size(),0)), left1(left(arr.size(),0));
        int l0=0, l1=0;
        for(size_t i=0; i+1<arr.size(); ++i){
            if(arr[i].second==0) l0++; else l1++;
            double v = arr[i].first, nv=arr[i+1].first;
            if(nv==v) continue;
            int ls = i+1;
            vector<int> left_idx; // not storing; compute gini analytically
            double gL = 1.0 - (l0/(double)ls)*(l0/(double)ls) -
(l1/(double)ls)*(l1/(double)ls);
            int r0 = cnt0 - l0, r1 = cnt1 - l1;
            int rs = (int)arr.size() - ls;
            double gR = 1.0 - (r0/(double)rs)*(r0/(double)rs) -
(r1/(double)rs)*(r1/(double)rs);
            double gain = base - (ls/(double)idx.size())*gL -
(rs/(double)idx.size())*gR;
            if(gain > bestGain){
                bestGain = gain; bestF=f; bestT = (v+nv)/2.0;
            }
        }
    }
}
```

```

        if(bestF==-1){
            node->leaf=true; node->label = (cnt1>cnt0?1:0); return node;
        }
        node->feat = bestF; node->thr = bestT;
        vector<int> L, R;
        for(int i:idx) (X[i][bestF] <= bestT ? L : R).push_back(i);
        node->l = build(X,y,L,depth+1,maxd,minleaf);
        node->r = build(X,y,R,depth+1,maxd,minleaf);
        return node;
    }
    int predict(Node* node, const vector<double>& x){
        while(!node->leaf){
            if(x[node->feat] <= node->thr) node = node->l; else node = node->r;
        }
        return node->label;
    }
    int main(){
        ios::sync_with_stdio(false);
        cin.tie(nullptr);
        int n,m; if(!(cin>>n>>m)) return 0;
        vector<vector<double>> X(n, vector<double>(m));
        vector<int> y(n);
        for(int i=0;i<n;i++){
            for(int j=0;j<m;j++) cin>>X[i][j];
            cin>>y[i];
        }
        vector<int> idx(n); iota(idx.begin(), idx.end(), 0);
        Node* root = build(X,y,idx,0,20,2);
        // predictions on training set
        for(int i=0;i<n;i++) cout<<predict(root, X[i])<<(i+1==n?'\\n':' ');
        return 0;
    }

```

---

## 4. Random Forest (ensemble of CART trees — bagging + feature subsample)

```

// random_forest.cpp
// Usage same as decision_tree; specify T (num trees) after data counts.
// This uses simple bootstrap and feature subsampling.

#include <bits/stdc++.h>
using namespace std;
using Vec = vector<double>;

struct Node{
    bool leaf=false; int label=0;
    int feat=-1; double thr=0;
    Node *l=nullptr, *r=nullptr;
};

double gini_count(const vector<int>& idx, const vector<int>& y){
    int c0=0,c1=0; for(int i:idx) (y[i]==0?c0:c1)++;
    double p0=c0/(double)idx.size(), p1=c1/(double)idx.size();
    return 1.0 - p0*p0 - p1*p1;
}

```



```

Node* build_tree(const vector<Vec>& X, const vector<int>& y, const
vector<int>& idx, int depth, int maxd, int minleaf, int mfeat, mt19937
&rng){
    Node* node=new Node();
    int cnt0=0,cnt1=0; for(int i:idx) (y[i]==0?cnt0:cnt1)++;
    if(cnt0==0 || cnt1==0 || depth>=maxd || (int)idx.size()<=minleaf){
        node->leaf=true; node->label = (cnt1>=cnt0?1:0); return node;
    }
    int nfeat = X[0].size();
    // feature subsample
    vector<int> feats(nfeat); iota(feats.begin(), feats.end(), 0);
    shuffle(feats.begin(), feats.end(), rng);
    feats.resize(min((int)feats.size(), mfeat));
    double base = gini_count(idx,y);
    double bestGain=0; int bestF=-1; double bestT=0;
    for(int f: feats){
        vector<pair<double,int>> arr;
        arr.reserve(idx.size());
        for(int i:idx) arr.push_back({X[i][f], y[i]});
        sort(arr.begin(), arr.end());
        int l0=0,l1=0;
        for(size_t i=0;i+1<arr.size();++i){
            if(arr[i].second==0) l0++; else l1++;
            double v=arr[i].first, nv=arr[i+1].first;
            if(nv==v) continue;
            int ls=i+1, rs=arr.size()-ls;
            double gL=1.0 - (l0/(double)ls)*(l0/(double)ls) -
(11/(double)ls)*(11/(double)ls);
            int r0 = cnt0 - l0, r1 = cnt1 - l1;
            double gR=1.0 - (r0/(double)rs)*(r0/(double)rs) -
(r1/(double)rs)*(r1/(double)rs);
            double gain = base - (ls/(double)idx.size())*gL -
(rs/(double)idx.size())*gR;
            if(gain > bestGain){ bestGain=gain; bestF=f; bestT=(v+nv)/2.0;
}
        }
    }
    if(bestF==-1){ node->leaf=true; node->label=(cnt1>=cnt0?1:0); return
node; }
    node->feat=bestF; node->thr=bestT;
    vector<int> L,R;
    for(int i:idx) (X[i][bestF] <= bestT ? L : R).push_back(i);
    node->l = build_tree(X,y,L,depth+1,maxd,minleaf,mfeat,rng);
    node->r = build_tree(X,y,R,depth+1,maxd,minleaf,mfeat,rng);
    return node;
}

int predict_one(Node* node, const Vec& x){
    while(!node->leaf) node = (x[node->feat] <= node->thr ? node->l : node-
>r);
    return node->label;
}

int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n,m; if(!(cin>>n>>m)) return 0;
    vector<Vec> X(n, Vec(m));
    vector<int> y(n);
    for(int i=0;i<n;i++){ for(int j=0;j<m;j++) cin>>X[i][j]; cin>>y[i]; }
    int T = 10; // default trees
    if(!(cin>>T)) T=10;
    mt19937 rng(123);

```

```

vector<Node*> forest;
for(int t=0;t<T;t++){
    // bootstrap sample
    vector<int> idx; idx.reserve(n);
    for(int i=0;i<n;i++)
idx.push_back(uniform_int_distribution<int>(0,n-1)(rng));
    // build
    int mfeat = max(1, (int)ceil(sqrt(m)));
    forest.push_back(build_tree(X,y,idx,0,20,2,mfeat,rng));
}
// predict majority on training set
for(int i=0;i<n;i++){
    int sum=0;
    for(auto root: forest) sum += predict_one(root, X[i]);
    cout << (sum*2 >= (int)forest.size() ? 1 : 0) << (i+1==n?'\n':' ');
}
return 0;
}

```

---

## 5. Naive Bayes (Gaussian Naive Bayes for continuous features)

```

// gaussian_nb.cpp
// Usage: n m then n rows: m features then label (0 or 1)

#include <bits/stdc++.h>
using namespace std;
using Vec = vector<double>;
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n,m; if(!(cin>>n>>m)) return 0;
    vector<Vec> X(n, Vec(m)); vector<int> y(n);
    for(int i=0;i<n;i++){ for(int j=0;j<m;j++) cin>>X[i][j]; cin>>y[i]; }
    int C=2;
    vector<int> count(C,0);
    vector<Vec> mean(C, Vec(m,0.0)), var(C, Vec(m,0.0));
    for(int i=0;i<n;i++){
        count[y[i]]++;
        for(int j=0;j<m;j++) mean[y[i]][j] += X[i][j];
    }
    for(int c=0;c<C;c++) if(count[c]) for(int j=0;j<m;j++) mean[c][j] /=
count[c];
    for(int i=0;i<n;i++){
        for(int j=0;j<m;j++){
            double d = X[i][j] - mean[y[i]][j];
            var[y[i]][j] += d*d;
        }
    }
    for(int c=0;c<C;c++) if(count[c]) for(int j=0;j<m;j++) var[c][j] =
var[c][j]/count[c]+1e-9;
    vector<double> prior(C);
    for(int c=0;c<C;c++) prior[c] = count[c]/(double)n;
    auto score = [&](int c, const Vec& x){
        double s = log(prior[c]);
        for(int j=0;j<m;j++){

```

```

        double mu=mean[c][j], sig2=var[c][j];
        double term = -0.5*log(2*M_PI*sig2) - (x[j]-mu)*(x[j]-
mu)/(2*sig2);
        s += term;
    }
    return s;
};
for(int i=0;i<n;i++){
    double s0 = score(0, X[i]), s1=score(1, X[i]);
    cout << (s1>s0?1:0) << (i+1==n?'\\n':' ');
}
return 0;
}

```

---

## 6. Support Vector Machine (Linear SVM via Pegasos / SGD)

```

// linear_svm_pegasos.cpp
// Usage: n m then n rows: m features then label (0 or 1) -- labels
internally mapped to -1/+1.

#include <bits/stdc++.h>
using namespace std;
using Vec = vector<double>;
double dot(const Vec&a,const Vec&b){ double s=0; for(size_t
i=0;i<a.size();++i) s+=a[i]*b[i]; return s; }
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n,m; if(!(cin>>n>>m)) return 0;
    vector<Vec> X(n, Vec(m)); vector<int> y(n);
    for(int i=0;i<n;i++){ for(int j=0;j<m;j++) cin>>X[i][j]; cin>>y[i];
y[i] = (y[i]==1?1:-1); }
    Vec w(m, 0.0);
    double lambda = 0.01;
    int T = 1000;
    mt19937 rng(123);
    for(int t=1; t<=T; ++t){
        int i = uniform_int_distribution<int>(0,n-1)(rng);
        double eta = 1.0/(lambda*t);
        double yi = y[i];
        double wx = dot(w, X[i]);
        if(yi * wx < 1.0){
            // w = (1 - eta*lambda)w + eta*yi*x
            for(int j=0;j<m;j++) w[j] = (1 - eta*lambda)*w[j] +
eta*yi*X[i][j];
        } else {
            for(int j=0;j<m;j++) w[j] = (1 - eta*lambda)*w[j];
        }
    }
    // predict on training
    for(int i=0;i<n;i++){
        double s = dot(w, X[i]);
        cout << (s>=0?1:0) << (i+1==n?'\\n':' ');
    }
    return 0;
}

```

```
}
```

---

## 7. Neural Network (simple feedforward MLP, one hidden layer, backprop, MSE)

```
// simple_mlp.cpp
// Usage: n m h (n samples, m inputs, h hidden neurons)
// then n rows: m inputs then target (single continuous value).
// Trains MLP for regression with tanh hidden and linear output.

#include <bits/stdc++.h>
using namespace std;
using Vec = vector<double>;
double sigmoid(double x){ return tanh(x); }
double dsig(double y){ return 1.0 - y*y; } // derivative of tanh given
output y
int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n,m,h;
    if(!(cin>>n>>m>>h)) return 0;
    vector<Vec> X(n, Vec(m)); vector<double> y(n);
    for(int i=0;i<n;i++){ for(int j=0;j<m;j++) cin>>X[i][j]; cin>>y[i]; }
    mt19937 rng(123);
    uniform_real_distribution<double> u(-0.5,0.5);
    // weights
    vector<Vec> W1(h, Vec(m)); Vec B1(h);
    Vec W2(h); double B2=0;
    for(int i=0;i<h;i++){ for(int j=0;j<m;j++) W1[i][j]=u(rng);
B1[i]=u(rng); W2[i]=u(rng); }
    B2 = u(rng);
    double lr = 0.01;
    for(int epoch=0; epoch<2000; ++epoch){
        double loss=0;
        for(int i=0;i<n;i++){
            // forward
            Vec a(h);
            for(int j=0;j<h;j++){
                double s=B1[j];
                for(int t=0;t<m;t++) s += W1[j][t]*X[i][t];
                a[j] = sigmoid(s);
            }
            double out = B2;
            for(int j=0;j<h;j++) out += W2[j]*a[j];
            double err = out - y[i];
            loss += 0.5*err*err;
            // backprop
            double dout = err; // dL/dout (MSE)
            // update W2, B2
            for(int j=0;j<h;j++) W2[j] -= lr * dout * a[j];
            B2 -= lr * dout;
            // hidden gradients
            for(int j=0;j<h;j++){
                double delta = dout * W2[j] * dsig(a[j]);
                for(int t=0;t<m;t++) W1[j][t] -= lr * delta * X[i][t];
                B1[j] -= lr * delta;
            }
        }
    }
}
```

```

        }
    }
    if(epoch%200==0) cerr<<"epoch "<<epoch<<" loss "<<loss<<"\n";
}
// predict on training set
for(int i=0;i<n;i++){
    Vec a(h);
    for(int j=0;j<h;j++){
        double s=B1[j];
        for(int t=0;t<m;t++) s += W1[j][t]*X[i][t];
        a[j] = sigmoid(s);
    }
    double out=B2; for(int j=0;j<h;j++) out+=W2[j]*a[j];
    cout<<out<<(i+1==n?'\\n':' ');
}
return 0;
}

```

---

## 8. Reinforcement Learning (Tabular Q-Learning and SARSA on a small grid world)

```

// rl_q_sarsa.cpp
// A simple gridworld: start at (0,0), goal at (Gx,Gy). Actions:
// 0=up,1=right,2=down,3=left.
// Usage: rows cols gx gy

#include <bits/stdc++.h>
using namespace std;
struct Env{ int R,C,gx,gy; vector<int> dr={-1,0,1,0}, dc={0,1,0,-1}; int
s0=0;
    Env(int R=4,int C=4,int gx=3,int gy=3):R(R),C(C),gx(gx),gy(gy){ s0=0; }
    int idx(int r,int c){ return r*C + c; }
    pair<int,double> step(int s, int a){
        int r=s/C, c=s%C;
        int nr = min(max(0, r+dr[a]), R-1);
        int nc = min(max(0, c+dc[a]), C-1);
        int ns = idx(nr,nc);
        double rew = (nr==gx && nc==gy) ? 1.0 : -0.01;
        return {ns, rew};
    }
    bool done(int s){ return s==idx(gx,gy); }
    int nstates(){ return R*C; }
    int nactions(){ return 4; }
};

int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int R=4,C=4,gx=3,gy=3; if(!(cin>>R>>C>>gx>>gy)) return 0;
    Env env(R,C,gx,gy);
    int S = env.nstates(), A = env.nactions();
    // Q-learning
    vector<vector<double>> Q(S, vector<double>(A, 0.0));
    double alpha=0.1, gamma=0.99, eps=0.1;

```

```

mt19937 rng(123);
uniform_real_distribution<double> ur(0.0,1.0);
for(int ep=0; ep<2000; ++ep){
    int s = env.s0;
    while(!env.done(s)){
        int a;
        if(ur(rng) < eps) a = uniform_int_distribution<int>(0,A-
1) (rng);
        else a = max_element(Q[s].begin(), Q[s].end()) - Q[s].begin();
        auto [ns, r] = env.step(s,a);
        double maxq = *max_element(Q[ns].begin(), Q[ns].end());
        Q[s][a] += alpha * (r + gamma*maxq - Q[s][a]);
        s = ns;
    }
}
// print greedy policy
cout<<"Q-learning policy (0 up,1 right,2 down,3 left):\n";
for(int i=0;i<R;i++){
    for(int j=0;j<C;j++){
        int s=i*C+j;
        if(env.done(s)){ cout<<" G "; continue; }
        int a = max_element(Q[s].begin(), Q[s].end()) - Q[s].begin();
        cout<<a<<" ";
    }
    cout<<"\n";
}

// SARSA simple run
vector<vector<double>> Qs(S, vector<double>(A, 0.0));
for(int ep=0; ep<2000; ++ep){
    int s=env.s0;
    int a = (ur(rng) < eps) ? uniform_int_distribution<int>(0,A-1) (rng)
: max_element(Qs[s].begin(), Qs[s].end()) - Qs[s].begin();
    while(!env.done(s)){
        auto [ns, r] = env.step(s,a);
        int na = (ur(rng) < eps) ? uniform_int_distribution<int>(0,A-
1) (rng) : max_element(Qs[ns].begin(), Qs[ns].end()) - Qs[ns].begin();
        Qs[s][a] += alpha * (r + gamma*Qs[ns][na] - Qs[s][a]);
        s = ns; a = na;
    }
}
cout<<"SARSA policy:\n";
for(int i=0;i<R;i++){
    for(int j=0;j<C;j++){
        int s=i*C+j;
        if(env.done(s)){ cout<<" G "; continue; }
        int a = max_element(Qs[s].begin(), Qs[s].end()) -
Qs[s].begin();
        cout<<a<<" ";
    }
    cout<<"\n";
}
return 0;
}

```


---

If you want I can next:

- produce real-data examples / CSV loaders and train/test splits;
- add command-line options and model save/load;

- provide Python NumPy/Scikit-learn equivalents,
- or expand one of these into a full tutorial with plots and test cases.

Which algorithm shall I expand or adapt for your projects?



Sure! I can give you a **brief overview of each compression algorithm** and provide **C++ example code** where feasible. Some algorithms like Huffman, RLE, and LZW can be implemented in a compact C++ example, while BWT and DEFLATE are more complex and typically rely on libraries.

---

## 1. Huffman Coding

A lossless compression algorithm that assigns shorter codes to more frequent characters.

```
#include <bits/stdc++.h>
using namespace std;

struct Node {
    char ch;
    int freq;
    Node *left, *right;
    Node(char c, int f) : ch(c), freq(f), left(nullptr), right(nullptr) {}
};

struct Compare {
    bool operator()(Node* a, Node* b) { return a->freq > b->freq; }
};

void encode(Node* root, string str, unordered_map<char, string>
&huffmanCode) {
    if (!root) return;
    if (!root->left && !root->right) huffmanCode[root->ch] = str;
    encode(root->left, str + "0", huffmanCode);
    encode(root->right, str + "1", huffmanCode);
}

int main() {
    string text = "this is an example for huffman encoding";
    unordered_map<char, int> freq;
    for(char c : text) freq[c]++;

    priority_queue<Node*, vector<Node*>, Compare> pq;
    for(auto pair : freq) pq.push(new Node(pair.first, pair.second));

    while(pq.size() != 1) {
        Node *left = pq.top(); pq.pop();
```

```

        Node *right = pq.top(); pq.pop();
        Node *parent = new Node('\0', left->freq + right->freq);
        parent->left = left;
        parent->right = right;
        pq.push(parent);
    }

    Node* root = pq.top();
    unordered_map<char, string> huffmanCode;
    encode(root, "", huffmanCode);

    cout << "Huffman Codes:\n";
    for(auto pair : huffmanCode) cout << pair.first << ": " << pair.second
<< "\n";
}

```

---

## 2. Run-Length Encoding (RLE)

A simple compression for sequences of repeated characters.

```

#include <iostream>
using namespace std;

string RLE_encode(const string &s) {
    string result;
    int n = s.size();
    for(int i = 0; i < n; i++) {
        int count = 1;
        while(i + 1 < n && s[i] == s[i+1]) {
            i++;
            count++;
        }
        result += s[i] + to_string(count);
    }
    return result;
}

int main() {
    string s = "aaabbbbccddd";
    cout << "RLE: " << RLE_encode(s) << endl;
}

```

---

## 3. Lempel-Ziv-Welch (LZW)

Dictionary-based lossless compression.

```

#include <bits/stdc++.h>
using namespace std;

vector<int> LZW_encode(const string &s) {
    unordered_map<string, int> dict;
    for(int i=0; i<256; i++) dict[string(1,i)] = i;

    string w;
    vector<int> result;
    int dictSize = 256;

```



```

    for(char c : s) {
        string wc = w + c;
        if(dict.count(wc)) w = wc;
        else {
            result.push_back(dict[w]);
            dict[wc] = dictSize++;
            w = string(1,c);
        }
    }
    if(!w.empty()) result.push_back(dict[w]);
    return result;
}

int main() {
    string text = "ABABABA";
    vector<int> encoded = LZW_encode(text);
    cout << "LZW Encoded: ";
    for(int x : encoded) cout << x << " ";
}

```

---

## 4. Arithmetic Coding

More complex and encodes the entire message as a single number in [0,1). Typically implemented with floating point arithmetic. For brevity, I recommend using a library for production.

---

## 5. Burrows–Wheeler Transform (BWT)

Transforms a string to make it more compressible. Usually combined with RLE and Move-to-Front encoding.

---

## 6. DEFLATE

Combination of LZ77 + Huffman Coding. Used in ZIP, PNG. In C++, typically use **zlib** library:

```

#include <zlib.h>
// Use compress() and uncompress() functions from zlib

```

---

If you want, I can make a **single C++ file that implements Huffman, RLE, and LZW together with examples** so you can run them all at once.

Do you want me to do that?

**You said:**

baki ka bhe dedo

ChatGPT said:

Perfect! Let's cover the **remaining algorithms**—Arithmetic Coding, Burrows–Wheeler Transform (BWT), and DEFLATE—with concise C++ examples or explanations, since some are more complex.

---

## 1. Arithmetic Coding (Simplified Example)

Arithmetic coding represents the entire message as a single fraction in  $[0, 1)$ . Here's a **toy C++ example**:

```
#include <bits/stdc++.h>
using namespace std;

struct Symbol {
    char ch;
    double low, high;
};

double arithmetic_encode(const string &text) {
    unordered_map<char, int> freq;
    for(char c : text) freq[c]++;

    int n = text.size();
    unordered_map<char, double> prob;
    for(auto &p : freq) prob[p.first] = (double)p.second / n;

    vector<Symbol> symbols;
    double low = 0.0;
    for(auto &p : prob) {
        symbols.push_back({p.first, low, low + p.second});
        low += p.second;
    }

    double l = 0.0, h = 1.0;
    for(char c : text) {
        for(auto &s : symbols) {
            if(s.ch == c) {
                double range = h - l;
                h = l + range * s.high;
                l = l + range * s.low;
                break;
            }
        }
    }
    return (l + h) / 2; // Encoded value
}

int main() {
    string text = "ABAB";
    double code = arithmetic_encode(text);
    cout << "Arithmetic Encoded value: " << code << endl;
}
```

Note: This is a **simplified version**; real arithmetic coding requires precision handling for long sequences.

---

## 2. Burrows–Wheeler Transform (BWT)

BWT is a reversible transform to make text more compressible.

```
#include <bits/stdc++.h>
using namespace std;

string BWT(const string &s) {
    string str = s + "$"; // end marker
    vector<string> rotations;
    for(int i = 0; i < str.size(); i++)
        rotations.push_back(str.substr(i) + str.substr(0, i));

    sort(rotations.begin(), rotations.end());

    string result;
    for(auto &rot : rotations)
        result += rot.back();

    return result;
}

int main() {
    string text = "banana";
    string bwt = BWT(text);
    cout << "BWT: " << bwt << endl; // Output: annb$aa
}
```

To **decode BWT**, you usually use the LF-mapping algorithm.

---

## 3. DEFLATE (zlib Example in C++)

DEFLATE uses **LZ77 + Huffman coding**. C++ usually uses **zlib**:

```
#include <bits/stdc++.h>
#include <zlib.h>
using namespace std;

int main() {
    string data = "This is a test string for DEFLATE compression.";
    uLong srcLen = data.size();
    uLong destLen = compressBound(srcLen);
    vector<Bytef> compressed(destLen);

    if (compress(compressed.data(), &destLen, (const Bytef*)data.c_str(),
srcLen) == Z_OK) {
        cout << "Compressed size: " << destLen << endl;
    }

    vector<Bytef> decompressed(srcLen);
```

```

        uLong decompressedLen = srcLen;
        if (uncompress(decompressed.data(), &decompressedLen,
compressed.data(), destLen) == Z_OK) {
            cout << "Decompressed string: " <<
string((char*)decompressed.data(), decompressedLen) << endl;
        }
    }
}

```

You need to link with **zlib** when compiling:

```
g++ deflate_example.cpp -lz -o deflate_example
```

---

✓ Now you have **C++ implementations or examples** for:

- Huffman Coding
  - Run-Length Encoding (RLE)
  - Lempel-Ziv-Welch (LZW)
  - Arithmetic Coding (simplified)
  - Burrows–Wheeler Transform (BWT)
  - DEFLATE (using zlib)
- 

If you want, I can **combine Huffman, RLE, LZW, and BWT into a single runnable C++ file** with examples for all, so you can test everything at once.

Do you want me to do that?

## 1. MapReduce

A programming model for processing large datasets in parallel across a cluster.

- **Map step:** Apply a function to each input to produce key-value pairs.
- **Reduce step:** Aggregate values with the same key.

**C++ Example (Simplified Word Count):**

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    vector<string> data = {"hello world", "hello mapreduce", "world of
parallel"};

    unordered_map<string,int> wordCount;

    // Map phase
    for(string line : data) {
        stringstream ss(line);
        string word;
        while(ss >> word) wordCount[word]++;
    }
}

```

```
// Reduce phase is implicit: we already aggregated counts
for(auto &p : wordCount)
    cout << p.first << ": " << p.second << endl;
}
```

---

## 2. Paxos Algorithm

A consensus algorithm for distributed systems ensuring all nodes agree on a single value, even with failures.

- Roles: **Proposer, Acceptor, Learner**
- Steps:
  1. Proposer suggests a value.
  2. Acceptors vote on it (promise not to accept smaller proposals).
  3. Once majority accept, value is chosen.

**Implementation** is complex in C++, usually done in distributed systems libraries. Conceptually:

```
Proposer -> Send prepare(n) to Acceptors
Acceptor -> Promise(n) if n > max_seen
Proposer -> Send accept(value) to Acceptors
Acceptor -> Accept if promised n == n
```

---

## 3. Raft Consensus Algorithm

Simpler alternative to Paxos for leader election and log replication.

- Nodes: **Leader, Follower, Candidate**
- Steps:
  1. Leader election (Bully-style timeout)
  2. Log replication from leader to followers
  3. Safety: commits happen in majority

C++ **simulation** usually involves threads for nodes and message passing.

---

## 4. Bully Algorithm (Leader Election)

Used in distributed systems to elect a coordinator.

- Steps:
  1. Node detects leader failure
  2. Sends election message to all higher-ID nodes
  3. If no higher-ID responds, it becomes leader
  4. Else, higher-ID node takes over

**Pseudo-C++:**

```
int electLeader(vector<int> nodes, int selfID) {
    for(int id : nodes)
        if(id > selfID) return -1; // wait for higher node
    return selfID; // become leader
}
```

---

## 5. Lamport Timestamps

Logical clocks to order events in distributed systems.

- Each process maintains a counter  $L$ .
- Rules:
  1.  $L += 1$  for each event
  2. When sending a message, send  $L$
  3. Receiving:  $L = \max(L, \text{received}) + 1$

### C++ Example:

```
#include <bits/stdc++.h>
using namespace std;

int main() {
    int L1=0, L2=0;
    // Event at process 1
    L1++;
    cout << "P1 event timestamp: " << L1 << endl;

    // Message sent P1->P2
    int msg = L1;

    // P2 receives message
    L2 = max(L2, msg) + 1;
    cout << "P2 event timestamp after message: " << L2 << endl;
}
```

---

## 6. Chandy-Lamport Snapshot Algorithm

Captures a **consistent global state** in a distributed system.

- Steps:
  1. Initiate snapshot at a process
  2. Record local state, send marker messages on all outgoing channels
  3. Each process records incoming messages until it sees a marker on that channel
  4. Global state is the combination of local states and in-transit messages

### Conceptual Example:

```
Process P starts snapshot:
- record own state
- send "marker" to all neighbors
- record messages on channels until "marker" received
```

---

If you want, I can **create a single C++ file that simulates Lamport Timestamps, Bully Algorithm, and a tiny MapReduce example together**, so you can see **parallel & distributed algorithms in action**.

Do you want me to do that?

Here's a detailed overview of the **Binary Search Tree (BST) algorithms** you listed, along with brief explanations and common implementation ideas:

---

## 1. Insert in BST

- **Goal:** Add a new node while maintaining BST property ( $\text{left} < \text{root} < \text{right}$ ).
- **Approach (Recursive):**

```
Node* insert(Node* root, int key) {
    if (!root) return new Node(key);
    if (key < root->data) root->left = insert(root->left, key);
    else root->right = insert(root->right, key);
    return root;
}
```

---

## 2. Delete from BST

- **Goal:** Remove a node while keeping BST property intact.
- **Cases:**
  1. Node is a **leaf** → remove directly.
  2. Node has **one child** → replace node with child.
  3. Node has **two children** → replace node with **inorder successor** (or **predecessor**), then delete successor.

```
Node* deleteNode(Node* root, int key) {
    if (!root) return nullptr;
    if (key < root->data) root->left = deleteNode(root->left, key);
    else if (key > root->data) root->right = deleteNode(root->right, key);
    else {
        if (!root->left) return root->right;
        if (!root->right) return root->left;
        Node* succ = minValueNode(root->right);
        root->data = succ->data;
        root->right = deleteNode(root->right, succ->data);
    }
    return root;
}
```

---

## 3. Search in BST

- **Goal:** Check if a value exists.
- **Approach:** Compare key with current node, recurse left/right.

```
bool search(Node* root, int key) {
    if (!root) return false;
    if (root->data == key) return true;
    return key < root->data ? search(root->left, key) : search(root->right,
key);
}
```

---

#### 4. Find Min/Max in BST

- **Min:** Go leftmost.
- **Max:** Go rightmost.

```
Node* findMin(Node* root) {
    while (root && root->left) root = root->left;
    return root;
}
Node* findMax(Node* root) {
    while (root && root->right) root = root->right;
    return root;
}
```

---

#### 5. Find Inorder Successor / Predecessor

- **Inorder Successor:** Smallest node **greater than** current.
    - If right child exists → go right, then leftmost.
    - Else → traverse from root to find closest ancestor where node is in left subtree.
  - **Inorder Predecessor:** Largest node **smaller than** current.
    - If left child exists → go left, then rightmost.
    - Else → traverse from root to find closest ancestor where node is in right subtree.
- 

#### 6. Check if a tree is a valid BST

- **Approach:** Ensure all nodes follow  $\text{min} < \text{node} < \text{max}$  property recursively.

```
bool isBST(Node* root, Node* minNode = nullptr, Node* maxNode = nullptr) {
    if (!root) return true;
    if ((minNode && root->data <= minNode->data) || (maxNode && root->data
>= maxNode->data)) return false;
    return isBST(root->left, minNode, root) && isBST(root->right, root,
maxNode);
}
```

---

#### 7. Lowest Common Ancestor (LCA) in BST

- **Goal:** Find common ancestor of two nodes.
- **Property:** For BST, first node where  $n1 \leq \text{root} \leq n2$  is LCA.



```
Node* LCA(Node* root, int n1, int n2) {
    if (!root) return nullptr;
    if (root->data > n1 && root->data > n2) return LCA(root->left, n1, n2);
    if (root->data < n1 && root->data < n2) return LCA(root->right, n1,
n2);
    return root;
}
```

---

## 8. Balanced BST Construction (from sorted array)

- **Goal:** Build height-balanced BST from a **sorted array**.
- **Approach:** Recursively pick middle element as root.

```
Node* sortedArrayToBST(vector<int>& arr, int start, int end) {
    if (start > end) return nullptr;
    int mid = start + (end - start) / 2;
    Node* root = new Node(arr[mid]);
    root->left = sortedArrayToBST(arr, start, mid - 1);
    root->right = sortedArrayToBST(arr, mid + 1, end);
    return root;
}
```

---

If you want, I can make a **single C++ file** containing all these BST operations with a **menu-driven program** so you can test all functions interactively.

Do you want me to do that?

implementation ideas:

---

## 1. Height / Depth of a Tree

- **Height:** Max distance from root to a leaf.
- **Depth:** Distance from root to a given node.

```
int height(Node* root) {
    if (!root) return 0;
    return 1 + max(height(root->left), height(root->right));
}
```

---

## 2. Diameter of a Tree (Longest Path)

- **Diameter:** Longest path between any two nodes (may pass through root).

```
int diameter(Node* root, int &res) {
    if (!root) return 0;
    int lh = diameter(root->left, res);
    int rh = diameter(root->right, res);
    res = max(res, lh + rh); // path through root
    return 1 + max(lh, rh);
}
```

```

}
// Usage:
int res = 0;
diameter(root, res); // res contains diameter

```

---

### 3. Balanced Tree Check

- **Balanced Tree:** Height difference between left and right  $\leq 1$  at every node.

```

bool isBalanced(Node* root, int &height) {
    if (!root) { height = 0; return true; }
    int lh = 0, rh = 0;
    if (!isBalanced(root->left, lh) || !isBalanced(root->right, rh)) return
false;
    height = 1 + max(lh, rh);
    return abs(lh - rh) <= 1;
}

```

---

### 4. Symmetric Tree Check

- **Goal:** Tree is mirror of itself.

```

bool isMirror(Node* t1, Node* t2) {
    if (!t1 && !t2) return true;
    if (!t1 || !t2) return false;
    return (t1->data == t2->data) &&
            isMirror(t1->left, t2->right) &&
            isMirror(t1->right, t2->left);
}
bool isSymmetric(Node* root) {
    if (!root) return true;
    return isMirror(root->left, root->right);
}

```

---

### 5. Mirror Tree Construction

```

void mirrorTree(Node* root) {
    if (!root) return;
    swap(root->left, root->right);
    mirrorTree(root->left);
    mirrorTree(root->right);
}

```

---

### 6. Path Sum Problems (Root-to-Leaf paths with given sum)

- **Check if path exists:**

```

bool hasPathSum(Node* root, int sum) {
    if (!root) return false;
    if (!root->left && !root->right) return root->data == sum;
    return hasPathSum(root->left, sum - root->data) ||

```

```

        hasPathSum(root->right, sum - root->data);
    }

```

- **Print all root-to-leaf paths with sum:**

```

void printPaths(Node* root, int sum, vector<int>& path) {
    if (!root) return;
    path.push_back(root->data);
    if (!root->left && !root->right && root->data == sum) {
        for (int x : path) cout << x << " ";
        cout << "\n";
    } else {
        printPaths(root->left, sum - root->data, path);
        printPaths(root->right, sum - root->data, path);
    }
    path.pop_back();
}

```

---

## 7. Count Leaf Nodes / Internal Nodes

```

int countLeafNodes(Node* root) {
    if (!root) return 0;
    if (!root->left && !root->right) return 1;
    return countLeafNodes(root->left) + countLeafNodes(root->right);
}

int countInternalNodes(Node* root) {
    if (!root || (!root->left && !root->right)) return 0;
    return 1 + countInternalNodes(root->left) + countInternalNodes(root->right);
}

```

---

## 8. Count Nodes, Edges, Levels

```

int countNodes(Node* root) {
    if (!root) return 0;
    return 1 + countNodes(root->left) + countNodes(root->right);
}

int countEdges(Node* root) {
    return max(0, countNodes(root) - 1); // edges = nodes - 1
}

int countLevels(Node* root) {
    return height(root); // same as tree height
}

```

---

## 9. Serialize and Deserialize a Tree

- **Serialize:** Convert tree to string (e.g., preorder with null markers #).

```

void serialize(Node* root, ostringstream &out) {
    if (!root) { out << "# "; return; }
    out << root->data << " ";
}

```

```

        serialize(root->left, out);
        serialize(root->right, out);
    }

Node* deserialize(istringstream &in) {
    string val; in >> val;
    if (val == "#") return nullptr;
    Node* root = new Node(stoi(val));
    root->left = deserialize(in);
    root->right = deserialize(in);
    return root;
}

```

---

## 10. Flatten Binary Tree to Linked List

- **Goal:** Transform tree into a linked list in-place (preorder traversal).

```


void flatten(Node* root) {
    if (!root) return;
    flatten(root->left);
    flatten(root->right);
    Node* tmp = root->right;
    root->right = root->left;
    root->left = nullptr;
    Node* curr = root;
    while (curr->right) curr = curr->right;
    curr->right = tmp;
}

```

---

If you want, I can also create a **single C++ file** with **all Binary Tree algorithms** implemented and **menu-driven**, so you can test each feature interactively.

Do you want me to do that?



Sure! I can provide you a **C++ implementation of a Segment Tree** that handles **Range Sum Queries, Range Minimum/Maximum Queries, and Lazy Propagation**. I'll make it modular so you can adapt it easily.

**Here's a complete example:**

```

#include <bits/stdc++.h>
using namespace std;

class SegmentTree {
private:
    vector<long long> treeSum, treeMin, treeMax, lazy;
    int n;

```

```

void build(vector<int> &arr, int node, int start, int end) {
    if (start == end) {
        treeSum[node] = arr[start];
        treeMin[node] = arr[start];
        treeMax[node] = arr[start];
    } else {
        int mid = (start + end) / 2;
        build(arr, 2*node, start, mid);
        build(arr, 2*node+1, mid+1, end);
        treeSum[node] = treeSum[2*node] + treeSum[2*node+1];
        treeMin[node] = min(treeMin[2*node], treeMin[2*node+1]);
        treeMax[node] = max(treeMax[2*node], treeMax[2*node+1]);
    }
}

void push(int node, int start, int end) {
    if (lazy[node] != 0) {
        treeSum[node] += (end - start + 1) * lazy[node];
        treeMin[node] += lazy[node];
        treeMax[node] += lazy[node];
        if (start != end) { // not a leaf
            lazy[2*node] += lazy[node];
            lazy[2*node+1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

void updateRange(int node, int start, int end, int l, int r, int val) {
    push(node, start, end);
    if (start > r || end < l) return; // no overlap
    if (start >= l && end <= r) { // total overlap
        lazy[node] += val;
        push(node, start, end);
        return;
    }
    int mid = (start + end) / 2;
    updateRange(2*node, start, mid, l, r, val);
    updateRange(2*node+1, mid+1, end, l, r, val);
    treeSum[node] = treeSum[2*node] + treeSum[2*node+1];
    treeMin[node] = min(treeMin[2*node], treeMin[2*node+1]);
    treeMax[node] = max(treeMax[2*node], treeMax[2*node+1]);
}

long long querySum(int node, int start, int end, int l, int r) {
    push(node, start, end);
    if (start > r || end < l) return 0;
    if (start >= l && end <= r) return treeSum[node];
    int mid = (start + end) / 2;
    return querySum(2*node, start, mid, l, r) + querySum(2*node+1,
mid+1, end, l, r);
}

long long queryMin(int node, int start, int end, int l, int r) {
    push(node, start, end);
    if (start > r || end < l) return LLONG_MAX;
    if (start >= l && end <= r) return treeMin[node];
    int mid = (start + end) / 2;
    return min(queryMin(2*node, start, mid, l, r), queryMin(2*node+1,
mid+1, end, l, r));
}

```

```

    long long queryMax(int node, int start, int end, int l, int r) {
        push(node, start, end);
        if (start > r || end < l) return LLONG_MIN;
        if (start >= l && end <= r) return treeMax[node];
        int mid = (start + end) / 2;
        return max(queryMax(2*node, start, mid, l, r), queryMax(2*node+1,
mid+1, end, l, r));
    }

public:
    SegmentTree(vector<int> &arr) {
        n = arr.size();
        treeSum.resize(4*n);
        treeMin.resize(4*n);
        treeMax.resize(4*n);
        lazy.assign(4*n, 0);
        build(arr, 1, 0, n-1);
    }

    void update(int l, int r, int val) {
        updateRange(1, 0, n-1, l, r, val);
    }

    long long getSum(int l, int r) {
        return querySum(1, 0, n-1, l, r);
    }

    long long getMin(int l, int r) {
        return queryMin(1, 0, n-1, l, r);
    }

    long long getMax(int l, int r) {
        return queryMax(1, 0, n-1, l, r);
    }
};

int main() {
    vector<int> arr = {1, 3, 5, 7, 9, 11};
    SegmentTree st(arr);

    cout << "Sum of range [1, 3]: " << st.getSum(1, 3) << "\n";
    cout << "Min of range [1, 4]: " << st.getMin(1, 4) << "\n";
    cout << "Max of range [0, 5]: " << st.getMax(0, 5) << "\n";

    st.update(1, 3, 3); // add 3 to range [1, 3]

    cout << "After update:\n";
    cout << "Sum of range [1, 3]: " << st.getSum(1, 3) << "\n";
    cout << "Min of range [1, 4]: " << st.getMin(1, 4) << "\n";
    cout << "Max of range [0, 5]: " << st.getMax(0, 5) << "\n";

    return 0;
}

```

### ✓ Features included:

1. Range Sum Query
2. Range Min / Max Query

3. **Lazy Propagation** for range updates
4. Modular and extendable

---

If you want, I can also make a **version that supports both range assignment (set value) and range addition with lazy propagation**, which is very useful for competitive programming.

Do you want me to do that too?



Sure! Here's a **C++ implementation of a Fenwick Tree (Binary Indexed Tree, BIT)** that supports **point updates and prefix sum queries**. Fenwick Trees are simpler than segment trees and very efficient for sum queries.

```
#include <bits/stdc++.h>
using namespace std;

class FenwickTree {
private:
    vector<long long> bit; // 1-indexed BIT
    int n;

public:
    FenwickTree(int size) {
        n = size;
        bit.assign(n+1, 0); // initialize with 0
    }

    // Update index `idx` by value `delta`
    void update(int idx, long long delta) {
        idx++; // convert to 1-based index
        while (idx <= n) {
            bit[idx] += delta;
            idx += idx & -idx; // move to parent
        }
    }

    // Get prefix sum from index 0 to idx
    long long query(int idx) {
        idx++; // convert to 1-based index
        long long sum = 0;
        while (idx > 0) {
            sum += bit[idx];
            idx -= idx & -idx; // move to parent
        }
        return sum;
    }

    // Get sum of range [l, r]
    long long rangeQuery(int l, int r) {
```

```

        return query(r) - query(l-1);
    }
};

int main() {
    vector<int> arr = {1, 2, 3, 4, 5};
    int n = arr.size();

    FenwickTree ft(n);

    // Build BIT
    for (int i = 0; i < n; i++) {
        ft.update(i, arr[i]);
    }

    cout << "Sum of range [1, 3]: " << ft.rangeQuery(1, 3) << "\n"; //
    2+3+4=9

    ft.update(2, 5); // arr[2] += 5

    cout << "Sum of range [1, 3] after update: " << ft.rangeQuery(1, 3) <<
    "\n"; // 2+8+4=14

    return 0;
}

```


### ✓ Features included:

1. Point updates (`update`)
2. Prefix sum queries (`query`)
3. Range sum queries (`rangeQuery`)
4. 1-indexed implementation internally (common for BIT)

---

If you want, I can also provide a **Fenwick Tree for range updates and point queries**—which is a slightly advanced version useful in many competitive programming problems.

Do you want me to provide that too?



Absolutely! A **Treap** is a randomized balanced binary search tree (BST) where each node has a **key** (BST property) and a **priority** (heap property). It combines **BST** and **heap** behavior. Here's a **C++ implementation** with insert, erase, and search:

```

#include <bits/stdc++.h>
using namespace std;
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

struct TreapNode {
    int key, priority;

```



```

    TreapNode *left, *right;
    TreapNode(int k) : key(k), priority(rng()), left(nullptr),
right(nullptr) {}
};

// Rotate right
TreapNode* rotateRight(TreapNode* y) {
    TreapNode* x = y->left;
    TreapNode* T2 = x->right;
    x->right = y;
    y->left = T2;
    return x;
}

// Rotate left
TreapNode* rotateLeft(TreapNode* x) {
    TreapNode* y = x->right;
    TreapNode* T2 = y->left;
    y->left = x;
    x->right = T2;
    return y;
}

// Insert a key
TreapNode* insert(TreapNode* root, int key) {
    if (!root) return new TreapNode(key);

    if (key < root->key) {
        root->left = insert(root->left, key);
        if (root->left->priority > root->priority)
            root = rotateRight(root);
    } else if (key > root->key) {
        root->right = insert(root->right, key);
        if (root->right->priority > root->priority)
            root = rotateLeft(root);
    }
    // If key == root->key, do nothing (no duplicates)
    return root;
}

// Delete a key
TreapNode* erase(TreapNode* root, int key) {
    if (!root) return nullptr;

    if (key < root->key)
        root->left = erase(root->left, key);
    else if (key > root->key)
        root->right = erase(root->right, key);
    else { // key == root->key
        if (!root->left) {
            TreapNode* temp = root->right;
            delete root;
            return temp;
        } else if (!root->right) {
            TreapNode* temp = root->left;
            delete root;
            return temp;
        } else if (root->left->priority < root->right->priority) {
            root = rotateLeft(root);
            root->left = erase(root->left, key);
        } else {

```

```

        root = rotateRight(root);
        root->right = erase(root->right, key);
    }
}
return root;
}

// Search a key
bool search(TreapNode* root, int key) {
    if (!root) return false;
    if (key == root->key) return true;
    if (key < root->key) return search(root->left, key);
    return search(root->right, key);
}

// Inorder traversal
void inorder(TreapNode* root) {
    if (!root) return;
    inorder(root->left);
    cout << "(" << root->key << "," << root->priority << ")" << " ";
    inorder(root->right);
}

int main() {
    TreapNode* root = nullptr;
    root = insert(root, 50);
    root = insert(root, 30);
    root = insert(root, 20);
    root = insert(root, 40);
    root = insert(root, 70);
    root = insert(root, 60);
    root = insert(root, 80);

    cout << "Inorder traversal of Treap:\n";
    inorder(root);
    cout << "\n";

    cout << "Search 40: " << (search(root, 40) ? "Found" : "Not Found") <<
    "\n";
    root = erase(root, 30);
    cout << "After deleting 30:\n";
    inorder(root);
    cout << "\n";

    return 0;
}

```

## ✓ Features:

1. **Insert** with heap balancing.
2. **Delete** with rotations.
3. **Search** in  $O(\log n)$  expected.
4. **Randomized priorities** ensure probabilistic balance.

Sure! Here's a **C++ implementation of an AVL Tree** (Self-Balancing Binary Search Tree) that supports **insertion, deletion, search, and inorder traversal**.

```
#include <bits/stdc++.h>
```

```

using namespace std;

struct AVLNode {
    int key;
    AVLNode* left;
    AVLNode* right;
    int height;
    AVLNode(int k) : key(k), left(nullptr), right(nullptr), height(1) {}
};

// Get height of node
int height(AVLNode* node) {
    return node ? node->height : 0;
}

// Get balance factor
int getBalance(AVLNode* node) {
    return node ? height(node->left) - height(node->right) : 0;
}

// Right rotate
AVLNode* rightRotate(AVLNode* y) {
    AVLNode* x = y->left;
    AVLNode* T2 = x->right;

    x->right = y;
    y->left = T2;

    y->height = max(height(y->left), height(y->right)) + 1;
    x->height = max(height(x->left), height(x->right)) + 1;

    return x;
}

// Left rotate
AVLNode* leftRotate(AVLNode* x) {
    AVLNode* y = x->right;
    AVLNode* T2 = y->left;

    y->left = x;
    x->right = T2;

    x->height = max(height(x->left), height(x->right)) + 1;
    y->height = max(height(y->left), height(y->right)) + 1;

    return y;
}

// Insert key
AVLNode* insert(AVLNode* node, int key) {
    if (!node) return new AVLNode(key);

    if (key < node->key)
        node->left = insert(node->left, key);
    else if (key > node->key)
        node->right = insert(node->right, key);
    else
        return node; // duplicate keys not allowed

    node->height = 1 + max(height(node->left), height(node->right));
}

```

```

    int balance = getBalance(node);

    // Left Left Case
    if (balance > 1 && key < node->left->key)
        return rightRotate(node);

    // Right Right Case
    if (balance < -1 && key > node->right->key)
        return leftRotate(node);

    // Left Right Case
    if (balance > 1 && key > node->left->key) {
        node->left = leftRotate(node->left);
        return rightRotate(node);
    }

    // Right Left Case
    if (balance < -1 && key < node->right->key) {
        node->right = rightRotate(node->right);
        return leftRotate(node);
    }

    return node;
}

// Find node with minimum key
AVLNode* minValueNode(AVLNode* node) {
    AVLNode* current = node;
    while (current->left) current = current->left;
    return current;
}

// Delete key
AVLNode* deleteNode(AVLNode* root, int key) {
    if (!root) return root;

    if (key < root->key)
        root->left = deleteNode(root->left, key);
    else if (key > root->key)
        root->right = deleteNode(root->right, key);
    else {
        if (!root->left || !root->right) {
            AVLNode* temp = root->left ? root->left : root->right;
            if (!temp) {
                temp = root;
                root = nullptr;
            } else
                *root = *temp;
            delete temp;
        } else {
            AVLNode* temp = minValueNode(root->right);
            root->key = temp->key;
            root->right = deleteNode(root->right, temp->key);
        }
    }

    if (!root) return root;

    root->height = 1 + max(height(root->left), height(root->right));

    int balance = getBalance(root);

```

```

// Left Left Case
if (balance > 1 && getBalance(root->left) >= 0)
    return rightRotate(root);

// Left Right Case
if (balance > 1 && getBalance(root->left) < 0) {
    root->left = leftRotate(root->left);
    return rightRotate(root);
}

// Right Right Case
if (balance < -1 && getBalance(root->right) <= 0)
    return leftRotate(root);

// Right Left Case
if (balance < -1 && getBalance(root->right) > 0) {
    root->right = rightRotate(root->right);
    return leftRotate(root);
}

return root;
}

// Search key
bool search(AVLNode* root, int key) {
    if (!root) return false;
    if (key == root->key) return true;
    if (key < root->key) return search(root->left, key);
    return search(root->right, key);
}

// Inorder traversal
void inorder(AVLNode* root) {
    if (!root) return;
    inorder(root->left);
    cout << root->key << " ";
    inorder(root->right);
}

int main() {
    AVLNode* root = nullptr;

    root = insert(root, 10);
    root = insert(root, 20);
    root = insert(root, 30);
    root = insert(root, 40);
    root = insert(root, 50);
    root = insert(root, 25);

    cout << "Inorder traversal of AVL tree: ";
    inorder(root);
    cout << "\n";

    root = deleteNode(root, 40);
    cout << "After deleting 40: ";
    inorder(root);
    cout << "\n";

    cout << "Search 25: " << (search(root, 25) ? "Found" : "Not Found") <<
    "\n";
}

```

```

        cout << "Search 40: " << (search(root, 40) ? "Found" : "Not Found") <<
"\n";

        return 0;
}


```

## ✓ Features:

1. **Self-balancing** with rotations (LL, RR, LR, RL)
2. **Insertion & Deletion** in  $O(\log n)$
3. **Search**
4. **Inorder traversal** (sorted order)

If you want, I can also provide a **version of AVL Tree that maintains subtree sums or sizes**, which is useful for **range queries or order statistics**.

Do you want me to show that?



Sure! A **Red-Black Tree (RBT)** is a self-balancing binary search tree with these properties:

1. Each node is either **red** or **black**.
2. The root is always **black**.
3. All leaves (NIL) are **black**.
4. Red nodes cannot have red children (no two reds in a row).
5. Every path from a node to its descendant NIL nodes has the same number of black nodes.

Here's a **basic C++ implementation** of a Red-Black Tree with **insertions and inorder traversal**:

```

#include <bits/stdc++.h>
using namespace std;

enum Color { RED, BLACK };

struct Node {
    int data;
    Color color;
    Node *left, *right, *parent;

    Node(int data) : data(data), color(RED), left(nullptr), right(nullptr),
parent(nullptr) {}
};

class RBTree {
private:

```

```

Node* root;

void rotateLeft(Node* &root, Node* x) {
    Node* y = x->right;
    x->right = y->left;
    if (y->left) y->left->parent = x;
    y->parent = x->parent;
    if (!x->parent) root = y;
    else if (x == x->parent->left) x->parent->left = y;
    else x->parent->right = y;
    y->left = x;
    x->parent = y;
}

void rotateRight(Node* &root, Node* y) {
    Node* x = y->left;
    y->left = x->right;
    if (x->right) x->right->parent = y;
    x->parent = y->parent;
    if (!y->parent) root = x;
    else if (y == y->parent->left) y->parent->left = x;
    else y->parent->right = x;
    x->right = y;
    y->parent = x;
}

void fixInsert(Node* &root, Node* z) {
    while (z->parent && z->parent->color == RED) {
        Node* grandparent = z->parent->parent;
        if (z->parent == grandparent->left) {
            Node* uncle = grandparent->right;
            if (uncle && uncle->color == RED) {
                z->parent->color = BLACK;
                uncle->color = BLACK;
                grandparent->color = RED;
                z = grandparent;
            } else {
                if (z == z->parent->right) {
                    z = z->parent;
                    rotateLeft(root, z);
                }
                z->parent->color = BLACK;
                grandparent->color = RED;
                rotateRight(root, grandparent);
            }
        } else {
            Node* uncle = grandparent->left;
            if (uncle && uncle->color == RED) {
                z->parent->color = BLACK;
                uncle->color = BLACK;
                grandparent->color = RED;
                z = grandparent;
            } else {
                if (z == z->parent->left) {
                    z = z->parent;
                    rotateRight(root, z);
                }
                z->parent->color = BLACK;
                grandparent->color = RED;
                rotateLeft(root, grandparent);
            }
        }
    }
}

```

```

        }
    }
    root->color = BLACK;
}

void inorderHelper(Node* node) {
    if (!node) return;
    inorderHelper(node->left);
    cout << node->data << (node->color == RED ? "R " : "B ");
    inorderHelper(node->right);
}

public:
    RBTREE() : root(nullptr) {}

    void insert(int data) {
        Node* z = new Node(data);
        Node* y = nullptr;
        Node* x = root;

        while (x) {
            y = x;
            if (z->data < x->data) x = x->left;
            else x = x->right;
        }

        z->parent = y;
        if (!y) root = z;
        else if (z->data < y->data) y->left = z;
        else y->right = z;

        fixInsert(root, z);
    }

    void inorder() {
        inorderHelper(root);
        cout << "\n";
    }
};

int main() {
    RBTREE tree;

    tree.insert(10);
    tree.insert(20);
    tree.insert(30);
    tree.insert(15);
    tree.insert(25);

    cout << "Inorder traversal (data + color R/B): ";
    tree.inorder();

    return 0;
}

```

## ✓ Features:

1. **Red-Black Properties Maintained** after insertions
2. **Rotations (Left/Right)** and **Recoloring** implemented




### 3. **Inorder Traversal** shows node color (R = Red, B = Black)

---

If you want, I can also provide **full deletion in Red-Black Tree**, which is a bit more complex but crucial for a fully functional RBT.

Do you want me to provide deletion as well?



Absolutely! A **Splay Tree** is a self-adjusting binary search tree that **brings the most recently accessed node to the root** using rotations (splay operation). This gives **amortized  $O(\log n)$  time** for operations.

Here's a clean **C++ class-based implementation** with **insert, search, and inorder traversal**:

```
#include <bits/stdc++.h>
using namespace std;

class SplayTree {
private:
    struct Node {
        int key;
        Node* left;
        Node* right;
        Node(int k) : key(k), left(nullptr), right(nullptr) {}
    };

    Node* root;

    Node* rightRotate(Node* x) {
        Node* y = x->left;
        x->left = y->right;
        y->right = x;
        return y;
    }

    Node* leftRotate(Node* x) {
        Node* y = x->right;
        x->right = y->left;
        y->left = x;
        return y;
    }

    Node* splay(Node* root, int key) {
        if (!root || root->key == key) return root;

        // Key in left subtree
        if (key < root->key) {
```

```

        if (!root->left) return root;

        // Zig-Zig (Left Left)
        if (key < root->left->key) {
            root->left->left = splay(root->left->left, key);
            root = rightRotate(root);
        }
        // Zig-Zag (Left Right)
        else if (key > root->left->key) {
            root->left->right = splay(root->left->right, key);
            if (root->left->right) root->left = leftRotate(root->left);
        }

        return root->left ? rightRotate(root) : root;
    }
    // Key in right subtree
    else {
        if (!root->right) return root;

        // Zag-Zig (Right Left)
        if (key < root->right->key) {
            root->right->left = splay(root->right->left, key);
            if (root->right->left) root->right = rightRotate(root->right);
        }
        // Zag-Zag (Right Right)
        else if (key > root->right->key) {
            root->right->right = splay(root->right->right, key);
            root = leftRotate(root);
        }

        return root->right ? leftRotate(root) : root;
    }
}

Node* insert(Node* root, int key) {
    if (!root) return new Node(key);
    root = splay(root, key);
    if (root->key == key) return root; // already exists

    Node* newNode = new Node(key);
    if (key < root->key) {
        newNode->right = root;
        newNode->left = root->left;
        root->left = nullptr;
    } else {
        newNode->left = root;
        newNode->right = root->right;
        root->right = nullptr;
    }
    return newNode;
}

Node* search(Node* root, int key) {
    return splay(root, key);
}

void inorder(Node* node) {
    if (!node) return;
    inorder(node->left);
    cout << node->key << " ";
}

```

```

        inorder(node->right);
    }

public:
    SplayTree() : root(nullptr) {}

    void insert(int key) {
        root = insert(root, key);
    }

    void search(int key) {
        root = search(root, key);
        if (root && root->key == key)
            cout << key << " found and splayed to root.\n";
        else
            cout << key << " not found.\n";
    }

    void inorder() {
        inorder(root);
        cout << "\n";
    }
};

int main() {
    SplayTree tree;

    tree.insert(10);
    tree.insert(20);
    tree.insert(30);
    tree.insert(25);

    cout << "Inorder traversal: ";
    tree.inorder();

    tree.search(20); // Splay 20 to root

    cout << "Inorder after splaying 20: ";
    tree.inorder();

    return 0;
}

```

## ✓ Features:

1. **Splay Operation** (Zig-Zig, Zig-Zag, Zag-Zig, Zag-Zag)
2. **Insert** with automatic splaying
3. **Search** brings the node to the root
4. **Inorder traversal**

---

If you want, I can also provide **Delete operation for Splay Tree** in the same class format, which is a bit trickier but very useful.

Do you want me to add deletion?

Absolutely! Let's cover **B-Tree and B+ Tree** with class-based C++ implementations. I'll provide a **simplified version suitable for educational and database-like purposes**.

---

## B-Tree (order $t$ )

A **B-Tree of order  $t$**  (minimum degree) has:

1. Every node except root has at least  $t-1$  keys.
2. Every node can have at most  $2t-1$  keys.
3. All leaves are at the same level.
4. Internal nodes have children one more than keys.

Here's a basic C++ class-based implementation:

```
#include <bits/stdc++.h>
using namespace std;

class BTreeNode {
public:
    vector<int> keys;
    vector<BTreeNode*> children;
    bool leaf;
    int t; // minimum degree

    BTreeNode(int _t, bool _leaf) {
        t = _t;
        leaf = _leaf;
    }

    void traverse() {
        int i;
        for (i = 0; i < keys.size(); i++) {
            if (!leaf) children[i]->traverse();
            cout << keys[i] << " ";
        }
        if (!leaf) children[i]->traverse();
    }

    BTreeNode* search(int k) {
        int i = 0;
        while (i < keys.size() && k > keys[i]) i++;
        if (i < keys.size() && keys[i] == k) return this;
        if (leaf) return nullptr;
        return children[i]->search(k);
    }

    void insertNonFull(int k) {
        int i = keys.size() - 1;

        if (leaf) {
            keys.push_back(0);
            while (i >= 0 && keys[i] > k) {
                keys[i+1] = keys[i];
            }
        }
    }
};
```

```

        i--;
    }
    keys[i+1] = k;
} else {
    while (i >= 0 && keys[i] > k) i--;
    i++;
    if (children[i]->keys.size() == 2*t - 1) {
        splitChild(i, children[i]);
        if (keys[i] < k) i++;
    }
    children[i]->insertNonFull(k);
}
}

void splitChild(int i, BTreeNode* y) {
    BTreeNode* z = new BTreeNode(y->t, y->leaf);
    for (int j = 0; j < t-1; j++) z->keys.push_back(y->keys[j+t]);
    if (!y->leaf) {
        for (int j = 0; j < t; j++) z->children.push_back(y-
>children[j+t]);
    }
    y->keys.resize(t-1);
    y->children.resize(y->leaf ? 0 : t);

    children.insert(children.begin()+i+1, z);
    keys.insert(keys.begin()+i, y->keys[t-1]);
}
};

class BTree {
public:
    BTreeNode* root;
    int t; // minimum degree

    BTree(int _t) {
        root = nullptr;
        t = _t;
    }

    void traverse() {
        if (root) root->traverse();
        cout << "\n";
    }

    BTreeNode* search(int k) {
        return root ? root->search(k) : nullptr;
    }

    void insert(int k) {
        if (!root) {
            root = new BTreeNode(t, true);
            root->keys.push_back(k);
        } else {
            if (root->keys.size() == 2*t - 1) {
                BTreeNode* s = new BTreeNode(t, false);
                s->children.push_back(root);
                s->splitChild(0, root);

                int i = (s->keys[0] < k) ? 1 : 0;
                s->children[i]->insertNonFull(k);
            }
        }
    }
};

```

```

        root = s;
    } else
        root->insertNonFull(k);
    }
};

int main() {
    BTree t(3); // minimum degree 3
    vector<int> keys = {10, 20, 5, 6, 12, 30, 7, 17};
    for (int key : keys) t.insert(key);

    cout << "Traversal of B-Tree: ";
    t.traverse();

    int k = 6;
    cout << "Searching " << k << ": " << (t.search(k) ? "Found" : "Not
Found") << "\n";

    return 0;
}

```

---

## B+ Tree (simplified)

Differences from B-Tree:

1. **All values are stored at leaf nodes.**
2. **Leaf nodes are linked** for range queries.
3. Internal nodes only store keys for navigation.

Here's a **simplified B+ Tree leaf-linked structure**:

```

// Due to complexity, B+ Tree is usually implemented with leaf linking.
// The concept: internal nodes store keys for navigation,
// leaves store actual values in sorted linked nodes for range queries.
// Full C++ implementation is large (~200+ lines) and includes
// insert, search, and range query.


```

✓ B+ Trees are **used in databases and filesystems** for efficient **disk reads** and **range queries**.

---

I can provide a **full working B+ Tree class with insert, search, and range query** if you want—it's very useful for database-style problems.

Do you want me to provide that full B+ Tree code?



Absolutely! Here's a **C++ class-based implementation of a Trie (Prefix Tree)** that supports **insertion, search, and prefix checking**:

```
#include <bits/stdc++.h>
using namespace std;

class Trie {
private:
    struct TrieNode {
        unordered_map<char, TrieNode*> children;
        bool isEndOfWord;
        TrieNode() : isEndOfWord(false) {}
    };

    TrieNode* root;

public:
    Trie() {
        root = new TrieNode();
    }

    // Insert a word into the Trie
    void insert(const string &word) {
        TrieNode* node = root;
        for (char c : word) {
            if (!node->children.count(c))
                node->children[c] = new TrieNode();
            node = node->children[c];
        }
        node->isEndOfWord = true;
    }

    // Search a word in the Trie
    bool search(const string &word) {
        TrieNode* node = root;
        for (char c : word) {
            if (!node->children.count(c)) return false;
            node = node->children[c];
        }
        return node->isEndOfWord;
    }

    // Check if any word starts with the given prefix
    bool startsWith(const string &prefix) {
        TrieNode* node = root;
        for (char c : prefix) {
            if (!node->children.count(c)) return false;
            node = node->children[c];
        }
        return true;
    }
};

int main() {
    Trie trie;

    trie.insert("apple");
    trie.insert("app");
}
```

```

        trie.insert("banana");

        cout << boolalpha;
        cout << "Search 'apple': " << trie.search("apple") << "\n";    // true
        cout << "Search 'app': " << trie.search("app") << "\n";        // true
        cout << "Search 'ap': " << trie.search("ap") << "\n";          // false
        cout << "Starts with 'ap': " << trie.startsWith("ap") << "\n";  // true
        cout << "Starts with 'ba': " << trie.startsWith("ba") << "\n";  // true
        cout << "Starts with 'cat': " << trie.startsWith("cat") << "\n"; //
false

        return 0;
    }

```

## ✓ Features:

1. **Insert words** into the Trie
2. **Search words** (exact match)
3. **Prefix search** (startsWith)
4. Uses **unordered\_map** for dynamic character storage

If you want, I can also provide a **more memory-efficient Trie using an array of size 26 for lowercase letters**, which is faster and often used in competitive programming.

Do you want me to show that optimized version?

Sure! A **Suffix Tree** is a **compressed trie of all suffixes of a string**. It allows efficient substring queries, pattern matching, longest repeated substring, etc.

Full-fledged **Ukkonen's online construction algorithm** is complex, so here I'll provide a **simplified version suitable for learning and small strings**.

## C++ Suffix Tree (Naive Implementation)

```

#include <bits/stdc++.h>
using namespace std;

class SuffixTreeNode {
public:
    unordered_map<char, SuffixTreeNode*> children;
    vector<int> indexes; // store suffix indexes for leaf nodes
};

class SuffixTree {
private:
    SuffixTreeNode* root;

    void insertSuffix(const string& suffix, int index) {
        SuffixTreeNode* node = root;
        for (char c : suffix) {
            if (!node->children.count(c))
                node->children[c] = new SuffixTreeNode();

```



```

        node = node->children[c];
    }
    node->indexes.push_back(index); // leaf node
}

public:
    SuffixTree(const string& text) {
        root = new SuffixTreeNode();
        int n = text.size();
        for (int i = 0; i < n; i++) {
            insertSuffix(text.substr(i), i); // insert all suffixes
        }
    }

    // Search pattern in text
    vector<int> search(const string& pattern) {
        SuffixTreeNode* node = root;
        for (char c : pattern) {
            if (!node->children.count(c)) return {}; // pattern not found
            node = node->children[c];
        }
        // Collect all suffix indexes under this node
        vector<int> result;
        function<void(SuffixTreeNode*)> dfs = [&](SuffixTreeNode* n) {
            for (int idx : n->indexes) result.push_back(idx);
            for (auto& child : n->children) dfs(child.second);
        };
        dfs(node);
        return result;
    }
};

int main() {
    string text = "banana";
    SuffixTree tree(text);

    string pattern = "ana";
    vector<int> positions = tree.search(pattern);

    cout << "Pattern '" << pattern << "' found at positions: ";
    for (int pos : positions) cout << pos << " ";
    cout << "\n";

    return 0;
}

```

### ✓ Features:


1. **Naive suffix tree construction:**  $O(n^2)$  time
2. **Pattern search:** returns all starting positions
3. Works well for **small strings** and learning purposes

---

For **large strings**, we use **Ukkonen's algorithm** which builds the suffix tree in  **$O(n)$  time**, but it's quite complex to implement.

I can provide a **Ukkonen's algorithm-based suffix tree** in C++ if you want—it's optimized for large-scale string matching.

Do you want me to provide that advanced version?



Cartesian Tree

ChatGPT said:

Sure! A **Cartesian Tree** is a **binary tree derived from a sequence of numbers** with these properties:

1. It **maintains the heap property**: the parent is smaller (or larger) than its children.
2. It **maintains the inorder sequence** of the original array.

It's often used in **range minimum queries (RMQ)**, **sequence reconstruction**, and **priority queue simulations**.

---

### C++ Class-Based Implementation (Min Cartesian Tree)

```
#include <bits/stdc++.h>
using namespace std;

class CartesianTree {
private:
    struct Node {
        int key;
        Node* left;
        Node* right;
        Node(int k) : key(k), left(nullptr), right(nullptr) {}
    };

    Node* root;

    Node* buildTree(vector<int>& arr) {
        stack<Node*> st;
        Node* last = nullptr;

        for (int val : arr) {
            Node* curr = new Node(val);
            last = nullptr;

            while (!st.empty() && st.top()->key > val) {
                last = st.top();
                st.pop();
            }

            if (!st.empty()) st.top()->right = curr;
            curr->left = last;
            st.push(curr);
        }

        return st.top();
    }
};
```

```

    }

    while (st.size() > 1) st.pop(); // root is bottom of stack
    return st.top();
}

void inorder(Node* node) {
    if (!node) return;
    inorder(node->left);
    cout << node->key << " ";
    inorder(node->right);
}

public:
    CartesianTree(vector<int>& arr) {
        root = buildTree(arr);
    }

    void inorder() {
        inorder(root);
        cout << "\n";
    }
};

int main() {
    vector<int> arr = {5, 10, 40, 30, 28};
    CartesianTree tree(arr);

    cout << "Inorder traversal of Cartesian Tree: ";
    tree.inorder(); // should match original array
    return 0;
}

```

## ✓ Features:

1. **Maintains heap property** (min-heap here)
2. **Maintains inorder sequence** of the original array
3. **O(n) construction** using a stack (efficient!)
4. Inorder traversal returns the **original array sequence**

If you want, I can also provide a **Max-Cartesian Tree version** (parent is max) and **support for range minimum queries using this tree**.

Do you want me to provide that?

Is this conversation helpful so far?

Absolutely! A **KD-Tree (k-dimensional tree)** is a **binary search tree for points in k-dimensional space**. It's widely used for **range searches** and **nearest neighbor queries**.

Here's a C++ **class-based implementation for 2D points** with insertion and range search:

```

#include <bits/stdc++.h>
using namespace std;

```

```

struct Point {
    int x, y;
    Point(int _x, int _y) : x(_x), y(_y) {}
};

class KDTree {
private:
    struct Node {
        Point point;
        Node* left;
        Node* right;
        Node(Point p) : point(p), left(nullptr), right(nullptr) {}
    };

    Node* root;

    Node* insertRec(Node* root, Point point, unsigned depth) {
        if (!root) return new Node(point);

        unsigned cd = depth % 2; // 0 = x, 1 = y
        if ((cd == 0 && point.x < root->point.x) || (cd == 1 && point.y <
root->point.y))
            root->left = insertRec(root->left, point, depth + 1);
        else
            root->right = insertRec(root->right, point, depth + 1);

        return root;
    }

    void rangeSearchRec(Node* root, Point lower, Point upper, unsigned
depth, vector<Point>& result) {
        if (!root) return;

        if (root->point.x >= lower.x && root->point.x <= upper.x &&
            root->point.y >= lower.y && root->point.y <= upper.y)
            result.push_back(root->point);

        unsigned cd = depth % 2;
        if ((cd == 0 && lower.x <= root->point.x) || (cd == 1 && lower.y <=
root->point.y))
            rangeSearchRec(root->left, lower, upper, depth + 1, result);
        if ((cd == 0 && upper.x >= root->point.x) || (cd == 1 && upper.y >=
root->point.y))
            rangeSearchRec(root->right, lower, upper, depth + 1, result);
    }

public:
    KDTree() : root(nullptr) {}

    void insert(Point point) {
        root = insertRec(root, point, 0);
    }

    vector<Point> rangeSearch(Point lower, Point upper) {
        vector<Point> result;
        rangeSearchRec(root, lower, upper, 0, result);
        return result;
    }
};

```

```

int main() {
    KDTree tree;
    vector<Point> points = {{3, 6}, {17, 15}, {13, 15}, {6, 12}, {9, 1},
{2, 7}, {10, 19}};

    for (auto p : points) tree.insert(p);

    Point lower(0, 0), upper(10, 10);
    vector<Point> result = tree.rangeSearch(lower, upper);

    cout << "Points in range [(0,0),(10,10)]:\n";
    for (auto p : result) cout << "(" << p.x << ", " << p.y << ") ";
    cout << "\n";

    return 0;
}

```

### ✓ Features:

1. **Insertion** in k-dimensional space (2D here)
2. **Range search** for points inside a rectangular query
3. Uses **depth modulo k** to alternate dimensions
4. Efficient for spatial queries (nearest neighbor search can be added)

---

I can also provide a **KD-Tree with Nearest Neighbor Search** in 2D/3D, which is extremely useful in graphics, AI, and geometry problems.

Do you want me to provide the nearest neighbor version?

Sure! An **Interval Tree** is a **variant of a binary search tree** designed to efficiently **store intervals** (like [low, high]) and answer queries such as **all intervals overlapping with a given interval**.

Here's a **C++ class-based implementation** using a BST augmented with **max endpoint in subtree**:

```

#include <bits/stdc++.h>
using namespace std;

struct Interval {
    int low, high;
    Interval(int l, int h) : low(l), high(h) {}
};

struct ITNode {
    Interval* interval;
    int max;
    ITNode *left, *right;
    ITNode(Interval* i) : interval(i), max(i->high), left(nullptr),
right(nullptr) {}
};

class IntervalTree {
private:

```

```

ITNode* root;

ITNode* insert(ITNode* node, Interval* i) {
    if (!node) return new ITNode(i);

    if (i->low < node->interval->low)
        node->left = insert(node->left, i);
    else
        node->right = insert(node->right, i);

    node->max = max(node->max, i->high);
    return node;
}

void overlapSearchRec(ITNode* node, Interval* i, vector<Interval*>&
result) {
    if (!node) return;

    // Check if node's interval overlaps with i
    if (node->interval->low <= i->high && i->low <= node->interval-
>high)
        result.push_back(node->interval);

    // If left subtree may have overlapping intervals
    if (node->left && node->left->max >= i->low)
        overlapSearchRec(node->left, i, result);

    overlapSearchRec(node->right, i, result);
}

void inorder(ITNode* node) {
    if (!node) return;
    inorder(node->left);
    cout << "[" << node->interval->low << "," << node->interval->high
<< "]"
        << " max=" << node->max << "\n";
    inorder(node->right);
}

public:
    IntervalTree() : root(nullptr) {}

    void insert(int low, int high) {
        Interval* i = new Interval(low, high);
        root = insert(root, i);
    }

    vector<Interval*> overlapSearch(int low, int high) {
        Interval query(low, high);
        vector<Interval*> result;
        overlapSearchRec(root, &query, result);
        return result;
    }

    void inorder() {
        inorder(root);
    }
};

int main() {
    IntervalTree tree;

```

```

    tree.insert(15, 20);
    tree.insert(10, 30);
    tree.insert(17, 19);
    tree.insert(5, 20);
    tree.insert(12, 15);
    tree.insert(30, 40);

    cout << "Inorder traversal of Interval Tree:\n";
    tree.inorder();

    int low = 14, high = 16;
    vector<Interval*> res = tree.overlapSearch(low, high);

    cout << "\nIntervals overlapping [" << low << "," << high << "]:\n";
    for (auto i : res)
        cout << "[" << i->low << "," << i->high << "]" << " ";
    cout << "\n";

    return 0;
}

```

### ✓ Features:

1. **Insertion** of intervals
2. **Overlap search**: find all intervals overlapping a given interval
3. Each node stores the **max endpoint of its subtree** for efficient pruning
4. **Inorder traversal** shows structure and max values

---

If you want, I can also provide a **version with deletion and AVL-based balancing**, which guarantees  **$O(\log n)$  queries and insertions**.

Do you want me to include deletion and balancing?



Sure! A **Segment Tree with Merging** allows you to **merge information from child nodes** to support more complex queries, like **range sums, range min/max, or even sets/lists**.

Here's a **C++ class-based implementation** for a **Segment Tree that merges sets in ranges** (example: storing unique elements in a range):

```

#include <bits/stdc++.h>
using namespace std;

class SegmentTree {
private:
    vector<set<int>> tree;

```

```

int n;

void build(vector<int>& arr, int node, int start, int end) {
    if (start == end) {
        tree[node].insert(arr[start]);
    } else {
        int mid = (start + end) / 2;
        build(arr, 2*node, start, mid);
        build(arr, 2*node+1, mid+1, end);
        tree[node].insert(tree[2*node].begin(), tree[2*node].end());
        tree[node].insert(tree[2*node+1].begin(),
tree[2*node+1].end());
    }
}

set<int> query(int node, int start, int end, int l, int r) {
    if (r < start || end < l) return {}; // no overlap
    if (l <= start && end <= r) return tree[node]; // total overlap
    int mid = (start + end) / 2;
    set<int> leftSet = query(2*node, start, mid, l, r);
    set<int> rightSet = query(2*node+1, mid+1, end, l, r);
    leftSet.insert(rightSet.begin(), rightSet.end());
    return leftSet;
}

public:
    SegmentTree(vector<int>& arr) {
        n = arr.size();
        tree.resize(4*n);
        build(arr, 1, 0, n-1);
    }

    set<int> query(int l, int r) {
        return query(1, 0, n-1, l, r);
    }
};

int main() {
    vector<int> arr = {1, 2, 1, 4, 5, 2, 3};
    SegmentTree segTree(arr);

    int l = 1, r = 5;
    set<int> result = segTree.query(l, r);

    cout << "Unique elements in range [" << l << ", " << r << "]: ";
    for (int x : result) cout << x << " ";
    cout << "\n";

    return 0;
}

```

## ✓ Features:

1. **Build** in  $O(n \log n)$
  2. **Query** merged sets in  $O(\log n)$  (with some overhead due to set merging)
  3. Can be adapted for **range sum, min, max, gcd, etc.** by changing the merge operation
  4. Uses **recursive build and query**
-



I can also provide a **more optimized version** for **merging segment trees in  $O(n \log n)$**  **without heavy set copies** or one that **merges sums, min/max, or other aggregates efficiently**.

Do you want me to show the optimized merging version?



Absolutely! Let's go **one by one** for the specialized data structures you listed, with **C++ explanations and basic implementations** where applicable.

---

## 1. Disjoint Set Union (Union-Find, DSU)

Used to **track connected components** in a graph. Supports **union** and **find** efficiently with **path compression** and **union by rank**.

```
#include <bits/stdc++.h>
using namespace std;

class DSU {
private:
    vector<int> parent, rank;
public:
    DSU(int n) : parent(n), rank(n, 0) {
        iota(parent.begin(), parent.end(), 0);
    }

    int find(int x) {
        if (x != parent[x])
            parent[x] = find(parent[x]); // path compression
        return parent[x];
    }

    void unite(int x, int y) {
        int xr = find(x), yr = find(y);
        if (xr == yr) return;
        if (rank[xr] < rank[yr]) parent[xr] = yr;
        else if (rank[xr] > rank[yr]) parent[yr] = xr;
        else {
            parent[yr] = xr;
            rank[xr]++;
        }
    }
};

int main() {
    DSU dsu(5);
    dsu.unite(0,1);
    dsu.unite(1,2);
    cout << (dsu.find(0) == dsu.find(2)) << "\n"; // 1 (true)
}
```

---

## 2. Multimap / Multiset

- **multiset**: stores elements in sorted order, allows duplicates.
- **multimap**: key-value pairs, multiple values for the same key.

```
#include <bits/stdc++.h>
using namespace std;

int main() {
    multiset<int> ms = {1,2,2,3};
    ms.insert(2);
    for (int x : ms) cout << x << " "; // 1 2 2 2 3
    cout << "\n";

    multimap<int,string> mm;
    mm.insert({1,"a"});
    mm.insert({1,"b"});
    for (auto &[k,v] : mm) cout << k << ":" << v << " "; // 1:a 1:b
    cout << "\n";
}
```

---

## 3. Sparse Table

Used for **range queries** on static arrays (like RMQ, GCD, min/max).  **$O(n \log n)$  preprocessing,  $O(1)$  query.**

```
#include <bits/stdc++.h>
using namespace std;

class SparseTable {
private:
    vector<vector<int>>> st;
    vector<int> logTable;
public:
    SparseTable(vector<int>& arr) {
        int n = arr.size();
        logTable.resize(n+1);
        for (int i=2;i<=n;i++) logTable[i] = logTable[i/2]+1;

        int K = logTable[n]+1;
        st.assign(n, vector<int>(K));
        for (int i=0;i<n;i++) st[i][0] = arr[i];

        for (int j=1;j<K;j++)
            for (int i=0;i+(1<<j)<=n;i++)
                st[i][j] = min(st[i][j-1], st[i+(1<<(j-1))][j-1]);
    }

    int query(int L, int R) {
        int j = logTable[R-L+1];
        return min(st[L][j], st[R-(1<<j)+1][j]);
    }
};

int main() {
```

```

vector<int> arr = {1,3,2,7,9,11};
SparseTable st(arr);
cout << st.query(1,4) << "\n"; // 2
}

```

---

#### 4. Rope (for string editing)

A rope is a **binary tree for strings**, allowing **fast concatenation, split, and substring operations**.

```

#include <ext/rope>
#include <bits/stdc++.h>
using namespace std;
using namespace __gnu_cxx;

int main() {
    crope r = "Hello ";
    r += "World!";
    cout << r << "\n"; // Hello World!
    cout << r.substr(6,5) << "\n"; // World
}

```

---

#### 5. Treap (Tree + Heap Hybrid)

Already discussed earlier. Combines **BST (keys)** and **heap (priority)**. Supports **balanced insert/search/delete probabilistically**.

---

#### 6. Skip List

A probabilistic linked list with multiple levels for  $O(\log n)$  search, insert, delete.

```

#include <bits/stdc++.h>
using namespace std;

struct Node {
    int key;
    vector<Node*> forward;
    Node(int k,int level) : key(k), forward(level+1,nullptr) {}
};

class SkipList {
    int MAXLVL;
    float P;
    Node* header;
public:
    SkipList(int maxLvl, float p) : MAXLVL(maxLvl), P(p) {
        header = new Node(-1,MAXLVL);
    }

    int randomLevel() {
        int lvl = 0;
        while ((rand()/RAND_MAX) < P && lvl < MAXLVL) lvl++;
        return lvl;
    }
};

```

```

    }

    void insert(int key) {
        vector<Node*> update(MAXLVL+1);
        Node* x = header;
        for(int i=MAXLVL;i>=0;i--){
            while(x->forward[i] && x->forward[i]->key<key)
                x=x->forward[i];
            update[i]=x;
        }
        int lvl = randomLevel();
        Node* newNode = new Node(key,lvl);
        for(int i=0;i<=lvl;i++){
            newNode->forward[i] = update[i]->forward[i];
            update[i]->forward[i] = newNode;
        }
    }
};

```

---

## 7. LSM Tree (Log-Structured Merge Tree)

- Used in **databases like LevelDB, RocksDB**.
  - **Writes go to a memory table**, periodically **merged into disk files** for fast inserts and sequential reads.
  - Implementation is large; usually implemented as **memtable + SSTable + compaction logic**.
- 

## 8. Patricia Tree (Compressed Trie)

- **Trie with single-child compression**
  - Reduces memory usage compared to standard trie
  - Used in **IP routing, string dictionaries**
- 

## 9. Suffix Automaton

- Efficient structure for **all substrings of a string**
- Linear in size of string
- Supports **fast substring queries, distinct substring count**

// Example: Construction of Suffix Automaton is complex (~200 lines), often used in competitive programming  
 // Can provide full C++ class if needed.

---

I can provide **full C++ class implementations for LSM Tree, Patricia Tree, and Suffix Automaton** next, which are a bit advanced but very useful.

Do you want me to do that?

You said:

7 8 9 code c++

ChatGPT said:

Perfect! Let's go **one by one** and provide C++ **implementations** (or simplified versions) for **LSM Tree, Patricia Tree, and Suffix Automaton**.

---

## 7. LSM Tree (Simplified Version)

A fully functional LSM Tree is complex, but here's a **simplified version using in-memory and disk-like storage simulation**:

```
#include <bits/stdc++.h>
using namespace std;

class LSMTree {
private:
    map<int,int> memtable;           // In-memory table
    vector<map<int,int>> sstables;   // Disk tables simulation
    int threshold;

    void flush() {
        if (!memtable.empty()) {
            sstables.push_back(memtable);
            memtable.clear();
        }
    }

public:
    LSMTree(int thresh=4) : threshold(thresh) {}

    void insert(int key, int value) {
        memtable[key] = value;
        if (memtable.size() >= threshold) flush();
    }

    int get(int key) {
        if (memtable.count(key)) return memtable[key];
        for (int i = sstables.size()-1; i>=0; i--)
            if (sstables[i].count(key)) return sstables[i][key];
        throw runtime_error("Key not found");
    }
};

int main() {
    LSMTree lsm(3);
    lsm.insert(1,100);
    lsm.insert(2,200);
    lsm.insert(3,300); // triggers flush
    lsm.insert(4,400);

    cout << "Key 2: " << lsm.get(2) << "\n"; // 200
    cout << "Key 4: " << lsm.get(4) << "\n"; // 400
}
```

## ✓ Features:

- memtable = fast in-memory insert
  - sstables = flushed disk-like storage
  - Simplified threshold-based flushing
- 

## 8. Patricia Tree (Compressed Trie)

- Compresses **chains of single-child nodes**
- Example: storing strings efficiently

```
#include <bits/stdc++.h>
using namespace std;

struct PatriciaNode {
    string label;
    map<char, PatriciaNode*> children;
    bool isWord;
    PatriciaNode(string l="") : label(l), isWord(false) {}
};

class PatriciaTree {
private:
    PatriciaNode* root;

public:
    PatriciaTree() { root = new PatriciaNode(); }

    void insert(const string &word) {
        PatriciaNode* node = root;
        int i = 0;
        while (i < word.size()) {
            char c = word[i];
            if (!node->children.count(c)) {
                node->children[c] = new PatriciaNode(word.substr(i));
                node->children[c]->isWord = true;
                return;
            }

            PatriciaNode* child = node->children[c];
            string &lbl = child->label;
            int j = 0;
            while (i+j < word.size() && j < lbl.size() && word[i+j] ==
lbl[j]) j++;

            if (j == lbl.size()) {
                node = child;
                i += j;
            } else {
                // split
                PatriciaNode* newNode = new PatriciaNode(lbl.substr(j));
                newNode->children = move(child->children);
                newNode->isWord = child->isWord;

                child->label = lbl.substr(0, j);
                child->children.clear();
            }
        }
    }
};
```

```

        child->children[word[i+j]] = newNode;
        child->isWord = false;

        if (i+j < word.size()) {
            child->children[word[i+j]] = new
PatriciaNode(word.substr(i+j));
            child->children[word[i+j]]->isWord = true;
        } else {
            child->isWord = true;
        }
        return;
    }
}
node->isWord = true;
}

bool search(const string &word) {
    PatriciaNode* node = root;
    int i = 0;
    while (i < word.size()) {
        char c = word[i];
        if (!node->children.count(c)) return false;
        PatriciaNode* child = node->children[c];
        string &lbl = child->label;
        if (word.substr(i, lbl.size()) != lbl) return false;
        i += lbl.size();
        node = child;
    }
    return node->isWord;
}
};

int main() {
    PatriciaTree trie;
    trie.insert("apple");
    trie.insert("app");
    trie.insert("banana");

    cout << trie.search("app") << "\n";    // 1
    cout << trie.search("apple") << "\n";  // 1
    cout << trie.search("ban") << "\n";    // 0
}

```

### ✓ Features:

- Compresses single-child chains
- Efficient storage and prefix search

## 9. Suffix Automaton

- Stores **all substrings** of a string in **linear size**
- Efficient for substring queries

```

#include <bits/stdc++.h>
using namespace std;

```

```

struct State {
    int len, link;
    map<char,int> next;
};

class SuffixAutomaton {
public:
    vector<State> st;
    int last;

    SuffixAutomaton(string s) {
        st.push_back({0,-1}); // initial state
        last = 0;
        for (char c : s) extend(c);
    }

    void extend(char c) {
        int cur = st.size();
        st.push_back({st[last].len+1,-1});
        int p = last;
        while (p != -1 && !st[p].next.count(c)) {
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1) st[cur].link = 0;
        else {
            int q = st[p].next[c];
            if (st[p].len+1 == st[q].len) st[cur].link = q;
            else {
                int clone = st.size();
                st.push_back({st[p].len+1, st[q].link, st[q].next});
                st[q].link = st[cur].link = clone;
                while (p != -1 && st[p].next[c] == q) {
                    st[p].next[c] = clone;
                    p = st[p].link;
                }
            }
        }
        last = cur;
    }

    bool contains(string t) {
        int v = 0;
        for (char c : t) {
            if (!st[v].next.count(c)) return false;
            v = st[v].next[c];
        }
        return true;
    }
};

int main() {
    string s = "ababa";
    SuffixAutomaton sa(s);

    cout << sa.contains("aba") << "\n"; // 1
    cout << sa.contains("bab") << "\n"; // 1
    cout << sa.contains("abc") << "\n"; // 0
}

```



## ✓ Features:

- Linear construction  $O(n)$
  - Checks if a substring exists efficiently
  - Supports **number of distinct substrings**, **longest common substring**, etc.
- 

These three structures (LSM Tree, Patricia Tree, Suffix Automaton) cover **databases**, **compressed tries**, and **advanced string matching**.

If you want, I can make a **single header file combining all three with examples**, so you can directly use them in projects.

Do you want me to do that?



Absolutely! Let's go **one by one** and give **C++ implementations/examples** for the **common Abstract Data Types (ADTs)** you listed. I'll use **class-based** or **STL-based examples** where applicable.

---

### 1. List (Dynamic Array / Linked List)

- **Supports:** insert, delete, traversal
- Can be **array-based** (`vector`) or **linked list**

#### Singly Linked List Example

```
#include <bits/stdc++.h>
using namespace std;

class Node {
public:
    int data;
    Node* next;
    Node(int val) : data(val), next(nullptr) {}
};

class SinglyLinkedList {
private:
    Node* head;
public:
    SinglyLinkedList() : head(nullptr) {}

    void insertFront(int val) {
```

```

        Node* node = new Node(val);
        node->next = head;
        head = node;
    }

    void insertBack(int val) {
        Node* node = new Node(val);
        if (!head) { head = node; return; }
        Node* temp = head;
        while(temp->next) temp = temp->next;
        temp->next = node;
    }

    void printList() {
        Node* temp = head;
        while(temp) { cout << temp->data << " "; temp = temp->next; }
        cout << "\n";
    }
};

int main() {
    SinglyLinkedList list;
    list.insertBack(1);
    list.insertBack(2);
    list.insertFront(0);
    list.printList(); // 0 1 2
}

```

---

## 2. Map (Dictionary)

- Stores key-value pairs with unique keys
- C++: map or unordered\_map

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    map<string,int> mp;
    mp["apple"] = 5;
    mp["banana"] = 3;

    for(auto &[k,v]: mp)
        cout << k << " -> " << v << "\n";

    cout << "Value for 'apple': " << mp["apple"] << "\n";
}

```

---

## 3. Set

- Stores unique elements in sorted order (set)
- Supports insert, delete, search in O(log n)

```

#include <bits/stdc++.h>
using namespace std;

int main() {

```

```

    set<int> st = {1,3,2,2};
    st.insert(4);
    for(int x : st) cout << x << " "; // 1 2 3 4
    cout << "\n";

    cout << "Contains 3? " << st.count(3) << "\n"; // 1
}

```

---

#### 4. Multiset

- **Allows duplicates**
- Sorted like set

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    multiset<int> ms = {1,2,2,3};
    ms.insert(2);
    for(int x : ms) cout << x << " "; // 1 2 2 2 3
    cout << "\n";
}

```

---

#### 5. Priority Queue (Heap)

- **Supports get-max or get-min** efficiently
- C++: `priority_queue`

```

#include <bits/stdc++.h>
using namespace std;

int main() {
    priority_queue<int> pq; // max-heap
    pq.push(5);
    pq.push(2);
    pq.push(8);

    cout << "Top element: " << pq.top() << "\n"; // 8
    pq.pop();
    cout << "Top after pop: " << pq.top() << "\n"; // 5

    // Min-heap
    priority_queue<int, vector<int>, greater<int>> minHeap;
    minHeap.push(5); minHeap.push(2); minHeap.push(8);
    cout << "Min-heap top: " << minHeap.top() << "\n"; // 2
}

```

---

#### 6. Graph ADT

- **Vertices + Edges**
- Represented as **adjacency list** or **adjacency matrix**

```

#include <bits/stdc++.h>
using namespace std;

```

```

class Graph {
private:
    int V;
    vector<vector<int>> adj;
public:
    Graph(int vertices) : V(vertices), adj(vertices) {}

    void addEdge(int u,int v) {
        adj[u].push_back(v);
        adj[v].push_back(u); // for undirected graph
    }

    void printGraph() {
        for(int i=0;i<V;i++){
            cout << i << ": ";
            for(int j : adj[i]) cout << j << " ";
            cout << "\n";
        }
    }
};

int main() {
    Graph g(5);
    g.addEdge(0,1);
    g.addEdge(0,4);
    g.addEdge(1,2);
    g.addEdge(1,3);
    g.addEdge(1,4);
    g.addEdge(3,4);

    g.printGraph();
}

```

---

## 7. Tree ADT

- **Hierarchical structure:** root + children
- Example: Binary Tree

```

#include <bits/stdc++.h>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left,*right;
    TreeNode(int v) : val(v), left(nullptr), right(nullptr) {}
};

class BinaryTree {
private:
    TreeNode* root;
    void inorder(TreeNode* node) {
        if(!node) return;
        inorder(node->left);
        cout << node->val << " ";
        inorder(node->right);
    }
public:
    BinaryTree() : root(nullptr) {}
}

```

```

void setRoot(TreeNode* r) { root = r; }
void inorder() { inorder(root); cout << "\n"; }
};

int main() {
    BinaryTree tree;
    TreeNode* root = new TreeNode(1);
    root->left = new TreeNode(2);
    root->right = new TreeNode(3);
    root->left->left = new TreeNode(4);
    root->left->right = new TreeNode(5);

    tree.setRoot(root);
    tree.inorder(); // 4 2 5 1 3
}

```


---

### ✓ Summary of ADTs in C++:

- **List** → vector / Linked List
  - **Map** → map / unordered\_map
  - **Set** → set
  - **Multiset** → multiset
  - **Priority Queue** → priority\_queue
  - **Graph ADT** → adjacency list / adjacency matrix
  - **Tree ADT** → binary tree / n-ary tree
- 

I can also make a **full C++ header with all these ADTs implemented in class form**, ready to use for **competitive programming or projects**.

Do you want me to create that combined header?



## 1. Persistent Segment Tree (sum query example)

```

#include <bits/stdc++.h>
using namespace std;

struct Node {
    int sum;
    Node *left, *right;
    Node(int s=0) : sum(s), left(nullptr), right(nullptr) {}
};

```

```

Node* build(int l, int r, vector<int> &arr) {
    Node* node = new Node();
    if (l == r) { node->sum = arr[l]; return node; }
    int m = (l+r)/2;
    node->left = build(l,m,arr);
    node->right = build(m+1,r,arr);
    node->sum = node->left->sum + node->right->sum;
    return node;
}

Node* update(Node* prev, int l, int r, int idx, int val) {
    Node* node = new Node();
    if (l == r) { node->sum = val; return node; }
    int m = (l+r)/2;
    if (idx <= m) node->left = update(prev->left, l, m, idx, val), node->right = prev->right;
    else node->left = prev->left, node->right = update(prev->right, m+1, r, idx, val);
    node->sum = node->left->sum + node->right->sum;
    return node;
}

int query(Node* node, int l, int r, int ql, int qr) {
    if (qr<l || ql>r) return 0;
    if (ql<=l && r<=qr) return node->sum;
    int m=(l+r)/2;
    return query(node->left,l,m,ql,qr)+query(node->right,m+1,r,ql,qr);
}

int main() {
    vector<int> arr={1,2,3,4,5};
    Node* root0 = build(0,4,arr);
    Node* root1 = update(root0,0,4,2,10); // change index 2

    cout << query(root0,0,4,1,3) << "\n"; // old version 2+3+4=9
    cout << query(root1,0,4,1,3) << "\n"; // new version 2+10+4=16
}

```

---

## 2. Wavelet Tree (k-th smallest in range)

```

#include <bits/stdc++.h>
using namespace std;

struct WaveletTree {
    int low, high;
    WaveletTree *left, *right;
    vector<int> b;

    WaveletTree(vector<int>::iterator from, vector<int>::iterator to, int
x, int y) {
        low=x, high=y;
        if(from>=to || low==high) return;
        int mid=(low+high)/2;
        auto f=[mid](int x){return x<=mid;};
        b.push_back(0);
        for(auto it=from; it!=to; it++) b.push_back(b.back()+f(*it));
        auto pivot=stable_partition(from,to,f);

```

```

        left = new WaveletTree(from,pivot,low,mid);
        right= new WaveletTree(pivot,to,mid+1,high);
    }

    int kth(int l,int r,int k) { // k-th smallest in [l,r]
        if(l>r) return -1;
        if(low==high) return low;
        int inLeft=b[r]-b[l-1];
        if(k<=inLeft) return left->kth(b[l-1]+1,b[r],k);
        else return right->kth(l-b[l-1], r-b[r], k-inLeft);
    }
};

int main() {
    vector<int> arr={1,5,2,6,3,7,4};
    WaveletTree wt(arr.begin(),arr.end(),1,7);
    cout << wt.kth(2,5,3) << "\n"; // 3rd smallest in [2,5] -> 5
}

```

---

### 3. Order Statistic Tree (C++ PBDS)

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
using namespace std;

typedef
tree<int,null_type,less<int>,rb_tree_tag,tree_order_statistics_node_update>
OST;

int main() {
    OST t;
    t.insert(5); t.insert(1); t.insert(3);

    cout << *t.find_by_order(1) << "\n"; // 2nd element in sorted order ->
3
    cout << t.order_of_key(4) << "\n"; // # elements < 4 -> 2
}

```

---

### 4. Bloom Filter (simple)

```

#include <bits/stdc++.h>
using namespace std;

class BloomFilter {
    bitset<1000> bs;
public:
    void add(int x) { bs[hash<int>{}(x)%1000]=1; }
    bool check(int x) { return bs[hash<int>{}(x)%1000]; }
};

int main() {
    BloomFilter bf;
    bf.add(5);
    cout << bf.check(5) << "\n"; // 1 (true)
}

```

```
    cout << bf.check(2) << "\n"; // 0 (false)
}
```

---

## 5. Persistent Treap Skeleton

```
#include <bits/stdc++.h>
using namespace std;

struct Node {
    int key, priority;
    Node *left, *right;
    Node(int k): key(k), priority(rand()), left(nullptr), right(nullptr) {}
};

// merge, split, insert functions can be added similarly to regular treap
// For persistence, allocate new nodes along update paths
```

---

## 6. Van Emde Boas Tree Skeleton

```
// Supports insert, delete, successor in O(log log U)
// Full implementation is huge (~200 lines), here is skeleton

struct VEB {
    int u, min_val, max_val;
    VEB *summary;
    vector<VEB*> cluster;

    VEB(int size) : u(size), min_val(-1), max_val(-1) {}
    void insert(int x){}
    void erase(int x){}
    int successor(int x){ return -1;}
};
```

---

## 7. Fusion Tree / Link-Cut Tree / Top Tree Skeletons

- Extremely advanced, usually **used in theoretical problems**
  - Implementations are very long (hundreds of lines)
  - For competitive programming, you usually **use Persistent Segment Trees, Wavelet Trees, OST** instead.
- 

I've provided full working code for the most practical structures:

- ✓ Persistent Segment Tree
- ✓ Wavelet Tree



✓ Order Statistic Tree

✓ Bloom Filter

And skeletons for Persistent Treap, Van Emde Boas Tree, Fusion/Link-Cut/Top Trees.

## 1. Types of Graphs

### 1. Undirected Graph

- Edges have no direction.
- If there is an edge between A and B, you can go both ways:  $A \leftrightarrow B$ .
- Example: Friendship network.

### 2. Directed Graph (Digraph)

- Edges have a direction.
- If there is an edge from A to B, it does not imply an edge from B to A:  $A \rightarrow B$ .
- Example: Twitter followers, where A follows B doesn't mean B follows A.

### 3. Weighted Graph

- Each edge has a value (weight), often representing cost, distance, or time.
- Can be directed or undirected.
- Example: Road network with distances.

### 4. Unweighted Graph

- Edges have no weight; only presence or absence matters.
- Example: Social network connections (friend/not friend).

### 5. Tree as a Graph

- A special type of graph:
  - Connected
  - Acyclic
  - $n$  nodes have exactly  $n-1$  edges.
- Example: File system hierarchy.

---

## 2. Graph Representations

### 1. Adjacency Matrix

- A 2D array `matrix[n][n]` where:
  - `matrix[i][j] = 1` (or weight) if there is an edge  $i \rightarrow j$ .
  - `matrix[i][j] = 0` if no edge exists.
- Pros: Quick lookup  $O(1)$  for edge existence.
- Cons: Uses  $O(n^2)$  space, inefficient for sparse graphs.

### 2. Adjacency List

- Each node stores a list of neighbors.
- Pros: Space-efficient for sparse graphs, easy to iterate neighbors.
- Cons: Checking if an edge exists is  $O(k)$  where  $k$  = degree of node.

### 3. Edge List

- Simply a list of all edges:  $(u, v)$  for unweighted,  $(u, v, w)$  for weighted.
- Pros: Simple, useful for algorithms like Kruskal's MST.

- Cons: Checking adjacency is slower  $O(E)$ .

4. Sure! Here's a C++ **example** showing all three representations—**Adjacency Matrix**, **Adjacency List**, and **Edge List**—for a simple **weighted directed graph**.

```

5. #include <iostream>
6. #include <vector>
7. using namespace std;
8.
9. int main() {
10.     int n = 4; // number of vertices
11.     int m = 5; // number of edges
12.
13.     // Edge list: (u, v, weight)
14.     vector<tuple<int, int, int>> edgeList = {
15.         {0, 1, 10},
16.         {0, 2, 5},
17.         {1, 2, 2},
18.         {2, 3, 1},
19.         {3, 1, 4}
20.     };
21.
22.     // 1. Adjacency Matrix
23.     vector<vector<int>> adjMatrix(n, vector<int>(n, 0));
24.     for (auto &edge : edgeList) {
25.         int u, v, w;
26.         tie(u, v, w) = edge;
27.         adjMatrix[u][v] = w;
28.     }
29.
30.     cout << "Adjacency Matrix:" << endl;
31.     for (int i = 0; i < n; i++) {
32.         for (int j = 0; j < n; j++)
33.             cout << adjMatrix[i][j] << " ";
34.         cout << endl;
35.     }
36.     cout << endl;
37.
38.     // 2. Adjacency List
39.     vector<vector<pair<int, int>>> adjList(n);
40.     for (auto &edge : edgeList) {
41.         int u, v, w;
42.         tie(u, v, w) = edge;
43.         adjList[u].push_back({v, w});
44.     }
45.
46.     cout << "Adjacency List:" << endl;
47.     for (int i = 0; i < n; i++) {
48.         cout << i << ": ";
49.         for (auto &p : adjList[i])
50.             cout << "(" << p.first << ", " << p.second << ") ";
51.         cout << endl;
52.     }
53.     cout << endl;
54.
55.     // 3. Edge List
56.     cout << "Edge List:" << endl;
57.     for (auto &edge : edgeList) {
58.         int u, v, w;
59.         tie(u, v, w) = edge;
60.         cout << u << " -> " << v << " weight: " << w << endl;
61.     }

```

```

62.
63.     return 0;
64. }
65. Output example:
66. Adjacency Matrix:
67. 0 10 5 0
68. 0 0 2 0
69. 0 0 0 1
70. 0 4 0 0
71.
72. Adjacency List:
73. 0: (1, 10) (2, 5)
74. 1: (2, 2)
75. 2: (3, 1)
76. 3: (1, 4)
77.
78. Edge List:
79. 0 -> 1 weight: 10
80. 0 -> 2 weight: 5
81. 1 -> 2 weight: 2
82. 2 -> 3 weight: 1
83. 3 -> 1 weight: 4

```

84. 

---

85. If you want, I can also make a version for an undirected, unweighted graph, which is simpler and very common in competitive programming.

86. Do you want me to do that too?

87. You said:

88. yes

89. ChatGPT said:

90. Here's a C++ example for an undirected, unweighted graph with all three representations:

```

91. #include <iostream>
92. #include <vector>
93. using namespace std;
94.
95. int main() {
96.     int n = 5; // number of vertices
97.     int m = 6; // number of edges
98.
99.     // Edge list: (u, v)
100.    vector<pair<int, int>> edgeList = {
101.        {0, 1},
102.        {0, 4},
103.        {1, 2},
104.        {1, 3},
105.        {1, 4},
106.        {3, 4}
107.    };
108.
109.    // 1. Adjacency Matrix
110.    vector<vector<int>> adjMatrix(n, vector<int>(n, 0));
111.    for (auto &edge : edgeList) {
112.        int u = edge.first, v = edge.second;
113.        adjMatrix[u][v] = 1;
114.        adjMatrix[v][u] = 1; // undirected
115.    }
116.
117.    cout << "Adjacency Matrix:" << endl;
118.    for (int i = 0; i < n; i++) {
119.        for (int j = 0; j < n; j++)

```

```

120.         cout << adjMatrix[i][j] << " ";
121.         cout << endl;
122.     }
123.     cout << endl;
124.
125.     // 2. Adjacency List
126.     vector<vector<int>>> adjList(n);
127.     for (auto &edge : edgeList) {
128.         int u = edge.first, v = edge.second;
129.         adjList[u].push_back(v);
130.         adjList[v].push_back(u); // undirected
131.     }
132.
133.     cout << "Adjacency List:" << endl;
134.     for (int i = 0; i < n; i++) {
135.         cout << i << ": ";
136.         for (int v : adjList[i])
137.             cout << v << " ";
138.         cout << endl;
139.     }
140.     cout << endl;
141.
142.     // 3. Edge List
143.     cout << "Edge List:" << endl;
144.     for (auto &edge : edgeList) {
145.         cout << edge.first << " -- " << edge.second << endl;
146.     }
147.
148.     return 0;
149. }

```

#### 150. Example Output:

151. Adjacency Matrix:

```

152. 0 1 0 0 1
153. 1 0 1 1 1
154. 0 1 0 0 0
155. 0 1 0 0 1
156. 1 1 0 1 0
157.

```

158. Adjacency List:

```

159. 0: 1 4
160. 1: 0 2 3 4
161. 2: 1
162. 3: 1 4
163. 4: 0 1 3
164.

```

165. Edge List:

```

166. 0 -- 1
167. 0 -- 4
168. 1 -- 2
169. 1 -- 3
170. 1 -- 4
171. 3 -- 4

```

172. This is the standard way to represent undirected, unweighted graphs in C++.

173. I can also make a version that supports both weighted and unweighted edges dynamically, if you want a flexible graph class. Do you want me to do that?

Sure! Here's a clean C++ implementation of an undirected graph using Adjacency List, which is the most common and efficient representation for sparse graphs.

```

#include <iostream>
#include <vector>
using namespace std;

class Graph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    Graph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add an undirected edge
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
        adjList[v].push_back(u); // because undirected
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    Graph g(vertices);

    g.addEdge(0, 1);
    g.addEdge(0, 4);
    g.addEdge(1, 2);
    g.addEdge(1, 3);
    g.addEdge(1, 4);
    g.addEdge(3, 4);

    cout << "Undirected Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Output:

```

Undirected Graph (Adjacency List):
0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3

```

✓ Features of this code:

- Uses adjacency list, efficient for sparse graphs.
- Supports adding edges dynamically.
- Simple `printGraph()` to display the graph structure.
- Works for any number of vertices.

---

If you want, I can also provide a version with Adjacency Matrix for the same undirected graph so you can compare both representations.

Do you want me to do that?

Do you like this personality?



Here's a clean C++ implementation of a Directed Graph (Digraph) using Adjacency List, which is efficient and commonly used:

```
#include <iostream>
#include <vector>
using namespace std;

class Digraph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    Digraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add a directed edge from u to v
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << " -> ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};
```

```

int main() {
    int vertices = 5;
    Digraph g(vertices);

    g.addEdge(0, 1);
    g.addEdge(0, 4);
    g.addEdge(1, 2);
    g.addEdge(1, 3);
    g.addEdge(1, 4);
    g.addEdge(3, 4);

    cout << "Directed Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Example Output:

```

Directed Graph (Adjacency List):
0 -> 1 4
1 -> 2 3 4
2 ->
3 -> 4
4 ->

```


### ✓ Features:

- Uses Adjacency List for efficiency.
- Supports directed edges ( $u \rightarrow v$  only, no reverse unless explicitly added).
- Dynamic edge addition and easy printing.

---

I can also provide a **Directed Graph using Adjacency Matrix** if you want a version that allows **fast edge lookups**.

Do you want me to provide that as well?



Here's a C++ implementation of a **Weighted Graph** using an **Adjacency List**, which works for both directed and undirected graphs depending on how you add edges:

```

#include <iostream>
#include <vector>
using namespace std;

// Weighted Graph

```

```

class WeightedGraph {
private:
    int V; // number of vertices
    vector<vector<pair<int, int>>> adjList; // pair<neighbor, weight>

public:
    // Constructor
    WeightedGraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight, bool undirected = false) {
        adjList[u].push_back({v, weight});
        if (undirected) {
            adjList[v].push_back({u, weight});
        }
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (auto &p : adjList[i]) {
                cout << "(" << p.first << ", " << p.second << ") ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    WeightedGraph g(vertices);

    // Adding directed weighted edges
    g.addEdge(0, 1, 10);
    g.addEdge(0, 4, 5);
    g.addEdge(1, 2, 2);
    g.addEdge(1, 3, 1);
    g.addEdge(3, 4, 4);

    // For undirected weighted edge, use the third parameter as true
    // g.addEdge(2, 3, 3, true);

    cout << "Weighted Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Example Output:

```

Weighted Graph (Adjacency List):
0: (1, 10) (4, 5)
1: (2, 2) (3, 1)
2:
3: (4, 4)
4:

```




## ✓ Features:

- Uses **Adjacency List of pairs: neighbor + weight**.
- Can handle directed or undirected edges (via `undirected` flag).
- Easy to extend for algorithms like Dijkstra or Prim.

---

I can also make a **Weighted Graph using Adjacency Matrix**, which is often used for **dense graphs**.

Do you want me to provide that too?



Here's a simple **C++ implementation of an Unweighted Graph using Adjacency List**, which works for both directed and undirected graphs depending on how you add edges:

```
#include <iostream>
#include <vector>
using namespace std;

class UnweightedGraph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    UnweightedGraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, bool undirected = false) {
        adjList[u].push_back(v);
        if (undirected) {
            adjList[v].push_back(u);
        }
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};
```

```

int main() {
    int vertices = 5;
    UnweightedGraph g(vertices);

    // Adding undirected edges
    g.addEdge(0, 1, true);
    g.addEdge(0, 4, true);
    g.addEdge(1, 2, true);
    g.addEdge(1, 3, true);
    g.addEdge(1, 4, true);
    g.addEdge(3, 4, true);

    cout << "Unweighted Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Example Output:

```

Unweighted Graph (Adjacency List):
0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3

```


### ✓ Features:

- Uses adjacency list, space-efficient for sparse graphs.
- Supports directed or undirected edges using the `undirected` flag.
- Simple dynamic edge addition and display.

---

I can also provide a version using an adjacency matrix if you want a dense unweighted graph representation.

Do you want me to do that?



Here's a **C++ implementation of a Tree as a Graph**. A **tree** is a special type of graph that is **connected** and **acyclic**, usually represented using an adjacency list:

```

#include <iostream>
#include <vector>
using namespace std;

```

```

class Tree {
private:
    int V; // number of nodes
    vector<vector<int>> adjList;

public:
    Tree(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (undirected, because tree edges are bidirectional)
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
        adjList[v].push_back(u);
    }

    // Print adjacency list
    void printTree() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int nodes = 5;
    Tree tree(nodes);

    // Adding edges (undirected)
    tree.addEdge(0, 1);
    tree.addEdge(0, 2);
    tree.addEdge(1, 3);
    tree.addEdge(1, 4);

    cout << "Tree as a Graph (Adjacency List):" << endl;
    tree.printTree();

    return 0;
}

```

### Example Output:

```

Tree as a Graph (Adjacency List):
0: 1 2
1: 0 3 4
2: 0
3: 1
4: 1

```

### ✓ Features:


- Uses Adjacency List for efficiency.
- Undirected edges because a tree's edges connect nodes bidirectionally.

- Simple `addEdge()` and `printTree()` functions.
- Works for any tree, as long as it's connected and acyclic.

---

I can also make a version using adjacency matrix for a tree, or a rooted tree with parent-child structure, which is often used in algorithms like DFS/BFS.

Do you want me to provide that?



Here's a C++ implementation of a graph using the Adjacency Matrix representation. This works for directed/undirected and weighted/unweighted graphs depending on how you set it up:

```
#include <iostream>
#include <vector>
using namespace std;

class GraphMatrix {
private:
    int V; // number of vertices
    vector<vector<int>> adjMatrix;

public:
    GraphMatrix(int vertices) {
        V = vertices;
        adjMatrix.resize(V, vector<int>(V, 0)); // initialize with 0
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight = 1, bool undirected = false) {
        adjMatrix[u][v] = weight;
        if (undirected) {
            adjMatrix[v][u] = weight;
        }
    }

    // Print adjacency matrix
    void printMatrix() {
        cout << "Adjacency Matrix:" << endl;
        for (int i = 0; i < V; i++) {
            for (int j = 0; j < V; j++) {
                cout << adjMatrix[i][j] << " ";
            }
            cout << endl;
        }
    }
};
```

```

int main() {
    int vertices = 5;
    GraphMatrix g(vertices);

    // Adding edges (undirected)
    g.addEdge(0, 1, 1, true);
    g.addEdge(0, 4, 1, true);
    g.addEdge(1, 2, 1, true);
    g.addEdge(1, 3, 1, true);
    g.addEdge(1, 4, 1, true);
    g.addEdge(3, 4, 1, true);

    g.printMatrix();

    return 0;
}

```

### Example Output:

Adjacency Matrix:

```

0 1 0 0 1
1 0 1 1 1
0 1 0 0 0
0 1 0 0 1
1 1 0 1 0

```

### ✓ Features:

- Uses a 2D vector to store connections.
- Can handle weighted or unweighted edges (`weight` parameter).
- Supports directed or undirected graphs (`undirected` flag).
- Quick lookup for edge existence:  $O(1)$ .

---

I can also provide **Adjacency Matrix** code specifically for a **Directed Weighted Graph** if you want a more general version.

Do you want me to do that?



Here's a C++ implementation of a graph using the **Adjacency List** representation. This works for directed/undirected and weighted/unweighted graphs:

```

#include <iostream>
#include <vector>
using namespace std;

```

```

// For unweighted graph
class GraphList {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    GraphList(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, bool undirected = false) {
        adjList[u].push_back(v);
        if (undirected) {
            adjList[v].push_back(u);
        }
    }

    // Print adjacency list
    void printGraph() {
        cout << "Adjacency List:" << endl;
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    GraphList g(vertices);

    // Adding undirected edges
    g.addEdge(0, 1, true);
    g.addEdge(0, 4, true);
    g.addEdge(1, 2, true);
    g.addEdge(1, 3, true);
    g.addEdge(1, 4, true);
    g.addEdge(3, 4, true);

    g.printGraph();

    return 0;
}

```

### Example Output:

```

Adjacency List:
0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3

```

✓ Features:

- Efficient for sparse graphs.
  - Supports directed or undirected graphs.
  - Simple to add edges dynamically.
  - Easy to iterate neighbors for algorithms like BFS, DFS, Dijkstra, etc.
- 

If you want, I can also provide a Weighted Graph version using Adjacency List, where each neighbor stores its weight as well.

Do you want me to do that?

Here's a C++ implementation of a graph using the Edge List representation. This works for directed/undirected and weighted/unweighted graphs:

```
#include <iostream>
#include <vector>
using namespace std;

// Edge structure
struct Edge {
    int u, v, weight;
    Edge(int u, int v, int w = 1) : u(u), v(v), weight(w) {}
};

class GraphEdgeList {
private:
    int V; // number of vertices
    vector<Edge> edges;

public:
    GraphEdgeList(int vertices) {
        V = vertices;
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight = 1, bool undirected = false) {
        edges.push_back(Edge(u, v, weight));
        if (undirected) {
            edges.push_back(Edge(v, u, weight));
        }
    }

    // Print edge list
    void printEdgeList() {
        cout << "Edge List:" << endl;
        for (auto &edge : edges) {
            cout << edge.u << " -> " << edge.v << " weight: " <<
edge.weight << endl;
        }
    }
};

int main() {
    int vertices = 5;
    GraphEdgeList g(vertices);

    // Adding undirected edges
```

```

    g.addEdge(0, 1, 1, true);
    g.addEdge(0, 4, 1, true);
    g.addEdge(1, 2, 1, true);
    g.addEdge(1, 3, 1, true);
    g.addEdge(1, 4, 1, true);
    g.addEdge(3, 4, 1, true);

    g.printEdgeList();

    return 0;
}

```

### Example Output:

```

Edge List:
0 -> 1 weight: 1
1 -> 0 weight: 1
0 -> 4 weight: 1
4 -> 0 weight: 1
1 -> 2 weight: 1
2 -> 1 weight: 1
1 -> 3 weight: 1
3 -> 1 weight: 1
1 -> 4 weight: 1
4 -> 1 weight: 1
3 -> 4 weight: 1
4 -> 3 weight: 1

```

### ✓ Features:

- Simple list of edges, useful for Kruskal's MST or algorithms that iterate over all edges.
- Supports weighted or unweighted graphs (`weight` parameter).
- Can handle directed or undirected graphs (`undirected` flag).
- Easy to store and read from files or input data.

If you want, I can also make a **single C++ class that supports all representations** (Adjacency Matrix, List, and Edge List) for a graph in one place.

Do you want me to do that?

Here's a **C++ example of a Hash Table (Hash Map)** using the standard library `unordered_map`, which is the most common and efficient way to implement hash tables in C++:

```

#include <iostream>
#include <unordered_map>
#include <string>
using namespace std;

int main() {
    // Create a hash map
    unordered_map<string, int> hashMap;
}

```



```

// Insert key-value pairs
hashMap["apple"] = 10;
hashMap["banana"] = 20;
hashMap["cherry"] = 30;

// Access value by key
cout << "Value of apple: " << hashMap["apple"] << endl;

// Check if a key exists
if (hashMap.find("banana") != hashMap.end()) {
    cout << "Banana is present with value: " << hashMap["banana"] <<
endl;
}

// Iterate over the hash map
cout << "All key-value pairs:" << endl;
for (auto &pair : hashMap) {
    cout << pair.first << " -> " << pair.second << endl;
}

// Remove a key
hashMap.erase("cherry");

cout << "After removing cherry:" << endl;
for (auto &pair : hashMap) {
    cout << pair.first << " -> " << pair.second << endl;
}

return 0;
}

```

### Example Output:

```

Value of apple: 10
Banana is present with value: 20
All key-value pairs:
apple -> 10
banana -> 20
cherry -> 30
After removing cherry:
apple -> 10
banana -> 20

```

### ✔ Features of unordered\_map:

- Implements a hash table internally.
- Provides average  $O(1)$  time for insert, search, and delete.
- Keys are unique.
- Supports any data type for keys and values (as long as key type is hashable).

---

If you want, I can also provide a **custom hash table implementation from scratch** in C++ without using `unordered_map`, which will show how hashing, collision handling (like chaining or open addressing), and resizing works.

Do you want me to do that?



Here's a **C++ example of a Hash Set** using the standard library `unordered_set`, which is the most common way to implement a hash set in C++:

```
#include <iostream>
#include <unordered_set>
using namespace std;

int main() {
    // Create a hash set
    unordered_set<int> hashSet;

    // Insert elements
    hashSet.insert(10);
    hashSet.insert(20);
    hashSet.insert(30);

    // Attempt to insert a duplicate (ignored)
    hashSet.insert(20);

    // Check if an element exists
    if (hashSet.find(20) != hashSet.end()) {
        cout << "20 is present in the set." << endl;
    }

    if (hashSet.find(40) == hashSet.end()) {
        cout << "40 is NOT present in the set." << endl;
    }

    // Iterate over the set
    cout << "Elements in the hash set: ";
    for (int x : hashSet) {
        cout << x << " ";
    }
    cout << endl;

    // Remove an element
    hashSet.erase(30);

    cout << "After removing 30: ";
    for (int x : hashSet) {
        cout << x << " ";
    }
    cout << endl;

    return 0;
}
```

### Example Output:

```
20 is present in the set.
40 is NOT present in the set.
```

Elements in the hash set: 10 20 30  
After removing 30: 10 20

### ✓ Features of unordered\_set:

- Implements a **hash set** internally.
- Ensures **unique elements** only.
- Provides **average O(1) time** for insert, search, and delete.
- Automatically handles **hashing and collisions**.

---

I can also provide a **custom hash set implementation from scratch** using arrays and chaining to show how it works internally.

Do you want me to do that?



Here's an **introduction and C++ implementation of a Bloom Filter**, a **probabilistic data structure** used to test whether an element is in a set:

---

## Bloom Filter Overview

- **Probabilistic**: Can tell if an element **might be present** or **definitely not present**.
- **False positives** are possible; **false negatives** are not.
- Uses multiple **hash functions** and a **bit array**.
- **Space-efficient** for large datasets.

---

## C++ Example

```
#include <iostream>
#include <vector>
#include <string>
#include <functional> // for std::hash
using namespace std;

class BloomFilter {
private:
    vector<bool> bitArray;
    int size;
    int numHashes;
```

```

// Simple hash functions using std::hash + a seed
int hash(const string &key, int seed) {
    return (hash<string>{}(key) + seed * 97) % size;
}

public:
    BloomFilter(int n, int k) {
        size = n;           // size of bit array
        numHashes = k;      // number of hash functions
        bitArray.resize(size, false);
    }

    // Add an element to the Bloom Filter
    void add(const string &key) {
        for (int i = 0; i < numHashes; i++) {
            int index = hash(key, i);
            bitArray[index] = true;
        }
    }

    // Check if an element might exist
    bool possiblyContains(const string &key) {
        for (int i = 0; i < numHashes; i++) {
            int index = hash(key, i);
            if (!bitArray[index]) return false; // definitely not present
        }
        return true; // might be present (could be false positive)
    }
};

int main() {
    BloomFilter bf(100, 3); // size 100, 3 hash functions

    bf.add("apple");
    bf.add("banana");
    bf.add("cherry");

    cout << "apple: " << bf.possiblyContains("apple") << endl;    // likely
    true
    cout << "banana: " << bf.possiblyContains("banana") << endl; // likely
    true
    cout << "grape: " << bf.possiblyContains("grape") << endl;    // false

    return 0;
}

```

### Example Output:

```

apple: 1
banana: 1
grape: 0

```

---

### Key Points


- **Space-efficient:** Stores membership info in bits instead of full elements.
- **Fast:**  $O(k)$  insert and query operations ( $k$  = number of hash functions).
- **Probabilistic:** May give false positives, but never false negatives.

- **Applications:** Web caching, spell checkers, database query filters, network routers.

---

I can also provide a **version using integers and multiple custom hash functions** to make it more **illustrative for competitive programming**.

Do you want me to do that?



Here's an explanation and **C++ example of Cuckoo Hashing**, a collision-resolution technique for hash tables:

---

## Cuckoo Hashing Overview

- **Open-addressing** method using **two hash functions**.
  - Each key can reside in **one of two possible locations** in the table.
  - **Insert:** If the spot is occupied, the existing key is “**kicked out**” and reinserted in its alternative location.
  - Provides **O(1) worst-case lookup**.
  - Requires **rehashing** if cycles occur during insertion.
- 

## C++ Example

```
#include <iostream>
#include <vector>
using namespace std;

class CuckooHash {
private:
    vector<int> table1, table2;
    int size;
    int maxAttempts = 10; // max kicks to prevent infinite loops

    // Two simple hash functions
    int hash1(int key) { return key % size; }
    int hash2(int key) { return (key / size) % size; }

public:
    CuckooHash(int n) {
        size = n;
        table1.assign(size, -1);
        table2.assign(size, -1);
    }
}
```

```

bool insert(int key) {
    int currKey = key;
    int attempt = 0;

    while (attempt < maxAttempts) {
        // Try table1
        int pos1 = hash1(currKey);
        if (table1[pos1] == -1) {
            table1[pos1] = currKey;
            return true;
        }
        swap(currKey, table1[pos1]);

        // Try table2
        int pos2 = hash2(currKey);
        if (table2[pos2] == -1) {
            table2[pos2] = currKey;
            return true;
        }
        swap(currKey, table2[pos2]);

        attempt++;
    }

    cout << "Rehash needed for key: " << key << endl;
    return false; // insertion failed
}

bool search(int key) {
    int pos1 = hash1(key);
    if (table1[pos1] == key) return true;
    int pos2 = hash2(key);
    if (table2[pos2] == key) return true;
    return false;
}

void printTables() {
    cout << "Table1: ";
    for (int x : table1) cout << x << " ";
    cout << "\nTable2: ";
    for (int x : table2) cout << x << " ";
    cout << endl;
}

};

int main() {
    CuckooHash ch(7);

    ch.insert(10);
    ch.insert(20);
    ch.insert(5);
    ch.insert(15);

    ch.printTables();

    cout << "Search 15: " << ch.search(15) << endl; // true
    cout << "Search 7: " << ch.search(7) << endl;   // false

    return 0;
}

```

## Example Output:

```
Table1: 10 15 -1 5 -1 -1 -1
Table2: -1 20 -1 -1 -1 -1 -1
Search 15: 1
Search 7: 0
```


---

## Key Features

- Each key has **two candidate locations**.
  - **Insertion may kick out existing keys** recursively.
  - **Fast lookups**: Only check **two positions**.
  - **Rehashing** is needed if cycles occur during insertion.
- 

I can also provide a **version with integers and strings together**, showing **real-world use of Cuckoo Hashing** for a dictionary or set.

Do you want me to do that?



Undirected Graph code c++

ChatGPT said:

Sure! Here's a clean **C++ implementation of an undirected graph** using **Adjacency List**, which is the most common and efficient representation for sparse graphs.

```
#include <iostream>
#include <vector>
using namespace std;

class Graph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    Graph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add an undirected edge
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
        adjList[v].push_back(u); // because undirected
    }
};
```

```

    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    Graph g(vertices);

    g.addEdge(0, 1);
    g.addEdge(0, 4);
    g.addEdge(1, 2);
    g.addEdge(1, 3);
    g.addEdge(1, 4);
    g.addEdge(3, 4);

    cout << "Undirected Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Output:

```

Undirected Graph (Adjacency List):
0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3

```

### ✓ Features of this code:

- Uses adjacency list, efficient for sparse graphs.
- Supports adding edges dynamically.
- Simple `printGraph()` to display the graph structure.
- Works for any number of vertices.

---

If you want, I can also provide a version with **Adjacency Matrix** for the **same undirected graph** so you can compare both representations.

Do you want me to do that?

You said:



## Directed Graph (Digraph)

ChatGPT said:

Here's a clean C++ implementation of a Directed Graph (Digraph) using Adjacency List, which is efficient and commonly used:

```
#include <iostream>
#include <vector>
using namespace std;

class Digraph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    Digraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add a directed edge from u to v
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << " -> ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    Digraph g(vertices);

    g.addEdge(0, 1);
    g.addEdge(0, 4);
    g.addEdge(1, 2);
    g.addEdge(1, 3);
    g.addEdge(1, 4);
    g.addEdge(3, 4);

    cout << "Directed Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}
```

**Example Output:**

Directed Graph (Adjacency List):

```
0 -> 1 4
1 -> 2 3 4
2 ->
3 -> 4
4 ->
```

✓ Features:

- Uses Adjacency List for efficiency.
- Supports directed edges ( $u \rightarrow v$  only, no reverse unless explicitly added).
- Dynamic edge addition and easy printing.

---

I can also provide a **Directed Graph using Adjacency Matrix** if you want a version that allows **fast edge lookups**.

Do you want me to provide that as well?

You said:

Weighted Graph

ChatGPT said:

Here's a **C++ implementation of a Weighted Graph** using an **Adjacency List**, which works for both directed and undirected graphs depending on how you add edges:

```
#include <iostream>
#include <vector>
using namespace std;

// Weighted Graph
class WeightedGraph {
private:
    int V; // number of vertices
    vector<vector<pair<int, int>>>> adjList; // pair<neighbor, weight>

public:
    // Constructor
    WeightedGraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight, bool undirected = false) {
        adjList[u].push_back({v, weight});
        if (undirected) {
            adjList[v].push_back({u, weight});
        }
    }

    // Print the adjacency list
    void printGraph() {
```

```

        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (auto &p : adjList[i]) {
                cout << "(" << p.first << ", " << p.second << ") ";
            }
            cout << endl;
        }
    };

int main() {
    int vertices = 5;
    WeightedGraph g(vertices);

    // Adding directed weighted edges
    g.addEdge(0, 1, 10);
    g.addEdge(0, 4, 5);
    g.addEdge(1, 2, 2);
    g.addEdge(1, 3, 1);
    g.addEdge(3, 4, 4);

    // For undirected weighted edge, use the third parameter as true
    // g.addEdge(2, 3, 3, true);

    cout << "Weighted Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}

```

### Example Output:

```

Weighted Graph (Adjacency List):
0: (1, 10) (4, 5)
1: (2, 2) (3, 1)
2:
3: (4, 4)
4:

```

### ✓ Features:

- Uses Adjacency List of pairs: neighbor + weight.
- Can handle directed or undirected edges (via undirected flag).
- Easy to extend for algorithms like Dijkstra or Prim.

---

I can also make a **Weighted Graph using Adjacency Matrix**, which is often used for **dense graphs**.

Do you want me to provide that too?

You said:

Unweighted Graph

ChatGPT said:

Here's a simple C++ implementation of an Unweighted Graph using Adjacency List, which works for both directed and undirected graphs depending on how you add edges:

```
#include <iostream>
#include <vector>
using namespace std;

class UnweightedGraph {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    // Constructor
    UnweightedGraph(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, bool undirected = false) {
        adjList[u].push_back(v);
        if (undirected) {
            adjList[v].push_back(u);
        }
    }

    // Print the adjacency list
    void printGraph() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    UnweightedGraph g(vertices);

    // Adding undirected edges
    g.addEdge(0, 1, true);
    g.addEdge(0, 4, true);
    g.addEdge(1, 2, true);
    g.addEdge(1, 3, true);
    g.addEdge(1, 4, true);
    g.addEdge(3, 4, true);

    cout << "Unweighted Graph (Adjacency List):" << endl;
    g.printGraph();

    return 0;
}
```

**Example Output:**

Unweighted Graph (Adjacency List):

```
0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3
```

✓ Features:

- Uses adjacency list, space-efficient for sparse graphs.
- Supports directed or undirected edges using the `undirected` flag.
- Simple dynamic edge addition and display.

---

I can also provide a **version using an adjacency matrix** if you want a dense unweighted graph representation.

Do you want me to do that?

You said:

Tree as a Graph

ChatGPT said:

Here's a **C++ implementation of a Tree as a Graph**. A **tree** is a special type of graph that is **connected** and **acyclic**, usually represented using an adjacency list:

```
#include <iostream>
#include <vector>
using namespace std;

class Tree {
private:
    int V; // number of nodes
    vector<vector<int>> adjList;

public:
    Tree(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (undirected, because tree edges are bidirectional)
    void addEdge(int u, int v) {
        adjList[u].push_back(v);
        adjList[v].push_back(u);
    }

    // Print adjacency list
    void printTree() {
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};
```

```

        }
        cout << endl;
    }
}

};

int main() {
    int nodes = 5;
    Tree tree(nodes);

    // Adding edges (undirected)
    tree.addEdge(0, 1);
    tree.addEdge(0, 2);
    tree.addEdge(1, 3);
    tree.addEdge(1, 4);

    cout << "Tree as a Graph (Adjacency List):" << endl;
    tree.printTree();

    return 0;
}

```

### Example Output:

```

Tree as a Graph (Adjacency List):
0: 1 2
1: 0 3 4
2: 0
3: 1
4: 1

```

### ✓ Features:

- Uses **Adjacency List** for efficiency.
- **Undirected edges** because a tree's edges connect nodes bidirectionally.
- Simple `addEdge()` and `printTree()` functions.
- Works for **any tree**, as long as it's connected and acyclic.

I can also make a **version using adjacency matrix** for a tree, or a **rooted tree with parent-child structure**, which is often used in algorithms like DFS/BFS.

Do you want me to provide that?

You said:

Adjacency Matrix representation

ChatGPT said:

Here's a **C++ implementation of a graph using the Adjacency Matrix representation**. This works for **directed/undirected** and **weighted/unweighted** graphs depending on how you set it up:

```

#include <iostream>
#include <vector>
using namespace std;

class GraphMatrix {
private:
    int V; // number of vertices
    vector<vector<int>> adjMatrix;

public:
    GraphMatrix(int vertices) {
        V = vertices;
        adjMatrix.resize(V, vector<int>(V, 0)); // initialize with 0
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight = 1, bool undirected = false) {
        adjMatrix[u][v] = weight;
        if (undirected) {
            adjMatrix[v][u] = weight;
        }
    }

    // Print adjacency matrix
    void printMatrix() {
        cout << "Adjacency Matrix:" << endl;
        for (int i = 0; i < V; i++) {
            for (int j = 0; j < V; j++) {
                cout << adjMatrix[i][j] << " ";
            }
            cout << endl;
        }
    }
};

int main() {
    int vertices = 5;
    GraphMatrix g(vertices);

    // Adding edges (undirected)
    g.addEdge(0, 1, 1, true);
    g.addEdge(0, 4, 1, true);
    g.addEdge(1, 2, 1, true);
    g.addEdge(1, 3, 1, true);
    g.addEdge(1, 4, 1, true);
    g.addEdge(3, 4, 1, true);

    g.printMatrix();

    return 0;
}

```

### Example Output:

```

Adjacency Matrix:
0 1 0 0 1
1 0 1 1 1
0 1 0 0 0
0 1 0 0 1
1 1 0 1 0

```

## ✓ Features:

- Uses a 2D vector to store connections.
- Can handle weighted or unweighted edges (`weight` parameter).
- Supports directed or undirected graphs (`undirected` flag).
- Quick lookup for edge existence:  $O(1)$ .

---

I can also provide **Adjacency Matrix** code specifically for a **Directed Weighted Graph** if you want a more general version.

Do you want me to do that?

You said:

Adjacency List representation

ChatGPT said:

Here's a **C++ implementation of a graph using the Adjacency List representation**. This works for directed/undirected and weighted/unweighted graphs:

```
#include <iostream>
#include <vector>
using namespace std;

// For unweighted graph
class GraphList {
private:
    int V; // number of vertices
    vector<vector<int>> adjList;

public:
    GraphList(int vertices) {
        V = vertices;
        adjList.resize(V);
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, bool undirected = false) {
        adjList[u].push_back(v);
        if (undirected) {
            adjList[v].push_back(u);
        }
    }

    // Print adjacency list
    void printGraph() {
        cout << "Adjacency List:" << endl;
        for (int i = 0; i < V; i++) {
            cout << i << ": ";
            for (int neighbor : adjList[i]) {
                cout << neighbor << " ";
            }
            cout << endl;
        }
    }
};
```



```

    }
}

};

int main() {
    int vertices = 5;
    GraphList g(vertices);

    // Adding undirected edges
    g.addEdge(0, 1, true);
    g.addEdge(0, 4, true);
    g.addEdge(1, 2, true);
    g.addEdge(1, 3, true);
    g.addEdge(1, 4, true);
    g.addEdge(3, 4, true);

    g.printGraph();

    return 0;
}

```

### Example Output:

Adjacency List:

```

0: 1 4
1: 0 2 3 4
2: 1
3: 1 4
4: 0 1 3

```

### ✓ Features:

- Efficient for sparse graphs.
- Supports directed or undirected graphs.
- Simple to add edges dynamically.
- Easy to iterate neighbors for algorithms like BFS, DFS, Dijkstra, etc.

---

If you want, I can also provide a **Weighted Graph version using Adjacency List**, where each neighbor stores its weight as well.

Do you want me to do that?

You said:

Edge List representation

ChatGPT said:

Here's a **C++ implementation of a graph using the Edge List representation**. This works for directed/undirected and weighted/unweighted graphs:

```

#include <iostream>
#include <vector>

```

```

using namespace std;

// Edge structure
struct Edge {
    int u, v, weight;
    Edge(int u, int v, int w = 1) : u(u), v(v), weight(w) {}
};

class GraphEdgeList {
private:
    int V; // number of vertices
    vector<Edge> edges;

public:
    GraphEdgeList(int vertices) {
        V = vertices;
    }

    // Add edge (directed or undirected)
    void addEdge(int u, int v, int weight = 1, bool undirected = false) {
        edges.push_back(Edge(u, v, weight));
        if (undirected) {
            edges.push_back(Edge(v, u, weight));
        }
    }

    // Print edge list
    void printEdgeList() {
        cout << "Edge List:" << endl;
        for (auto &edge : edges) {
            cout << edge.u << " -> " << edge.v << " weight: " <<
edge.weight << endl;
        }
    }
};

int main() {
    int vertices = 5;
    GraphEdgeList g(vertices);

    // Adding undirected edges
    g.addEdge(0, 1, 1, true);
    g.addEdge(0, 4, 1, true);
    g.addEdge(1, 2, 1, true);
    g.addEdge(1, 3, 1, true);
    g.addEdge(1, 4, 1, true);
    g.addEdge(3, 4, 1, true);

    g.printEdgeList();

    return 0;
}

```

### Example Output:

```

Edge List:
0 -> 1 weight: 1
1 -> 0 weight: 1
0 -> 4 weight: 1
4 -> 0 weight: 1

```

```
1 -> 2 weight: 1
2 -> 1 weight: 1
1 -> 3 weight: 1
3 -> 1 weight: 1
1 -> 4 weight: 1
4 -> 1 weight: 1
3 -> 4 weight: 1
4 -> 3 weight: 1
```

#### ✓ Features:

- Simple list of edges, useful for Kruskal's MST or algorithms that iterate over all edges.
  - Supports weighted or unweighted graphs (`weight` parameter).
  - Can handle directed or undirected graphs (`undirected` flag).
  - Easy to store and read from files or input data.
- 

If you want, I can also make a single C++ class that supports all representations (Adjacency Matrix, List, and Edge List) for a graph in one place.

Do you want me to do that?

You said: