

Last login: Fri Jun 7 18:25:16 on ttys000
sahilkumar@SAHILs-MacBook-Air ~ % brew services start mysql
Service `mysql` already started, use `brew services restart mysql` to restart.
sahilkumar@SAHILs-MacBook-Air ~ %
sahilkumar@SAHILs-MacBook-Air ~ % mysql -u root
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 21
Server version: 8.3.0 Homebrew

Copyright (c) 2000, 2024, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;

Database
information_schema
mysql
performance_schema
school
sys

5 rows in set (0.03 sec)

mysql> use school;

Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed

mysql>

mysql> show tables;

Tables_in_school
courses
students
votingList

3 rows in set (0.00 sec)

mysql> select * from students;

studentid	firstname	lastname	dateOfBirth	email
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com

2 rows in set (0.01 sec)

mysql> select * from students where studentid = 3;

studentid	firstname	lastname	dateOfBirth	email
3	Chris	Evan	2001-03-03	chris123@gmail.com

1 row in set (0.00 sec)

mysql> select studentid,firstname,lastname from students where studentid = 3;

studentid	firstname	lastname
3	Chris	Evan

1 row in set (0.00 sec)

mysql>

```
mysql> select * from students;
```

studentid	firstname	lastname	dateOfBirth	email
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com

```
2 rows in set (0.00 sec)
```

```
mysql> insert into students (studentid,firstname,lastname,dateofbirth,email) values (1,'John','Doe','2000-02-20','johndoe@gmail.com');
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into students (studentid,firstname,lastname,dateofbirth,email) values (4,'Allen','Cooper','2000-02-20','allen@gmail.com');
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into students (studentid,firstname,lastname,dateofbirth,email) values (5,'donny','yen','2001-02-20');
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from students;
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students;
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students;
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students where id=1;
```

```
ERROR 1054 (42S22): Unknown column 'id' in 'where clause'
```

```
mysql> select * from students where studentid=1;
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com

```
1 row in set (0.00 sec)
```

```
mysql> select * from students where studentid between 1 and 3;
```

studentid	firstname	lastname	dateOfBirth	email
-----------	-----------	----------	-------------	-------

1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com

3 rows in set (0.00 sec)

mysql> select * from students where studentid in (1,2,5);

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

3 rows in set (0.00 sec)

mysql> select * from students;

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

5 rows in set (0.00 sec)

mysql> select * from students where id=1 or id =4;

ERROR 1054 (42S22): Unknown column 'id' in 'where clause'

mysql> select * from students where studentid=1 or studentid =4;

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com

2 rows in set (0.00 sec)

mysql> select * from students where firstname = "John" and lastname = "doe";

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com

1 row in set (0.00 sec)

mysql> select * from students where firstname = "John" or lastname = "doe";

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com

1 row in set (0.00 sec)

mysql> select * from students

-> ;

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

5 rows in set (0.00 sec)

mysql> show tables;

Tables_in_school

courses
students
votingList

3 rows in set (0.00 sec)

mysql> select * from courses;
Empty set (0.00 sec)

mysql> desc courses;

Field	Type	Null	Key	Default	Extra
courseid	int	NO	PRI	NULL	
coursename	varchar(100)	NO		NULL	
credits	int	YES		NULL	

3 rows in set (0.00 sec)

mysql> insert into courses values (101,"DBMS",3),(102,"DSA",4),(103,"
">
"> Java" , 3);

Query OK, 3 rows affected (0.00 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql> select * from courses;

courseid	coursename	credits
101	DBMS	3
102	DSA	4
103	;	

Java | 3 |

3 rows in set (0.00 sec)

mysql> delete from courses;
Query OK, 3 rows affected (0.00 sec)

mysql> select * from courses;
Empty set (0.00 sec)

mysql> insert into courses values (101,"DBMS",3),(102,"DSA",4),(103,"JAVA",3);
Query OK, 3 rows affected (0.01 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql> select * from courses;

courseid	coursename	credits
101	DBMS	3
102	DSA	4
103	JAVA	3

3 rows in set (0.00 sec)

mysql> select * from students
-> ;

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

5 rows in set (0.00 sec)

```
mysql> select * from students where dateOfBirth>"2000-01-01";
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

5 rows in set (0.01 sec)

```
mysql> select * from students where dateOfBirth>"2001-01-01";
```

studentid	firstname	lastname	dateOfBirth	email
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

3 rows in set (0.00 sec)

```
mysql> select * from students where id =2 or id =10;
```

ERROR 1054 (42S22): Unknown column 'id' in 'where clause'

```
mysql> select * from students where studentid =2 or studentid =10;
```

studentid	firstname	lastname	dateOfBirth	email
2	Johny	Dep	2002-05-21	johndep@gmail.com

1 row in set (0.00 sec)

```
mysql> select * from students where firstname="Johny" and lastname="yen";
```

Empty set (0.00 sec)

```
mysql> select * from students where not studentid = 5;
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com

4 rows in set (0.00 sec)

```
mysql> select * from students where firstname like "j%";
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com

2 rows in set (0.00 sec)

```
mysql> select * from students where firstname like "%s";
```

studentid	firstname	lastname	dateOfBirth	email
3	Chris	Evan	2001-03-03	chris123@gmail.com

1 row in set (0.00 sec)

```
mysql> select * from students where firstname like "%n%";
```

studentid	firstname	lastname	dateOfBirth	email
1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

```
+-----+
4 rows in set (0.00 sec)
```

```
mysql> select * from students where firstname like "__h%";
```

```
+-----+
| studentid | firstname | lastname | dateOfBirth | email |
+-----+
|          1 | John     | Doe      | 2000-02-20  | johndoe@gmail.com |
|          2 | Johny    | Dep      | 2002-05-21  | johndep@gmail.com |
+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from students
-> ;
```

```
+-----+
| studentid | firstname | lastname | dateOfBirth | email |
+-----+
|          1 | John     | Doe      | 2000-02-20  | johndoe@gmail.com |
|          2 | Johny    | Dep      | 2002-05-21  | johndep@gmail.com |
|          3 | Chris    | Evan     | 2001-03-03   | chris123@gmail.com |
|          4 | Allen    | Cooper   | 2000-02-20   | allen@gmail.com    |
|          5 | donny    | yen      | 2001-02-20   | donny@gmail.com    |
+-----+
5 rows in set (0.00 sec)
```

```
mysql> select count(*) from students;
```

```
+-----+
| count(*) |
+-----+
|          5 |
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select count(*) as Total_Students from students;
```

```
+-----+
| Total_Students |
+-----+
|                5 |
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select * from courses;
```

```
+-----+
| courseid | coursename | credits |
+-----+
|        101 | DBMS      |        3 |
|        102 | DSA       |        4 |
|        103 | JAVA      |        3 |
+-----+
```

```
3 rows in set (0.00 sec)
```

```
mysql> select sum(credits) from courses;
```

```
+-----+
| sum(credits) |
+-----+
|             10 |
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select sum(credits) as "Total Credits" from courses;
```

```
+-----+
| Total Credits |
+-----+
|             10 |
+-----+
```

```
1 row in set (0.01 sec)
```

```
mysql> select avg(credits) as "average credits" from courses;
```

```
+-----+
| average credits |
+-----+
```

3.3333

1 row in set (0.00 sec)

```
mysql> select min(credits) as "min credits" from courses;
```

min credits
3

1 row in set (0.01 sec)

```
mysql> select max(credits) as "min credits" from courses;
```

min credits
4

1 row in set (0.00 sec)

```
mysql> select round( avg(credits)) from courses;
```

round(avg(credits))
3

1 row in set (0.01 sec)

```
mysql> select round( avg(credits),2) from courses;
```

round(avg(credits),2)
3.33

1 row in set (0.00 sec)

```
mysql> select round( 1.66,2) from courses;
```

round(1.66,2)
1.66
1.66
1.66

3 rows in set (0.00 sec)

```
mysql> select round( 1.66,2);
```

round(1.66,2)
1.66

1 row in set (0.00 sec)

```
mysql> select * from course
-> ;
ERROR 1146 (42S02): Table 'school.course' doesn't exist
mysql> select * from courses;
```

courseid	coursename	credits
101	DBMS	3
102	DSA	4
103	JAVA	3

3 rows in set (0.00 sec)

```
mysql> select * from students;
```

studentid	firstname	lastname	dateOfBirth	email
-----------	-----------	----------	-------------	-------

1	John	Doe	2000-02-20	johndoe@gmail.com
2	Johny	Dep	2002-05-21	johndep@gmail.com
3	Chris	Evan	2001-03-03	chris123@gmail.com
4	Allen	Cooper	2000-02-20	allen@gmail.com
5	donny	yen	2001-02-20	donny@gmail.com

5 rows in set (0.00 sec)

mysql>

mysql> create database company;
Query OK, 1 row affected (0.01 sec)

mysql> use company;

Database changed

mysql> create table employees (id int primary key auto_increment, emp_name varchar(100) not null, dept varchar(100) not null, salary int);
Query OK, 0 rows affected (0.02 sec)

mysql> insert into employees (emp_name, dept, salary) values ("Lokesh", "IT", 25000), ("Sahil", "IT", 95000), ("Amit", "Admin", 100000), ("Ram", "Sales", 100000);
Query OK, 4 rows affected (0.00 sec)
Records: 4 Duplicates: 0 Warnings: 0

mysql> select * from company;
ERROR 1146 (42S02): Table 'company.company' doesn't exist
mysql> select * from employees;

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000

4 rows in set (0.00 sec)

mysql> insert into employees (emp_name, dept, salary) values ("Lokesh", "IT", 25000), ("Ashish", "IT", 195000), ("Amit kr", "Security", 9000), ("Himanshu", "Sales", 10000);
Query OK, 4 rows affected (0.00 sec)
Records: 4 Duplicates: 0 Warnings: 0

mysql> select * from employees;

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
5	Lokesh	IT	25000
6	Ashish	IT	195000
7	Amit kr	Security	9000
8	Himanshu	Sales	10000

8 rows in set (0.00 sec)

mysql> select dept, count(dept) from employees;
ERROR 1140 (42000): In aggregated query without GROUP BY, expression #1 of SELECT list contains nonaggregated column 'company.employees.dept'; this is incompatible with sql_mode=only_full_group_by

mysql>

mysql> select dept, count(dept) from employees group by dept;

dept	count(dept)
IT	4
Admin	1
Sales	2
Security	1

4 rows in set (0.00 sec)


```
mysql> select dept , count(dept) as "Total Employees in each dept" from employees group by dept;
```

dept	Total Employees in each dept
IT	4
Admin	1
Sales	2
Security	1

4 rows in set (0.00 sec)

```
mysql> select dept , count(dept) as "Total Employees in each dept" from employees group by dept having count(dept)<2;
```

dept	Total Employees in each dept
Admin	1
Security	1

2 rows in set (0.00 sec)

```
mysql> select * from employees;
```

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
5	Lokesh	IT	25000
6	Ashish	IT	195000
7	Amit kr	Security	9000
8	Himanshu	Sales	10000

8 rows in set (0.00 sec)

```
mysql> select min(salary) from employees;
```

min(salary)
9000

1 row in set (0.00 sec)

```
mysql> select max(salary) from employees;
```

max(salary)
195000

1 row in set (0.00 sec)

```
mysql> select avg(salary) from employees;
```

avg(salary)
69875.0000

1 row in set (0.00 sec)

```
mysql> select * from employees;
```

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
5	Lokesh	IT	25000
6	Ashish	IT	195000
7	Amit kr	Security	9000

8	Himanshu	Sales	10000
---	----------	-------	-------

8 rows in set (0.00 sec)

```
mysql> select * from employees oder by salary;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'by salary' at line 1

```
mysql> select * from employees order by salary;
```

id	emp_name	dept	salary
7	Amit kr	Security	9000
8	Himanshu	Sales	10000
1	Lokesh	IT	25000
5	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
6	Ashish	IT	195000

8 rows in set (0.00 sec)

```
mysql> select * from employees order by salary asc;
```

id	emp_name	dept	salary
7	Amit kr	Security	9000
8	Himanshu	Sales	10000
1	Lokesh	IT	25000
5	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
6	Ashish	IT	195000

8 rows in set (0.00 sec)

```
mysql> select * from employees order by salary desc;
```

id	emp_name	dept	salary
6	Ashish	IT	195000
3	Amit	Admin	100000
4	Ram	Sales	100000
2	Sahil	IT	95000
1	Lokesh	IT	25000
5	Lokesh	IT	25000
8	Himanshu	Sales	10000
7	Amit kr	Security	9000

8 rows in set (0.00 sec)

```
mysql> select * from employees;
```

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
5	Lokesh	IT	25000
6	Ashish	IT	195000
7	Amit kr	Security	9000
8	Himanshu	Sales	10000

8 rows in set (0.00 sec)

```
mysql> select * from employees where id between 1 and 5;
```

id	emp_name	dept	salary
1	Lokesh	IT	25000
2	Sahil	IT	95000
3	Amit	Admin	100000
4	Ram	Sales	100000
5	Lokesh	IT	25000

	1		Lokesh		IT		25000	
	2		Sahil		IT		95000	
	3		Amit		Admin		100000	
	4		Ram		Sales		100000	
	5		Lokesh		IT		25000	
+-----+								

5 rows in set (0.00 sec)

mysql> select * from employees limit 3;

	id		emp_name		dept		salary	
+-----+								
	1		Lokesh		IT		25000	
	2		Sahil		IT		95000	
	3		Amit		Admin		100000	
+-----+								

3 rows in set (0.00 sec)

mysql> select * from employees limit 5;

	id		emp_name		dept		salary	
+-----+								
	1		Lokesh		IT		25000	
	2		Sahil		IT		95000	
	3		Amit		Admin		100000	
	4		Ram		Sales		100000	
	5		Lokesh		IT		25000	
+-----+								

5 rows in set (0.00 sec)

mysql>