

EXERCISE ON jQUERY


1). Console "Hello Word" in document.ready function

```
$(document).ready()
```

```
$(function() {
```

```
    console.log("Hello World!");
```


```
});
```



2). Select a ID name "#test" and add class "load" when DOM is loaded.

E:\TTND\jQuery\e2.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help



```
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
5 <script>
6 $(document).ready(function(){
7     $("#test").addClass("load");
8     alert('class is added');
9 });
10 </script>
11 </head>
12 <body>
13 <div id="test">
14 <p>Hello</p>
15 <p>Welcomes</p>
16 </div>
17 </body>
18 </html>
```

Elements Console Sources Network Performance M

```
<!DOCTYPE html>
<html>
  <head>...</head>
  <body>
    <div id="test" class="load">...</div> == $0
  </body>
</html>
```

3). Change the color of element which class name end with "-new"

E:\TTND\jQuery\e3.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e2.html x e3.html x
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
5 <script>
6 $(document).ready(function(){
7     $("button").click(function() {
8         $(".class$=-new" ).css( "background-color", "green");
9     });
10 });
11 </script>
12 </head>
13 <body>
14 <div style="background-color:yellow" class="test-new">
15 <p>Click the button to Change the color of element which class name end with "-new".</p>
16 <button>Click me!</button>
17 </div>
18 </body>
19 </html>
```

Click the button to Change the color of element which class name end with "-new".

Click me!

Click the button to Change the color of element which class name end with "-new".


Click me!

4). Disable submit button using jquery attr method.

E:\TTND\jQuery\e4.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e2.html x e3.html x e4.html x
1 <!DOCTYPE>
2 <html>
3 <head>>
4   <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
5   <script>
6
7   $(document).ready(function(){
8     $("button").attr('disabled',true);
9   });
10  </script>
11  </head>
12  <body>
13  <button>Disabled Button</button>
14  </body>
```



> Disabled Button

5). Change the font size of ".target" which has parent element with id name "#main"



Hello World!

Click Here!



Hello World!


Click Here!

6). After page load change the HTML of div element with "p" element.

E:\TTND\jQuery\e6.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e2.html x e3.html x e4.html x e5.html x
1 <html>
2 <head>
3 <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
4 <script>
5     $(document).ready(function(){
6         var a=document.getElementById('first').innerHTML;
7         $("#first").html(document.getElementById('second').innerHTML);
8         $("#second").html(a);
9     });
10 </script>
11 </head>
12 <body>
13     <div id="first">Hello</div>
14     <p id="second">World</p>
15 </body>
16 </html>
```



World

Hello

7). Bind a click function to an "click" element and append next "click" next to it.

E:\TTND\jQuery\e7.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html x
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function(){
8     $("p").live("click", function(){
9         ... .. $("p").append("<h2>Dynamically added element</h2>");
10    ... });
11 });
12 </script>
13 </head>
14 <body>
15 <p>This is a static paragraph</p>
16 </body>
17 </html>
```

8.) Click event not working on element which added dynamically or via script, make it work using .on method

E:\TTND\jQuery\e8.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html x
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function(){
8     $("p").on("click", function(){
9         ... .. $("p").append("<h2>Dynamically added element</h2>");
10    ... });
11 });
12 </script>
13 </head>
14 <body>
15 <p>This is a static paragraph</p>
16 </body>
17 </html>
18
```

9). Get dropdown selected value on onchange event and append in div container

E:\TTND\jQuery\e9.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
<< >> e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.htm
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function(){
8     $("#target").change(function(){
9         var c=$("#target").val();
10        $("#d").append(c);
11    });
12 });
13 </script>
14 </head>
15 <body>
16
17 <select id="target">
18     <option value="volvo">Volvo</option>
19     <option value="saab">Saab</option>
20     <option value="opel">Opel</option>
21     <option value="audi">Audi</option>
22 </select>
23 <div id="d">
24 </div>
25 </body>
26 </html>
```


10). Create a dropdown menu using hover

E:\TTND\jQuery\10.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html
1
2 <html xmlns="http://www.w3.org/1999/xhtml">
3 <head>
4 <title>jQuery hover dropdown menu with css example</title>
5 <script type="text/javascript" src="http://code.jquery.com/jquery-1.8.2.js"></script>
6 <script type="text/javascript">
7 $(function() {
8 $(".menu").hover(
9 function() { $(".sub").slideToggle(400); },
10 function() { $(".sub").hide(); }
11 );
12 });
13 </script>
14 <style type="text/css">
15
16 a{
17 text-decoration: none;
18 }
19 .menu{
20 font-family: Arial;
21 color: #515151;
22 width: 200px;
23 position: relative;
24 height: 40px;
25 text-align:left;
26 width: 202px;
27 margin: 0 auto;
28 }
29 .menu li a{
30 color: #515151;
31 display: block;
32 padding: 6px 15px;
33 cursor: pointer;
34 font-size: 14px;
35 }
36 .menu li a:hover{
37 background: #f44141;
38 color: #fff;
39 }
40 .sub{
41 background: #fff;
42 position: absolute;
43 z-index: 2;
44 width: 200px;
45 padding: 40px 0 3px;
46 border-radius: 3px;
47 box-shadow: 0 2px 4px #ddd;
48 border: 1px solid #ddd;
```

Line 87, Column 8



method in jquery

```
47 box-shadow: 0 2px 4px #ddd;
48 border: 1px solid #ddd;
49 display: none;
50 }
51 a.hover-link{
52 width: 190px;
53 background: #fff;
54 font-size: 14px;
55 color: #515151;
56 position: absolute;
57 z-index: 110;
58 display: block;
59 padding: 10px 0 1px 10px;
60 height: 28px;
61 cursor:pointer;
62 border-radius: 5px 5px 0 0;
63 font-weight: bold;
64 border: 1px solid #ddd;
65 }
66 .sub-options{
67 list-style:none;
68 margin:0px;
69 padding:0px;
70 font-size: 11px;
71 }
72 </style>
73 </head>
74 <body>
75 <div class='menu'>
76 <a class='hover-link'>Hover on Menu</a>
77 <div class='sub'>
78 <ul class='sub-options'>
79 <li><a href='#'>Home</a></li>
80 <li><a href='#'>About</a></li>
81 <li><a href='#'>Services</a></li>
82 <li><a href='#'>Contact</a></li>
83 </ul>
84 </div>
85 </div>
86 </body>
87 </html>
```

11). On clicking on "google" tag. It is taking us to google home page. Stop it from happening.

E:\TTND\jQuery\e11.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function(){
8     $("a").bind("click", function(e){
9         e.preventDefault();
10    });
11 });
12 </script>
13 </head>
14 <body>
15 <a href="www.google.com">Google</a>
16 </body>
17 </html>
18
```

12). We have bind a click funtion to parent div but we want stop it from performing when user clicks on its child li

E:\TTND\jQuery\e12.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function() {
8
9     $("#main").click(function() {
10         $("#main").css('background-color','green');
11     });
12     $("li").click(function(e) {
13         $("li").css('background-color','red');
14         e.stopPropagation();
15     });
16 });
17 });
18 </script>
19 </head>
20 <body>
21 <div id="main">Hello
22
23     <li>Link1</li>
24     <li>Link2</li>
25     <li>Link3</li>
26     <li>Link4</li>
27 </div>
28 </div>
29 </body>
30 </html>
31
```

13). Get the max height of elements using jquery each method

E:\TTND\jQuery\13.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

```
1
2 <!DOCTYPE html>
3 <html>
4 <head>
5 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
6 </script>
7 <script>
8 $(document).ready(function() {
9     var maxHeight = -1;
10
11     $('body *').each(function() {
12         maxHeight = maxHeight > $(this).height() ? maxHeight : $(this).height();
13     });
14     alert('maxHeight'+maxHeight);
15 });
16 </script>
17 </head>
18 <body>
19 <div style="height:100px;width:300px;padding:10px;margin:3px;border:1px solid blue;background-color:lightblue;"></div><br>
20 <div style="height:200px;width:300px;padding:10px;margin:3px;border:1px solid blue;background-color:lightblue;"></div><br>
21 <p style="height:400px;width:300px;">Hello</p>
22 </body>
23 </html>
```

14). Change color of every cell which has number larger than 10.

```
E:\TTND\jQuery\14.html - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help

e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html

1 <!DOCTYPE html>
2 <html>
3 <head>
4 <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.7/jquery.min.js">
5 </script>
6 <script>
7 $(document).ready(function(){
8   $('#t tr').each(function() {
9     var v=$(this).find("td");
10    $.each(v,function(index,item){
11      values=item.innerHTML;
12      if(values>10)
13      {
14        $(this).css('background-color', 'red');
15      }
16    });
17  });
18 });
19 </script>
20 </head>
21 <body>
22 <table id="t">
23   <tr>
24     <td>10</td>
25     <td>58</td>
26   </tr>
27   <tr>
28     <td>20</td>
29   </tr>
30   <tr>
31     <td>30</td>
32   </tr>
33 </table>
34 </body>
35 </html>
```

15). Retrive the data from server using ajax get call

```
E:\TTND\jQuery\15.html - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help

e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html x e13.html x e15.html x e14.html x e16.html x 17.html x

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title></title>
5   <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
6   <script type="text/javascript">
7     jQuery(document).ready(function ($) {
8       $('#button').click(function() {
9         $('#res').html("");
10        $.get({
11          url: 'https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js',
12          success: function(response) {
13            $('#res').html(response);
14            alert('Load was performed.');
```

16). Add cross button on row and bind click function which make a delete request to server, after success event remove the row from dom

E:\TTND\jQuery\16.html - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help


e6.html x e7.html x e8.html x e9.html x e10.html x e11.html x e12.html x e13.html

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title></title>
5   <style>
6   table, th, td {
7     border: 1px solid black;
8     border-collapse: collapse;
9   }
10  th, td {
11    padding: 5px;
12    text-align: left;
13  }
14  table#t01 {
15    width: 100%;
16    background-color: #f1f1c1;
17  }
18 </style>
19 <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
20 <script type="text/javascript">
21   jQuery(document).ready(function ($) {
22     $('button').on("click",function(){
23       var $tr = $(this).closest('tr');
24       $.get({
25         url: 'https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js',|
26         success: function(response) {
27           alert('Load was performed.');
```

28 \$tr.remove();
29 },
30 error: function(){
31 alert('Fail');

32 }
33 });
34 });
35 });
36 });
37 </script>
38 </head>
39
40 <body>
41 <table id="t01">
42 <tr>
43 <th>Firstname</th>
44 <th>Lastname</th>
45 </tr>
46 <tr>
47 <td>Jill</td>
48 <td>Smith</td>

Line 25, Column 77



```
41 <table id="t01">
42   <tr>
43     <th>Firstname</th>
44     <th>Lastname</th>
45   </tr>
46   <tr>
47     <td>Jill</td>
48     <td>Smith</td>
49     <td><button>X</button></td>
50   </tr>
51   <tr>
52     <td>Eve</td>
53     <td>Jackson</td>
54     <td><button>X</button></td>
55   </tr>
56   <tr>
57     <td>John</td>
58     <td>Doe</td>
59     <td><button>X</button></td>
60   </tr>
61 </table>
62 </body>
63 </html>
64
```

17) **Create a simple button and one(or two?) paragraph with text “Hi”. Once the button is clicked, the paragraph text should change to “Hello”. If button is clicked once again, the paragraph text should again change to “Hi”. This process must repeat on subsequent clicks.**

```
<!DOCTYPE html>
<html>
<head>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
<script>
$(document).ready(function () {
    $("button").click(function () {
        if($(".p").text()=="hello")
        {
            $(".p").text("hy");
        }
        else
        {
            $(".p").text("hello")
        }
    });
});
</script>
</head>
<body>

<p>hello</p>
<button>helo</button>
</body>
</html>
```

18.) **Show text value of Textbox in a <p></p> tag when user press ENTER key.**


```
<!DOCTYPE html>
<html>
<head>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
<script>
i = 0;
$(document).ready(function(){
    $("input").keypress(function(e){
        if(e.which==13)
        {
            $("p").html($("input:text").val());
        }
    });
});
</script>
</head>
<body>

Enter your name: <input type="text">

<p>Keypresses: <span>0</span></p>

</body>
</html>
```