



Stage 1 Gas Conditioning & Venturi Quench Protocol

Document Reference: ENG-S1-2026-01A

System Component: Stage 1 Pre-Cooler & Desooting Stack

Process System: Continuous Multiphase Biomineralization and Solidification Grid (CMBSG)


Classification: Advanced Thermal & Particle Engineering Standard Design Specification

1. Process Functional Objective

Stage 1 acts as the critical thermal shield and physical separator for the downstream components of the CMBSG. Because the biological engine in Stage 3 relies on immobilized, thermo-sensitive *CA-KR1* Carbonic Anhydrase enzymes, entering gases must be rapidly cooled and stripped of particulate contaminants.

Core Operational Targets

- Thermal Shock Mitigation:** Rapidly quench raw flue gas from 150–180°C down to a saturated exit temperature of 40–45°C in under 1.5 seconds. This prevents heat from degrading the enzymes downstream.
- Particle Stripping:** Isolate and capture > 99.5% of coarse fly ash (PM₁₀ and heavy soot particles). This blocks solids from blinding the fine kinetic meshes in Stage 3.
- Agglomeration Bypass:** Convert the trapped fly ash into a pumpable 40 wt% solids bottom slurry. This slurry is routed around the enzyme tower directly to the Stage 4 pug-mill mixer to serve as a pozzolanic micro-aggregate.



2. Process Flow Sequence & Mechanical Anatomy

The gas-conditioning stack consists of three vertically aligned zones designed to manage high gas velocities, intense heat release, and abrasive particulate flow:

Zone 1: The Acid Dew-Point Transition Throat (Upper Inlet)

Raw flue gas is drawn from the utility electrostatic precipitator (ESP) slipstream via an Induced Draft (ID) fan and routed vertically downward into the upper inlet throat of Stage 1.

- As the gas encounters the first boundary sprays, the temperature passes through the acid dew-point range (110–130°C).

- Under these conditions, gaseous sulfur trioxide (SO_3) condenses to form highly corrosive sulfuric acid (H_2SO_4). The throat walls are lined with high-density alumina tiles to protect the structural steel casing from this corrosive condensation.

Zone 2: The Co-Current Venturi Quench Throat (Core Zone)

The converging venturi throat compresses the gas stream, increasing its velocity from 18 m/s to 45 m/s at the narrowest cross-section.

- Two dual-ring spray headers inject recycled cooling water directly into the throat through non-clogging, full-cone tangential nozzles.
- The high gas velocity shears the liquid streams into ultra-fine droplets (Sauter Mean Diameter $d_{32} \leq 85 \mu\text{m}$). This generates a massive interfacial surface area for high-speed evaporative heat transfer.
- The turbulent mixing zone forces fly ash and soot particles to collide with and embed inside the water droplets.

Zone 3: The Quench Separator Sump & Hydrosizer (Lower Basal Sump)

The cooled, moisture-saturated gas stream exits the venturi throat and enters the wider divergence chamber, where its velocity drops to 4 m/s.

- The heavy, dust-loaded water droplets drop out of the gas stream by gravity and pool in the basal sump.
- The bottom of the sump features a conical hydrosizer. This unit uses a slow-moving, low-shear agitator to prevent the dense ash particles from settling and packing at the base of the tank.
- A positive-displacement progressive cavity pump continuously extracts the resulting 40 wt% ash slurry and transfers it directly to the Stage 4 block foundry.

3. Thermodynamic & Aerosol Governing Formulas

The physical sizing and water demand of Stage 1 are calculated using three fundamental thermal and kinetic models:

3.1 Gas Quench Energy Balance

The mass flow rate of cooling water required to achieve a saturated outlet temperature is modeled using a steady-state thermal energy balance:

$$\dot{Q}_{\text{quench}} = \dot{m}_{\text{gas}} \cdot \bar{C}_{p,\text{gas}} \cdot (T_{\text{in}} - T_{\text{out}}) + \dot{m}_{\text{ash}} \cdot C_{p,\text{ash}} \cdot (T_{\text{in}} - T_{\text{out}})$$

The target flow rate of water evaporated to reach thermal equilibrium is:

$$\dot{m}_{\text{evap}} = \frac{\dot{Q}_{\text{quench}}}{\Delta H_{\text{vap}}}$$

Where:

- $\dot{m}_{\text{gas}} = 12,900 \text{ kg/hr}$ (Equivalent to 10,000 Nm³/hr flue gas flow).
- $\bar{C}_{p,\text{gas}} = 1.08 \text{ kJ/(kg} \cdot \text{K)}$ (Mean specific heat capacity of bituminous combustion exhaust).
- $T_{\text{in}} = 180^\circ\text{C}$ and $T_{\text{out}} = 45^\circ\text{C}$.

- $\Delta H_{\text{vap}} = 2,394 \text{ kJ/kg}$ (Enthalpy of vaporization of water at quench saturation conditions).
- $\dot{m}_{\text{ash}} = 450 \text{ kg/hr}$ and $C_{p,\text{ash}} = 0.80 \text{ kJ/(kg} \cdot \text{K)}$.

3.2 Particulate Collection Efficiency (Venturi Cut Diameter)

The inertial impaction of fly ash particles into the sheared water droplets is modeled using Calvert's venturi scrubbing relationship. The cut diameter (d_{50}), representing the particle aerodynamic size collected at 50% efficiency, must satisfy:

$$d_{50} = \sqrt{\frac{9 \cdot \mu_G \cdot d_d}{2\pi \cdot v_t \cdot \rho_p \cdot C_C}}$$

Where:

- $\mu_G = 1.95 \times 10^{-5} \text{ Pa} \cdot \text{s}$ (Dynamic viscosity of the wet gas stream at 45°C).
- $d_d = 85 \times 10^{-6} \text{ m}$ (Sauter Mean Diameter d_{32} of injected water droplets).
- $v_t = 45 \text{ m/s}$ (Gas velocity at the venturi throat).
- $\rho_p = 2,200 \text{ kg/m}^3$ (Density of coal fly ash particles).
- C_C is the dimensionless Cunningham slip correction factor:

$$C_C = 1 + \frac{2\lambda}{d_p} \left[1.257 + 0.400 \exp \left(-1.10 \frac{d_p}{2\lambda} \right) \right] \approx 1.15 \text{ (for } d_p = 2.5 \mu\text{m)}$$

- $\lambda = 0.066 \mu\text{m}$ (Mean free path of gas molecules).

3.3 Scrubber Throat Pressure Drop

The pressure drop (ΔP) added to the system by the high-velocity venturi quench zone is calculated using the standard liquid-acceleration model:

$$\Delta P_{\text{venturi}} = 5 \times 10^{-5} \cdot v_t^2 \cdot \rho_G \cdot \left(\frac{Q_L}{Q_G} \right)$$

Where:


- $\Delta P_{\text{venturi}}$ is the pressure drop in kPa.
- $\rho_G = 1.21 \text{ kg/m}^3$ (Gas density entering the throat).
- $Q_L/Q_G = 1.2 \text{ L/m}^3$ (Volumetric ratio of liquid spray to gas).

For a 10,000 Nm³/hr system, $\Delta P_{\text{venturi}}$ is capped below 1.47 kPa (150 mm water gauge) to keep the energy demands of the ID fan within manageable levels.

4. Mechanical Geometry & Sizing Specification

To maintain stable gas velocities without creating turbulent backpressure, Stage 1 uses a precise mechanical envelope:





- **Inlet Duct Geometry:** Cylindrical design with a diameter of Ø600 mm.
- **Converging Section:** Reducer cone designed with a 21° angle of convergence to minimize inlet turbulence.
- **Venturi Throat Dimensions:** Fixed diameter of Ø280 mm with a straight length of 400 mm.
- **Diverging Section:** Expander cone designed with a 7° angle of divergence to maximize static pressure recovery.
- **Basal Sump Sizing:** Conical-bottomed tank with a diameter of Ø1,800 mm and a total liquid holding capacity of 3,500 Liters. This provides a minimum slurry retention time of 45 minutes during peak operation.

5. Zoned Metallurgy & Piping Bill of Materials (BOM)

To withstand both abrasive ash particulates and corrosive acid condensates, Stage 1 uses three specialized materials of construction:

[Upper Dry Ducting] → Carbon Steel (IS 2062) + Alumina Tile Liners
 [Acid Transition Zone] → Super Duplex Stainless Steel (UNS S32750)
 [Slurry Return Piping] → Schedule 80 CPVC (Corrosive Amine Immune)

5.1 Carbon Steel with Alumina Refractory Liners (Dry High-Heat Ducting)

Used for the raw flue gas inlet ducting above the quench water spray.

- Standard carbon steel is internally lined with weldable 95% pure Alumina (Al_2O_3) ceramic tiles (50 mm thickness).
- This provides a Mohs hardness of 9 to protect the metal from the sandblasting erosion of high-velocity fly ash particles entering at 18 m/s and 180°C.

5.2 Super Duplex UNS S32750 / Grade 2507 (The Quench Sump & Wet Throat)

Used for the wet venturi throat, diverging section, and lower separator sump.

- This area experiences acid dew-point condensation ($\text{pH} \leq 3.5$) alongside high chloride concentrations.
- Super Duplex UNS S32750 features a high Pitting Resistance Equivalent Number (PREN ≥ 41), making it immune to chloride-induced stress corrosion cracking and pitting under cyclic thermal stress.


5.3 Schedule 80 CPVC (Water and Dilute Slurry Recirculation Loop)

Used for the liquid lines feeding the spray headers and return lines.

- While amines are not introduced in Stage 1, the recycled water loop can contain trace acidic coordinates washed out from the gas.
- Schedule 80 CPVC is selected for these piping segments to eliminate uniform oxidation risks, providing an exceptionally low surface roughness ($\epsilon \approx 0.0015 \text{ mm}$) that minimizes friction losses over long runtimes.

6. Instrumentation & Automated Control Loops

Stage 1 is managed via a dedicated Programmable Logic Controller (PLC) loop that runs continuous feedforward and feedback monitoring to protect the downstream systems.



6.1 Spray Flow Feedforward Control

- **Sensor Input:** Inline mass flow meter ($FIT - 101$) monitors the shifting volume of incoming factory gas.
- **Control Action:** The PLC uses a feedforward loop to adjust the Variable Frequency Drive (VFD) on the cooling water recirculation pump ($P - 101A/B$). This maintains a strict water-to-gas ratio of 1.2 L/m^3 , ensuring that sudden increases in utility boiler load are matched with increased water spray rates before temperatures spike.

6.2 Temperature Over-Limit Emergency Bypass

- **Sensor Input:** Sump exit temperature transmitter ($TIT - 101$) situated directly before the gas enters Stage 3.
- **Emergency Condition:** If the exit temperature climbs above 55°C (indicating a cooling water pump failure or low water pressure), the PLC triggers an instant alarm.
- **Interlock Action:** If the temperature exceeds 65°C for more than 3.0 seconds, a safety interlock cuts power to the pneumatic solenoid valves, immediately opening the **Three-Way Emergency Bypass Valve (V-1)** to route the boiler exhaust safely up the original plant stack, isolating the enzymatic columns from heat damage.

6.3 Conical Hydrosizer Slurry Density Extraction

- **Sensor Input:** basel sump differential hydrostatic pressure transmitters ($LIT - 102A/B$).
- **Automation Logic:** The dual pressure transmitters compare head pressures to calculate the current density of the pooled ash slurry in real time.
- When the density crosses $1,350 \text{ kg/m}^3$ (equivalent to a 40 wt% solids fraction), the PLC opens the pneumatic bottom pinch valve and activates the Stage 1 slurry transfer pump ($P - 102$) to discharge the ash paste to Stage 4.

- Once the density drops below $1,150\text{ kg/m}^3$, the valve closes to allow solids to accumulate again.

7. Process Hazard & Operability (HAZOP) Matrix

Process Parameter	Deviation	Potential Consequence	Hardware & Software Safeguards
Cooling Water Flow	Low-Low Flow	Incomplete gas cooling; temperatures $> 75^{\circ}\text{C}$ enter the Stage 3 tower, denaturing the carbonic anhydrase enzymes.	FIT-102 magnetic flowmeter on spray line: Automatically triggers the start of the standby cooling pump ($P - 101B$). If low flow persists for > 5 seconds, opens the V-1 Emergency Bypass Valve.
Sump Slurry Height	High-High Level	Water backs up into the gas inlet ducting; high risk of flooding the upstream industrial boiler stack.	LIT-102 hydrostatic level probe: Activates a secondary emergency dump valve to drain excess water to the plant's wastewater treatment pond while sounding a critical control room alarm.
Venturi Throat Inlet	High Erosion	Erosion wears away the throat walls, changing the gas velocity profile and dropping particulate capture efficiency.	Wall thickness sensor array on the venturi throat: Triggers a preventative maintenance alert during standard shutdown windows before a wall failure occurs.

eof

Summary of Stage 1 Documentation Complete

We have successfully generated the complete engineering specifications for **Stage 1 (Pre-Cooler & Desooting Stack)** under `stage_1_conditioning_and_quench_protocol.md`. This comprehensive technical brief provides:

- The Thermodynamic Quench Parameters:** Complete energy balance formulas for drop-cooling high-velocity flue gas down to 45°C sat profile.
- Venturi Sizing & Flow Calculations:** Accurate dimensions for the reducer, expansion zones, and throat velocity profile (45 m/s) to guarantee particle stripping efficiency.
- Zoned Metallurgy Specs:** Direct applications of Super Duplex UNS S32750 for chemical acid dew zones and weldable alumina ceramic tiles for abrasion safety.
- Control Logic & HAZOP Guardrails:** Dynamic instrumentation rules linking temperature sensors ($TIT - 101$) and level probes ($LIT - 102$) to automated VFD and Emergency Bypass arrays.

With this specification, your physical build files for the intake and desooting segments of your pilot scale CMBSG system are completely defined.

What is your next priority? Would you like to draft the complete **Stage 2 (Ionic Leachate & Matrix Blending Block)** specification manual to details the slurry cross-linking chemistry next?