

Network Security Audit Report

Basic Information

Audit ID: AUDIT-20260911-090CF2
Vendor: Cisco

Security Score

Overall Security Score: **12/100**

Security Findings

Rule ID & Issue	Evidence / Details	Severity
[CISCO-TELNET-001] Telnet is enabled for remote management	transport input telnet	High
[CISCO-SSH-001] Insecure SSH version 1 is enabled	ip ssh version 1	High
[CISCO-CRYPTO-001] Weak RSA key length detected	crypto key generate rsa modulus 1024	High
[CISCO-AUTH-001] Privileged user account uses a weak/plaintext password	Accounts configured with plaintext/weak password: admin (privilege 15), operator (privilege 1)	High
[CISCO-AUTH-002] Weak enable password detected	enable password [PROTECTED]	High
[CISCO-SNMP-001] SNMP is using the default/public community string	snmp-server community [REDACTED_PUBLIC] RO	High
[CISCO-WEB-001] HTTP management is enabled	ip http server	High
[CISCO-AAA-001] AAA authentication may not be configured	aaa new-model not present in configuration	High
[CISCO-PWD-001] Weak password policy detected	security passwords min-length 6 (minimum recommended is 10 or greater)	High
[CISCO-LOGIN-001] Login protection may not be configured	login block-for / quiet-mode not configured	Medium
[CISCO-LOG-001] Console logging is disabled or centralized logging configuration should be verified	no logging console (no remote syslog host configured)	Medium
[CISCO-ACL-001] Overly permissive access-control rule detected	access-list 10 permit any	High

Suggestions / Remediation

- Disable Telnet and use SSH for secure remote administration.
- Disable SSH version 1 and configure SSH version 2.
- Regenerate RSA keys using a stronger key size appropriate for the device and security policy.
- Use securely hashed/secret-protected credentials and enforce strong password policies.

- Replace the weak enable password with a stronger protected credential or use the recommended secret-based authentication mechanism.
- Replace the public community string with a unique protected value or migrate to SNMPv3.
- Disable insecure HTTP management and use HTTPS with appropriate security controls.
- Configure AAA using an appropriate authentication service.
- Enforce strong passwords and appropriate password security policies.
- Configure login attempt limits, lockout or equivalent protection.
- Configure centralized system logging and monitor security events.
- Restrict access-list rules to specific authorized hosts, subnets, and required service ports.

Audit Verification QR



Scan this QR code to identify audit AUDIT-20260911-090CF2.