

SENTRY SHIELD

Network Security & Compliance Audit Report

Audit Reference ID: AUDIT-20260927-412E29

Target Device: AEGIS-ROUTER-01

Platform / Vendor: Cisco

Engine Version: Sentry Core 2.0 (Deterministic Compliance)

Security Score & Compliance Status

Overall Security Score: **12/100** | Compliance Status: **NON-COMPLIANT (HIGH SEVERITY CONTROLS FAILED)**
| Audit State: **Evaluation Complete**

Severity Tier	Findings	Remediation Priority & Impact
Critical	0	Immediate remediation required (RCE, default read-write credentials, full exposure)
High	10	High priority (Cleartext management, legacy SSHv1, plaintext credentials, open ACLs)
Medium	2	Moderate priority (Disabled console logging, missing brute-force protection, time sync)
Low / Info	0	Hardening improvement (Banner configuration, logging microsecond precision)

Evaluated Framework Baselines: CIS Cisco IOS Benchmark v8, NIST SP 800-53 Rev 5, DISA STIG, ISO/IEC 27001:2022

Non-Compliant Control Violations: CIS Cisco IOS Benchmark v8 (1.1), CIS Cisco IOS Benchmark v8 (1.10), CIS Cisco IOS Benchmark v8 (1.2), CIS Cisco IOS Benchmark v8 (1.3), CIS Cisco IOS Benchmark v8 (1.4), CIS Cisco IOS Benchmark v8 (1.5), CIS Cisco IOS Benchmark v8 (1.6), CIS Cisco IOS Benchmark v8 (1.7), CIS Cisco IOS Benchmark v8 (1.8), CIS Cisco IOS Benchmark v8 (1.9), CIS Cisco IOS Benchmark v8 (2.1), CIS Cisco IOS Benchmark v8 (3.1), DISA STIG, DISA STIG (NET-040), DISA STIG (NET-045), DISA STIG (NET-080), ISO/IEC 27001 (A.13.1.1), ISO/IEC 27001 (A.9.4.2), ISO/IEC 27001 (A.9.4.3), NIST SP 800-131A, NIST SP 800-53 (AC-17), NIST SP 800-53 (AC-2, IA-2), NIST SP 800-53 (AC-4), NIST SP 800-53 (AC-7), NIST SP 800-53 (AU-2, AU-3), NIST SP 800-53 (IA-5), NIST SP 800-53 (IA-5, SC-8), NIST SP 800-53 (SC-8)

Security Findings & Evidence

Rule & Issue Details	Verified Configuration Evidence	Severity
[CISCO-TELNET-001] Telnet is enabled for remote management Compliance: CIS Cisco IOS Benchmark v8 (1.1), NIST SP 800-53 (AC-17), DISA STIG (NET-040) Threat Intel: CVE-1999-0524	Line 27: transport input telnet	High
[CISCO-SSH-001] Insecure SSH version 1 is enabled Compliance: CIS Cisco IOS Benchmark v8 (1.2), NIST SP 800-53 (IA-5, SC-8), DISA STIG (NET-045) Threat Intel: CVE-2001-0144	Line 22: ip ssh version 1	High
[CISCO-CRYPTO-001] Weak RSA key length detected Compliance: NIST SP 800-131A, CIS Cisco IOS Benchmark v8 (1.3), DISA STIG Threat Intel: CVE-2015-4000	Line 21: crypto key generate rsa modulus 1024	High
[CISCO-AUTH-001] Privileged user account uses a weak/plaintext password Compliance: CIS Cisco IOS Benchmark v8 (1.4), NIST SP 800-53 (IA-5), ISO/IEC 27001 (A.9.4.2) Threat Intel: CVE-1999-0501	Accounts configured with plaintext/weak password: Line 15: username admin (privilege 15) password [PROTECTED], Line 16: username operator (privilege 1) password [PROTECTED]	High

[CISCO-AUTH-002] Weak enable password detected Compliance: CIS Cisco IOS Benchmark v8 (1.5), NIST SP 800-53 (IA-5), DISA STIG Threat Intel: CVE-1999-0501	Line 18: enable password [PROTECTED]	High
[CISCO-SNMP-001] SNMP is using the default/public community string Compliance: CIS Cisco IOS Benchmark v8 (1.6), NIST SP 800-53 (SC-8), DISA STIG (NET-080) Threat Intel: CVE-2002-0012	Line 35: snmp-server community [REDACTED_PUBLIC] RO	High
[CISCO-WEB-001] HTTP management is enabled Compliance: CIS Cisco IOS Benchmark v8 (1.7), NIST SP 800-53 (AC-17), DISA STIG Threat Intel: CVE-2000-0945	Line 33: ip http server	High
[CISCO-AAA-001] AAA authentication may not be configured Compliance: CIS Cisco IOS Benchmark v8 (1.8), NIST SP 800-53 (AC-2, IA-2) Threat Intel: CWE-306	Explicit control absent: 'aaa new-model' is not present in configuration	High
[CISCO-PWD-001] Weak password policy detected Compliance: CIS Cisco IOS Benchmark v8 (1.9), NIST SP 800-53 (IA-5), ISO/IEC 27001 (A.9.4.3) Threat Intel: CWE-521	Line 43: security passwords min-length 6 (minimum recommended is 10 or greater)	High
[CISCO-LOGIN-001] Login protection may not be configured Compliance: CIS Cisco IOS Benchmark v8 (1.10), NIST SP 800-53 (AC-7) Threat Intel: CWE-307	Explicit control absent: 'login block-for' / 'login quiet-mode' is not configured	Medium
[CISCO-LOG-001] Console logging is disabled or centralized logging configuration should be verified Compliance: CIS Cisco IOS Benchmark v8 (2.1), NIST SP 800-53 (AU-2, AU-3) Threat Intel: CWE-778	Line 37: no logging console (no remote syslog host configured)	Medium
[CISCO-ACL-001] Overly permissive access-control rule detected Compliance: CIS Cisco IOS Benchmark v8 (3.1), NIST SP 800-53 (AC-4), ISO/IEC 27001 (A.13.1.1) Threat Intel: CWE-732	Line 45: access-list 10 permit any	High

Authoritative Remediation Guidance

- Disable Telnet and use SSH for secure remote administration.
- Disable SSH version 1 and configure SSH version 2.
- Regenerate RSA keys using a stronger key size appropriate for the device and security policy ($\geq$ 2048 bits).
- Use securely hashed/secret-protected credentials and enforce strong password policies.
- Replace the weak enable password with a stronger protected credential ('enable secret') and remove the legacy directive ('no enable password').
- Replace the public community string with a unique protected value or migrate to SNMPv3.
- Disable insecure HTTP management ('no ip http server') and enforce HTTPS ('ip http secure-server').
- Configure AAA using an appropriate authentication service ('aaa new-model').
- Enforce strong passwords and appropriate password security policies ('security passwords min-length 10').
- Configure login attempt limits, lockout or equivalent protection ('login block-for 180 attempts 3 within 60').
- Configure centralized system logging and monitor security events ('logging host <ip>').

- Restrict access-list rules to specific authorized hosts, subnets, and required service ports.

Cryptographic Audit Verification & Registry



Audit Registry Verification ID: AUDIT-20260927-412E29

Integrity Fingerprint (SHA-256):

37ad3cff05bfb1dd9e098723e869554e27260f89193066ec9b49cbaf8c1eb1d9

Scan the adjacent QR code to query the Sentry Shield verification endpoint. This cryptographic checksum ensures the audit results, score, and findings have not been altered since engine execution.