

# SENTRY SHIELD

## Network Security & Compliance Audit Report

Audit Reference ID: AUDIT-20260927-C4895A

Target Device: core-switch-01

Platform / Vendor: Cisco

Engine Version: Sentry Core 2.0 (Deterministic Compliance)

### Security Score & Compliance Status

Overall Security Score: **52/100** | Compliance Status: **NON-COMPLIANT (HIGH SEVERITY CONTROLS FAILED)**  
| Audit State: **Evaluation Complete**

| Severity Tier | Findings | Remediation Priority & Impact                                                           |
|---------------|----------|-----------------------------------------------------------------------------------------|
| Critical      | 0        | Immediate remediation required (RCE, default read-write credentials, full exposure)     |
| High          | 5        | High priority (Cleartext management, legacy SSHv1, plaintext credentials, open ACLs)    |
| Medium        | 2        | Moderate priority (Disabled console logging, missing brute-force protection, time sync) |
| Low / Info    | 0        | Hardening improvement (Banner configuration, logging microsecond precision)             |

Evaluated Framework Baselines: CIS Cisco IOS Benchmark v8, NIST SP 800-53 Rev 5, DISA STIG, ISO/IEC 27001:2022

**Non-Compliant Control Violations:** CIS Cisco IOS Benchmark v8 (1.1), CIS Cisco IOS Benchmark v8 (1.10), CIS Cisco IOS Benchmark v8 (1.6), CIS Cisco IOS Benchmark v8 (1.7), CIS Cisco IOS Benchmark v8 (1.8), CIS Cisco IOS Benchmark v8 (1.9), CIS Cisco IOS Benchmark v8 (2.1), DISA STIG, DISA STIG (NET-040), DISA STIG (NET-080), ISO/IEC 27001 (A.9.4.3), NIST SP 800-53 (AC-17), NIST SP 800-53 (AC-2, IA-2), NIST SP 800-53 (AC-7), NIST SP 800-53 (AU-2, AU-3), NIST SP 800-53 (IA-5), NIST SP 800-53 (SC-8)

### Security Findings & Evidence

| Rule & Issue Details                                                                                                                                                                                                  | Verified Configuration Evidence                                          | Severity |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|----------|
| <b>[CISCO-TELNET-001]</b><br>Telnet is enabled for remote management<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.1), NIST SP 800-53 (AC-17), DISA STIG (NET-040)<br><b>Threat Intel:</b> CVE-1999-0524        | Line 3: transport input telnet ssh                                       | High     |
| <b>[CISCO-SNMP-001]</b><br>SNMP is using the default/public community string<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.6), NIST SP 800-53 (SC-8), DISA STIG (NET-080)<br><b>Threat Intel:</b> CVE-2002-0012 | Line 5: snmp-server community [REDACTED_PUBLIC] RO                       | High     |
| <b>[CISCO-WEB-001]</b><br>HTTP management is enabled<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.7), NIST SP 800-53 (AC-17), DISA STIG<br><b>Threat Intel:</b> CVE-2000-0945                                  | Line 4: ip http server                                                   | High     |
| <b>[CISCO-AAA-001]</b><br>AAA authentication may not be configured<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.8), NIST SP 800-53 (AC-2, IA-2)<br><b>Threat Intel:</b> CWE-306                                | Explicit control absent: 'aaa new-model' is not present in configuration | High     |

|                                                                                                                                                                                                |                                                                                                         |               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|---------------|
| <b>[CISCO-PWD-001]</b><br>Weak password policy detected<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.9), NIST SP 800-53 (IA-5), ISO/IEC 27001 (A.9.4.3)<br><b>Threat Intel:</b> CWE-521 | Explicit control absent: No minimum password length policy configured ('security passwords min-length') | <b>High</b>   |
| <b>[CISCO-LOGIN-001]</b><br>Login protection may not be configured<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (1.10), NIST SP 800-53 (AC-7)<br><b>Threat Intel:</b> CWE-307              | Explicit control absent: 'login block-for' / 'login quiet-mode' is not configured                       | <b>Medium</b> |
| <b>[CISCO-LOG-001]</b><br>Logging may not be configured<br><b>Compliance:</b> CIS Cisco IOS Benchmark v8 (2.1), NIST SP 800-53 (AU-2, AU-3)<br><b>Threat Intel:</b> CWE-778                    | Explicit control absent: No centralized syslog server or logging buffer configured                      | <b>Medium</b> |

Authoritative Remediation Guidance

- Disable Telnet and use SSH for secure remote administration.
- Replace the public community string with a unique protected value or migrate to SNMPv3.
- Disable insecure HTTP management ('no ip http server') and enforce HTTPS ('ip http secure-server').
- Configure AAA using an appropriate authentication service ('aaa new-model').
- Enforce strong passwords and appropriate password security policies ('security passwords min-length 10').
- Configure login attempt limits, lockout or equivalent protection ('login block-for 180 attempts 3 within 60').
- Configure centralized system logging and monitor security events.

Cryptographic Audit Verification & Registry



**Audit Registry Verification ID:** AUDIT-20260927-C4895A

**Integrity Fingerprint (SHA-256):**

e6f3957cd3551ddd13f4e22deb113b03b2b14f2e20d71b11ec2b334881991f51

Scan the adjacent QR code to query the Sentry Shield verification endpoint. This cryptographic checksum ensures the audit results, score, and findings have not been altered since engine execution.