

Simulation Step 7D Summary Statistics

March 13, 2024

Table of Contents

- 1 Prelude
- 2 Utilities (as before)
- 3 Finding Shortest Path (as before)
- 4 Finding Shortest Delivery Route (as before)
- 5 Time Handling
- 6 Class Recorder
- 7 Class Parcel
- 8 Class Customer
- 9 Class Driver
- 10 Class Delivery Centre
- 11 Simulation
 - 11.1 Parameters from Specification
 - 11.2 Generate Input Data
 - 11.3 Simulation Routine
 - 11.4 Model Verification

1 Prelude

```
[1]: import matplotlib.pyplot as plt
import pulp
import math
import random
import pandas as pd
import numpy as np
import time
import simpy
```

2 Utilities (as before)

2.1 Points and Distances

```
[2]: def dist(p1, p2):  
      (x1, y1) = p1  
      (x2, y2) = p2  
      return int(math.sqrt((x1-x2)**2+(y1-y2)**2))
```

2.2 PlotMap

```
[3]: def plotMap(G, T=[], P=[], W=None,  
               style='r-o', lw=1, ms=3,  
               styleT='go', msT=5,  
               styleP='b-o', lwP=3, msP=1,  
               stylePT='go', msPT=7,  
               styleW='bo', msW=9,  
               text=None, grid=False):  
    fig = plt.gcf()  
    fig.set_size_inches(6, 6)  
    V, E = G  
  
    if not grid:  
        plt.axis('off')  
    plt.plot( [ p[0] for p in V ], [ p[1] for p in V ], 'ro', lw=lw, ms=ms)  
    for (p, q) in E:  
        plt.plot( [ p[0], q[0] ], [ p[1], q[1] ], 'r-o', lw=lw, ms=ms)  
    for t in T:  
        plt.plot( [ t[0] ], [ t[1] ],  
                  styleT, ms=msT)  
    plt.plot( [ p[0] for p in P ],  
              [ p[1] for p in P ],  
              styleP, lw=lwP, ms=msP)  
    for p in P:  
        if p in T:  
            plt.plot( [ p[0] ], [ p[1] ],  
                      stylePT, ms=msPT)  
    if W is not None:  
        plt.plot( [ W[0] ], [ W[1] ],  
                  styleW, ms=msW)  
    if text is not None:  
        maxX = max([p[0] for p in V])  
        plt.text(0.8*maxX, 0, text)  
    if grid:  
        plt.grid()  
    plt.show()
```

2.3 Add Targets

```
[4]: def addTarget(M, T):
    V, E = M
    E = E.copy()
    V = V.copy()
    for t in T:
        minD = math.inf
        minE = None
        for e in E:
            P, Q = e
            distT = dist(P, t)+dist(t, Q)-dist(P, Q)
            if distT < minD:
                minD = distT
                minE = e
        P, Q = minE
        E.remove( (P, Q) )
        E.append( (P, t) )
        E.append( (t, Q) )
        V.append(t)
    return V, E
```

2.4 Generate Warehouse Location

```
[5]: def generateWarehouseLocation(M):
    V, _ = M
    W = random.sample(V, k=1)[0]
    return W
```

2.5 Time Handling

Convention: In this project we measure time in seconds. The simulation will start at 0:00. Time related methods will be added as they are needed.

timestamp(t) generates a timestamp string in the form [dd] hh:mm:ss.d

```
[6]: def timestamp(t):
    day = int(t)//(24*3600)
    t = t - day*24*3600
    hour = int(t)//3600
    t = t - hour*3600
    mins = int(t)//60
    t = t - mins*60
    secs = int(math.floor(t))
    t = int(math.floor((t - secs)*10))
    return f"[{day:2d}] {hour:02d}:{mins:02d}:{secs:02d}. {t:1d}"
```

```
[7]: timestamp(24*3600*3+17*3600+615.1)
```

```
[7]: '[ 3] 17:10:15.0'
```

```
[8]: def nextHour(env, hour):  
    beginningOfDay = int(env.now//(24*3600))*24*3600  
    timeOfDay = env.now-beginningOfDay  
    if hour*3600 > timeOfDay:  
        return hour*3600 - timeOfDay  
    else:  
        return hour*3600 + 24*3600 - timeOfDay
```

```
[9]: def day(now):  
    return int(now//(24*3600))
```

2.6 Plotting Routines

```
[10]: import scipy.stats as stats  
  
def histplot(data, title="", xlabel="",  
             width=None, height=None):  
  
    minx = min(data)  
    maxx = max(data)  
    loc = np.mean(data)  
    scale = np.std(data)  
  
    fig = plt.figure()  
    fig.set_figwidth(width if width is not None else 4)  
    fig.set_figheight(height if height is not None else 2.5)  
    ax = fig.gca()  
  
    hist=plt.hist(data, density=True)  
    plt.xlabel(xlabel)  
    plt.ylabel('Density')  
    plt.title(title)  
  
    x = np.linspace(minx, maxx, 100)  
    y = [ stats.norm(loc= , scale= ).pdf(p) for p in x]  
    ax.plot(x, y, lw=1, color='red')  
    ax.axvline(x= , color='red')  
    maxy = max(max(y), max(hist[0]))  
    ax.text(maxx, maxy,  
           f'={:2.2f}\n={:2.2f}',  
           ha='right', va='top',  
           color='red', fontsize=12)  
    ax.grid(True)  
    plt.show()
```

```
[11]: def dailyPlot(data,
                title="", ylabel="",
                width=None, height=None):

    days = len(data)

    fig = plt.figure()
    fig.set_figwidth(width if width is not None else 6)
    fig.set_figheight(height if height is not None else 2)

    ax = fig.gca()
    diff = (max(data)-min(data))*0.1
    ymin = int(math.floor(min(data)-diff))
    ymax = int(math.ceil(max(data)+diff))
    ax.set_xlim(-1, days)
    ax.set_ylim(ymin, ymax)
    ax.grid(True)

    ms = 2 if len(data)>100 else 5
    lw = 0.5 if len(data)>100 else 1

    x = np.arange(0, len(data))
    y = np.array([ y for y in data ])
    b, m = np.polynomial.polynomial.polyfit(x, y, 1)

    plt.plot(x, y, 'bo-', linewidth=lw, markersize=ms)
    plt.plot(x, m*x+b, 'r-')

    plt.xlabel('Day')
    plt.ylabel(ylabel)
    plt.title(title)
    plt.show()
```

3 Finding Shortest Path (as before)

```
[12]: def dist(p1, p2):
    (x1, y1) = p1
    (x2, y2) = p2
    return int(math.sqrt((x1-x2)**2+(y1-y2)**2))
```

```
[13]: def pathLength(P):
    return 0 if len(P)<=1 else \
        dist(P[0], P[1])+pathLength(P[1:])
```

```
[14]: def shortestPath(M, A, B):
```

```

def h(p):
    return pathLength(p)+dist(p[-1],B)

# candidates C are pairs of the path so far and
# the heuristic function of that path,
# sorted by the heuristic function, as maintained by
# insert function
def insert(C, p):
    hp = h(p)
    c = (p, hp)
    for i in range(len(C)):
        if C[i][1]>hp:
            return C[:i]+[c]+C[i:]
    return C+[c]

V, E = M
assert(A in V and B in V)
C = insert([], [A])

while len(C)>0:
    # take the first candidate out of the list of candidates
    path, _ = C[0]
    C = C[1:]
    if path[-1]==B:
        return path
    else:
        for (x, y) in E:
            if path[-1]==x and y not in path:
                C = insert(C, path+[y])
            elif path[-1]==y and x not in path:
                C = insert(C, path+[x])

return None

```

4 Finding Shortest Delivery Route (as before)

4.1 Iterative Integer Programming

```

[15]: def createTables(M, T):

    def reverse(P):
        return [ P[-i] for i in range(1,len(P)+1) ]

    def index(x, L):
        for i in range(len(L)):
            if x==L[i]:
                return i
        return None

```

```

n = len(T)
d = [ [ math.inf for t in T ] for t in T ]
p = [ [ None for t in T ] for t in T ]
for i in range(n):
    d[i][i] = 0
    p[i][i] = [ T[i] ]
for i in range(n):
    for j in range(n):
        if p[i][j] is None:
            s = shortestPath(M, T[i], T[j])
            d[i][j] = d[j][i] = pathLength(s)
            p[i][j] = s
            p[j][i] = reverse(s)
            for m in range(len(s)-1):
                smi = index(s[m], T)
                if smi is None:
                    continue
                for l in range(m+1, len(s)):
                    sli = index(s[l], T)
                    if sli is None:
                        continue
                    sub = s[m:l+1]
                    if p[smi][sli] is None:
                        p[smi][sli] = sub
                        p[sli][smi] = reverse(sub)
                        d[smi][sli] = d[sli][smi] = pathLength(sub)

return d,p

```

```

[16]: def roundtrips(x, n):

    def isElem(x, l):
        for i in range(len(l)):
            if l[i]==x:
                return True
        return False

    def startpoint(trips):
        for i in range(n):
            for t in trips:
                if isElem(i, t):
                    break
            else:
                return i

    def totalLength(trips):
        s=0

```

```

        for i in range(0, len(trips)):
            s += len(trips[i])-1
        return s

trips = []
while totalLength(trips)<n:
    start = startpoint(trips)
    trip = [ start ]
    i = start
    while len(trip) < n-totalLength(trips):
        for j in range(0, n):
            if pulp.value(x[i][j])==1:
                trip.append(j)
                i=j
                break
        if pulp.value(x[trip[-1]][start])==1:
            trip.append(start)
            break
    trips.append(trip)
return sorted(trips, key=lambda t: len(t), reverse=True)

```

```

[17]: import time

def createLoop(M, T, timing=False):

    if timing:
        start_time = time.time()
        last_time = time.time()

    D, P = createTables(M, T)    # These are the distances between customers and
    ↪ warehouse only

    if timing:
        print(f"createTables:    {time.time()-start_time:6.2f}s")
        last_time = time.time()

    n = len(T)

    if n==1:
        return T

    # create variables
    x = pulp.LpVariable.dicts("x", ( range(n), range(n) ),
                               lowBound=0, upBound=1, cat=pulp.LpInteger)

    # create problem
    prob = pulp.LpProblem("Loop",pulp.LpMinimize)
    # add objective function

```



```

prob += pulp.lpSum([ D[i][j]*x[i][j]
                    for i in range(n) for j in range(n) ])

# add constraints
constraints=0
for j in range(n):
    prob += pulp.lpSum([ x[i][j] for i in range(n) if i!=j ]) ==1
constraints += n
for i in range(n):
    prob += pulp.lpSum([ x[i][j] for j in range(n) if i!=j ]) ==1
constraints += n
for i in range(n):
    for j in range(n):
        if i!=j:
            prob += x[i][j]+x[j][i] <= 1
            constraints += 1

# initialise solver
solvers = pulp.listSolvers(onlyAvailable=True)
solver = pulp.getSolver(solvers[0], msg=0)
prob.solve(solver)

if timing:
    print(f"Solver:          {time.time()-last_time:6.2f}s {constraints:6,d}␣
↳Constraints")
    last_time = time.time()

trips = roundtrips(x, n)
while len(trips)>1:
    longest = max([ len(t) for t in trips ])
    for t in trips:
        if len(t)<longest:
            prob += pulp.lpSum([ x[t[i]][t[i+1]] + x[t[i+1]][t[i]]
                                for i in range(0,len(t)-1) ]) <=␣
↳len(t)-2
            constraints += 1
        else:
            longest = math.inf
    prob.solve(solver)

    if timing:
        print(f"Solver:          {time.time()-last_time:6.2f}s {constraints:
↳6,d} Constraints")
        last_time = time.time()

    trips = roundtrips(x, n)

trip = trips[0]
loop = []

```

```

for k in range(len(trip)-1):
    sub = P[trip[k]][trip[k+1]]
    loop += sub if len(loop)==0 else sub[1:]

if timing:
    print(f"createLoop:      {time.time()-start_time:6.2f}s")

return loop

```

4.2 Heuristic Algorithm

```

[18]: def FW(M):

    V, E = M

    n = len(V)
    d = [ [ math.inf for j in range(n) ] for i in range(n) ]
    p = [ [ None for j in range(n) ] for i in range(n) ]

    for (A, B) in E:
        a = V.index(A)
        b = V.index(B)
        d[a][b] = d[b][a] = dist(A, B)
        p[a][b] = [A, B]
        p[b][a] = [B, A]

    for i in range(n):
        d[i][i] = 0
        p[i][i] = [V[i]]

    for k in range(n):
        for i in range(n):
            for j in range(n):
                dk = d[i][k] + d[k][j]
                if d[i][j] > dk:
                    d[i][j] = dk
                    p[i][j] = p[i][k][:-1] + p[k][j]

    return d, p

```

```

[19]: def createLoopH(M, T, timing=False):

    def makeLoop(L):
        loop = []
        for i in range(len(L)-1):
            A = L[i]
            B = L[i+1]

```

```

        a = V.index(A)
        b = V.index(B)
        sub = P[a][b]
        loop += sub if len(loop)==0 else sub[1:]
    return loop

if timing:
    start_time = time.time()
    last_time = time.time()

V, E = M
D, P = FW(M)    # note these are the distances between all vertices in  $M$ 
↪ (and T)

if timing:
    print(f"createTables:    {time.time()-start_time:6.2f}s")
    last_time = time.time()

W = T[0]
customers = T[1:]
if len(T)==1:
    L = T
elif len(T)<=3:
    L = T + [T[0]]
else:
    L = T[:3]+[T[0]]
    T = T[3:]
    while len(T)>0:
        minExt = math.inf
        minInd = None
        selInd = None
        for k in range(len(T)):
            C = T[k]
            c = V.index(C)
            for i in range(0, len(L)-1):
                A = L[i]
                B = L[i+1]
                a = V.index(A)
                b = V.index(B)
                ext = D[a][c] + D[c][b] - D[a][b]
                if ext<minExt:
                    minExt, minInd, selInd = ext, i+1, k
            L = L[:minInd]+[T[selInd]]+L[minInd:]
            T = T[:selInd]+T[selInd+1:]

if timing:
    print(f"createLoopH:    {time.time()-start_time:6.2f}s")

```

```
return makeLoop(L)
```

5 Class Recorder

We will use a class Recorder as a reference point for capturing data during the simulation. There will be only one recorder. It will be created at the beginning of every simulation run. Every entity will carry a reference to the Recorder.

```
[20]: class Recorder:

    def __init__(self, env, M, W, C, days,
                 log=False, plot=False, timing=False):
        self.env = env
        self.M = M
        self.W = W
        self.C = C
        self.days = days
        self.log = log
        self.plot = plot

        self.timing = timing
        self.start_time = time.time()
        self.last_time = self.start_time
        self.cum_timer = {}

        Customer.REGISTER = []
        Parcel.REGISTER = []

        # create a data frame for records per working day
        self.daily = pd.DataFrame()
        self.daily['begin work at'] = [None]*days
        self.daily['end work at'] = [None]*days
        self.daily['dist'] = [None]*days
        self.daily['left'] = [None]*days

    def timer(self, s):
        t = time.time()
        Δt = t-self.last_time
        if self.timing:
            print(f"==== t: {t-self.start_time:6.2f}s "
                  f"Δt: {Δt:6.2f}s [{s:s}]")
        if s in self.cum_timer:
            self.cum_timer[s] += Δt
        else:
            self.cum_timer[s] = Δt
        self.last_time = t
```

```

def reportTimer(self):
    print(f"==== t: {self.total_time:6.2f}s Total")
    for k in sorted(self.cum_timer, key=lambda x: self.cum_timer[x],
↪reverse=True):
        print(f"====  $\Sigma\Delta t$ : {self.cum_timer[k]:6.2f}s "+ k)

def trace(self, event):
    if self.log:
        print(timestamp(self.env.now), event)

def recordDriverBeginsWork(self):
    self.trace("Driver arrives for work")
    self.daily.at[day(self.env.now), 'begin work at'] = int(round(self.env.
↪now))

def recordDriverEndsWork(self):
    self.trace("Driver goes home")
    self.daily.at[day(self.env.now), 'end work at'] = int(round(self.env.
↪now))

def recordTourLength(self, length):
    self.daily.at[day(self.env.now), 'dist'] = int(length)

def recordParcelsLeftOver(self, numberOfParcels):
    self.trace(f"{numberOfParcels:d} left over for next day")
    self.daily.at[day(self.env.now), 'left'] = numberOfParcels

def finish(self):
    # simulation is finished for good
    # by removing the simulation environment we can
    # pickle recorder
    self.env = None
    self.total_time = time.time()-self.start_time
    self.daily['working time'] = (self.daily['end work at']-self.
↪daily['begin work at'])//60

def __stats__(self, column):
    d = self.daily[column].copy()
    return d.mean(), d.median(), d.std()

def statsWorkingTime(self):
    return self.__stats__('working time')

def histWorkingTime(self):
    histplot(self.daily['working time'],

```

```

        xlabel='Working Time [min]',
        title='Daily Working Time')

    def plotWorkingTime(self):
        dailyPlot(self.daily['working time'],
                  ylabel='Working Time [min]',
                  title='Daily Working Time')

    def statsTourLength(self):
        return self.__stats__('dist')

    def histTourLength(self):
        histplot(self.daily['dist'],
                 xlabel='Tour Length [m]',
                 title='Daily Tour Length')

    def plotTourLength(self):
        dailyPlot(self.daily['dist'],
                  ylabel='Tour Length [m]',
                  title='Daily Tour Length')

    def statsLeftOver(self):
        return self.__stats__('left')

    def histLeftOver(self):
        histplot(self.daily['left'],
                 xlabel='Left-Over Parcels',
                 title='Daily Left-Over Parcels')

    def plotLeftOver(self):
        dailyPlot(self.daily['left'],
                  ylabel='Number of Parcels',
                  title='Daily Left-Over Parcels')

```

6 Class Parcel

Parcels follow through a sequence of states: - processing - in transit (from manufacture to distribution centre) - arrived in distribution centre - ready for delivery - out for delivery - customer not present - returned to distribution centre - delivered

```

[21]: class Parcel:

    REGISTER = []

    def __init__(self, rec, i, cust, custIndex):
        self.rec = rec
        self.i = i  # row index in data frames of input data

```

```

        self.dest = cust.location
        self.custIndex = custIndex
        self.status = [ 'processing' ] # status record and
        self.timing = [ self.rec.env.now ] # timing
        assert(len(Parcel.REGISTER)==i)
        Parcel.REGISTER += [ self ]

# factory method ensures that there is only
# one Parcel per location
    def getParcel(rec, i, location, custIndex):
        for p in Parcel.REGISTER:
            if p.i == i:
                return p
        return Parcel(rec, i, location, custIndex)

    def __str__(self):
        return f"Parcel: {self.i:3d} ({self.custIndex:3d})"

    def index(self):
        return self.i

    def destination(self):
        return self.dest

    def __reg(self, state):
        self.status += [ state ]
        self.timing += [ self.rec.env.now ]
        self.rec.trace(str(self)+" "+state)

    def arrivedAtDeliveryCentre(self):
        self.__reg('arr at delivery centre')

    def outForDelivery(self):
        self.__reg('out for delivery')

    def returnFromDelivery(self):
        self.__reg('return from delivery')

```

7 Class Customer

```
[22]: class Customer:
```

```
    REGISTER = []
```

```

def __init__(self, rec, location):
    self.rec = rec
    self.location = location
    self.i = len(Customer.REGISTER)
    Customer.REGISTER += [ self ]
    self.atHome = True
    self.answersDoor = False
    self.parcelsReceived = []
    rec.env.process(self.process())

def __str__(self):
    return f"Customer: {self.i:2d} {str(self.location):s}"

# factory method ensures that there is only
# one customer per location
def getCustomer(rec, location):
    for c in Customer.REGISTER:
        if c.location == location:
            return c
    return Customer(rec, location)

def leaveHouse(self):
    assert(self.atHome and not self.answersDoor)
    # self.rec.trace(str(self)+" leaves house")
    self.atHome = False

def returnHome(self):
    assert(not self.atHome)
    # self.rec.trace(str(self)+" returns home")
    self.atHome = True

def answerDoor(self):
    if self.atHome:
        yield self.rec.env.timeout(random.expovariate(1/
↪AVERAGE_TIME_ANSWER_DOOR))
        self.rec.trace(str(self)+" answers door")
        self.answersDoor = True
    else:
        yield self.rec.env.timeout(WAIT_TIME_IF_CUSTOMER_DOESNT_ANSWER_DOOR)
        self.rec(str(self)+" not at home")

def acceptParcel(self, parcel):
    assert(self.answersDoor)
    self.parcelsReceived += [parcel]
    self.rec.trace(str(self)+" accepts "+str(parcel))

def signOff(self):

```



```

    assert(self.answersDoor)
    self.rec.trace(str(self)+" signs off")
    self.answersDoor = False

def process(self):
    yield self.rec.env.timeout(nextHour(self.rec.env, 8))
    while day(self.rec.env.now)<self.rec.days:
        # in a refinement we may use random times
        self.leaveHouse()
        yield self.rec.env.timeout(nextHour(self.rec.env, 18))
        self.returnHome()
        yield self.rec.env.timeout(nextHour(self.rec.env, 8))

```

8 Class Driver

```

[23]: class Driver:

    def __init__(self, rec, DC):
        self.rec = rec
        self.DC = DC
        self.location = None
        self.parcels = None
        self.tour = None
        self.rec.env.process(self.process())

    # activity
    def __drive(self, target):
        assert(self.tour[0] == self.location)
        while self.location!=target:
            d = dist(self.location, self.tour[1])
            yield self.rec.env.timeout(d / AVERAGE_SPEED)
            self.location = self.tour[1]
            self.tour = self.tour[1:]
        assert(self.tour[0] == self.location == target)

    def arriveForWork(self):
        self.location = self.DC.W
        self.parcels = []
        self.returns = []
        self.tour = [ self.DC.W ]
        self.rec.recordDriverBeginsWork()

    def leaveForDelivery(self, tour, parcels):
        self.tour, self.parcels = tour, parcels
        self.rec.trace(f"Driver leaves for delivery " \
                       f"of {len(parcels):d} parcels")

```

```

def process(self):
    yield self.rec.env.timeout(nextHour(self.rec.env, 18))
    while day(self.rec.env.now)<self.rec.days:
        self.arriveForWork()
        tour, parcels = self.DC.sendForDelivery()
        yield self.rec.env.timeout(PREP_TIME_PER_PARCEL*len(parcels))
        self.rec.recordTourLength(pathLength(tour))
        self.leaveForDelivery(tour, parcels)
        while len(self.parcels)>0:
            # drive to customer
            custLocation = self.parcels[0].dest
            cust = Customer.getCustomer(self.rec, custLocation)
            self.rec.trace("Driver drives to "+str(cust))
            yield from self.__drive(custLocation)
            self.rec.trace("Driver arrived at "+str(cust))
            # call at customer
            yield from cust.answerDoor()

            if cust.answersDoor:
                while len(self.parcels)>0 and \
                    custLocation == self.parcels[0].dest:
                    cust.acceptParcel(self.parcels[0])
                    yield self.rec.env.timeout(random.expovariate(1/10))
                    self.parcels = self.parcels[1:]
                cust.signOff()
                yield self.rec.env.timeout(random.expovariate(1/10))
            else:
                while len(self.parcels)>0 and \
                    custLocation == self.parcels[0].dest:
                    self.returns += self.parcels[0]
                    self.parcels = self.parcels[1:]

            # return to delivery centre
            self.rec.trace("Driver returns to delivery centre")
            yield from self.__drive(self.DC.W)
            self.rec.trace("Driver arrived at delivery centre")

        for parcel in self.returns:
            self.DC.returnFromDelivery(parcel)
            yield self.rec.env.timeout(RETURN_TIME_PER_PARCEL)
        yield self.rec.env.timeout(600)

        self.rec.recordParcelsLeftOver(len(self.DC.parcels)+
                                       len(self.DC.leftOver))

    self.rec.recordDriverEndsWork()

```

```
yield self.rec.env.timeout(nextHour(self.rec.env, 18))
```

9 Class Delivery Centre

```
[24]: class DeliveryCentre:

    def __init__(self, rec, M, W):
        self.rec = rec
        self.M = M
        self.W = W
        self.limit = 35000

        self.leftOver = []      # list of parcels
        self.parcels = []      # list of parcels scheduled for delivery
        self.dest = []         # list of unique customer destinations
        self.tour = None        # tour planned for delivery

    def __accept(self, parcel):
        custLoc = parcel.dest
        if custLoc not in self.dest:
            MT = addTargets(self.M, self.dest + [custLoc])
            self.rec.timer("addTarget")
            SH = createLoopH(MT, [self.W] + self.dest + [custLoc],
                             timing=self.rec.timing)
            self.rec.timer("createLoopH")
            if self.tour is None and pathLength(SH) < self.limit:
                self.parcels.append(parcel)
                self.dest += [custLoc]
            else:
                S = createLoop(MT, [self.W] + self.dest + [custLoc],
                                timing=self.rec.timing)
                self.rec.timer("createLoop")
                if pathLength(S) < self.limit:
                    self.parcels.append(parcel)
                    self.dest += [custLoc]
                    self.tour = S
                else:
                    self.leftOver.append(parcel)
        else:
            self.parcels.append(parcel)

    def acceptParcel(self, parcel):
        parcel.arrivedAtDeliveryCentre()
        self.__accept(parcel)
```

```

def sendForDelivery(self):
    parcels = []
    if self.tour is None:
        MT = addTarget(self.M, self.dest)
        self.rec.timer("addTarget")
        self.tour = createLoop(MT, [self.W] + self.dest,
                                timing=self.rec.timing)
        self.rec.timer("createLoop")
    tour = self.tour
    addresses = self.dest

    # pick parcels in sequence to be delivered
    for i in range(1, len(tour)-1):
        dest = tour[i]
        for p in self.parcels:
            if p.dest == dest and p not in parcels:
                parcels += [p]
                p.outForDelivery()

    # arrange the left overs
    L = self.leftOver
    self.tour = None
    self.parcels = []
    self.leftOver = []
    self.dest = []
    for p in L:
        self.__accept(p)

    if self.rec.plot:
        plotMap(self.rec.M, T=addresses, P=tour, W=tour[0],
                text=f"Day {day(self.rec.env.now):2d}, {pathLength(tour):
↪,d}m")

    return tour, parcels

def returnFromDelivery(self, parcel):
    parcel.returnFromDelivery()
    self.__accept(parcel)

def getInventory(self):
    return len(self.parcels)+len(self.leftOver)

```

10 Simulation

10.1 Parameters from Specification

The time required for driving is based on the distance between way points at an average speed of 15km/h.

```
[25]: AVERAGE_SPEED = 15/3.6
```

The **cumulative preparation time** (route planning and sorting of the parcels in the delivery order and packing the cargo-bike) is assumed to be 50 sec per parcel to be delivered.

```
[26]: PREP_TIME_PER_PARCEL = 50
```

Additional assumption: The time to **process returned parcels** in the delivery centre is 30 sec per parce.

```
[27]: RETURN_TIME_PER_PARCEL = 30
```

The average time to answer the door.

```
[28]: AVERAGE_TIME_ANSWER_DOOR = 40
```

```
[29]: WAIT_TIME_IF_CUSTOMER_DOESNT_ANSWER_DOOR = 60
```

10.2 Generate Input Data

```
[30]: def generateDeliveryData(p, C, days, seed=0):  
    ## p is the average number of parcels per day per customer  
    ## C is the number of customers to be served  
    ## days is the number of days for which data are to be generated.  
    np.random.seed(seed)  
    R = np.random.poisson(lam=len(C)*p, size=days)  
    D = [ sorted(list(np.random.choice(range(len(C)), size=i))) for i in R ]  
    return D
```

```
[31]: def generateInputData(D, log=False):  
  
    R = [ len(d) for d in D ]  
    N = sum(R)  
  
    DAY_LENGTH = 24*3600      # measured in minutes  
    DAY_START = 8*3600        # first delivery in the morning  
    DAY_END = 17*3600         # last delivery during day time  
  
    x = pd.DataFrame()  
  
    x['iarr'] = [None]*N  
    x['time'] = [None]*N  
    x['day'] = [None]*N
```

```

x['dest'] = [None]*N

current_day = 0
last_time = 0
i = 0

for d in D: # for each day

    if log:
        print("generating for day: ",current_day, D[current_day])

    time = current_day*DAY_LENGTH + DAY_START

    for c in d: # for each customer that should get a

        IARR = (DAY_END-DAY_START-2*3600) / len(d) # estimated average IAT
        ↪for the current day

        iat = random.expovariate(1.0/IARR)
        new_time = time + iat

        x.at[i, 'iarr'] = round(new_time - last_time,1)
        x.at[i, 'time'] = round(new_time - current_day*DAY_LENGTH , 1)
        x.at[i, 'day'] = current_day
        x.at[i, 'dest'] = c

        i += 1
        last_time = time = new_time

    current_day += 1

return x

```

10.3 Simulation Routine

```

[32]: def simulation(M, W, C, p=0.2, days=10, seed=0, log=False, plot=False,
        ↪timing=False):

    random.seed(seed)
    D = generateDeliveryData(p, C, days, seed)
    X = generateInputData(D, log=log)

    env = simpy.Environment()
    rec = Recorder(env, M, W, C, days, log=log, plot=plot, timing=timing)

    print(f"Simulating delivery of {len(X):d} parcels "
          f"over {len(D):d} days to {len(C):d} customers")

```

```

for c in C:
    Customer.getCustomer(rec, c)
DC = DeliveryCentre(rec, M, W)
D = Driver(rec, DC)

def generatorProcess(env):
    # generate the parcels based on input data x
    for i in range(len(X)):
        yield env.timeout(X.at[i, 'iarr'])
        custIndex = X.at[i, 'dest']
        custLoc = C[custIndex]
        cust = Customer.getCustomer(rec, custLoc)
        p = Parcel.getParcel(rec, i, cust, custIndex)
        DC.acceptParcel(p)

env.process(generatorProcess(env))
env.run()

rec.finish()

if log:
    print(f"Delivery Centre Inventory: {DC.getInventory():d} parcels")

return rec

```

10.4 Small Simulation Run



```
[33]: import pickle
with open('data.pickled', 'rb') as f:
    M, C = pickle.load(f)
```

```
[34]: random.seed(0)
W = generateWarehouseLocation(M)
rec = simulation(M, W, C, p=0.16, days=20)
with open('rec.pickle', 'wb') as f:
    pickle.dump(rec, f)
```

Simulating delivery of 484 parcels over 20 days to 150 customers



```
[35]: with open('rec.pickle', 'rb') as f:
    rec1 = pickle.load(f)
```

```
[36]: rec1.histWorkingTime()
rec1.plotWorkingTime()
rec1.statsWorkingTime()
```




[36]: (184.1, 183.5, 12.371018764158347)

```
[37]: rec1.histTourLength()
rec1.plotTourLength()
rec1.statsTourLength()
```

[37]: (32882.4, 33239.0, 2008.1697978114562)

```
[38]: rec1.histLeftOver()
      rec1.plotLeftOver()
      rec1.statsLeftOver()
```



[38]: (2.45, 1.5, 3.086046696102688)

[39]: rec1.reportTimer()

```
==== t: 225.48s Total
==== ΣΔt: 175.78s createLoop
==== ΣΔt: 49.01s createLoopH
==== ΣΔt: 0.69s addTarget
```

[]: