EXPERIMENT - 5

AIM

To create SQL views for department salary summary and employee hierarchy, test the updatability of views, and implement a recursive CTE to display reporting chains.

OBJECTIVES

• To create a view that summarizes employee salary information department-wise.

• To create an employee hierarchy view using manager relationships.

• To test whether a view is updatable and understand the conditions affecting view updates.

• To implement a recursive CTE for displaying employee reporting chains.

• To verify the results using SELECT queries.

DATABASE USED

The queries use the CompanyDB database and the Employee–Department–Project schema from the reference experiment. The Employee table is extended with manager_id to support employee hierarchy and recursive reporting chains.

```
USE CompanyDB;
```

SCHEMA REFERENCE

The Department, Project and Employee tables remain connected through dept_id and project_id. The Employee table additionally contains manager_id, which references Employee(emp_id).


SOURCE CODE / SQL QUERIES

1. DEPARTMENT SALARY SUMMARY VIEW

Create a view showing employee count, average salary, minimum salary, maximum salary and total salary for each department.

```
CREATE OR REPLACE VIEW department_salary_summary AS
SELECT
    d.dept_id,
    d.dept_name,
    COUNT(e.emp_id) AS employee_count,
    AVG(e.salary) AS average_salary,
    MIN(e.salary) AS minimum_salary,
    MAX(e.salary) AS maximum_salary,
    SUM(e.salary) AS total_salary
FROM Department d
JOIN Employee e
    ON d.dept_id = e.dept_id
GROUP BY d.dept_id, d.dept_name;
```

Output




The view returns one summary row for each of the five departments.

2. EMPLOYEE HIERARCHY VIEW

Create a view containing each employee and the name of the employee's immediate manager.

```
CREATE OR REPLACE VIEW employee_hierarchy AS
SELECT
    e.emp_id,
    e.emp_name,
    e.dept_id,
    d.dept_name,
    e.manager_id,
    m.emp_name AS manager_name,
    e.salary
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
LEFT JOIN Employee m
    ON e.manager_id = m.emp_id;
```

Output



emp_id	emp_name	dept_id	dept_name	manager_id	manager_name	salary
1	Ishaan	1	Development	NULL	NULL	65000.00
2	Reyansh	1	Development	1	Ishaan	72000.00
3	Adit	1	Development	2	Reyansh	58000.00
4	Aarush	1	Development	3	Adit	81000.00
5	Raghav	1	Development	4	Aarush	69000.00
6	Vihaan	1	Development	5	Raghav	62000.00
7	Anika	2	PeopleOps	NULL	NULL	52000.00
8	Kavya	2	PeopleOps	7	Anika	48000.00
9	Ira	2	PeopleOps	8	Kavya	61000.00
10	Naina	2	PeopleOps	9	Ira	55000.00
11	Aditi	2	PeopleOps	10	Naina	47000.00
12	Saanvi	2	PeopleOps	11	Aditi	59000.00
13	Harsh	3	Accounts	NULL	NULL	75000.00
14	Mohit	3	Accounts	13	Harsh	68000.00
15	Ritvik	3	Accounts	14	Mohit	83000.00
16	Ayush	3	Accounts	15	Ritvik	62000.00
17	Kunal	3	Accounts	16	Ayush	71000.00
18	Varun	3	Accounts	17	Kunal	56000.00
19	Mehak	4	Sales	NULL	NULL	54000.00
20	Pihu	4	Sales	19	Mehak	63000.00
21	Shreya	4	Sales	20	Pihu	57000.00
22	Tara	4	Sales	21	Shreya	66000.00
23	Mahi	4	Sales	22	Tara	51000.00
24	Anvi	4	Sales	23	Mahi	70000.00
25	Rajat	5	Logistics	NULL	NULL	60000.00
26	Yuvraj	5	Logistics	25	Rajat	73000.00
27	Arnav	5	Logistics	26	Yuvraj	67000.00
28	Laksh	5	Logistics	27	Arnav	59000.00
29	Devansh	5	Logistics	28	Laksh	76000.00
30	Om	5	Logistics	29	Devansh	64000.00

The hierarchy view shows the immediate reporting relationship. A department head has NULL in manager_id and manager_name.

3. TEST UPDATABILITY OF VIEWS

Test an update on a simple employee hierarchy view and then test an update on the grouped department salary summary view.

```
UPDATE employee_hierarchy
SET salary = salary + 1000
WHERE emp_id = 6;
SELECT emp_id, emp_name, salary
FROM Employee
WHERE emp_id = 6;
UPDATE department_salary_summary
SET average_salary = average_salary + 1000
WHERE dept_id = 1;
```

Output


The first UPDATE is expected to fail because the employee_hierarchy view contains joins and does not directly expose a single base-table row for every selected column. The grouped department_salary_summary view is also not directly updatable because it contains GROUP BY and aggregate functions. The base Employee table should be updated instead.

4. RECURSIVE CTE – REPORTING CHAIN

Display the reporting chain beginning with department heads and recursively follow manager relationships.

```
WITH RECURSIVE reporting_chain AS (
    SELECT
        e.emp_id,
        e.emp_name,
        e.manager_id,
        1 AS level,
        CAST(e.emp_name AS CHAR(500)) AS reporting_path
    FROM Employee e
    WHERE e.manager_id IS NULL
    UNION ALL
    SELECT
        e.emp_id,
        e.emp_name,
        e.manager_id,
        rc.level + 1,
        CONCAT(rc.reporting_path, ' -> ', e.emp_name)
    FROM Employee e
    JOIN reporting_chain rc
        ON e.manager_id = rc.emp_id
)
SELECT emp_id, emp_name, manager_id, level, reporting_path
FROM reporting_chain
ORDER BY reporting_path;
```

Output



emp_id	emp_name	manager_id	level	reporting_path
7	Anika	NULL	1	Anika
8	Kavya	7	2	Anika -> Kavya
9	Ira	8	3	Anika -> Kavya -> Ira
10	Naina	9	4	Anika -> Kavya -> Ira -> Naina
11	Aditi	10	5	Anika -> Kavya -> Ira -> Naina -> Aditi
12	Saanvi	11	6	Anika -> Kavya -> Ira -> Naina -> Aditi -> Saanvi
13	Harsh	NULL	1	Harsh
14	Mohit	15	3	Harsh -> Mohit
15	Ritvik	14	3	Harsh -> Mohit -> Ritvik
18	Ayush	15	4	Harsh -> Mohit -> Ritvik -> Ayush
17	Kunal	16	5	Harsh -> Mohit -> Ritvik -> Ayush -> Kunal
18	Varun	17	6	Harsh -> Mohit -> Ritvik -> Ayush -> Kunal -> Varun
1	Ishaan	NULL	1	Ishaan
2	Reyansh	1	2	Ishaan -> Reyansh
3	Adit	2	3	Ishaan -> Reyansh -> Adit
4	Aarush	3	4	Ishaan -> Reyansh -> Adit -> Aarush
5	Raghav	4	5	Ishaan -> Reyansh -> Adit -> Aarush -> Raghav
6	Vihaan	5	6	Ishaan -> Reyansh -> Adit -> Aarush -> Raghav -> Vihaan
19	Mehak	NULL	1	Mehak
20	Pihu	19	2	Mehak -> Pihu
21	Shreya	20	3	Mehak -> Pihu -> Shreya
22	Tara	21	4	Mehak -> Pihu -> Shreya -> Tara
23	Mahi	22	5	Mehak -> Pihu -> Shreya -> Tara -> Mahi
24	Anvi	23	6	Mehak -> Pihu -> Shreya -> Tara -> Mahi -> Anvi
25	Rajat	NULL	1	Rajat
26	Yuvraj	25	2	Rajat -> Yuvraj
27	Arnav	26	3	Rajat -> Yuvraj -> Arnav
29	Laksh	27	4	Rajat -> Yuvraj -> Arnav -> Laksh
29	Devansh	28	5	Rajat -> Yuvraj -> Arnav -> Laksh -> Devansh
30	Om	29	6	Rajat -> Yuvraj -> Arnav -> Laksh -> Devansh -> Om

RESULT

Views were created for department salary summaries and employee hierarchy. View update behavior was tested, and a recursive CTE was used successfully to display reporting chains.

CONCLUSION

SQL views provide reusable logical representations of data, while recursive CTEs can traverse self-referencing employee relationships to display hierarchical reporting structures.