AUTONOMOUS ML RESEARCH AGENT (AMRA)

Comprehensive Technical Architecture, System Design & Production Brief

Document Version:	3.0.0 (Staff-Certified)	**Date:**	November 2026
Author / Engineering:	AI Systems Architecture & DevSecOps	**Status:**	Production Ready / Passing Benchmarks
Operating Cost:	**$0.00 / month** (100% Free Quotas)	**Core Frameworks:**	Next.js 15, FastAPI, FastMCP, Pandas

[4-TIER ARCHITECTURE]	**[MULTI-SOURCE DISCOVERY]**	**[HITL SECURITY GATING]**	**[SPLIT-FIRST PIPELINE]**	**[BR-01 to BR-06]**

Executive Overview:

The **Autonomous ML Research Agent (AMRA)** is an enterprise-grade AI workspace engineered to eliminate manual toil in early-stage machine learning workflows. Traditional exploratory research requires hours of fragmented tab-switching across academic preprint repositories, dataset hubs, and local Jupyter environments. AMRA unifies these disparate phases by leveraging the open **Model Context Protocol (MCP)** to decouple high-level cognitive reasoning from local sandboxed execution.

Researchers input high-level hypotheses; AMRA concurrently explores 250M+ scholarly works across **arXiv** and **OpenAlex** with verified citation metrics and open-access PDFs, sources quality-vetted datasets across **Kaggle** and **Hugging Face Hub**, and safely executes an autonomous tabular cleaning, outlier profiling, and **LightGBM baseline modeling pipeline**—all governed by single-use cryptographic **Human-in-the-Loop (HITL)** security tokens and operating at **$0.00/month**.

Document Architecture & Table of Contents:

Section 1: Problem Statement & Modern ML Friction	**Section 7:** Algorithmic Data Health Scoring (0-100)
Section 2: Four-Tier Decoupled Architecture	**Section 8:** Automated LightGBM Baseline Benchmarks
Section 3: Multi-Source Academic & Dataset Discovery	**Section 9:** Defense-in-Depth Security Architecture
Section 4: Real-time SSE Streaming Protocol	**Section 10:** Sustainable Zero-Cost Operating Model
Section 5: Cryptographic HITL Security Gate	**Section 11:** Production Benchmark Compliance (BR-01 to 06)
Section 6: Split-First Data Cleaning Pipeline v3.0	**Section 12:** Complete API & Schema Reference

1. Problem Statement: Friction in Modern ML Prototyping

Modern machine learning practitioners and researchers spend upwards of **70% of exploratory project time** on repetitive, non-cognitive tasks that impede scientific discovery:

1. Literature Fragmentation & Citation Hallucination: Researchers oscillate between Google Scholar, arXiv, and publisher paywalls. Standard commercial LLMs frequently hallucinate plausible-sounding paper titles, fictitious author lists, and synthetic DOIs that waste researcher time.

2. Dataset Quality & Discovery Bottlenecks: Sifting through thousands of stale or poorly formatted repositories on Kaggle or Hugging Face. Downloading multi-gigabyte files that crash local machines or lack proper target feature documentation.

3. Repetitive Preprocessing & Critical Data Leakage: Writing 30+ minutes of manual Pandas boilerplate for every dataset (imputation, string stripping, duplicate removal, outlier handling). More dangerously, executing imputation or scaling across the entire dataset *prior* to train/test partitioning introduces subtle data leakage from test into train sets, invalidating scientific claims.

4. Unsustainable API Costs: Existing research assistants depend exclusively on paid commercial APIs (such as Claude 3.5 Sonnet or GPT-4o), incurring $20 to $50/month in exploratory research costs, making them inaccessible to students and resource-constrained labs.

2. Four-Tier Decoupled Architecture

AMRA decouples cognitive reasoning from direct local operating system execution via the **Model Context Protocol (MCP)**. The system is organized into four strictly segregated tiers:

• **Tier 1 (Presentation):** Next.js 15 App Router, React 19, TypeScript, Tailwind CSS with Neo-Brutalist design language. Consumes real-time SSE streams and dynamically renders PaperCards, DatasetCards, ApprovalPrompts, and interactive DataPreviewTables.

• **Tier 2 (Agentic Middleware Gateway):** FastAPI (Python 3.11+), Pydantic v2 event contracts, constant-time Bearer authentication, and SQLite WAL-mode session memory (chat_history.db). Houses the provider-agnostic LLM factory.

• **Tier 3 (Execution Layer - FastMCP):** Exposes strictly typed Python tool interfaces. Manages academic preprints (arXiv), scholarly graph metrics (OpenAlex), dataset discovery (Kaggle, Hugging Face Hub), SQLite TTL query caching, and the Pandas data cleaner.

• **Tier 4 (Data Lake & Storage):** Isolated local directories (/data/raw/ for raw ingestion, /processed_data/ for clean CSV and Snappy Parquet partitions, /data/cache/, /data/sessions/).




Figure 1: AMRA Four-Tier Decoupled Architecture and Communication Boundaries.

3. Multi-Source Academic & Dataset Discovery Pipeline

To guarantee **zero hallucination** and comprehensive recall, AMRA executes parallel multi-source discovery across verified scientific and machine learning repositories:

- **Domain Acronym Query Expansion:** Incoming conversational queries undergo stopword stripping and domain expansion (e.g., 'SOTA GNN for fraud' expands to 'state of the art graph neural network models for fraud detection'), maximizing recall across academic search engines.
- **Dual Academic Literature Pipeline:** Concurrently queries the official arXiv export API and OpenAlex (indexing 250M+ scholarly works). Normalizes paper titles, deduplicates cross-listed preprints, filters for open-access accepted PDFs, and sorts literature strictly by verified peer-reviewed citation counts (cited_by_count).
- **Dual Dataset Discovery Pipeline:** Searches Kaggle public benchmarks and Hugging Face Hub (150K+ ML datasets). Automatically filters out repositories with Usability Scores below 0.70 or uncompressed sizes exceeding 250 MB.
- **Sub-Millisecond SQLite TTL Caching:** Search queries are cryptographically hashed and cached in SQLite with a 24-hour TTL, delivering hot cache hits in **<0.15 ms**.




Figure 2: Multi-Source Literature and Dataset Discovery Flow with SQLite TTL Caching.

4. Real-Time Server-Sent Events (SSE) Protocol

Communication between the Next.js frontend and FastAPI backend is governed by a strict Server-Sent Events (SSE) streaming protocol (POST /api/chat/stream and POST /api/chat/approve). All streamed blocks conform 100% to Pydantic v2 event models:

Event Type	Payload Fields	UI & Operational Behavior
`thought`	`content: str`	Renders live agent reasoning disclosure box
`tool_start`	`tool: str, args: dict`	Signals tool dispatch (arXiv, OpenAlex, Kaggle, Pipeline)
`tool_result`	`tool: str, result: any`	Delivers verified paper/dataset records for card rendering
`hitl_required`	`dataset_id, approval_token, recipe`	Halts pipeline; renders interactive ApprovalPrompt card
`text_delta`	`content: str`	Real-time streaming synthesized explanation chunks
`cost_audit`	`provider, model, tokens, cost_usd`	Verifies $0.00 free-tier resource consumption

`complete`	`session_id: str`	Finalizes conversation turn and updates SQLite memory

5. Cryptographic Human-in-the-Loop (HITL) Security Gate

AMRA strictly enforces a **Human-in-the-Loop (HITL) authorization boundary**. The agent cannot download raw data, modify the local file system, or execute data cleaning pipelines autonomously without explicit user verification:

- **Cryptographic Single-Use Tokens:** Tokens are 32-character hex UUIDs (hitl_tok_...) bound strictly to the user's active session_id with an automated **10-minute TTL**.
- **Anti-Replay Invalidation:** Once an approval token is consumed or rejected, it is immediately purged from memory. Replayed requests receive HTTP 400 errors.
- **Explicit Rejection Handling:** If a user clicks Reject (action: 'reject'), the pipeline is cancelled, the token is destroyed, and the local file system remains completely untouched.




Figure 3: Cryptographic HITL Token Gating and Single-Use Lifecycle.

6. Split-First Tabular Data Cleaning Engine (v3.0)

AMRA features a staff-level Pandas preprocessing engine engineered to solve the chronic problem of **Data Leakage** in automated ML pipelines. Traditional AutoML tools compute statistical metrics across the full dataset before partitioning, contaminating the test evaluation. AMRA enforces a strict **Split-First Architecture**:

1. **Dynamic Character Encoding Fallback:** Automatically cycles through UTF-8, Latin-1, CP1252, and ISO-8859-1 encodings, eliminating parsing crashes.
2. **Header Normalization:** Converts inconsistent column headers into clean, uniform snake_case with collision resolution.
3. **Split-First 80/20 Partitioning:** Partitions the dataset into 80% train and 20% test sets *before* calculating statistical imputations or scaling, ensuring 100% mathematical zero-leakage.
4. **Imputation Strategy:** Median imputation for numeric continuous distributions; mode imputation for categorical columns.
5. **IQR Outlier Winsorization:** Computes Interquartile Range fences [Q1 - 1.5 IQR, Q3 + 1.5 IQR] and smoothly caps extreme values without deleting critical anomaly instances.
6. **LightGBM Baseline Benchmark:** Heuristically detects the target prediction column and trains an automated baseline model reporting Accuracy, ROC-AUC, and Top Feature Importances.
7. **Dual Parquet & CSV Export:** Generates cleaned CSV alongside high-compression Snappy Parquet files (full, train partition, test partition).




Figure 4: Split-First Tabular Data Cleaning and Baseline ML Modeling Flow.

7. Algorithmic Data Health Scoring (0.0 to 100.0)

AMRA evaluates data quality through a deterministic, mathematically bounded **Data Health Score**. It resolves the *'Anomaly Outlier Paradox'*: in fraud, network intrusion, and anomaly detection domains, outliers are primary signal rather than defects, and must not penalize the dataset score.

Data Health Score Formula:
Health Score = max(0.0, min(100.0, 100.0 - (Null_Penalty + Duplicate_Penalty + Outlier_Penalty)))
• **Null Penalty:** min(40.0, (null_count / total_cells) * 100 * 1.5)
• **Duplicate Penalty:** min(30.0, (duplicate_rows / total_rows) * 100 * 2.0)
• **Outlier Penalty:** 0.0 for anomaly domains; min(20.0, (outliers / total_numeric) * 100 * 0.5) otherwise.

8. Enterprise Security Architecture & Defense-in-Depth

AMRA implements a multi-layered security model adhering to strict DevSecOps and sandboxing standards:

- **Authentication & Timing Defense:** All data and chat endpoints are protected via verify_api_key supporting Bearer tokens and X-API-Key headers. Token matching uses constant-time comparisons (secrets.compare_digest) to eliminate timing attack vectors.
- **Path Traversal Fuzzing Defense:** File paths are strictly resolved via Path.resolve() and verified against parent boundaries. Disallowed extensions (.py, .sh, .env, .exe) and directory escape characters (.., %2e%2e) are blocked.
- **Chunked Streaming Upload Guard (DoS Defense):** Uploads stream in 1 MB chunks with an active byte counter enforcing a hard 250 MB ceiling. Exceeding streams are truncated immediately, preventing Out-Of-Memory (OOM) crashes.
- **CSV / Formula Injection Sanitization:** Exported CSV cells starting with =, +, -, @, or tabs are prepended with an apostrophe ('), preventing Dynamic Data Exchange (DDE) command execution in Excel.
- **Secret Masking & Network Hardening:** Google Gemini API keys are transmitted via the official x-goog-api-key header instead of URL query parameters, preventing leakages in proxy logs. CORS is restricted to localhost.




Figure 5: Defense-in-Depth Multi-Layered Security Architecture.

9. Sustainable Zero-Cost Operating Model ($0.00 / month)

Unlike commercial research assistants that require expensive proprietary tokens, AMRA is engineered to operate with **zero mandatory recurring cost** across three interchangeable providers:

Provider	Target Model	Throughput / Context	Cost & Quota Tier
Google Gemini	Gemini 2.5 / 3.8 Flash	1,000,000+ tokens Sub-1.5s TTFT	**$0.00** (15 RPM, 1M TPM, 1,500 req/day via Google AI Studio)
Groq Cloud	Llama 3.3 70B Versatile	280–350 tokens/sec Ultra-low latency	**$0.00** (Free developer tier via Groq Console)
Local Ollama	Qwen 2.5 14B / Llama 3.1	Local hardware 100% air-gapped	**$0.00** (Zero network egress, private local inference)

Deterministic Mock	MockLLMAdapter	Instant (<1ms) CI/CD verification	**$0.00** (Zero API keys required for testing)

10. Production Benchmark Compliance (BR-01 through BR-06)

AMRA enforces six global production benchmark rules tested across four comprehensive test suites:

Rule	Benchmark Name	Standard Target Metric	Measured Result	Status
BR-01	Schema Contracts	100% Pydantic v2 validation	100% valid typing across all APIs	**PASSED**
BR-02	Edge Resilience	Zero unhandled crashes on dirty data	Catches corrupt CSVs, invalid tokens	**PASSED**
BR-03	Zero Hallucination	100% verified arXiv & OpenAlex URLs	All PDFs match canonical endpoints	**PASSED**
BR-04	Latency SLA	Cache hits < 15ms; Cleaning < 500ms	**0.10 ms** cache; **180 ms** cleaning	**PASSED**
BR-05	Path Sandboxing	0 command injections; 0 traversals	Storage strictly bounded in sandboxes	**PASSED**
BR-06	Health Score Math	Deterministic [0.0, 100.0] bounds	Verified score delta post-clean	**PASSED**
SEC-01	Auth Gating	Bearer token / X-API-Key required	Unauthenticated blocked with HTTP 401	**PASSED**
SEC-02	HITL Cancellation	10-min TTL & user rejection handling	Zero disk writes on rejection	**PASSED**

Production Benchmark Rules (BR-01 to BR-06) Verification




Figure 6: Production Benchmark Certification (BR-01 through BR-06).

11. Complete API Endpoint & Schema Reference

Endpoint	Method	Auth	Description & Request Payload
`/api/health`	GET	Public	Health check & active LLM provider configuration status
`/api/chat/stream`	POST	Bearer	Initiates multi-turn SSE agent reasoning ({message, session_id, provider})

`/api/chat/approve`	POST	Bearer	Authorizes or cancels dataset cleaning ({approval_token, session_id, action})
`/api/chat/sessions`	GET	Bearer	Lists conversation threads with message counts and timestamps
`/api/chat/history/{id}`	GET	Bearer	Retrieves chronological messages and tool outputs for a session
`/api/data/processed`	GET	Bearer	Lists all cleaned CSV and Parquet files ready for modeling
`/api/data/upload`	POST	Bearer	Multipart chunked upload for custom CSV datasets (<250 MB ceiling)
`/api/data/download/{f}`	GET	Bearer/Key	Downloads cleaned CSV or Snappy Parquet partition

12. Developer Quickstart & Benchmark Verification

```
# 1. Clone & Install Dependencies pip install -r backend/requirements.txt -r mcp_server/requirements.txt cd frontend && npm install && cd .. # 2. Run All 4 Production Benchmark Suites python tests/test_multi_source.py # arXiv, OpenAlex, Kaggle, HF Hub python tests/test_phase1_production.py # FastMCP Tool Rules BR-01 to BR-06 python tests/test_phase2_backend.py # FastAPI SSE Streaming & Auth Guard python tests/test_phase4_security_devops.py # Path Traversal Fuzzing, HITL Rejection # 3. Start Backend & Frontend Servers python -m uvicorn backend.app.main:app --host 127.0.0.1 --port 8000 cd frontend && npm run dev # http://localhost:3000
```