

Learning Lab: Internet of Things (IoT)

2025/26 winter semester | module |

Assignment 02: Connect with the Internet - BayernWLAN

Objectives

- In this assignment we start the wireless connection

Required Equipment

- Installed and running Raspberry Pi with OS
- Monitor with HDMI cable
- Keyboard
- Mouse

Solutions Steps

Step 1: Run the CLI/ Terminal

Step 2: Connect to WLAN

First we activate a wireless connection via terminal.

To scan for WiFi networks, use the command `sudo iwlist wlan0 scan`. This will list all available WiFi networks, along with other information. Locate the name of your Wi-Fi network in the list; this will be listed next to ESSID `ESSID: "@BayernWLAN"` is the name of the BayernWLAN WiFi network. `IE: IEEE 802.11i/WPA2 Version 1` (or similar) is for the authentication. You will need a password for this kind of networks. But, for the BayernWLAN you don't need a password.

Now you need to add your WiFi settings to the wpa-supPLICANT configuration file. Type the following in the command line to the configuration file: `sudo nano /etc/wpa_supplicant/wpa_supplicant.conf`. Go to the bottom of the file and add the following WiFi setting, adding your setting in the quotation marks.

```
network={
    ssid="@BayernWLAN"
    key_mgmt=NONE
}
```

Save the changes. At this point, the wpa-supPLICANT configuration file will normally notice within a few seconds when a change has occurred and it will try to connect to the WiFi network. If the WiFi does not connect then a reboot maybe required with `sudo reboot`. Once your WiFi has connected successfully you can verify it by typing `ifconfig wlan0`; if the `inet addr` field has an IP address in it then it has successfully connected.

3. Step 3: Click accept rules

Try to use a web browser to connect with the Internet. It will search and search and search. What

happened: you have to accept the rules of BayernWLAN.

Follow the link

`hotspot.vodafone.de/bayern`


and accept the regulations. Perhaps you have to accept "unsecure".

Step 4: Find your Network Address

To find your own network address you can just run the following command in the Terminal:

```
ifconfig
```

this will give you a picture like this [1]:



```
pi@raspberrypi:~ $ ifconfig -a
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
    inet 169.254.249.43  netmask 255.255.0.0  broadcast 169.254.255.255
    inet6 fe80::c6bc:4829:83eb:721e  prefixlen 64  scopeid 0x20<link>
    ether dc:a6:32:f3:73:44  txqueuelen 1000  (Ethernet)
    RX packets 43100  bytes 11875485 (11.3 MiB)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 110590  bytes 27370750 (26.1 MiB)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
    inet 127.0.0.1  netmask 255.0.0.0
    inet6 ::1  prefixlen 128  scopeid 0x10<host>
    loop txqueuelen 1000  (Local Loopback)
    RX packets 276509  bytes 57907920 (55.2 MiB)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 276509  bytes 57907920 (55.2 MiB)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

wlan0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
    inet 192.168.18.218  netmask 255.255.255.0  broadcast 192.168.18.255
    inet6 fe80::ea4b:287c:1360:a73e  prefixlen 64  scopeid 0x20<link>
    ether dc:a6:32:f3:73:46  txqueuelen 1000  (Ethernet)
    RX packets 280542  bytes 241838424 (230.6 MiB)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 214786  bytes 53890403 (51.3 MiB)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

pi@raspberrypi:~ $
```

The lines where your IP stands is in the wlan0 section. inet: **192.168.18.218** is your IP address for *wifi connection*. This is a unique address in your network only one device can have this address.

ether **dc:a6:32:f3:73:46** is your MAC address. This is a unique address for your device. Only your device has this unique address and there is no other device in the world who has the same address.

These two numbers are closely related to each other. The IP address may change over time or every time you reconnect to the network you get an other ip address but your mac stays forever usually.

Further Input

Hints

Useful Resources for Own Searches

Source of this assignment: <https://www.raspberrypi.org/>

Retrospective

Please answer the following questions

1. What is the difference between MAC and IP?
2. Do you find an easier way to configure your WiFi access?

and document each answer.

Source(s)

[1] <https://linuxhint.com/get-mac-address-raspberry-pi/>