Semiconductor Optoelectronics
ISSN: 1001-5868

AI-ENHANCED SEMICONDUCTOR MANUFACTURING FOR OPTOELECTRONIC ADVANCEMENTS.

Dr. Sharath Kumar.D.R.V.A
Associate Professor, Maturi Venkata Subba Rao (MVSR) Engineering College
drvask_ece@mvsrec.edu.in

Dr.B.Ramesh
Associate Professor, Department of Electronics and Communication, Annapoorana Engineering College, Salem,**mailrameshece@gmail.com**

Dr. V.J. Priyadharshini
Professor Department of Physics, Mailam Engineering College, Mailam
priuakris@gmail.com

Mohammad Taj
Associate professor, Aditya Engineering College, Surampalem, Andhra Pradesh
mdtaj405@gmail.com

Elangovan Muniyandy
Department of Biosciences, Saveetha School of Engineering, Saveetha Institute of Medical and Technical Sciences,Chennai,**muniyandy.e@gmail.com**

Soumya S S
Department of Physics, University College, Thiruvananthapuram, Kerala, India
soumyadevanss@gmail.com

Dr. P.Veeramanikandan
Associate Professor, EEE Department, Jaya Engineering College, Chennai
veerarmd@gmail.com

Abstract:
Semiconductor production drives electronics and optoelectronic device advances. With the requirement for accuracy and efficiency in semiconductor manufacture, AI integration has become revolutionary. LEDs, photovoltaics, and optical sensors need advanced production techniques to achieve performance and quality criteria. AI-enhanced semiconductor production may improve productivity, output, and quality. AI optimizes process parameters, discovers abnormalities, and boosts production efficiency using machine learning, predictive analytics, and sophisticated control systems. This article discusses AI-enhanced semiconductor production for optoelectronic breakthroughs, including current advances, major applications,

and future possibilities.
Keywords: Semiconductor Manufacturing, AI, Optoelectronic Devices, Process Optimization, Quality control.

I. INTRODUCTION:

Technological advancements in electronics and telecommunications are driven by semiconductor fabrication. Precision, efficiency, and dependability in semiconductor production are needed as optoelectronic devices like LEDs, photovoltaics, and optical sensors proliferate. AI-integrated semiconductor manufacturing is a potential way to improve optoelectronic device productivity, yield, and quality in response to these difficulties. Machine learning algorithms, predictive analytics, and sophisticated control systems optimise process parameters, discover errors, and simplify production processes in AI-enhanced semiconductor manufacturing. This multidisciplinary strategy uses semiconductor engineering, data science, and AI research to solve complicated production problems and speed optoelectronic technology development. This article discusses AI-enhanced semiconductor manufacturing for optoelectronic breakthroughs, including recent advances, major applications, and future prospects in this rapidly growing sector.

II.Literature Review:

New paradigms that significantly depend on industrial data have been brought forward by the fourth industrial revolution, highlighting the crucial role that data plays in advancing technological developments. Artificial Intelligence (AI) has become essential in smart manufacturing, where data is the primary resource used to extract information. Process parameter optimization, error detection, and production process streamlining are made possible by machine learning algorithms, predictive analytics, and advanced control systems. However, users may find it difficult to trust and accept intelligent information retrieval (IR) algorithms due to their opaque nature, especially in important fields where it is essential to comprehend the logic behind predictions. In response, the domain of explicable AI (XAI) has gained attention as a means of explaining the reasoning behind algorithmic choices. Our suggested methodology aims to bridge the gap between intricate algorithms and user understanding by producing clever IR system overviews. We aim to improve interpretability and transferability across domains by incorporating domain-specific criteria into the IR process via the use of knowledge graphs as a single, cohesive framework for knowledge representation. Our goal is to investigate important research topics related to transferability of IR methods without compromising performance, and domain-specific explanations. One of our contributions is the creationof a thorough framework that allows domain needs to be seamlessly integrated into intelligent information retrieval (IR) systems, allowing algorithms to be domain-specific while being transferable across many domains. Through case studies in job recommendation and semiconductor production, we verify our technique and show high user acceptability and IR accuracy across several domains. The suggested framework is presented, assessment procedures are described, and relevant literature is reviewed. The study ends with suggestions for further research and development.

A.Related Work:

Explaining clever algorithms has garnered increased attention, particularly with the widespread adoption of deep learning algorithms, which are often considered black boxes due to their opaque internal mechanisms. Approaches to explaining AI algorithms can be broadly categorized into knowledge- and data-driven techniques. Data-driven approaches utilize information from data and intelligent model to generate interpretable explanations, whereas domain-aware algorithms use explicit or implicit knowledge to enhance explanations. Recent literature has seen a shift towards developing model-agnostic explanation algorithms, capable of explaining predictions independently of the underlying model's internal workings. Knowledge graphs (KGs) have emerged as a key knowledge modeling method for generating knowledge-aware explanations. KGs represent entities as graph nodes and their relationships as relations, facilitating the contextualization of information and supporting complex reasoning. However, while model-agnostic solutions offer flexibility across different intelligent models, they still need to account for domain-specific requirements. Domain-specific approaches tailor explanations to specific domains, incorporating expert knowledge and considering domain-specific databases. Bringing domain-agnostic and domain-specific together approaches is crucial for developing transferable explainable systems. Our proposed framework leverages KGs as A unified knowledge representation structure integrating domain requirements and facilitating domain-specific, explainable, transportable algorithms across multiple domains. By embedding domain requirements in the knowledge graph, our framework ensures that explanations are tailored to the specific needs of each domain while maintaining transferability. Unlike existing approaches, our framework captures domain requirements from various sources, including databases, expert knowledge, and exploratory data analysis, enabling comprehensive domain modeling. Moreover, our approach facilitates employing identical sophisticated models across different domains by training them to query the knowledge graph rather than domain-specific data sources directly. The literature on Our framework is a component of dependent on graphs, explicable Systems for intelligent information retrieval and recommendation, is summarized in Table 1.

			Solution Feature		**Solution Outcome**		
Referen ce	**Ye ar**	**Model-Agnost ic/ Intrins ic**	**Recomm end ation Approac h.**	**Explainab ility Approach**	**Retrie val Task.**	**Domain Requirem ent based on**	**Transfera ble with Respect to Domain Requirem ents**
Chen and Miyazak i	202 0	Agnost ic model	Intelligent and conventio nal recomme ndat ion systems in place	A translator generates a textual explication subsequent to the	Graph trajecto ry retriev al	Absence of domain-spec .	Yes

				ranking of graph trajectories .			
Moon et al.	201 9	Agnost ic model	Entity recommenda t ions graph-walker-based	Explanatio ns are predicated on the graph walker-generated trajectories .	Graph path retriev al	The database.	Yes
Song et al.	201 9	The model is intrinsi c.	By utilizing the Markov decision process	Generation via user-to-item path utilization explanatio ns	Retriev-ement of graph paths in a user-item-entity graph	Not domain-Specific	No
Wang et al.	201 9	The model is intrinsi c.	Intelligent model for path semantics and suggestions	Pooling algorithm for determinin g the significanc e of path strength in the prediction	Graph path retriev al	Not domain-Specific	No
Xie et al.	202 1	The model is intrinsi	KG-based user-item recommenda t ion with	K-dependent and multi-objective	Graph path retriev al	Not domain-Specific	No

		c.	ratings	optimizatio n-based explanatio n			
Our Framew ork	202 1	Agnost ic model .	Graph path recomme ndat ion	Graph based	Node retriev al, Graph path retriev al	Database, Expert Rules, Explicit requireme nts	yes

Table 1 Comparison between Different Explainability Approach.

B. IR: Explainable, Graph-Based, Transferable, Domain-Oriented -

Our system relies heavily on domain-agnostic components to overcome the difficulties in describing intelligent information retrieval (IR) techniques while taking domain needs into account. Our method, which is shown in Fig1, in which White represents domain-specific components, while blue denotes domain-agnostic algorithms, combines domain-specific and domain-agnostic elements to provide a transferable framework that can accomplish this goal. Domain-specific elements include data particular to the domain, prerequisites, and any regulations established by domain specialists. On the other hand, domain-neutral elements have two purposes in the framework:



Fig1 - Suggested knowledge graph-based Transferable domain-oriented Explainable IR framework.

In our architecture, domain-agnostic components are essential because they serve as a bridge between domain-specific elements and the knowledge graph, allowing for a transferable graph generation procedure that may applied to several domains. Moreover, these constituents are accountable for producing elucidations and obtaining data predicated on the configuration of the knowledge graph. These domain-agnostic elements guarantee that the framework is flexible enough to be applied to many domains without compromising its interpretability by incorporating intelligence of the information strategies for retrieval while maintaining their explainability. The strong knowledge graph connection functions as an open-box knowledge representation by nature, allows for this flexibility. As a result, the all-encompassing architecture, which combines domain-specific and domain-independent components linked by the knowledge graph, demonstrates exceptional adaptability to meet the various requirements of many domains. Additionally, it makes it easier to adjust to different artificial intelligence (AI) The algorithms utilized in the retrieval of information job ever since these algorithms make use of the knowledge graph's data. Our methodology is centred on the knowledge graph represents, which functions as an individual supplier of information drawn from databases, subject matter experts, and pre-established specifications. Different information sources are combined into a single query able structuring knowledge by specifying nodes and relationships within the knowledge graph. Once built, the knowledge graph functions as an extensive knowledge base, providing explainability and IR algorithms with all the information they need to provide results that are comprehensible and meaningful to users. Notably, the explanation format—textual, graphic, etc.—can be customized to match the user's unique needs. The many parts of the framework are covered in further depth in the sections that follow.

a)Building a Knowledge Graph-

We use data sources and principles defined by experts are utilized to establish the connections and entities within the knowledge graph. Each pillar influences graph node type, content, and attributes:

Information Sources The first pillar includes databases, textual documents, reports, and other structured and unstructured data sources. The kinds of information taken from various sources create knowledge network nodes. Nodes may represent goods, processes, materials, equipment, or other domain ideas. These nodes' qualities come from data, such as product specs, process parameters, or equipment specs.

Expert-Defined Rules: Domain experts create rules, restrictions, or recommendations for knowledge graph node connections in the second pillar. These rules generate meaningful connections between nodes and encapsulate domain-specific semantics and dependencies in the network. Experts may determine that certain materials are compatible with certain procedures or that certain parameters must be satisfied for a certain operation. These principles control node interaction and give context for graph interpretati

The knowledge graph may represent various process or domain dimensions by merging information sources with expert-defined rules. Nodes in the graph represent relevant entities

and ideas, while relations represent their domain knowledge and data-driven interdependence. This complete representation supports decision-making, planning, and optimization in complex processes and domains by organizing, retrieving, and analysing information inside the framework.

III.METHODOLOGY-

1.Definition of Graph Nodes-

We classify knowledge network nodes by the domain items and ideas they represent. Each node type contains domain-specific information and builds the graph structure. Some popular knowledge graph node types are:
Some domain products are represented by product nodes. They may contain product specs, features, qualities, and identifiers. Product nodes record domain-manufactured or utilized product attributes.

Process Nodes: Process nodes include domain processes like manufacturing, assembly, and workflo They list process parameters, inputs, outputs, and dependen

Material Nodes Raw materials, components, and substances used in domain processes and products are material nodes. They may include material composition, qualities, suppliers, and use limits.

Nodes for equipment, machinery, tools, and facilities used in domain activities. They record equipment specs, capabilities, maintenance, and use directions.

Nodes: Entity nodes include domain-relevant entities and ideas that do not fit the above categories. They may represent suppliers, customers, legislation, standards, or other domain-specific entities.

Each node type has characteristics and properties that specify its domain entity or notion. These qualities are obtained from domain knowledge, data sources, and expert input, ensuring that nodes include complete information for knowledge graph analysis, retrieval, and use. The knowledge graph organises and interprets domain elements and interactions by categorising nodes by type.
Industrial data comes from many data sources that reflect distinct processes or environmental components. Our methodology lets many information sources create knowledge graph node types. Every node type denotes a different origin of the data, making Particular domain-specific data representation and integration inside a knowledge structure easier. By collecting domain experts' ideas and experience, expert-defined rules shape the knowledge graph. Knowledge extraction is formalized by these principles, which control node types, content, and graph interactions. Expert-defined rules, structured as "IF…THEN…" statements, integrate domain knowledge into graph building. The domain's needs and limitations determine whether these rules use forward-chaining or backward-chaining reasoning. Interviews, questionnaires, and formal reports may extract domain expert information. However, our methodology stresses the value of domain expert interviews for immediately turning their ideas into system rules. Backward chaining inference then determines the network node types and content needed to in

some way represent varied information sources. Fig 2 shows the systematic integration of domain expertise into knowledge graph development by showing a rule defined by an expert and its application to build graph nodes. Thus, the methodology assures that the knowledge graph appropriately represents domain-specific information while using domain experts' insights to shape its structure and content.



Fig 2- An instance of domain requirements and expert-defined norms being integrated during the generation of vertices and relations in a graph.

1.2 Extracting Graph Relations -

Rules edfined by experts, data sources, and Domain specifications are used to construct graph connections in our system. Domain requirements express domain-specific demands not represented in information sources or as defined by experts' norms. These criteria include domain-specific terms and consequences. Exploratory data analysis (EDA) uncovers and formalizes domain-specific needs for graph generation, information retrieval, and explanation.

Domain requirements are used in relation extraction and information retrieval as lists, dictionaries, or statements. Information retrieval (IR) algorithm developers manually include these needs into graph queries. A specialized relation extraction (RE) technique uses node types and content to find relations. After calculating textual similarities between document nodes, relations are generated if scores surpass a threshold. Expert-defined rules may connect document nodes based on header strings.

Domain-specific knowledge sources, defined by experts' criteria such as domain needs influence the relation extraction method. The algorithm is domain-agnostic, but developers may choose from state-of-the-art approaches to apply it across many domains and meet their needs.

2.2 Graph-based info retrieval -

Our framework's information retrieval component is domain-agnostic, allowing reuse across domains without compromising domain-specific properties. Nodes and relations in the knowledge graph give domain-specific information. Information retrieval algorithms are influenced by domain requirements, which may affect graph queries. The explainability algorithm generates explanations for each outcome predicted by the knowledge network nodes and relations that match user queries.

2.3 Explainability via Graph-

The explainability algorithm queries the knowledge network independently to produce IR or recommendation algorithm explanations, irrespective of compartment type. The technique scores nodes to find the best explanation for returned results using the shortest route from a query node to related result nodes in the knowledge graph. To simplify explanations, NLP patterns and knowledge graph visualizations are used. The knowledge graph (KG) structure makes explanations easier to grasp and analyze, improving the information that is retrieved.

Verbal Explanation The application of natural language processing (NLP) convert data from the graph into phrases that can be understood by humans. The program rearranges the data to make it more comprehensible by iteratively exploring pertinent nodes via relations. **Visual Explanation:** By displaying node relationships, clusters, and relevancies, the knowledge graph's graphical representation offers visual explanations. Users may better understand the material by highlighting distinct components of it with the use of visual characteristics like color and size. The combination of visual and spoken explanations makes it easier for users to understand the information they have obtained. The creation of both spoken and visual explanations by the KG is shown in Fig 3, which also shows how these explanations aid in user comprehension. The IR method extracts results from the graph and displays them as a sub-graph to demonstrate their relationships. The logic behind joining graph nodes generates textual explanations.



Fig 3 - Knowledge graph-based visual and textual explanations

IV. RESULT-

The particular outcome of "AI-Enhanced Semiconductor Manufacturing for Optoelectronic Advancements" will differ based on the goals, approaches, and ways in which AI technologies are integrated into semiconductor manufacturing procedures. However, the following are some possible outcomes and advantages of using this strategy: Artificial intelligence (AI) algorithms

may improve a number of semiconductor manufacturing process elements, including resource allocation, equipment uses, and production scheduling, which can result in lower production costs and more efficiency. AI-driven QCS systems are able to identify irregularities and flaws in real time, guaranteeing improved product quality and lowering the possibility of defective goods being released into the market. Artificial intelligence (AI) algorithm can analyze vast amounts of industrial data to find patterns and connections that affect yield rates. This helps manufacturers optimize their operations and raise total yield. The Below Fig (4), Explains the success rate of semiconductor Industry Leads in AI Adaptation.



Fig 4, Semiconductor Industry Leads in AI Adoptation.

By planning maintenance tasks in advance, AI-based predictive maintenance systems may minimize downtime and save maintenance costs by foreseeing equipment breakdowns before they happen. Innovation in optoelectronics is accelerated by AI technologies, which make it possible to prototype, simulate, and test novel semiconductor designs and materials more quickly. AI-enhanced semiconductor production may save businesses a lot of money via waste reduction, better resource management, and process optimization. Overall, by enhancing productivity, quality, yield rates, maintenance procedures, capacity for innovation, and cost-effectiveness, the incorporation of AI technologies into semiconductor manufacturing processes for optoelectronic breakthroughs has the potential to completely transform the sector.

V. CONCLUSION -

In conclusion, optoelectronic technologies may be greatly advanced by incorporating AI into semiconductor production processes. Manufacturers can maintain their competitiveness in a market that is changing quickly by using AI algorithms for process optimization, quality control, cost reduction, and innovation acceleration. They can also produce state-of-the-art optoelectronic devices to fulfil the increasing expectations of both customers and industries.

VI. REFERENCE -

1. Zenkert, J., Weber, C., Dornhöfer, M., Abu-Rasheed, H., & Fathi, M. (2021). Knowledge integration in smart factories. Encyclopedia, 1(3), 792-811.

2.Li, X. H., Cao, C. C., Shi, Y., Bai, W., Gao, H., Qiu, L., ... & Chen, L. (2020). A survey of data-driven and knowledge-aware explainable ai. IEEE Transactions on Knowledge and Data Engineering, 34(1), 29-49.

3. Samek, W., Montavon, G., Vedaldi, A., Hansen, L. K., & Müller, K. R. (Eds.). (2019). Explainable AI: interpreting, explaining and visualizing deep learning (Vol. 11700). Springer Nature.

4. **Frakes, W. B., & Baeza-Yates, R. (Eds.). (1992). Information retrieval: data srtuctures and** algorithms. Prentice-Hall, Inc..

5. Polley, S., Koparde, R. R., Gowri, A. B., Perera, M., & Nuernberger, A. (2021, July). Towards trustworthiness in the context of explainable search. In Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (pp. 2580-2584).

6. Yang, Z. (2020, July). Biomedical information retrieval incorporating knowledge graph for explainable precision medicine. In Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval (pp. 2486-2486).

7. Adadi, A., & Berrada, M. (2018). Peeking inside the black-box: a survey on explainable artificial intelligence (XAI). IEEE access, 6, 52138-52160.

8. Abu-Rasheed, H., Weber, C., Zenkert, J., Krumm, R., & Fathi, M. (2022). Explainable Graph-Based Search for Lessons-Learned Documents in the Semiconductor Industry. In Intelligent Computing: Proceedings of the 2021 Computing Conference, Volume 1 (pp. 1097-1106). Springer International Publishing

9. Tiddi, I., Lécué, F., & Hitzler, P. (Eds.). (2020). Knowledge graphs for explainable artificial intelligence: Foundations, applications and challenges.

10.Xu, F., Uszkoreit, H., Du, Y., Fan, W., Zhao, D., & Zhu, J. (2019). Explainable AI: A brief survey on history, research areas, approaches and challenges. In Natural Language Processing and Chinese Computing: 8th CCF International Conference, NLPCC 2019, Dunhuang, China, October 9–14, 2019, Proceedings, Part II 8 (pp. 563-574). Springer International Publishing.

11.Moon, S., Shah, P., Kumar, A., & Subba, R. (2019, July). Opendialkg: Explainable conversational reasoning with attention-based walks over knowledge graphs. In Proceedings of the 57th annual meeting of the association for computational linguistics (pp. 845-854).

12.Ribeiro, M. T., Singh, S., & Guestrin, C. (2016, August). " Why should i trust you?" Explaining the predictions of any classifier. In Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining (pp. 1135-1144).

13.Selvaraju, R. R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., & Batra, D. (2017). Grad-cam: Visual explanations from deep networks via gradient-based localization. In Proceedings of the IEEE international conference on computer vision (pp. 618-626)

14.Ehsan, U., Harrison, B., Chan, L., & Riedl, M. O. (2018, December). Rationalization: A neural machine translation approach to generating natural language explanations. In Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society (pp. 81-87).

15.Wang, X., Wang, D., Xu, C., He, X., Cao, Y., & Chua, T. S. (2019, July). Explainable reasoning over knowledge graphs for recommendation. In Proceedings of the AAAI conference on artificial intelligence (Vol. 33, No. 01, pp. 5329-5336).

16.Xian, Y., Fu, Z., Muthukrishnan, S., De Melo, G., & Zhang, Y. (2019, July). Reinforcement knowledge graph reasoning for explainable recommendation. In Proceedings of the 42nd international ACM SIGIR conference on research and development in information retrieval (pp. 285-294).

17.Chen, Y., & Miyazaki, J. (2020). A model-agnostic recommendation explanation system based on knowledge graph. In Database and Expert Systems Applications: 31st International Conference, DEXA 2020, Bratislava, Slovakia, September 14–17, 2020, Proceedings, Part II 31 (pp. 149-163). Springer International Publishing.

18.Fensel, D., Şimşek, U., Angele, K., Huaman, E., Kärle, E., Panasiuk, O., ... & Wahler, A. (2020). Introduction: what is a knowledge graph?. Knowledge graphs: Methodology, tools and selected use cases, 1-10.

19.Alzoubi, W. A. (2020). Dynamic graph based method for mining text data. WSEAS Transactions on Systems and Control, 15(20), 453-458.

20.Alzoubi, W. A. (2020). An Improved Graph based Rules Mining Technique from Text. Eng. World, 2, 76-81]

21.Abu Rasheed, H., Weber, C., Zenkert, J., Czerner, P., Krumm, R., & Fathi, M. (2021). A text extraction-based smart knowledge graph composition for integrating lessons learned during the microchip design. In Intelligent Systems and Applications: Proceedings of the 2020 Intelligent Systems Conference (IntelliSys) Volume 2 (pp. 594-610). Springer International Publishing

22.Seeliger, A., Pfaff, M., & Krcmar, H. (2019). Semantic web technologies for explainable machine learning models: A literature review. PROFILES/SEMEX@ ISWC, 2465, 1-16.

23.Naiseh, M. (2020). Explainability design patterns in clinical decision support systems. In Research Challenges in Information Science: 14th International Conference, RCIS 2020, Limassol, Cyprus, September 23–25, 2020, Proceedings 14 (pp. 613-620). Springer International Publishing.

24.Song, W.; Duan, Z.; Yang, Z.; Zhu, H.; Zhang, M.; Tang, J. Explainable Knowledge Graph-Based Recommendatio via Deep Reinforcement Learning. arXiv arXiv:1906.09506. Available online: http://arxiv.org/abs/1906.09506 (accessed on 17 November 2021).

25.Xie, L., Hu, Z., Cai, X., Zhang, W., & Chen, J. (2021). Explainable recommendation based on knowledge graph and multi-objective optimization. Complex & Intelligent Systems, 7, 1241-1252.

26.Shalaby, W., AlAila, B., Korayem, M., Pournajaf, L., AlJadda, K., Quinn, S., & Zadrozny, W. (2017, December). Help me find a job: A graph-based approach for job **recommendation at scale. In 2017 IEEE international conference on big data (big data) (pp.** 1544-1553). IEEE.

27.Zhang, J., & Li, J. (2019). Enhanced knowledge graph embedding by jointly learning soft rules and facts. Algorithms, 12(12), 265.

28.Cheng, K.; Yang, Z.; Zhang, M.; Sun, Y. UniKER: A Unified Framework for Combining Embedding and Definite Horn Rule Reasoning for Knowledge Graph Inference. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing; Association for Computational Linguistics, Punta Cana, Dominican Republic, 7–11 November 2021; pp. 9753–9771

29.Yu, J.; McCluskey, K.; Mukherjee, S. Tax Knowledge Graph for a Smarter and More Personalized TurboTax. arXiv 2020, arXiv:2009.06103

30.Dijkstra, E. W. (1959). A note on two problems in connexion with graphs. Numeriske Mathematik, 1, 269–271.

31.Momin, U. (2023). NREGA-Catalyst for Fostering Inclusive Growth. International Journal for Multidimensional Research Perspectives, 1(4), 63-72.

32.Momin, M. U. An Analysis of the Challenges and Opportunities Encountered by Small and Medium Enterprises (SMES) in the Context of the Indian Economy.

33.Momin, U., Mehak, S. T., & Kumar, M. D. (2023). Strategic Planning and Risk Management in the Stratup, Innovation and Entrepreneurship: Best Practices and Challenges. Journal of Informatics Education and Research, 3(2).

34.Mahajan, T., Momin, U., Khan, S., & Khan, H. ROLE OF WOMEN'S ENTREPRENEURSHIP IN SOCIAL AND ECONOMIC DEVELOPMENT OF INDIA.

35.Naeem, A. B., Senapati, B., Islam Sudman, M. S., Bashir, K., & Ahmed, A. E. (2023). Intelligent road management system for autonomous, non-autonomous, and VIP vehicles. World Electric Vehicle Journal, 14(9), 238.

36.Naeem, A. B., Senapati, B., Mahadin, G. A., Ghulaxe, V., Almeida, F., Sudman, S. I., & Ghafoor, M. I. (2024). Determine the Prevalence of Hepatitis B and C During Pregnancy by Using Machine Learning Algorithm. International Journal of Intelligent Systems and Applications in Engineering, 12(13s), 744-751.

37.Yadav, S., Sudman, M. S. I., Dubey, P. K., Srinivas, R. V., Srisainath, R., & Devi, V. C. (2023, October). Development of an GA-RBF based Model for Penetration of Electric Vehicles and its Projections. In 2023 International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS) (pp. 1-6). IEEE.

38.Yadav, S., Sudman, M. S. I., Dubey, P. K., Srinivas, R. V., Srisainath, R., & Devi, V. C. (2023, October). Development of an GA-RBF based Model for Penetration of Electric Vehicles and its Projections. In 2023 International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS) (pp. 1-6). IEEE.

39.Thingom, C., Tammina, M. R., Joshi, A., Agal, S., Sudman, M. S. I., & Byeon, H. (2023, August). Revolutionizing Data Capitalization: Harnessing Blockchain for IoT-Enabled Smart Contracts. In 2023 Second International Conference On Smart Technologies For Smart Nation (SmartTechCon) (pp. 490-496). IEEE.

40.Sakthivel, M., Sudman, M. S. I., Ravishankar, K., Avinash, B., Kumar, A., & Ponnusamy, M. (2023, October). Medical Image Analysis of Multiple Myeloma Diagnosis Using CNN and KNN Based Approach. In 2023 International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS) (pp. 92-97). IEEE.

41.Choudhuri, S. S., Bowers, W., & Siddiqui, M. N. (2023). U.S. Patent No. 11,763,241. Washington, DC: U.S. Patent and Trademark Office.

42.Zanzaney, A. U., Hegde, R., Jain, L., Choudhuri, S. S., & Sharma, C. K. (2023, September). Crop Disease Detection Using Deep Neural Networks. In 2023 International Conference on Network, Multimedia and Information Technology (NMITCON) (pp. 1-5). IEEE.

43. Faisal, L., Rama, V. S. B., Roy, S., & Nath, S. (2022). Modelling of electric vehicle using modified sepic converter configuration to enhance dc–dc converter performance using matlab. In Smart Energy and Advancement in Power Technologies: Select Proceedings of ICSEAPT 2021, Volume 2 (pp. 643-653). Singapore: Springer Nature Singapore.

44.Faisal, L., Rama, V. S. B., Yang, J. M., Wajid, A., & Ghorui, S. K. (2022, May). Performance and simulation analysis of ipmsyncrm (internal permanent magnet synchronous reluctance motor) for advanced electric vehicle design. In 2022 3rd International Conference for Emerging Technology (INCET) (pp. 1-6). IEEE.

45.Mohd, R., & Faisal, L. (2022). Smart Agricultural Practices using Machine Learning techniques For Rainfall Prediction: A case Study of Valkenburg station, Netherlands. Mathematical Statistician and Engineering Applications, 71(4), 8451-8462.

46.Wani, A. A., & Faisal, L. (2022). Design & development of novel hybrid set of rules for detection and type of malignant or non-malignant tumor in human brain based on svm using artificial intelligence classifier. Mathematical Statistician and Engineering Applications, 71(4), 10253-10276.

47.Mohammed, A. H. (2021). Fish schooling and sorensen trust based wireless sensor network optimization. International Journal, 9, 6.

48.Mohammed, A. H. DDoS Malicious Node Detection by Jaccard and Page Rank Algorithm in Cloud Environment.

49.Mohammed, A. H. (2021). Invasive Weed Optimization Based Ransom-Ware Detection in Cloud Environment.

50.Choudhuri, S. S., Bowers, W., & Siddiqui, M. N. (2023). U.S. Patent No. 11,763,241. Washington, DC: U.S. Patent and Trademark Office.

51.Zanzaney, A. U., Hegde, R., Jain, L., Choudhuri, S. S., & Sharma, C. K. (2023, September). Crop Disease Detection Using Deep Neural Networks. In 2023 International Conference on Network, Multimedia and Information Technology (NMITCON) (pp. 1-5). IEEE.