

# StringBuffer

Java StringBuffer class is used to create mutable (modifiable) String objects.

The StringBuffer class in Java is the same as String class except it is mutable i.e. it can be changed.

Note: Java StringBuffer class is thread-safe i.e. multiple threads cannot access it simultaneously. So it is safe and will result in an order.

Java String Buffer use synchronized by default.

## Constructors of StringBuffer Class

Constructor	Description
StringBuffer()	It creates an empty String buffer with the initial capacity of 16.
StringBuffer(String str)	It creates a String buffer with the specified string..
StringBuffer(int capacity)	It creates an empty String buffer with the specified capacity as length.

## Methods

### Important methods of StringBuffer class

Modifier and Type	Method	Description
public synchronized StringBuffer	append(String s)	It is used to append the specified string with this string. The append() method is overloaded like append(char), append(boolean), append(int), append(float), append(double) etc.
public synchronized StringBuffer	insert(int offset, String s)	It is used to insert the specified string with this string at the specified position. The insert() method is overloaded like insert(int, char), insert(int, boolean), insert(int, int), insert(int, float), insert(int, double) etc.
public synchronized StringBuffer	replace(int startIndex, int endIndex, String str)	It is used to replace the string from specified startIndex and endIndex.
public synchronized StringBuffer	delete(int startIndex, int endIndex)	It is used to delete the string from specified startIndex and endIndex.
public synchronized StringBuffer	reverse()	is used to reverse the string.
public int	capacity()	It is used to return the current capacity.
public void	ensureCapacity(int minimumCapacity)	It is used to ensure the capacity at least equal to the given minimum.
public char	charAt(int index)	It is used to return the character at the specified position.
public int	length()	It is used to return the length of the string i.e. total number of characters.
public String	substring(int	It is used to return the substring from

	beginIndex)	the specified beginIndex.
public String	substring(int beginIndex,       int endIndex)	It is used to return the substring from the specified beginIndex and endIndex.
Public boolean	compareTo()	Return 0(true) if two data values are equal else return -1

## What is a mutable String?

A String that can be modified or changed is known as mutable String. StringBuffer and StringBuilder classes are used for creating mutable strings.

different between String vs StringBuffer vs StringBuilder

	String	StringBuffer	StringBuilder
Java version	Since Java 1.0	Since Java 1.0	Since Java 1.5
Storage Area	String constant pool	Heap	Heap
Mutability	Immutable	Mutable	Mutable
Thread-safe	Yes	Yes	No
Synchronized	No	Yes	No
Performance	Slower	Faster	Super Faster
Capacity	NA	16	16
Best suited for	Less modifications	More modifications	More modifications
Additional operations	Concat, Equals & EqualsIgnoreCase	Reverse, Append, Deletion, Insertion, & Comparison	Reverse, Append, Deletion, Insertion, & Comparison

# Java StringBuilder Class

Java StringBuilder class is used to create mutable (modifiable) String. The Java StringBuilder class is same as StringBuffer class except that it is non-synchronized. It is available since JDK 1.5.

## Important Constructors of StringBuilder class

Constructor	Description
StringBuilder()	It creates an empty String Builder with the initial capacity of 16.
StringBuilder(String str)	It creates a String Builder with the specified string.
StringBuilder(int length)	It creates an empty String Builder with the specified capacity as length.

## Methods

## Important methods of StringBuffer class

Modifier and Type	Method	Description
public synchronized StringBuffer	append(String s)	It is used to append the specified string with this string. The append() method is overloaded like append(char), append(boolean), append(int), append(float), append(double) etc.
public synchronized StringBuffer	insert(int offset, String s)	It is used to insert the specified string with this string at the specified position. The insert() method is overloaded like insert(int, char), insert(int, boolean), insert(int, int), insert(int, float), insert(int, double) etc.

public synchronized StringBuffer	replace(int startIndex, int endIndex, String str)	It is used to replace the string from specified startIndex and endIndex.
public synchronized StringBuffer	delete(int startIndex, int endIndex)	It is used to delete the string from specified startIndex and endIndex.
public synchronized StringBuffer	reverse()	is used to reverse the string.
public int	capacity()	It is used to return the current capacity.
public void	ensureCapacity(int minimumCapacity)	It is used to ensure the capacity at least equal to the given minimum.
public char	charAt(int index)	It is used to return the character at the specified position.
public int	length()	It is used to return the length of the string i.e. total number of characters.
public String	substring(int beginIndex)	It is used to return the substring from the specified beginIndex.
public String	substring(int beginIndex,       int endIndex)	It is used to return the substring from the specified beginIndex and endIndex.
Public boolean	compareTo()	Return 0(true) if two data values are equal else return -1