Linux 10 commands:

```
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ pwd
/home/sai_meghanaa
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ mkdir hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ cd hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ touch hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ vi hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ cat hello
Hello from hello text file
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ cat hello | grep hello
Hello from hello text file
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ps -ef
UID          PID    PPID  C STIME TTY          TIME CMD
root           1       0  0 04:30 ?        00:00:00 /sbin/init
root           2       1  0 04:30 ?        00:00:00 /init
root           6       2  0 04:30 ?        00:00:00 plan9 --control-socket 7 --log-level 4 --server-fd 8 --pipe-fd 10 --
root          42       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-journald
root          89       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-udevd
systemd+     163       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-resolved
systemd+     167       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-timesyncd
root         176       1  0 04:30 ?        00:00:00 /usr/sbin/cron -f -P
message+     177       1  0 04:30 ?        00:00:00 @dbus-daemon --system --address=systemd: --nofork --nopidfile --syst
root         189       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-logind
root         192       1  0 04:30 ?        00:00:00 /usr/libexec/wsl-pro-service
root         195       1  0 04:30 hvc0     00:00:00 /sbin/agetty -o -p -- \u --noclear --keep-baud - 115200,38400,9600 v
syslog       212       1  0 04:30 ?        00:00:00 /usr/sbin/rsyslogd -n -iNONE
root         215       1  0 04:30 tty1     00:00:00 /sbin/agetty -o -p -- \u --noclear - linux
root         223       1  0 04:30 ?        00:00:00 /usr/bin/python3 /usr/share/unattended-upgrades/unattended-upgrade-s
root         326       2  0 04:30 ?        00:00:00 /init
root         327     326  0 04:30 ?        00:00:00 /init
sai_meg+     328     327  0 04:30 pts/0    00:00:00 -bash
root         329       2  0 04:30 pts/1    00:00:00 /bin/login -f
sai_meg+     377       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd --user
sai_meg+     378     377  0 04:30 ?        00:00:00 (sd-pam)
sai_meg+     404     329  0 04:30 pts/1    00:00:00 -bash
sai_meg+     566     328 50 04:40 pts/0    00:00:00 ps -ef
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ps -ef | grep root
root           1       0  0 04:30 ?        00:00:00 /sbin/init
root           2       1  0 04:30 ?        00:00:00 /init
```

```
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ps -ef | grep root
root           1       0  0 04:30 ?        00:00:00 /sbin/init
root           2       1  0 04:30 ?        00:00:00 /init
root           6       2  0 04:30 ?        00:00:00 plan9 --control-socket 7 --log-level 4 --server-fd 8 --pipe-fd 10 --log-truncate
root          42       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-journald
root          89       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-udevd
root         176       1  0 04:30 ?        00:00:00 /usr/sbin/cron -f -P
root         189       1  0 04:30 ?        00:00:00 /usr/lib/systemd/systemd-logind
root         192       1  0 04:30 ?        00:00:00 /usr/libexec/wsl-pro-service
root         195       1  0 04:30 hvc0     00:00:00 /sbin/agetty -o -p -- \u --noclear --keep-baud - 115200,38400,9600 vt220
root         215       1  0 04:30 tty1     00:00:00 /sbin/agetty -o -p -- \u --noclear - linux
root         223       1  0 04:30 ?        00:00:00 /usr/bin/python3 /usr/share/unattended-upgrades/unattended-upgrade-shutdown --wait-for-signal
root         326       2  0 04:30 ?        00:00:00 /init
root         327     326  0 04:30 ?        00:00:00 /init
root         329       2  0 04:30 pts/1    00:00:00 /bin/login -f
sai_meg+     568     328  0 04:40 pts/0    00:00:00 grep --color=auto root
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ls
hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ chmod
chmod: missing operand
Try 'chmod --help' for more information.
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ls -l
total 4
-rw-r--r-- 1 sai_meghanaa sai_meghanaa 27 Oct 12 04:39 hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ chmod +x hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ls -l
total 4
-rwxr-xr-x 1 sai_meghanaa sai_meghanaa 27 Oct 12 04:39 hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ chmod 777 hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ ls -l
total 4
-rwxrwxrwx 1 sai_meghanaa sai_meghanaa 27 Oct 12 04:39 hello
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ whoami
sai_meghanaa
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ cat /var
cat: /var: Is a directory
sai_meghanaa@LAPTOP-MA8Q2RTS:~/hello$ cd /var
sai_meghanaa@LAPTOP-MA8Q2RTS:/var$ ls
backups  cache  crash  lib  local  lock  log  mail  opt  run  snap  spool  tmp
sai_meghanaa@LAPTOP-MA8Q2RTS:/var$ cat log
```

```
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ sudo adduser ec2_user
[sudo] password for sai_meghanaa:
info: Adding user `ec2_user' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `ec2_user' (1002) ...
info: Adding new user `ec2_user' (1002) with group `ec2_user (1002)' ...
info: Creating home directory `/home/ec2_user' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for ec2_user
Enter the new value, or press ENTER for the default
        Full Name []: ec2_user
        Room Number []:
        Work Phone []:
        Home Phone []:
        Other []:
Is the information correct? [Y/n] y
info: Adding new user `ec2_user' to supplemental / extra groups `users' ...
info: Adding user `ec2_user' to group `users' ...
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ groups
sai_meghanaa adm cdrom sudo dip plugdev users docker
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ sudo groups
root
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ groups ec2_user
ec2_user : ec2_user users
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ sudo groupadd devops
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ sudo usermod -aG devops ec2_user
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ groups ec2_user
ec2_user : ec2_user users devops
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ id ec2_user
uid=1002(ec2_user) gid=1002(ec2_user) groups=1002(ec2_user),100(users),1003(devops)
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ groups ec2_user
ec2_user : ec2_user users devops
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ mkdir hello.txt
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ rmdir hello.txt
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ mkdir hello
mkdir: cannot create directory ‘hello’: File exists
sai_meghanaa@LAPTOP-MA8Q2RTS:~$ ls
CPU.sh      backup          checkServer     demo     docs     myfolder        sample.log
```