# Online-Adaptive Sequencing with Verified Stopping for Multi-Container DNA Storage: A Computational Evaluation on a Digital Twin and Real Read Streams

Sai Mouli
*[Affiliation to be completed by the author]*
[City, Country]
[e-mail to be completed by the author]

***Abstract*—We study retrieval from DNA archives whose erasure-coded strands are spread over several separately synthesised and handled containers of unknown quality. A streaming decoder reads in batches and stops only when every stripe, its CRC-32 and the file's SHA-256 verify; an online-adaptive controller with a discrete posterior over each container's efficiency chooses which container to read next. All work is computational: nothing was synthesised or sequenced. On the DT4DDS digital twin, with six independently synthesised, aged and amplified containers, the full chain from simulated reads to bytes ran without any oracle in 23,040 retrievals with no wrong output (95% upper bound $1.6\times10^{-4}$) and no false accept in 28.1 million fragment decodes (bound $1.3\times10^{-7}$). Verified stopping is what saves reads: round-robin reading with verified stopping needs 3.49k reads on average in the baseline scenario, against 4.80k that the best hindsight-tuned static plan must reserve. Adaptive container selection does not add to this. With the calibrated beta-binomial posterior, every model-based rule costs more than round-robin (Thompson sampling $+7\%$, coverage-greedy $+15\%$, information-greedy $+441\%$), because one efficiency multiplier cannot represent a near-dead container's dropout; adaptive rules pay off only when a container has failed outright (UCB $-24\%$) or degradation is mild ($-2$ to $-3\%$). No rule lowers the 0.99-quantile, so the gain is for pay-per-read users only. The posterior's 90% intervals cover 87% of held-out targets but 20% for the near-dead container, and completion forecasts score worse than a constant forecast. On replayed real Illumina read streams (secondary, oracle decodability), verified stopping again supplies most of the saving (Twist: $-11\%$ against the hindsight static budget) and adaptive allocation adds 2–3%.**

***Index Terms*—DNA data storage, adaptive sequencing, verified stopping, erasure coding, coverage depth, digital twin, Bayesian calibration, multi-armed bandits, reproducibility**

## I. Introduction

DNA has been demonstrated as an archival medium at kilobyte to hundreds-of-megabyte scale [1]–[5]. Retrieval requires sequencing, which samples molecules at random: some strands are read many times, others never, and reads carry substitution, insertion and deletion errors [6], [7]. Systems therefore protect each strand with an inner code and groups of strands with an outer erasure code, and sequence to a fixed depth expected to recover enough strands [3], [5]. The number of reads needed for decoding—the *coverage depth*—is now studied in its own right [8], [9].

We consider archives split across several physically separate *containers* (vials, capsules, pools) that are synthesised, stored and handled separately. This is a working assumption rather than established practice; random access so far addresses files within one pool [5], [10], and recent theory treats erasure-coded data partitioned over containers with uniform sampling [11] and container failures [12]. Containers age, are amplified and fail differently, and these differences are unknown when a retrieval starts. Two operational questions follow: *when* to stop sequencing, and *which* container to sequence next.

**Problem.** Given an erasure-coded file distributed over $M$ containers of unknown, heterogeneous quality, some of which may have failed, sequence in batches and decide after each batch which container to read and whether to stop, so that the output file is byte-identical to the stored one with high probability while the number of reads is small.

**Scope.** All work is computational. Nothing was synthesised or sequenced for this paper, and no result should be read as a wet-lab demonstration. We use the term *exact retrieval* only for our digital-twin pipeline, where the output file is checked byte for byte against the stored file; on replayed real reads, decodability is an oracle event and we speak of *recovery*.

**Contributions.**

1) A verification-gated streaming retrieval pipeline and an *online-adaptive* controller family for multi-container DNA storage: a discrete posterior over each container's efficiency with a failure atom and a beta-binomial likelihood, eight allocation rules (round-robin, coverage-greedy, pivotal, Thompson sampling, UCB, learn-then-commit, information-greedy and a tail-aware rule), and stopping only when every stripe, its CRC-32 and the file's SHA-256 verify (Section IV). Stopping when decodable [13], checksum-verified decoding [4] and the bandit rules themselves [14]–[17] are known; their combination for container selection is, to our knowledge, not studied in DNA storage.

2) An end-to-end computational evaluation on the DT4DDS digital twin [7]: independently synthesised, aged and amplified containers produce reads that pass through the full decoding chain with no oracle, under an evaluation protocol frozen before the final runs, with exact bounds on wrong outputs and false accepts (Sections V–VI).
3) A leak-free re-analysis on real Illumina read streams from two vendors as secondary evidence, with our earlier leaky analysis retained in an appendix as an upper bound (Appendix A).
4) Measured negative results: Measured negative results: on the digital twin, no model-based allocation rule beats round-robin with verified stopping when one container is near-dead, the better-calibrated posterior makes allocation costlier, no rule (including a tail-aware one) lowers the 0.99-quantile, and the completion forecast is worse than a constant forecast (Section VI).

## II. Background and Related Work

**DNA storage systems and channels.** Storage systems combine constrained encodings with inner and outer codes [2]–[5], [18], [19]. Coverage is over-dispersed, a few percent of strands drop out, and errors arise mostly in synthesis and sequencing [6], [7], [20]. DT4DDS [7] is a digital twin of the synthesis, aging, PCR and sequencing steps whose error and bias parameters were fitted to experiments; we use it as the simulator of our primary evidence. Information-theoretic models treat the channel as sampling with replacement followed by noise [21]–[23].

**Coverage depth.** For a sampler that cannot be controlled, MDS codes and uniform sampling minimise the expected number of reads [8]. Follow-ups study random access [9], real-data sampling distributions [24], partitioning over containers [11], container failures [12] and the reliability of MDS-coded retrieval [25]. These works analyse *fixed* sampling laws; we study a *controllable* sampler.

**Adaptive sequencing and sequential decisions.** Nanopore adaptive sampling selects molecules in real time [26]–[28], and DNA-storage readouts have been sequenced until sufficient coverage [13]. Choosing a container resembles a multi-armed bandit with a combinatorial ($K$-of-$N$ per stripe) reward; we use Thompson sampling [14], [29], upper confidence bounds [15], explore-then-commit [16] and an information-greedy rule from Bayesian experimental design [17] as baselines (see [30]). We prove no regret bound.

**Placement and consensus.** Erasure-coded storage limits the fragments of a stripe per failure domain [31]–[35]. Strands are reconstructed from noisy reads by trace reconstruction [36]–[38] after clustering [39] or learned models [40]; systematic nanopore errors are documented [41], [42]. Table I positions this work.

## III. System Model

Table II lists the notation.

### A. Storage

A file is bundled, hashed (SHA-256) and split into $S$ stripes of $K$ data fragments of $P$ bytes. A systematic Cauchy Reed–Solomon code [45] over GF($2^8$) extends each stripe to $N$ fragments, any $K$ of which suffice. Each fragment becomes a strand carrying an address, an address check byte, the payload and an inner Reed–Solomon code with four parity bytes plus a CRC-16, mapped to DNA by a whitened 2-bit code. Code parameters, a CRC-32 per stripe and the SHA-256 are kept in a manifest outside the DNA. Fragments are assigned round-robin to $M$ containers.

### B. Sequencing and recovery model used by the controller

Reads from container $j$ form a stream. The controller's model (used only to rank containers and to forecast; never to decide that a fragment is recovered) treats the reads of a stored fragment as negative-binomial with mean $\theta_j\, R_j\, \bar{\pi}_j$ after $R_j$ reads, where $\bar{\pi}_j$ is the prior per-fragment read share (yield over stored fragments) and $\theta_j$ an unknown efficiency multiplier ($\theta_j$=0: failed container). A fragment becomes decodable after $t$ reads with probability $\varphi(t)$ (consensus-success curve), and a molecule is absent with probability $d$ (dropout). Integrating over abundance gives the probability $Q(\mu)$ that a stored fragment is decodable at mean coverage $\mu$:

$$Q(\mu) = (1-d)\,\mathbb{E}_g\Big[\sum_{n\geq 0} \mathrm{NB}(n; k, g\mu)\,\varphi(n)\Big], \qquad (1)$$

with a shared log-normal strand effect $g$ (Gauss–Hermite quadrature). Every container starts from the same generic literature prior (yield 0.9, NB shape $k$=10, dropout 0.5%, a generic consensus curve, failure probability $10^{-3}$); no calibration data of the evaluated system is used in the primary experiments.

### C. Objective and who benefits

A policy chooses, after each batch of $b$ reads, a container and whether to stop. We report two costs because they serve different users. A *pay-per-read* user (e.g. streaming nanopore sequencing, or a service that bills reads) pays the reads actually used: the relevant metric is the *mean* reads per retrieval. A user who must *reserve* capacity in advance (e.g. a fixed flowcell) pays for the 0.99-quantile (q99) on every retrieval. A static plan, which commits read proportions and a budget in advance, pays its q99 every time; its mean cost *is* its q99. Adaptive stopping helps the first user even when it does not reduce q99.

## IV. Online-Adaptive Retrieval

### A. Posterior over container efficiency

The support of $\theta_j$ is $\Theta = \{0\} \cup \{\theta^{(1)}, \ldots, \theta^{(25)}\}$, log-spaced in $[0.01, 5]$, with prior $p_0(0) = f_j$ and $p_0(\theta^{(\ell)}) \propto (1-f_j)\exp(-\frac{1}{2}(\ln\theta^{(\ell)}/s)^2)$, with $s = 0.5$ in every policy run. After $R_j$ reads with $U_j$ verified fragments among the $n_j$ stored in container $j$, we use a beta-binomial likelihood with intra-container correlation $\rho_U$:

$$p(\theta \mid R_j, U_j) \propto p_0(\theta)\,\mathrm{BB}\big(U_j;\, n_j,\, Q(\theta R_j \bar{\pi}_j),\, \rho_U\big), \qquad (2)$$

TABLE I

POSITIONING AGAINST THE CLOSEST PRIOR WORK. Y: YES; N: NO; P: PARTIAL; I: IMPLICIT (EXPECTED READS UNTIL DECODABILITY ANALYSED, NO OPERATIONAL STOPPING RULE); –: NOT STATED. "CONTAINERS" ARE STORAGE NODES IN [35] AND SAMPLING SOURCES IN [43].

| Work | Multi-container | Container failures | Heterog. containers | Correlated errors | Adaptive read allocation | Stopping rule | Real reads | End-to-end digital twin |
|---|---|---|---|---|---|---|---|---|
| Lopez et al. 2019 [13] | N | N | N | – | N | P | Y | N |
| Gimpel et al. 2023 [7] | N | N | P | N | N | N | Y | Y |
| Bar-Lev et al. 2025 [8] | N | N | N | N | N | I | N | N |
| Gruica et al. 2024 [9] | N | N | N | N | N | I | N | N |
| Cao & Chen 2025 [24] | N | N | N | N | N | I | P | N |
| Kas Hanna 2026 [25] | N | N | N | N | N | N | N | N |
| Levy et al. 2026 [12] | Y | Y | N | N | N | I | N | N |
| Kong et al. 2026 [11] | Y | N | P | N | N | I | N | N |
| Leong et al. 2012 [35] | Y | Y | N | N | N | N | N | N |
| Weilguny et al. 2023 [28] | N | N | – | N | Y | – | Y | N |
| Bubeck et al. 2013 [43] | Y | N | Y | N | Y | N | N | N |
| This work | Y | P | Y | P | Y | Y | P | Y |

Notes on "this work": container failures are simulated (digital twin) or injected (replay), not observed; correlated errors are validated on real nanopore reads but enter the controller only through consensus curves; real reads (ENA PRJEB65931 [44], same-batch aliquots) are used in a semi-empirical replay with oracle decodability, so they are marked partial; the end-to-end digital twin is DT4DDS [7]. Gimpel et al. [7]: heterogeneity characterised across handling conditions of one pool, and the digital twin itself. Cao & Chen [24]: log-normal channel fitted to their own data. Weilguny et al. [28]: genomic loci, not storage containers.





Fig. 1. Pipeline of the primary experiments (conceptual diagram). Every container is an independent DT4DDS synthesis with its own handling history; its reads are consumed in batches by the same streaming decoder that reads FASTQ files. The true file is used only after a retrieval ends, to count wrong outputs and false accepts.

where $\mathrm{BB}(u; n, p, \rho)$ has mean $np$ and variance $np(1-p)(1+(n-1)\rho)$; $\rho_U{=}0$ recovers the binomial. Recoveries of a container's fragments are correlated (shared synthesis bias, dropout), so the binomial is over-confident; $\rho_U$ is chosen on disjoint calibration replicates (Section V-D). We call the controller *online-adaptive*, not self-calibrating: it adapts to observations, but its uncertainty is not well calibrated (Section VI-F).

### B. Allocation rules

For an unrecovered fragment $i$ in container $j$, the hazard of becoming decodable within the next $b$ reads is $h_{ij} = [Q(\tilde{\theta}_j(R_j{+}b)\bar{\pi}_j) - Q(\tilde{\theta}_j R_j \bar{\pi}_j)]/[1 - Q(\tilde{\theta}_j R_j \bar{\pi}_j)]$, where $\tilde{\theta}_j$ is chosen by the rule:

- *Round-robin + verified stop*: reads every container in turn (no model).
- *Coverage-greedy*: $\tilde{\theta}_j$ = posterior mean; reads $\arg\max_j \sum_i h_{ij}$ over fragments of unfinished stripes.
- *Pivotal*: weights each fragment by a normal-approximation sensitivity of its stripe's completion probability (our earlier rule; details in the supplement).
- *Thompson sampling* [14], [29]: $\tilde{\theta}_j$ drawn from the posterior; coverage score.
- *UCB* [15]: $\tilde{\theta}_j$ = posterior 0.9-quantile.
- *Learn-then-commit* [16]: five round-robin batches per container, then the posterior is frozen and the coverage score used.
- *Info-greedy* (Bayesian experimental design [17]): reads the container with the largest posterior variance of $\ln \theta_j$ until all fall below $10^{-3}$, then coverage-greedy.
- *Tail-aware*: $\tilde{\theta}_j$ = posterior 0.1-quantile (pessimistic) and the score counts only the 10% of stripes with the largest remaining need (the bottleneck stripes that set the retrieval's length); a heuristic aimed at the q99.

All rules probe each container with one batch first. The *static* family reads fixed proportions $w_j \propto e_j^{\alpha}$, $\alpha \in \{0, 0.5, 1, 2\}$,

TABLE II
NOTATION (CODE OBJECTS IN PACKAGE D3RA).

| Symbol | Meaning | Code |
|---|---|---|
| $K, N, S, P$ | data / total fragments per stripe, stripes, payload bytes | `erasure_codes` |
| $M$, $j$ | number of containers, container index | `Layout` |
| $n_j$ | fragments stored in container $j$ | `Layout` |
| $b$ | batch size (reads per decision) | `AdaptiveConfig` |
| $R_j$, $U_j$ | reads taken from $j$, verified fragments from $j$ | `StreamRetriever` |
| $\theta_j$, $\Theta$, $s$ | efficiency multiplier, its grid, prior log-sd | `AdaptiveConfig` |
| $f_j$ | prior probability that container $j$ failed | `ChannelParams` |
| $\bar{\pi}_j$ | prior per-fragment read share of container $j$ | `AdaptiveController` |
| $k$, $d$, $\varphi(t)$ | NB shape, dropout, consensus-success curve | `ChannelParams` |
| $Q(\mu)$ | P(fragment decodable) at mean coverage $\mu$ | `_QTable` |
| $\rho_U$ | beta-binomial ICC of recoveries in the likelihood | `overdispersion` |
| $h_{ij}$ | hazard of recovery within the next batch | `scores` |
| $q$ | posterior quantile for UCB ($q$) and tail-aware ($1-q$) | `quantile` |
| $\nu_s$ | remaining need of stripe $s$ ($K$ minus verified) | `scores` |
| $w_j$, $e_j$, $\alpha$ | static proportions, hindsight per-read recovery rate, exponent | `static_family` |
| $\theta^*_j$ | calibration target (best-fitting multiplier) | `_theta_star` |
| q99 | 0.99-quantile of reads per retrieval | `dt_analysis` |

until decodable, where $e_j$ is the per-read recovery rate of container $j$ measured in hindsight on the same scenario: $\alpha{=}0$ is uniform fixed depth, $\alpha{=}1$ equalises expected coverage, and the best $\alpha$ is a hindsight-tuned ("oracle") static plan.

### C. Verified stopping

A retrieval stops with an output file only when (i) every stripe holds $K$ fragments that each passed inner RS decoding, CRC-16 and the address check, (ii) every stripe matches its CRC-32, and (iii) the file matches its SHA-256. If (ii) fails, one more fragment is requested for that stripe and the faulty fragment is localised by leave-one-out decoding. If the streams are exhausted first, the retrieval reports failure; it never returns an unverified file. An early-abandonment (futility) rule is disabled in all runs.

### D. Completion forecast

The controller also forecasts the probability of finishing within a remaining budget. The *analytic* forecast multiplies per-stripe normal approximations of $\mathbb{P}(\sum_{i\in s} X_i \geq \nu_s)$ with the remaining budget spread evenly over containers. The *posterior-simulation* forecast (default) draws 200 values of $\theta$ from the posterior, spreads the remaining budget in proportion to the reads spent so far, simulates per-fragment recoveries and reports the fraction of draws in which every stripe completes.

## V. EVALUATION METHODOLOGY

### A. Digital-twin end-to-end pipeline (primary evidence)

We store a fixed 18,432-byte random file with $P{=}24$-byte payloads, $(K, N) = (32, 48)$, 25 stripes and 1,200 strands of 136 nt over $M{=}6$ containers. For each container we run DT4DDS 1.1.0 [7] with its published default parameters: array synthesis (Twist model; log-normal oligo counts, $\sigma{=}0.3$), sampling of a given number of copies per strand, aging, high-fidelity PCR and Illumina iSeq100 single-end 150 nt sequencing, producing 60 reads per stored strand. The six containers are *independent* syntheses with their own seeds and histories. The reads, after adapter trimming, go through inventory clustering against the expected address prefixes, consensus (at most 24 reads per cluster), inner decoding, outer decoding with CRC-32 repair and SHA-256 verification, in batches of 50 reads. Every container decodes its own clusters; nothing uses the stored strands to decide recovery. The stored file and payloads are used only after the retrieval to count wrong outputs and false accepts (a wrong payload that passed the inner checks).

### B. Scenarios

*Baseline*: fresh; aged one half-life; aged two half-lives with 10 copies per strand; 30 PCR cycles; 45 PCR cycles with 20 copies; near-dead (two half-lives, 40 cycles, $\sigma{=}0.5$, 3 copies). *One/two failed*: the fresh (and the 30-cycle) container returns only non-informative reads. *Homogeneous control*: six fresh containers. *Photolithographic*: the baseline histories with DT4DDS's photolithographic synthesis model. *Severity sweep*: the baseline with the near-dead container's copy number set to 200, 30, 10, 3 or 1.

### C. Frozen protocol and statistics

Design, policies, metrics, statistics, pre-specified comparisons and the calibration rule were written to `dt_protocol.yaml` before the final runs; deviations are listed in Appendix B. Each scenario uses 30 independent syntheses of all six containers $\times$ 10 read orders (300 retrievals per policy); seeds are derived with CRC-32 of the scenario, replicate and container, so every run is bit-for-bit reproducible. CIs are cluster bootstrap percentile intervals over syntheses (2,000 resamples [46]); comparisons are paired over the same syntheses and read orders; wrong-output and false-accept rates carry exact Clopper–Pearson bounds [47]. We report every pre-specified comparison, including negative ones, and no significance stars.

### D. Calibration protocol

$\rho_U$ is chosen from $\{0, 0.003, 0.01, 0.03, 0.1\}$ on ten *disjoint* baseline replicates (seeds 1000–1009) as the value whose 90% credible interval covers the target $\theta^*_j$ closest to 90% of the time. $\theta^*_j$ is the multiplier that best fits the container's full recovery curve under the generic model, and the selection used prior sd $s{=}1$ whereas the policy runs use $s{=}0.5$ (a mismatch we noticed after freezing and report rather than re-tune); intervals are evaluated at the read count where the prior predicts 40% recovery and at twice that. The selected value is then fixed as the default for every policy run, evaluated on the held-out replicates 0–29, and used on the real-read replay. The completion forecast is evaluated with a budget equal to the median coverage-greedy cost, at 30/50/70/85% of it, by expected calibration error (ECE, 10 bins), Brier score against a constant (climatology) forecast [48] and AUC.

TABLE III
SAFETY OF VERIFICATION-GATED STOPPING OVER EVERY DIGITAL-TWIN RETRIEVAL RUN FOR THIS PAPER (ALL SCENARIOS, POLICIES, STATIC PLANS AND ABLATIONS; THE FORECAST-EVALUATION RUNS ARE EXCLUDED). EXACT 95% UPPER BOUNDS (CLOPPER–PEARSON).

| | |
|---|---|
| End-to-end retrievals | 23,040 |
| output byte-identical to stored file | 16,032 |
| reported as not recovered (no output) | 7,008 |
| wrong output (file returned, not identical) | 0 |
| Wrong-output rate, 95% upper bound | 1.6e-04 |
| Fragment decode attempts | 28,101,524 |
| false accepts (wrong payload passed inner checks) | 0 |
| False-accept rate per attempt, 95% upper bound | 1.3e-07 |

### E. Real read streams (secondary evidence)

We replay public Illumina iSeq runs of two pools from ENA PRJEB65931 [7], [44]: a 12,000-strand Twist pool after 0/2/7 days of aging or 15/60/90 PCR cycles, and a 12,472-strand Genscript pool (aging 0 d A/B, 2 d, 7 d; PCR 15/30 cycles). Each run emulates one container holding 250 stripes of $(32, 48)$. A fragment counts as recovered when the consensus of its first $t$ reads in a random permutation of the run equals the designed strand, with $t$ drawn from per-strand consensus curves estimated from real reads; decodability is therefore an *oracle* event and the replay is semi-empirical (read orders and counts real, containers emulated by subsetting runs of one synthesis batch). The primary belief is the generic prior; the optional "calibrated" belief now uses only the calibration split (the first 300k reads of each run; evaluation uses the next 900k). 200 read permutations, paired bootstrap.

## VI. RESULTS

### A. Safety of verified stopping

Table III pools every digital-twin retrieval run for this paper. No retrieval returned a file that differed from the stored one, and no wrong payload passed the inner RS + CRC-16 + address checks. The bounds are those of zero events in the given number of trials; they are statements about this archive geometry, these error rates and this code stack, not about DNA storage in general. Unsuccessful retrievals (one or two failed containers) ended by exhausting the streams and reported failure instead of returning a file.

### B. Policy comparison on the digital twin

Table IV and Fig. 2 give the pre-specified comparisons. In the baseline scenario every policy recovered the file in all 300 retrievals. Round-robin with verified stopping used 3.49k reads on average (95% CI 3.37–3.60k). Every model-based rule was costlier on the same syntheses and read orders: Thompson sampling by 7% (4–11%), tail-aware by 13% (9–18%), coverage-greedy by 15% (10–21%), UCB by 15% (11–20%), learn-then-commit by 45% (40–49%), pivotal by 49% (39–60%) and information-greedy by 441% (408–467%). The ordering follows the share of reads spent on the near-dead container: 16% for round-robin, 23% for Thompson sampling, 25–27% for tail-aware, UCB and coverage-greedy, 40–41% for pivotal and learn-then-commit, and 66% for information-greedy. In the homogeneous control (six fresh, independently synthesised containers), where we expected no allocation effect, most model-based rules were 2–4% cheaper than round-robin (coverage-greedy 2.18k vs. 2.26k; information-greedy even at 2.26k): independent syntheses differ enough for mild adaptive gains, consistent with the low-severity end of the sweep below. With DT4DDS's photolithographic synthesis model (reduced design, 30 retrievals per policy) no policy recovered the file: every retrieval read the whole 72k-read stream and reported failure, with no wrong output. The higher synthesis error rate of this model exceeds what the inner code and 60 reads per strand can correct for this archive; we did not test deeper streams or a stronger inner code.

### C. Why adaptive allocation loses under dropout

The controller models a container by one efficiency multiplier $\theta_j$ that scales every fragment's coverage. The near-dead container (two half-lives, 40 PCR cycles, $\sigma{=}0.5$, three copies per strand) instead loses a large fraction of its molecules outright: many of its fragments are never read however long it is sequenced, while the surviving ones are read often. Early batches from it therefore recover fragments at a rate that the model explains with a moderate $\theta_j$ and extrapolates to the missing fragments, so coverage-based scores keep predicting gains there. The beta-binomial likelihood ($\rho_U{=}0.1$) widens the posterior, which is what calibration asked for, and slows the correction further; information-greedy, which reads the container with the largest posterior variance, never brings that variance below its threshold and spends two thirds of its reads there. A post-hoc run with the binomial likelihood ($\rho_U{=}0$, Appendix B) makes coverage-greedy, Thompson sampling and tail-aware 3–4% *cheaper* than round-robin on the same retrievals (pivotal: 4% costlier, against 49%): the better-calibrated posterior is the costlier one. We did not adopt $\rho_U{=}0$, because it was not the pre-specified choice and is badly calibrated (Section VI-F). The fix this points to is a dropout-aware container model (a fraction of absent fragments as a second parameter), which we leave for future work.

### D. Failed containers and severity sweep

With one failed container (the fresh one, which returns only non-informative reads), 34% of retrievals succeeded under every policy, and success was identical for all policies on every synthesis and read order: whether the file can be recovered is set by which fragments the remaining five containers lost, i.e. by the archive's redundancy, not by the policy. On the 102 retrievals where all succeeded, adaptive allocation helped, because the failed container is easy to identify and stops being read: UCB used 24% (17–28%) fewer reads than round-robin, coverage-greedy 17% (8–23%), pivotal 15% (6–21%) and Thompson sampling 9% (2–15%); tail-aware was even (+2%, −8 to +14%), learn-then-commit 8% (2–14%) and information-greedy 81% (49–133%) costlier. With two failed containers no policy recovered the file; every retrieval read all 72,000 reads and reported failure.

TABLE IV

DIGITAL-TWIN END-TO-END RETRIEVAL (DT4DDS; PRIMARY EVIDENCE). PER SCENARIO AND POLICY: SHARE OF RETRIEVALS WHOSE OUTPUT FILE IS BYTE-IDENTICAL TO THE STORED FILE (NO RETRIEVAL RETURNED A WRONG FILE), MEAN READS PER RETRIEVAL (THOUSANDS; CLUSTER-BOOTSTRAP 95% CI OVER SYNTHESES), THE 0.99-QUANTILE Q99 (THE BUDGET TO RESERVE), AND THE PAIRED RELATIVE DIFFERENCE IN MEAN READS AGAINST ROUND-ROBIN WITH VERIFIED STOPPING ON RETRIEVALS WHERE BOTH SUCCEEDED (95% CI). STATIC PLANS READ FIXED PROPORTIONS UNTIL DECODABLE AND MUST RESERVE THEIR Q99 ON EVERY RETRIEVAL, SO THEIR MEAN COST EQUALS Q99; THEIR PROPORTIONS USE PER-CONTAINER EFFICIENCIES MEASURED IN HINDSIGHT ON THE SAME SCENARIO.

| Scenario | Policy | Success | Mean reads (k) [95% CI] | q99 (k) | vs. round-robin, % [95% CI] |
|---|---|---|---|---|---|
| Baseline | Round-robin + verified stop | 1.00 | 3.49 [3.37, 3.60] | 5.15 | |
| | Coverage-greedy | 1.00 | 4.02 [3.76, 4.30] | 9.05 | +15 [+10, +21] |
| | Pivotal | 1.00 | 5.21 [4.76, 5.70] | 9.60 | +49 [+40, +60] |
| | Thompson sampling | 1.00 | 3.75 [3.56, 3.95] | 6.45 | +7 [+4, +11] |
| | UCB ($q$=0.9) | 1.00 | 4.02 [3.78, 4.30] | 8.15 | +15 [+11, +20] |
| | Learn-then-commit | 1.00 | 5.05 [4.74, 5.31] | 7.65 | +45 [+40, +49] |
| | Info-greedy (exp. design) | 1.00 | 18.87 [17.15, 20.37] | 37.45 | +441 [+407, +470] |
| | Tail-aware (LCB) | 1.00 | 3.94 [3.72, 4.18] | 7.15 | +13 [+8, +18] |
| | Static, uniform (fixed depth) | 1.00 | 5.15 (= q99) | 5.15 | |
| | Static, $w \propto e^{0.5}$ | 1.00 | 4.90 (= q99) | 4.90 | |
| | Static, $w \propto e$ (equal coverage) | 1.00 | 4.80 (= q99) | 4.80 | |
| | Static, $w \propto e^2$ | 1.00 | 4.90 (= q99) | 4.90 | |
| One container failed | Round-robin + verified stop | 0.34 | $20.31^s$ | – | |
| | Coverage-greedy | 0.34 | $16.86^s$ | – | -17 [-23, -9] |
| | Pivotal | 0.34 | $17.30^s$ | – | -15 [-21, -6] |
| | Thompson sampling | 0.34 | $18.43^s$ | – | -9 [-15, -1] |
| | UCB ($q$=0.9) | 0.34 | $15.49^s$ | – | -24 [-28, -17] |
| | Learn-then-commit | 0.34 | $21.91^s$ | – | +8 [+3, +14] |
| | Info-greedy (exp. design) | 0.34 | $36.68^s$ | – | +81 [+50, +130] |
| | Tail-aware (LCB) | 0.34 | $20.63^s$ | – | +2 [-8, +14] |
| | Static, uniform (fixed depth) | 0.34 | – | – | |
| | Static, $w \propto e^{0.5}$ | 0.34 | – | – | |
| | Static, $w \propto e$ (equal coverage) | 0.34 | – | – | |
| | Static, $w \propto e^2$ | 0.34 | – | – | |
| Two containers failed | all 12 policies and static plans | 0.00 | – (stream exhausted, 72k reads) | – | |
| Homogeneous (control) | Round-robin + verified stop | 1.00 | 2.26 [2.23, 2.29] | 2.85 | |
| | Coverage-greedy | 1.00 | 2.18 [2.16, 2.21] | 2.70 | -3 [-4, -2] |
| | Pivotal | 1.00 | 2.18 [2.16, 2.20] | 2.75 | -4 [-5, -3] |
| | Thompson sampling | 1.00 | 2.19 [2.17, 2.22] | 2.70 | -3 [-4, -2] |
| | UCB ($q$=0.9) | 1.00 | 2.18 [2.16, 2.20] | 2.75 | -4 [-5, -3] |
| | Learn-then-commit | 1.00 | 2.19 [2.17, 2.21] | 2.75 | -3 [-4, -2] |
| | Info-greedy (exp. design) | 1.00 | 2.25 [2.23, 2.28] | 2.90 | -0 [-1, +0] |
| | Tail-aware (LCB) | 1.00 | 2.20 [2.18, 2.23] | 2.75 | -2 [-4, -1] |
| | Static, uniform (fixed depth) | 1.00 | 2.85 (= q99) | 2.85 | |
| | Static, $w \propto e^{0.5}$ | 1.00 | 2.85 (= q99) | 2.85 | |
| | Static, $w \propto e$ (equal coverage) | 1.00 | 2.85 (= q99) | 2.85 | |
| | Static, $w \propto e^2$ | 1.00 | 2.85 (= q99) | 2.85 | |
| Photolithographic synthesis[‡] | all 8 policies and static plans | 0.00 | – (stream exhausted, 72k reads) | – | |

30 independent syntheses of all six containers × 10 read orders = 300 retrievals per policy and scenario, except [‡]10 × 3 (protocol deviation, compute). A failed retrieval read the whole stream (72,000 reads) without verifying; [s]: mean over successful retrievals only (a mean or quantile including failures is undefined, "–"). When success < 1, success was identical for every policy on every synthesis and read order, so the paired comparison uses the same retrievals for all policies.

The severity sweep (Fig. 3) varies only the near-dead container's copies per strand. At 200 and 30 copies, coverage-greedy and Thompson sampling are 2–3% cheaper than round-robin (2.65k vs. 2.72k at 200 copies) and tail-aware is even; at 10 copies the policies are within ±1% except tail-aware (+5%); at 3 and 1 copies all adaptive rules are costlier (at one copy: coverage-greedy 4.69k, Thompson 4.51k, tail-aware 4.47k vs. 4.16k). Success was 1.00 throughout. The point at 3 copies reproduces the baseline design with other seeds (round-robin 3.46k vs. 3.49k). Adaptive allocation therefore helps only while the model's single multiplier is a fair description of the worst container.

### *E. Tail and static plans*

No allocation rule lowers the 0.99-quantile. In the baseline, round-robin with verified stopping has q99 5.15k; the adaptive rules have 6.45k (Thompson) to 9.6k (pivotal) and the tail-aware rule, designed for the bottleneck stripes, 7.15k. At one copy per strand in the sweep, q99 is 5.65k for round-robin and 10.1k for coverage-greedy. The tail is therefore not fixed, and we reframe the claim: the benefit of this paper's machinery is a lower *mean* cost, which matters to a pay-per-read user. That benefit comes from verified stopping, not from allocation. The static plans have to reserve their q99 on every retrieval: 5.15k for uniform fixed depth and 4.80k for the best hindsight-tuned proportions ($\alpha$=1), whose weights were measured on the evaluated syntheses and are therefore an optimistic baseline. Round-robin with verified stopping costs 3.49k on average, 27% less than the best static reservation, while needing no knowledge of the containers. A user who must reserve capacity gains nothing from stopping early unless unused capacity is refunded; for that user the q99 of round-robin (5.15k) equals the uniform static budget, and the tuned static plan is the better





Fig. 2. Digital-twin end-to-end retrieval. (a) Baseline scenario: mean reads (95% cluster-bootstrap CI) and q99 per policy; vertical lines: static plans (whose cost equals their q99). (b) Paired relative cost against round-robin with verified stopping on retrievals where both succeeded (95% CI); negative is cheaper.





Fig. 3. Severity sweep: the near-dead container's copy number varied from 200 to 1 (300 retrievals per point and policy).

choice. In the homogeneous control the static plans reserve 2.85k against a round-robin mean of 2.26k (−21%). With failed containers no static plan can be sized: it either reads the whole stream or fails, and its q99 is the full 72k reads.

### F. Calibration and completion forecast

On the ten selection replicates, 90% credible-interval coverage of $\theta^*$ rose with $\rho_U$ from 0.45 (binomial) through 0.63, 0.73 and 0.80 to 0.87 at $\rho_U$=0.1, the edge of the grid; we kept the pre-specified grid and selected 0.1. On the 30 held-out replicates the selected value gave the same overall coverage, 0.87 (0.84 at the earlier and 0.89 at the later read count), and 1.00 for five of the six containers but 0.20 for the near-dead one, whose target the generic model cannot fit (Fig. 4). With the binomial likelihood held-out coverage is 0.54.

The completion forecast was evaluated on 1,127 checkpoints from 300 baseline retrievals with a budget of 3.75k reads (the median coverage-greedy cost); 52% of retrievals finished within it. Both forecasts were over-confident (mean forecast 0.86 vs. 0.52 observed at 30% of the budget). The posterior-simulation forecast was better than the analytic one on every metric (ECE 0.29 vs. 0.34; Brier 0.30, 95% CI 0.27–0.34, vs. 0.34, 0.29–0.38; AUC 0.73, 0.69–0.78, vs. 0.69, 0.65–0.73; cluster bootstrap), but both Brier scores are worse than the 0.25 of a constant forecast at the observed base rate. The forecasts rank retrievals usefully late in a retrieval (AUC 0.82 at 85% of the budget) but should not be used as probabilities. Futility stopping, which would rely on them, stays disabled.

TABLE V

SECONDARY EVIDENCE: SEMI-EMPIRICAL REPLAY OF REAL ILLUMINA READ STREAMS (ENA PRJEB65931), GENERIC PRIOR, NO EVALUATION-SPLIT STATISTICS. MEAN READS (THOUSANDS) AND Q99; Δ: MEAN MINUS THE HINDSIGHT-TUNED STATIC BUDGET (PAIRED BOOTSTRAP 95% CI). DECODABILITY IS AN ORACLE EVENT HERE (CONSENSUS EQUALS THE DESIGNED STRAND), SO THIS IS *not* EXACT RETRIEVAL.

| Pool | Policy | Mean | q99 | Δ vs. static [95% CI] |
|---|---|---|---|---|
| Twist | Static, uniform (hindsight budget) | 68.1 | 68.1 | |
| | Static, hindsight-tuned | 65.7 | 65.7 | |
| | Round-robin + verified stop | 58.6 | 68.4 | -7.1 [-17.4, -6.5] |
| | Coverage-greedy | 56.7 | 66.0 | -9.0 [-19.3, -8.5] |
| | Pivotal | 56.6 | 67.2 | -9.1 [-19.4, -8.6] |
| | Thompson sampling | 56.9 | 66.0 | -8.9 [-19.1, -8.4] |
| | UCB | 56.7 | 66.6 | -9.0 [-19.2, -8.5] |
| | Learn-then-commit | 57.2 | 66.6 | -8.5 [-18.8, -8.0] |
| | Info-greedy | 56.7 | 66.0 | -9.0 [-19.3, -8.5] |
| | Tail-aware (LCB) | 56.7 | 65.6 | -9.0 [-19.3, -8.5] |
| | Coverage-greedy, leak-free calibrated | 56.6 | 67.6 | -9.1 [-19.4, -8.6] |

### G. Secondary evidence: real read streams

Table V gives the leak-free replay with the generic prior. On the Twist pool, round-robin with verified stopping used 58.6k reads on average against the 65.7k budget of the hindsight-tuned static plan (−11%), and the model-based rules used 56.6–57.2k, 2–3% fewer than round-robin; coverage-greedy was 9.0k (95% CI 8.5–19.3k) below the hindsight static budget. Information-greedy reduced to coverage-greedy after the first probes (identical results), and the leak-free calibrated belief changed coverage-greedy by −0.2%. As on the digital twin, no rule lowered q99 materially: 65.6–67.2k for the model-based rules against the 65.7k static budget. Stopping supplies most of the gain (about 7.1k of 9.0k reads). [TBD: Genscript replay still running at the time of this build]

### H. Supporting channel result (real nanopore reads)

On two independent nanopore flowcells of DNAformer reads [40], [49], a strand-specific error propensity persists across flowcells ($r$=0.57; null with matched contexts 0.002), and a hierarchical beta-binomial error model fitted on one flowcell predicts consensus success on held-out strands of the





Fig. 4. Calibration on the digital twin. Left: 90% credible-interval coverage of $\theta^*$ per container on the selection replicates for each $\rho_U$, and on held-out replicates at the selected $\rho_U$. Right: reliability of the completion forecast (analytic vs. posterior simulation).

other with mean absolute error 0.083, against 0.181 for an i.i.d. model. This motivates over-dispersed models but does not enter the controller.

## VII. Discussion

**What helps, and whom.** The robust gain in our experiments is verified stopping: reading until every stripe, its CRC-32 and the file hash verify, and then stopping. It needs no model, never returned a wrong file, and costs a pay-per-read user 27% less on average than the best hindsight-tuned static plan in the baseline digital twin. It does not reduce the reads a user must reserve. Choosing *which* container to read with a posterior model helped only where the model fits: an outright failure, which the posterior detects within a few batches, or mild heterogeneity. With a near-dead container, every model-based rule we tried, including standard bandit and experimental-design rules, was costlier than round-robin.

**Calibration versus cost.** The likelihood that gave the best-calibrated intervals ($\rho_U$=0.1) also gave the costlier allocations, and the binomial likelihood, whose intervals covered only 54%, gave the cheaper ones. Calibrating the uncertainty of a misspecified model does not make its decisions better; the misspecification (one multiplier for a container with dropout) is the problem to fix. We therefore present the controller as online-adaptive, not self-calibrating, and do not recommend its forecasts as probabilities.

**Digital twin versus replay.** The two settings agree that stopping is the main saving and that no rule lowers q99; they disagree on allocation, which helps slightly on the replay (2–3%) but hurts on the digital twin with a near-dead container. The replay's containers are runs of one synthesis batch with no near-dead member, which resembles the mild-heterogeneity end of the sweep; the digital twin's independent syntheses include the harder case.

**Practical recommendation.** For multi-container archives like ours, read the containers in turn and stop on verification; switch a container off once it is clearly failed (the setting in which coverage-greedy, pivotal, Thompson sampling and UCB helped). Use model-based allocation only with a container model that represents dropout, and check it against round-robin on a digital twin before relying on it.

TABLE VI
Assumptions, limitations and their consequence.

| Limitation | Consequence |
|---|---|
| Computational only (digital twin + replay) | no wet-lab confirmation; DT4DDS fidelity bounds external validity |
| DT4DDS default parameters, one archive geometry | conclusions may change with other codes, strand lengths, error regimes |
| Failures simulated (junk reads) | real failure modes and rates unknown; failure budget uncalibrated |
| Single efficiency multiplier $\theta_j$ | cannot represent dropout; adaptive allocators over-read near-dead containers |
| $\rho_U$ at the edge of its grid | selection coverage 0.87 $<$ 0.90; grid not extended post hoc |
| $\rho_U$ selected with $s$=1, runs use $s$=0.5 | selection and use not perfectly aligned |
| Calibration-optimal vs. cost-optimal $\rho_U$ differ | better-calibrated posterior made allocation costlier (post-hoc) |
| Gains in the mean only | no allocator, including the tail-aware one, lowers q99 |
| Replay is semi-empirical | oracle decodability; containers are aliquots of one batch |
| Abstract read costs, no setup cost | favours small batches; Illumina run economics not modelled |
| Reduced design for photolithographic scenario | 30 instead of 300 retrievals per policy |
| No theory (regret, optimality) | empirical claims only |

## VIII. Limitations and Threats to Validity

Table VI lists the main threats. *External validity*: every result is computational. The digital twin uses DT4DDS's default parameters and one archive geometry (1,200 strands, $(32, 48)$, six containers), and its failure mode is simulated (a failed container returns non-informative reads). The replay uses real reads, but decodability is an oracle event and the "containers" are runs of one synthesis batch. *Internal validity*: $\rho_U$ was selected with prior sd $s$=1 and used with $s$=0.5; the selected value lies at the edge of the pre-specified grid; the photolithographic scenario uses a reduced design; and one code fix (static allocator) was made after freezing (Appendix B). The static baselines use efficiencies measured in hindsight on the evaluated syntheses, which favours them. *Construct validity*: read counts are a proxy for cost; we do not model run set-up costs, which favour fewer, larger batches. *Statistical*: wrong-output and false-accept bounds come from zero events and scale with the number of trials; the comparisons are paired but within one archive design. We prove no optimality or regret result.

## IX. Reproducibility and Availability

All code, configuration and result files are in the accompanying repository and artifact archive. The digital-twin experiments are driven by `experiments/dt_experiments.py` (sub-commands `gen`, `run`, `static`, `calib`, `calib_eval`, `forecast`, `posthoc_rho0`); the replay by `experiments/paper_experiments.py replay_v3`; statistics by `dt_analysis.py`; tables and figures by `make_tables.py` and `make_dt_figures.py`, which read only committed result files (no number in the tables is entered by hand). Every random draw is seeded by CRC-32 of a string naming the scenario, replicate, container, read order and policy, so results do not depend on process scheduling or worker count. Re-executing 24 randomly sampled baseline retrievals in a fresh single-process run, in reverse order, reproduced every recorded field (reads, per-container reads, rounds, decode attempts, status) exactly (`rerun_check.py`). The protocol (`dt_protocol.yaml`) with its deviation log, the DT4DDS version (1.1.0), Python and package versions are in the artifact. The public data are ENA PRJEB65931 (Illumina) and the DNAformer nanopore reads. Table VII maps each claim to its experiment and result file.

## X. Conclusion

On a digital twin with independently synthesised containers, verified stopping retrieved the file without a single wrong output and cut the mean reads per retrieval by 27% against the best static reservation; adaptive container selection added nothing when a container was near-dead and helped (by up to 24%) only after an outright failure or under mild heterogeneity. No rule lowered the 0.99-quantile, and the controller's forecasts are over-confident. The results are computational, for one archive design and one simulator; their value is a reproducible, leak-free baseline and a clear account of where online adaptation fails. A container model with dropout, wet-lab containers and a real failure distribution are the next steps.

## Appendix A
## Upper bound with evaluation leakage

Our first analysis of the real read streams (Table VIII) used a "calibrated" belief whose per-strand consensus curves were pooled over reads that included the evaluation split. The controller therefore had information about the very reads it was evaluated on, and the static plans were tuned on them too. We keep the table only as an *upper bound with evaluation leakage*; no claim in the main text uses it. In the leak-free re-analysis (Table V) the primary belief is the generic prior, and the optional calibrated belief uses only the first 300k reads of each run while evaluation uses the next 900k. On Twist, the leaky analysis put coverage-greedy at 55.7k reads and the oracle-tuned static plan at 63.1k; the leak-free analysis gives 56.7k and 65.7k. The leak therefore flattered the adaptive policy by about 1k reads and the static baseline by about 2.6k, and the leak-free gap is larger, not smaller.

## Appendix B
## Protocol deviations and post-hoc analyses

**Deviations.** The frozen protocol and every change made after freezing are in `dt_protocol.yaml`. (i) The planned CustomArray scenario was replaced, before any policy run, by DT4DDS's photolithographic synthesis model, because the CustomArray settings carry a 117-nt position-bias table that cannot be applied to 136-nt strands. (ii) We suspected from commit timestamps that the first Twist replay had run with $\rho_U{=}0$ and re-ran it; a direct test showed that it had used the frozen $\rho_U{=}0.1$, and the re-run reproduced it exactly, so nothing changed. (iii) One cached homogeneous replicate was truncated by an interrupted job; it was regenerated from its seed and the scenario re-run in full. (iv) The photolithographic scenario was run with 10 syntheses $\times$ 3 read orders for compute reasons; the first 50 retrievals of the full run were discarded unseen. (v) The static allocator crashed when only zero-weight (failed) containers remained; it now reads them out, which can only affect failed retrievals of the failure scenarios. The $\rho_U$ rule was applied as frozen even though the selected value lies at the edge of the grid.

**Post-hoc analyses** (not pre-specified). With the binomial likelihood ($\rho_U{=}0$), on the same 300 baseline retrievals, coverage-greedy used 3.34k reads ($-4.4\%$ vs. round-robin, against $+15.1\%$ at $\rho_U{=}0.1$), Thompson sampling 3.37k ($-3.5\%$, against $+7.4\%$), tail-aware 3.37k ($-3.5\%$, against $+12.9\%$) and pivotal 3.64k ($+4.4\%$, against $+49.3\%$); q99 was 4.95–5.70k, still not below round-robin's 5.15k. With one failed container the binomial likelihood helped tail-aware ($-25\%$ vs. $+2\%$) and Thompson sampling ($-20\%$ vs. $-9\%$) and hurt coverage-greedy and pivotal slightly ($-15\%$ vs. $-17\%$; $-8\%$ vs. $-15\%$). Success and safety were unchanged (no wrong output). On the Twist replay, the binomial likelihood made coverage-greedy and Thompson sampling costlier (57.6k each, against 56.7k and 56.9k at $\rho_U{=}0.1$), the opposite of the digital-twin result: the two settings disagree on which likelihood allocates better.


## Acknowledgment

We thank the authors of the public datasets and of DT4DDS (ENA PRJEB65931; DNAformer; Srinivasavaradhan *et al.*) for releasing reads, designs and software.


## References


[1] G. M. Church, Y. Gao, and S. Kosuri, "Next-generation digital information storage in DNA," *Science*, vol. 337, no. 6102, p. 1628, 2012.

[2] N. Goldman, P. Bertone, S. Chen, C. Dessimoz, E. M. LeProust, B. Sipos, and E. Birney, "Towards practical, high-capacity, low-maintenance information storage in synthesized DNA," *Nature*, vol. 494, no. 7435, pp. 77–80, 2013.

[3] R. N. Grass, R. Heckel, M. Puddu, D. Paunescu, and W. J. Stark, "Robust chemical preservation of digital information on DNA in silica with error-correcting codes," *Angewandte Chemie International Edition*, vol. 54, no. 8, pp. 2552–2555, 2015.

[4] Y. Erlich and D. Zielinski, "DNA fountain enables a robust and efficient storage architecture," *Science*, vol. 355, no. 6328, pp. 950–954, 2017.

TABLE VII

CLAIM-TO-EVIDENCE SUMMARY (FULL TABLE: `evidence/evidence_traceability.csv`). DT: DT4DDS DIGITAL TWIN, FULL DECODE CHAIN, NO ORACLE. REPLAY: REAL READS, ORACLE DECODABILITY. NO RESULT IS WET-LAB EVIDENCE.

| Claim | Command (`dt_experiments.py` unless noted) | Result file (`results/`) | Evidence |
|---|---|---|---|
| No wrong output, no false accept (Table III) | all DT runs | `dt_*.csv` | DT |
| Verified stop: $-27\%$ mean vs. best static reservation | `run`/`static baseline` | `dt_baseline.csv`, `dt_baseline_static.csv` | DT |
| Model-based rules costlier than round-robin (baseline) | `run baseline` | `dt_summary.csv` | DT, negative |
| Gains after outright failure (UCB $-24\%$); success set by redundancy | `run fail1`, `run fail2` | `dt_fail1.csv`, `dt_fail2.csv` | DT, simulated failures |
| Crossover with severity of the worst container | `run sweep_cov*` | `dt_sweep_cov*.csv` | DT |
| No rule lowers q99 | all DT runs | `dt_summary.csv` | DT, negative |
| $\rho_U$ selection and held-out coverage | `calib`, `calib_eval` | `dt_calibration_{select,eval}_ba...` | DT, partly negative |
| Forecasts over-confident, worse than climatology | `forecast baseline` | `dt_forecast_baseline.csv` | DT, negative |
| Binomial likelihood cheaper (post hoc) | `posthoc_rho0` | `dt_*_posthoc_rho0.csv` | DT, post hoc |
| Homogeneous control; photolithographic synthesis | `run homog`, `run photolitho` | `dt_homog.csv`, `dt_photolitho.csv` | DT (photolitho reduced) |
| Leak-free real-read replay | `paper_experiments.py replay_v3` | `replay_v3{,_genscript}.csv` | Replay |
| Leaky first analysis (upper bound only) | `real_data.py policies` | `realdata_*policies*_v2.csv` | superseded |
| Correlated nanopore errors (MAE 0.083 vs. 0.181) | `q3_correlated_errors.py` | `q3_summary.json` | real nanopore reads |
| Regret bounds; wet-lab containers; real failure rates | – | – | not attempted |

TABLE VIII

**UPPER BOUND WITH EVALUATION LEAKAGE** (SUPERSEDED FIRST ANALYSIS, KEPT FOR TRANSPARENCY). REPLAY OF REAL READ STREAMS WITH "CALIBRATED" BELIEFS WHOSE CONSENSUS CURVES WERE POOLED FROM *evaluation*-SPLIT READS (APPENDIX A); THOUSANDS OF READS AT 0.99. THESE NUMBERS ARE NOT USED FOR ANY CLAIM IN THE MAIN TEXT. STATIC PLANS PAY THEIR BUDGET ON EVERY RETRIEVAL; FOR ADAPTIVE POLICIES THE 0.99-QUANTILE Q99 IS SHOWN SEPARATELY. $\Delta$: ADAPTIVE (PIVOTAL) MINUS ORACLE-TUNED STATIC, PAIRED (95% CI).

| Pool | Placement | Fixed depth | Oracle-tuned static | Adaptive stop, round-robin | Adaptive, cov.-greedy | Adaptive, pivotal | q99 of pivotal | $\Delta$ (95% CI) |
|---|---|---|---|---|---|---|---|---|
| Twist | round-robin (6) | 67.9 | 63.1 | 57.8 | 55.7 | 55.8 | 63.2 | $-7.3$ ($-12.1$, $-7.0$) |
| Twist | reliability-weighted | 65.4 | 61.9 | 56.0 | 54.2 | 54.1 | 61.8 | $-7.9$ ($-13.3$, $-7.6$) |
| Twist | tiered (4) | 61.9 | 53.1 | 51.3 | 46.4 | 46.2 | 53.0 | $-6.9$ ($-19.1$, $-6.2$) |
| Twist | single best | 53.9 | 53.9 | 44.8 | 44.8 | 44.8 | 54.0 | $-9.1$ ($-11.0$, $-6.7$) |
| Genscript | round-robin (6) | 810.4 | 617.9 | 639.9 | 532.1 | 531.9 | 694.2 | $-86.0$ ($-127.1$, $-78.8$) |
| Genscript | single best$^\dagger$ | 279.4 | 279.4 | 219.0 | 219.0 | 219.0 | 279.6 | $-60.4$ ($-70.5$, $-54.2$) |

200 read permutations, except $^\dagger$100. All policies completed in every trial. The single-best container is chosen with the calibrated belief, which contains the evaluation-split leak of Appendix A. Superseded first-run Genscript numbers (computed before the per-strand consensus cache was regenerated) are kept in `results/realdata_genscript_policies_{roundrobin,part2}.csv`.


[5] L. Organick, S. D. Ang, Y.-J. Chen, R. Lopez, S. Yekhanin, K. Makarychev, M. Z. Racz, G. Kamath, P. Gopalan, B. Nguyen, C. N. Takahashi, S. Newman, H.-Y. Parker, C. Rashtchian, K. Stewart, G. Gupta, R. Carlson, J. Mulligan, D. Carmean, G. Seelig, L. Ceze, and K. Strauss, "Random access in large-scale DNA data storage," *Nature Biotechnology*, vol. 36, no. 3, pp. 242–248, 2018.

[6] R. Heckel, G. Mikutis, and R. N. Grass, "A characterization of the DNA data storage channel," *Scientific Reports*, vol. 9, no. 1, p. 9663, 2019.

[7] A. L. Gimpel, W. J. Stark, R. Heckel, and R. N. Grass, "A digital twin for DNA data storage based on comprehensive quantification of errors and biases," *Nature Communications*, vol. 14, no. 1, p. 6026, 2023.

[8] D. Bar-Lev, O. Sabary, R. Gabrys, and E. Yaakobi, "Cover your bases: How to minimize the sequencing coverage in DNA storage systems," *IEEE Transactions on Information Theory*, vol. 71, no. 1, pp. 192–218, 2025.

[9] A. Gruica, D. Bar-Lev, A. Ravagnani, and E. Yaakobi, "A combinatorial perspective on random access efficiency for DNA storage," in *Proc. IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2024, pp. 675–680.

[10] J. Bornholt, R. Lopez, D. M. Carmean, L. Ceze, G. Seelig, and K. Strauss, "A DNA-based archival storage system," in *Proceedings of the 21st International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS)*. ACM, 2016, pp. 637–649.

[11] X. Kong, O. Elishco, C. Wang, and T. M. Duman, "The coverage depth problem in distributed DNA data storage," arXiv:2610.02931 [cs.IT], 2026, preprint.

[12] A. Levy, R. Con, E. Yaakobi, and H. M. Kiah, "Expected recovery time in DNA-based distributed storage systems," arXiv:2602.07601 [cs.IT], 2026, preprint.

[13] R. Lopez, Y.-J. Chen, S. Dumas Ang, S. Yekhanin, K. Makarychev, M. Z. Racz, G. Seelig, K. Strauss, and L. Ceze, "DNA assembly for nanopore data storage readout," *Nature Communications*, vol. 10, no. 1, p. 2933, 2019.

[14] W. R. Thompson, "On the likelihood that one unknown probability exceeds another in view of the evidence of two samples," *Biometrika*, vol. 25, no. 3-4, pp. 285–294, 1933.

[15] P. Auer, N. Cesa-Bianchi, and P. Fischer, "Finite-time analysis of the multiarmed bandit problem," *Machine Learning*, vol. 47, no. 2–3, pp. 235–256, 2002.

[16] A. Garivier, T. Lattimore, and E. Kaufmann, "On explore-then-commit strategies," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 29, 2016.

[17] K. Chaloner and I. Verdinelli, "Bayesian experimental design: A review," *Statistical Science*, vol. 10, no. 3, pp. 273–304, 1995.

[18] P. L. Antkowiak, J. Lietard, M. Z. Darestani, M. M. Somoza, W. J. Stark, R. Heckel, and R. N. Grass, "Low cost DNA data storage using photolithographic synthesis and advanced information reconstruction and error correction," *Nature Communications*, vol. 11, no. 1, p. 5345, 2020.

[19] W. H. Press, J. A. Hawkins, S. K. Jones, J. M. Schaub, and I. J. Finkelstein, "HEDGES error-correcting code for DNA storage corrects indels and allows sequence constraints," *Proceedings of the National Academy of Sciences*, vol. 117, no. 31, pp. 18 489–18 496, 2020.

[20] Y.-J. Chen, C. N. Takahashi, L. Organick, C. Bee, S. D. Ang, P. Weiss, B. Peck, G. Seelig, L. Ceze, and K. Strauss, "Quantifying molecular bias in DNA data storage," *Nature Communications*, vol. 11, no. 1, p. 3264, 2020.

[21] I. Shomorony and R. Heckel, "DNA-based storage: Models and fundamental limits," *IEEE Transactions on Information Theory*, vol. 67, no. 6, pp. 3675–3689, 2021.

[22] N. Weinberger and N. Merhav, "The DNA storage channel: Capacity and error probability bounds," *IEEE Transactions on Information Theory*, vol. 68, no. 9, pp. 5657–5700, 2022.

[23] A. Lenz, P. H. Siegel, A. Wachter-Zeh, and E. Yaakobi, "Coding over sets for DNA storage," *IEEE Transactions on Information Theory*, vol. 66, no. 4, pp. 2331–2351, 2020.

[24] R. Cao and X. Chen, "Optimizing sequencing coverage depth in DNA storage: Insights from DNA storage data," in *Proc. IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2025.

[25] S. Kas Hanna, "On the reliability of information retrieval from MDS coded data in DNA storage," *IEEE Transactions on Molecular, Biological, and Multi-Scale Communications*, vol. 12, pp. 585–598, 2026.

[26] M. Loose, S. Malla, and M. Stout, "Real-time selective sequencing using nanopore technology," *Nature Methods*, vol. 13, no. 9, pp. 751–754, 2016.

[27] A. Payne, N. Holmes, T. Clarke, R. Munro, B. J. Debebe, and M. Loose, "Readfish enables targeted nanopore sequencing of gigabase-sized genomes," *Nature Biotechnology*, vol. 39, no. 4, pp. 442–450, 2021.

[28] L. Weilguny, N. De Maio, R. Munro, C. Manser, E. Birney, M. Loose, and N. Goldman, "Dynamic, adaptive sampling during nanopore sequencing using Bayesian experimental design," *Nature Biotechnology*, vol. 41, no. 7, pp. 1018–1025, 2023.

[29] D. J. Russo, B. Van Roy, A. Kazerouni, I. Osband, and Z. Wen, "A tutorial on Thompson sampling," *Foundations and Trends in Machine Learning*, vol. 11, no. 1, pp. 1–96, 2018.

[30] T. Lattimore and C. Szepesvári, *Bandit Algorithms*. Cambridge University Press, 2020.

[31] S. Weil, S. Brandt, E. Miller, and C. Maltzahn, "CRUSH: Controlled, scalable, decentralized placement of replicated data," in *Proceedings of the 2006 ACM/IEEE Conference on Supercomputing (SC'06)*. IEEE, 2006, p. 31.

[32] A. Cidon, S. Rumble, R. Stutsman, S. Katti, J. Ousterhout, and M. Rosenblum, "Copysets: Reducing the frequency of data loss in cloud storage," in *2013 USENIX Annual Technical Conference (USENIX ATC '13)*. San Jose, CA, USA: USENIX Association, 2013, pp. 37–48. [Online]. Available: https://www.usenix.org/conference/atc13/technical-sessions/presentation/cidon

[33] D. Ford, F. Labelle, F. I. Popovici, M. Stokely, V.-A. Truong, L. Barroso, C. Grimes, and S. Quinlan, "Availability in globally distributed storage systems," in *9th USENIX Symposium on Operating Systems Design and Implementation (OSDI '10)*. Vancouver, BC, Canada: USENIX Association, 2010. [Online]. Available: https://www.usenix.org/conference/osdi10/availability-globally-distributed-storage-systems

[34] S. Nath, H. Yu, P. B. Gibbons, and S. Seshan, "Subtleties in tolerating correlated failures in wide-area storage systems," in *3rd USENIX Symposium on Networked Systems Design and Implementation (NSDI '06)*. San Jose, CA, USA: USENIX Association, 2006. [Online]. Available: https://www.usenix.org/conference/nsdi-06/subtleties-tolerating-correlated-failures-wide-area-storage-systems

[35] D. Leong, A. G. Dimakis, and T. Ho, "Distributed storage allocations," *IEEE Transactions on Information Theory*, vol. 58, no. 7, pp. 4733–4752, 2012.

[36] T. Batu, S. Kannan, S. Khanna, and A. McGregor, "Reconstructing strings from random traces," in *Proceedings of the 15th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, New Orleans, LA, USA, 2004, pp. 910–918.

[37] S. R. Srinivasavaradhan, S. Gopi, H. D. Pfister, and S. Yekhanin, "Trellis BMA: Coded trace reconstruction on IDS channels for DNA storage," in *Proc. IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2021, pp. 2453–2458.

[38] O. Sabary, A. Yucovich, G. Shapira, and E. Yaakobi, "Reconstruction algorithms for DNA-storage systems," *Scientific Reports*, vol. 14, no. 1, p. 1951, 2024.

[39] C. Rashtchian, K. Makarychev, M. Racz, S. Ang, D. Jevdjic, S. Yekhanin, L. Ceze, and K. Strauss, "Clustering billions of reads for DNA data storage," in *Advances in Neural Information Processing Systems 30 (NIPS 2017)*, 2017. [Online]. Available: https://papers.nips.cc/paper_files/paper/2017/hash/ab7314887865c4265e896c6e209d1cd6-Abstract.html

[40] D. Bar-Lev, I. Orr, O. Sabary, T. Etzion, and E. Yaakobi, "Scalable and robust DNA-based storage via coding theory and deep learning," *Nature Machine Intelligence*, vol. 7, no. 4, pp. 639–649, 2025.

[41] C. Delahaye and J. Nicolas, "Sequencing DNA with nanopores: Troubles and biases," *PLOS ONE*, vol. 16, no. 10, p. e0257521, 2021.

[42] R. R. Wick, L. M. Judd, and K. E. Holt, "Performance of neural network basecalling tools for Oxford Nanopore sequencing," *Genome Biology*, vol. 20, no. 1, p. 129, 2019.

[43] S. Bubeck, D. Ernst, and A. Garivier, "Optimal discovery with probabilistic expert advice: Finite time analysis and macroscopic optimality," *Journal of Machine Learning Research*, vol. 14, no. 17, pp. 601–623, 2013. [Online]. Available: https://www.jmlr.org/papers/v14/bubeck13a.html

[44] FML, ETH Zurich, "DT4DDS – characterization of errors and biases in DNA data storage," European Nucleotide Archive, study PRJEB65931, 2023, sequencing data of Gimpel et al., Nat. Commun. 14:6026 (2023); first public 2023-09-08. [Online]. Available: https://www.ebi.ac.uk/ena/browser/view/PRJEB65931

[45] I. S. Reed and G. Solomon, "Polynomial codes over certain finite fields," *Journal of the Society for Industrial and Applied Mathematics*, vol. 8, no. 2, pp. 300–304, 1960.

[46] B. Efron and R. J. Tibshirani, *An Introduction to the Bootstrap*. Springer US, 1993.

[47] C. J. Clopper and E. S. Pearson, "The use of confidence or fiducial limits illustrated in the case of the binomial," *Biometrika*, vol. 26, no. 4, pp. 404–413, 1934.

[48] T. Gneiting and A. E. Raftery, "Strictly proper scoring rules, prediction, and estimation," *Journal of the American Statistical Association*, vol. 102, no. 477, pp. 359–378, 2007.

[49] Technion – Israel Institute of Technology, "Binned Nanopore/Illumina reads from DNAformer, split by the data type," Zenodo dataset, 2025. [Online]. Available: https://doi.org/10.5281/zenodo.17473983