NeuroBot: An EEG-Based Deep Learning Pipeline for Movement- and Finger-Level Intention Decoding and Deployment

A Development Report, from Base Paper to Current Status

Veeravajhula Sai Phani Anirudh
B.Tech CSE student
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
saiphanianirudh@gmail.com
ORCID: 0009-0003-0562-3098

Chaganti Sreevatsalya
B.Tech CSE student
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
sreevatsalyachaganti@gmail.com
ORCID: 0009-0007-8825-5348

Ulindala Trinath
B.Tech CSE student
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
ulindalatrinath@gmail.com
ORCID: 0009-0008-6428-8927

Bashetty Sumukh
B.Tech CSE student
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
sumukhbashetty@gmail.com
ORCID: 0009-0006-1503-3448

Majji Kiran
B.Tech CSE student
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
majjikiran8@gmail.com
ORCID: 0009-0005-5628-4086

A. Shilpa Gupta
Faculty Mentor
Keshav Memorial College of Engineering
Koheda Road, Chintpalliguda(V), Ibrahimpatnam(M), R.R.Dist-501510, Telangana, India
a.shilpagupta@gmail.com

***Abstract*—This report describes NeuroBot, an EEG brain-computer interface that we trained ourselves. We were motivated by the real-time finger-level robotic hand control of Ding *et al.* [1], so we began with two limb-level decoders (left fist, right fist or rest; both fists, both feet or rest) on the PhysioNet Motor Movement/Imagery Database [2], [3]. We used EEGNet [4] and the convolutional transformer TCFormer [5] (through Braindecode [6]), each trained with a per-subject pretrain and fine-tune protocol. Over eleven iterations we found and fixed two leaks in our evaluation split, one caused by subject order and one by overlapping windows. On ten subjects with a trial-level split, TCFormer with cross-subject pretraining and three-seed averaging reaches group-mean majority-vote accuracies of 74.4% and 70.0% for Task A and 86.7% and 71.1% for Task B (executed and imagined movement; chance 33.3%). Compared with the same model trained without pretraining, the gain is significant only for Task B executed movement (+7.8 points, p = 0.003). A single-subject pilot on the finger dataset [7] reaches 79.9% for two fingers and 44.6% for three fingers on executed movement. The system is deployed as a software-only three-tier web service with no external API. Code: https://github.com/SaiPhaniAnirudh/NeuroBot.**

***Index Terms*—Electroencephalography (EEG), Brain-Computer Interface (BCI), Motor Imagery, Motor Execution, EEGNet, Transformer, TCFormer, Deep Learning, PhysioNet, Finger-Level Decoding, Deployment.**

1. Introduction

Brain-computer interfaces (BCIs) turn neural activity into control signals. They can give people with motor impairment a way to communicate and operate devices, and they offer anyone a new way to interact with computers [8]. Invasive BCIs record from inside the brain or from its surface. They offer high spatial precision, but they require surgery. Noninvasive BCIs based on scalp EEG can reach far more people. So far, though, they have mostly been limited to coarse control such as whole-limb movement, binary choices or slow spelling, because closely spaced neural sources are hard to separate in scalp recordings. Executed and imagined movement both change the sensorimotor rhythms over the motor cortex (event-related desynchronization and synchronization) [9], [10], and motor-imagery BCIs learn to decode that signal [11].

NeuroBot started as our attempt to rebuild such a decoding pipeline on our own, using models we trained ourselves and no external API or pretrained third-party service. We tested the approach on limb-level motor tasks first and moved to the finger-level task of the base paper afterwards. Fig. 1 shows the pipeline from raw EEG to the output the user sees.




Fig. 1. End-to-end NeuroBot pipeline: input, preprocessing, deep model, decision, and application output.

The rest of this report is organized as follows. Section 2 reviews related work, Section 3 states the problem and scope, Section 4 describes the datasets, and Section 5 explains the

methodology. Section 6 gives the development history, Section 7 summarizes the results, and Section 8 describes the software and how it is deployed. Sections 9, 10 and 11 cover limitations, future work and the conclusion.

1.1 The Base Paper

Ding, Udompanyawit, Zhang, and He [1] recorded 128-channel EEG (BioSemi ActiveTwo, 1024 Hz, international 10-20 placement) from 21 right-handed subjects who were experienced BCI users. The subjects made cued finger movements, either physically executed (ME) or imagined (MI), over one offline session and several online sessions each. A deep convolutional network (EEGNet [4]) was trained for each subject and fine-tuned online. It decoded 1-second windows into finger classes that moved a robotic hand in real time. In the offline sessions the four fingers of the right hand (thumb, index, middle and pinky) were each flexed and extended repeatedly, or imagined being so. The online tasks used thumb versus pinky (two fingers) and thumb, index and pinky (three fingers). The study reports online accuracies of 81.10% (executed) and 80.56% (imagined) for two fingers and 60.11% and 60.61% for three fingers. It also finds that fingers which activate more distinct cortical regions, such as thumb and pinky, are easier to tell apart than neighboring fingers.

The authors released both the dataset and their training code, so we read both rather than guess at the methodology. The dataset (KiltHub/Figshare, DOI 10.1184/R1/29104040 [7]) is about 502.77 GB for 21 subjects, stored as per-subject FieldTrip-style MATLAB files with event markers. The code release (github.com/bfinl/FingerBCI-Decoding) shows the preprocessing they used: 1-second windows, downsampling from 1024 Hz to 100 Hz, a 4–40 Hz band-pass filter, and EEGNet hyperparameters F1=8, D=2, F2=16 and a temporal kernel length of 32. We adopted these values for our own EEGNet (Section 5.2). The code covers only two- and three-class setups. It has no four-finger configuration.

1.2 Novelty: How This Work Differs from the Base Paper

The base paper [1] describes a human-in-the-loop system. Subjects wore a 128-channel cap over several sessions, received real-time feedback, and had a fine-tuning mechanism update the network online while it moved a physical robotic hand. Our work differs from it in scope and in what it contributes.

- Open data, offline, no hardware. We train and evaluate offline on public data: 64-channel PhysioNet recordings for limb-level tasks, and the base paper's own released dataset for a single-subject finger pilot. There is no online closed-loop training and no physical robot (Section 3.2).
- A new model comparison. The base paper uses EEGNet. We also use TCFormer, a convolutional transformer, and compare the two under a single protocol. In addition, we correct a token bottleneck that appears when TCFormer is applied to short 1-second windows (Section 5.2).
- A hybrid protocol and an open evaluation. We pretrain one model on pooled executed and imagined data, fine-tune a specialist for each mode, and evaluate by whole trial. We report how two leaks in our own split inflated early results, and we measure the effect of cross-subject pretraining against a same-protocol baseline with three seeds (Sections 5.3, 6 and 7).
- A deployed software system. The trained models are exported to ONNX and served by a FastAPI back end on a Hugging Face Space, with a Vercel-hosted 3D Decode Console that replays held-out trials, and the system has automated tests (Section 8).

We do not claim better accuracy than the base paper. Its finger-level results come from 21 subjects with online fine-tuning, while ours come from ten subjects for limb-level tasks and one subject for fingers, so the numbers are not comparable (Section 7).

2. Related Work

Classical and deep-learning decoders. Early motor-imagery BCIs relied on hand-engineered spectral-spatial features fed to linear or kernel classifiers; the field has since moved toward end-to-end deep learning, as surveyed in [12], [13]. Schirrmeister *et al.* showed that deep and shallow convolutional networks trained on raw EEG can match filter-bank common spatial patterns on movement decoding [14]. EEGNet [4] is a compact network built from a temporal convolution, a depthwise spatial convolution, and a separable convolution, and has become a standard baseline across BCI paradigms because of its small parameter count.

Attention-based decoders. The Transformer [15] models long-range dependencies with self-attention. EEG Conformer [16] puts a self-attention module after a temporal-spatial convolution module, so it can capture global relations among local temporal features. TCFormer [5] combines a multi-kernel convolutional front end, a Transformer encoder with grouped-query attention [17] and rotary position embeddings [18], and a temporal convolutional network (TCN) classification head [19].

Noninvasive robotic control. Edelman *et al.* demonstrated continuous, noninvasive EEG-based control of a robotic arm, using EEG source imaging to improve decoding [20]; Ding *et al.* [1] extend noninvasive control to the individual-finger level.

Training practice and tooling. Transformer-style training commonly uses the Adam optimizer [21] with decoupled weight decay (AdamW) [22], a warm-up followed by cosine learning-rate decay [23], and label smoothing [24]. We use PyTorch [25] and MNE-Python [26] for EEG handling, and take TCFormer from Braindecode [6]. Relative to this literature, NeuroBot adds three things: (i) a per-subject hybrid pretrain/fine-tune protocol, a form of transfer learning [27], applied to a CNN and a CNN-Transformer; (ii) a documented diagnosis and fix of a self-attention token bottleneck when TCFormer is applied to short windows; and (iii) a software-only deployment of the trained models with no external API.

3. Problem Statement and Scope

3.1 Problem Statement

The goal is a pipeline that we train ourselves and that decodes movement intention from EEG. It should work for coarse limb-level tasks and for the finger-level task of the base paper, without an external API, a cloud inference service or a pretrained third-party model. If we can get useful accuracy from raw EEG all the way to a working software output, we will have taken a small but reproducible step toward more accessible noninvasive assistive BCIs.

3.2 Scope

In scope:

- EEG preprocessing: common-average referencing, band-pass filtering, sliding-window segmentation, per-window normalization.
- Limb-level decoding on PhysioNet eegmmidb: left-fist/right-fist/rest (Task A) and both-fists/both-feet/rest (Task B).
- Finger-level decoding on the base paper's released dataset: a single-subject pilot (subject S01) in the 2- and 3-finger configurations.
- Two model architectures—EEGNet (CNN) and TCFormer (CNN-Transformer hybrid)—compared head to head under the earlier window-level split (v7–v8); under the final trial-level split both TCFormer and EEGNet are evaluated on both tasks (v11).
- A per-subject hybrid pretrain/fine-tune training protocol developed for this project.
- A software backend (REST + WebSocket API) and a browser-based Decode Console, deployed as a two-part web service (front end on Vercel, back end on a Hugging Face Space) and also runnable on a laptop.

Out of scope:

- Physical robotic hardware or actuation—the system is deliberately software-only.
- Real-time, in-session closed-loop neurofeedback training of the kind used in the base paper's online sessions.
- Clinical trials or evaluation on a patient population.
- Any call to an external large language model or third-party inference API.

4. Datasets

4.1 PhysioNet EEG Motor Movement/Imagery Database (eegmmidb)

The eegmmidb corpus [2], collected with the BCI2000 system [3], provides 64-channel EEG at 160 Hz from 109 subjects performing and imagining left/right fist movements and both-fists/both-feet movements, cued by on-screen prompts (T0 = rest; T1/T2 = the two movement classes for a given run). Five subjects (88, 92, 100, 104, 106) are excluded throughout this project because their recordings have known annotation anomalies; the curated release of the dataset [30] also drops them.

4.2 Finger-Level Dataset

The base paper's own dataset [7] provides 128-channel EEG across 21 subjects performing individual-finger ME and MI tasks, with an explicit real-time decoding log recorded alongside the raw EEG for each online session. This project evaluates the two configurations of the base paper's validated pipeline—two-finger (thumb/pinky) and three-finger (thumb/index/pinky)—on one subject, S01, the only subject that could be downloaded (16.46 GB of the 502.77 GB corpus). The exploratory four-finger configuration (thumb/index/middle/pinky), which is not part of the authors' validated pipeline, is not supported by the session-held-out protocol used here: the middle finger was recorded only in the offline session, so no later session can serve as a held-out test set. It was not attempted.

5. Proposed Methodology

5.1 Preprocessing

Each recording $\mathbf{x}$ with C channels and T samples is re-referenced to the common average (1), band-pass filtered to 4–40 Hz (FIR), and segmented into overlapping windows of W = 160 samples (1 s at 160 Hz) with a step of s = 20 samples (125 ms), matching the temporal resolution of the base paper's released code. The number of windows per recording is given by (2).

$$\tilde{x}_c(t) = x_c(t) - \frac{1}{C}\sum_{j=1}^{C} x_j(t) \tag{1}$$

$$N_w = \left\lfloor \frac{T-W}{s} \right\rfloor + 1, \quad W = 160,\ s = 20 \tag{2}$$

Each window is then independently z-score normalized per channel (3), where μ_c and σ_c are the mean and standard deviation of channel c within the window and ε is a small constant for numerical stability. Every window retains a trial identifier, enabling trial-level majority-vote evaluation (Section 5.4) in addition to raw per-window accuracy.

$$z_{c,t} = \frac{x_{c,t} - \mu_c}{\sigma_c + \varepsilon} \tag{3}$$

5.2 Model Architectures

EEGNet [4] is a compact convolutional network using depthwise and separable convolutions. Its hyperparameters were corrected during development to match the base paper's values (F1=8, D=2, F2=16, temporal kernel length 32; Table I), which are also those of the official Finger-BCI-Decoding release.

TCFormer [5] is a temporal-convolutional Transformer combining a multi-kernel CNN front end, a grouped-query-attention Transformer encoder, and a TCN classification head, accessed through its maintained implementation in Braindecode [6]. The encoder applies scaled dot-product self-attention (4), with d_k the key dimension.

$$\mathrm{Attn}(Q,K,V)=\mathrm{softmax}\left(\frac{QK^{\top}}{\sqrt{d_k}}\right)V \tag{4}$$

Direct inspection of the model's internal tensor shapes on this project's 160-sample (1 s) windows revealed that TCFormer's published default pooling configuration collapses the self-attention sequence to only two temporal tokens—an artifact of its benchmarks having used substantially longer (4–4.5 s) windows. The token count is approximately given by (5), where P_1 and P_2 are the two pooling lengths.

$$N_{tok}\approx\left\lfloor\frac{W}{P_1P_2}\right\rfloor \tag{5}$$

Reducing the pooling lengths to P_1=4 and P_2=2 restores twenty tokens at an identical parameter count (85,816), and was adopted as a targeted, empirically verified correction rather than a general hyperparameter search. The same relation predicts that a 2 s window (W=320) yields forty tokens, which motivates the window-length ablation in Section 6.

TABLE I
KEY CONFIGURATION VALUES

Parameter	Value
Sampling rate / EEG channels (eegmmidb)	160 Hz / 64
Band-pass filter	4–40 Hz (FIR)
Window / step	160 samples (1 s) / 20 samples (125 ms)
EEGNet F1 / D / F2 / kernel	8 / 2 / 16 / 32
Fine-tune dropout (all models)	0.65
TCFormer pooling (P_1, P_2)	4, 2 (default gives 2 tokens)
TCFormer parameters	85,816
Self-attention tokens	20 (1 s) / 40 (2 s ablation)
Split (per mode, by whole trial)	first 60% of trials pretrain; remaining 40% split 20% fine-tune / 20% evaluation
Excluded subjects	88, 92, 100, 104, 106

5.3 Hybrid Pretrain/Fine-Tune Protocol

A protocol was developed specifically for this project to address limited per-subject data. For each subject, let D_{ME} and D_{MI} be the windows from movement-execution and motor-imagery runs, and let K=3 be the number of classes. All training minimizes a class-weighted, label-smoothed cross-entropy (6), with smoothed targets and inverse-frequency class weights given by (7), where N_k is the number of training windows of class k and ε is the smoothing factor (ε=0 for EEGNet).

$$\mathcal{L}(\theta;\mathcal{D})=-\frac{1}{|\mathcal{D}|}\sum_{i\in\mathcal{D}}w_{y_i}\sum_{k=1}^{K}q_{ik}\log p_\theta(k\mid x_i) \tag{6}$$

$$q_{ik}=(1-\varepsilon)\,\mathbb{1}[k=y_i]+\frac{\varepsilon}{K},\qquad w_k=\frac{N}{KN_k} \tag{7}$$

Stage 1 (pretraining). A single base model is pretrained on the pooled movement-execution and motor-imagery data (8), which preserves data volume.

$$\theta_0=\arg\min_{\theta}\mathcal{L}(\theta;\mathcal{D}_{ME}\cup\mathcal{D}_{MI}) \tag{8}$$

Stage 2 (fine-tuning). The base model is cloned and independently fine-tuned into two mode-specialist copies (9), one for ME and one for MI, each evaluated only on held-out data of its own mode. Within each mode's block, trials are ordered chronologically and split by whole trial: the first 60% form the pretraining pool, and the remaining 40% are divided by stratified sampling into 20% fine-tuning and 20% held-out evaluation trials. Validation sets for early stopping are also drawn by trial (15% of the pretraining trials and 20% of the fine-tuning trials). The split is made per mode because a single global chronological split would place an entire mode in the evaluation set (Section 6, v5). Splitting by trial matters: consecutive windows overlap by 87.5%, so a window-level split lets near-duplicate windows of one trial appear in both fine-tuning and evaluation data (Section 6, v10).

$$\theta_m=\arg\min_{\theta}\mathcal{L}(\theta;\mathcal{D}_m),\quad \theta^{(0)}=\theta_0,\ m\in\{ME,MI\} \tag{9}$$

Optimization. EEGNet is trained with Adam [21] and ReduceLROnPlateau scheduling. TCFormer additionally uses AdamW (10) [22], where $\hat{m}_t$ and $\hat{v}_t$ are the bias-corrected first and second moment estimates and λ is the decoupled weight-decay coefficient, together with a linear-warmup/cosine-decay learning-rate schedule (11) over T steps with T_w warm-up steps [23] and label smoothing [24]—standard Transformer training practice not applied to EEGNet, whose tuning was left undisturbed. For TCFormer, $\eta_{\max}=5\times10^{-4}$ for pretraining and 3×10^{-4} for fine-tuning, $\eta_{\min}=0$, T_w is 10% of the total steps, $\lambda=10^{-2}$, and $\varepsilon=0.1$; the batch size is 16, and training runs for at most 250 (pretraining) and 100 (fine-tuning) epochs with early-stopping patience 25 and 18. EEGNet uses Adam with learning rates of 10^{-3} and 5×10^{-4}, ReduceLROnPlateau (factor 0.5, patience 8), at most 150 and 60 epochs, and patience 20 and 12. During fine-tuning, dropout is set to 0.65 and only the last 50% (TCFormer) or 30% (EEGNet) of the parameters are updated. Training batches are augmented with Gaussian noise ($\sigma=0.05$) and a random circular time shift of up to ±8 samples. Early stopping and learning-rate scheduling use validation trials held out from the training trials; the evaluation trials are never used for gradient updates or early stopping. Light augmentation (additive noise and time shift) is applied to training data only.

$$\theta_{t+1}=\theta_t-\eta_t\left(\frac{\hat{m}_t}{\sqrt{\hat{v}_t}+\varepsilon}+\lambda\theta_t\right) \tag{10}$$

$$\eta_t=\eta_{max}\frac{t}{T_w},\qquad t<T_w \tag{11a}$$

$$\eta_t=\eta_{min}+\tfrac{1}{2}(\eta_{max}-\eta_{min})\left[1+\cos\left(\pi\frac{t-T_w}{T-T_w}\right)\right],\quad t\geq T_w \tag{11b}$$

5.4 Evaluation Methodology

Two accuracy metrics are reported throughout. The raw per-window accuracy is (12), where $\hat{y}_i$ and y_i are the predicted and true labels of window i.

$$\mathrm{Acc}_{win} = \frac{1}{N_w} \sum_{i=1}^{N_w} \mathbb{1}[\hat{y}_i = y_i] \tag{12}$$

The trial-level majority-vote accuracy matches the base paper's own primary metric: every window in the set W_τ belonging to trial τ casts a vote, and the trial's predicted label is the majority class (13); the accuracy is the fraction of trials labelled correctly (14), where N_τ is the number of trials.

$$\hat{y}_\tau = \arg\max_k \sum_{i \in W_\tau} \mathbb{1}[\hat{y}_i = k] \tag{13}$$

$$\mathrm{Acc}_{trial} = \frac{1}{N_\tau} \sum_{\tau=1}^{N_\tau} \mathbb{1}[\hat{y}_\tau = y_\tau] \tag{14}$$

Because one model is trained per subject, results are reported as the group mean and standard deviation of per-subject accuracy A_s over S subjects (15). With K=3 classes, chance level is $1/K$ = 33.3%.

$$\bar{A} = \frac{1}{S} \sum_{s=1}^{S} A_s, \qquad \sigma_A = \sqrt{\frac{1}{S} \sum_{s=1}^{S} (A_s - \bar{A})^2} \tag{15}$$

6. Development Timeline

The method changed over eleven iterations. Several of these were fixes for real methodological errors rather than hyperparameter tuning. We report the whole history so that others can reproduce it and see where things went wrong. Fig. 2 shows the three-tier software architecture that the models are deployed in, and Table II lists every iteration with its result.




Fig. 2. NeuroBot three-tier architecture: presentation (Decode Console), application and ML logic (FastAPI server, preprocessing pipeline, EEGNet and TCFormer pathways, majority vote), and data and storage (EEG datasets, model checkpoints, decode logs). The system is software-only, uses self-trained models, and calls no external API.

Table II
Development timeline, v1 to v11

#	Change	Result
v1	Single-subject EEGNet baseline (3-class left/rest/right).	64.2% per-window accuracy (chance = 33%).
v2	10-subject pooled training; later found to leak subject identity across the train/test split (pooled subjects were split by raw index, so the model trained on early subjects and was evaluated on unseen later ones).	~57% on both tasks—discarded once diagnosed as cross-subject transfer rather than genuine within-subject accuracy.
v3	Per-subject methodology (one model per subject, matching the base paper); leakage bug fixed.	Task A 65.2%, Task B 68.9% (10-subject majority-vote means).

#	Change	Result
v4	Fully separated ME and MI models (no pooling).	Task A 59.8% on average—a regression, diagnosed as data starvation (each mode loses half its training runs).
v5	Hybrid pretrain (pooled) / fine-tune (per-mode) protocol introduced; within-mode 70/30 split fix.	Task A ME 74.1% / MI 66.3%; Task B ME 76.3% / MI 71.1%.
v6	Ensemble of ME- and MI-specialist EEGNet models (same architecture).	Accuracy fell by 1.9–4.6 points in the original run and by 0.7–0.9 points in a later rerun—discarded as no improvement; diagnosed as averaging in an unreliable off-mode opinion.
v7	TCFormer introduced via Braindecode, same hybrid protocol.	Beat EEGNet on all four task/mode conditions in a like-for-like re-run (+3.7 to +17.4 points); flagship best-subject exports of 81.4% / 86.4% per-window accuracy. Window-level split; not repeated under the trial-level split.
v8	TCFormer pooling-bottleneck fix (2 → 20 tokens) plus AdamW, warm-up, cosine decay, and label smoothing.	Window-level split. Group means: Task A ME 75.2% / MI 65.2%; Task B ME 80.7% / MI 75.6%. Flagship fine-tune validation accuracy 86.8% (Task A) / 95.6% (Task B).
v9	Window-length ablation (1 s → 2 s windows, 20 → 40 self-attention tokens at identical parameter count), TCFormer only, Task A, four subjects. A planned cross-architecture EEGNet+TCFormer ensemble was dropped when EEGNet runs were removed to cut training time from 5–7 h.	Inconclusive: 2 s windows changed executed-movement accuracy by −4.2 points and imagined-movement accuracy by +2.8 points, within run-to-run noise. Not scaled up.
v10	Audit of the fine-tune/evaluation split: overlapping windows of one trial appeared on both sides of the window-level split. Replaced by a split by whole trial (60% / 20% / 20%) with larger evaluation sets (about 18 trials per subject and mode); TCFormer only.	Group means (10 subjects): Task A ME 65.6% / MI 60.0%; Task B ME 70.0% / MI 59.4%. An earlier independent run of the same code gave Task A 58.9% / 57.2% and Task B ME 76.1%.
v11	Cross-subject pretraining (notebook v5): TCFormer and EEGNet each pretrained once on 30 other subjects (S011–S040), then trained per subject with three seeds averaged; EEGNet re-run under the trial-level split; automatic leakage checks; Tasks A and B. Baseline arm (notebook v6): TCFormer without pretraining, same trials and seeds.	Group means (10 subjects), Task A: TCFormer ME 74.4% / MI 70.0%; EEGNet 75.0% / 61.7%. Task B: TCFormer ME 86.7% / MI 71.1%; EEGNet 78.9% / 65.0%. Same-protocol baseline without pretraining: A ME 66.1% / MI 61.7%; B ME 78.9% / MI 71.1%. Gain +8.3 / +8.3 (not significant) on A; +7.8 (p = 0.003) / 0.0 on B.

Note: EEGNet figures (v1–v7) come from separate runs under earlier splits; EEGNet was re-run under the final trial-level split with cross-subject pretraining for both tasks (v11, Tables VI and VII). The like-for-like window-level comparison is in Table V.

Five lessons came out of this history. First, the v2 result of about 57% on both tasks looked too similar across tasks to be believable, and checking it led us to the subject-order leak. After the fix, Task B (both fists or feet) again scored higher than Task A, as the physiology would suggest. Second, separating ME and MI completely (v4) cost more through lack of data than it gained through specialization, so we moved to the hybrid protocol. Third, the hybrid protocol exposed a second bug: the data were loaded as one block of ME followed by one block of MI, so a single chronological split left one mode with no training data. We now split within each mode. Fourth, averaging in a specialist for the other mode (v6) made results worse, so the ME and MI models stay separate. Fifth, an audit showed that overlapping windows from the same trial ended up on both sides of the fine-tune/evaluation split. Splitting by whole trial lowered the executed-movement group means from 75.2% and 80.7% to 65.6% and 70.0% (Section 7). Leakage of this kind is common in deep-learning EEG studies [28] and should be checked for before any accuracy is reported.

7. Results Summary

Table III gives the trial-level evaluation of TCFormer on ten subjects: the group-mean majority-vote accuracy and its spread across subjects, with about 18 held-out trials per subject and mode. Task A is left fist, right fist or rest, and Task B is both fists, both feet or rest. Fig. 3 plots the means against chance and the 85% target.

TABLE III
TCFORMER, TRIAL-LEVEL SPLIT: MAJORITY-VOTE ACCURACY (%), TEN SUBJECTS

Task / mode	Mean	Std.	Min	Max	Subjects ≥ 85%
Task A – ME	65.6	15.9	44.4	88.9	1
Task A – MI	60.0	14.0	38.9	88.9	1
Task B – ME	70.0	25.6	22.2	100.0	2
Task B – MI	59.4	18.9	27.8	94.4	1




Fig. 3. Group-mean majority-vote accuracy (± std. across subjects) under the trial-level split: TCFormer without pretraining (light bars, three-seed average, Table VIII) and with cross-subject pretraining (dark bars, Tables VI and VII), with the earlier window-level-split means (diamonds), chance (33.3%), and the 85% target.

All four single-run group means (Table III) are well above the 33.3% chance level and below the 85% target. The differences between subjects matter most. Task B executed-movement accuracy ranges from 22.2% to 100%, and in each condition only one or two subjects reach 85%. Two subjects (S006 and S009) score below chance on Task B executed movement; with only 18 trials, that is within sampling noise for a subject whose signal the model cannot use. Imagined movement is lower than executed movement in both tasks (by 5.6 and 10.6 points).

TABLE IV
EFFECT OF SPLITTING BY TRIAL: GROUP-MEAN ACCURACY (%)

Task / mode	Window-level split	Trial-level split	Change
Task A – ME	75.2	65.6	−9.6
Task A – MI	65.2	60.0	−5.2
Task B – ME	80.7	70.0	−10.7
Task B – MI	75.6	59.4	−16.2

Table IV compares the earlier window-level split with the final trial-level split. A drop of 5–16 points is what we would expect once near-duplicate windows are removed from the evaluation data. The table does not measure leakage cleanly, because the two protocols also differ in split proportions (70/15/15 versus 60/20/20) and in evaluation-set size, and each figure comes from a single run.

EEGNet versus TCFormer. The comparison rests on two earlier head-to-head runs with the window-level split (Table V; Section 6, v7–v8) and one run per task under the trial-level split with cross-subject pretraining (Tables VI and VII). TCFormer scored higher in all eight comparisons, by 3.7 to 17.4 points (mean 12.1), although EEGNet itself varied by up to 8.1 points between the two runs. Both runs used the window-level split, so they show only which architecture ranks higher under that protocol and do not estimate the gap under the trial-level split. In the trial-level runs with cross-subject pretraining the gap is smaller and depends on task and mode. For Task A it is 8.3 points on imagined movement and none on executed movement. For Task B it is 7.8 points on executed movement (significant) and 6.1 on imagined movement (not significant) (Tables VI and VII).

TABLE V
EEGNET VERSUS TCFORMER, WINDOW-LEVEL SPLIT: GROUP-MEAN MAJORITY-VOTE ACCURACY (%), TWO INDEPENDENT RUNS

Task / mode	EEGNet run 1	TCFormer run 1	EEGNet run 2	TCFormer run 2
Task A – ME	68.5	72.2	60.4	76.7
Task A – MI	58.9	68.5	57.0	69.3
Task B – ME	68.5	80.7	70.7	81.5
Task B – MI	57.8	75.2	61.1	75.9

Run-to-run variation. We did not seed the model initialization or batch order, while the data split is fixed. Two independent runs of the same trial-level code gave Task A means of 58.9% (ME) and 57.2% (MI) the first time and 65.6% and 60.0% the second time, and Task B executed-movement means of 76.1% and 70.0%. The group means differ by up to 6.7 points. For Task A executed movement, the per-subject difference between the two runs has a standard deviation of 12.4 points (maximum 22.2), even though the runs are correlated (r=0.71). A difference of a few points between conditions therefore cannot be interpreted from single runs.

Pilot: seed averaging and cross-subject pretraining. We first ran a pilot on Task A with subjects S001–S004, two seeds and the same held-out trials. It compared the trial-level recipe with a variant that pretrains TCFormer on 20 other subjects (never an evaluated subject) before the per-subject stages. With the softmax outputs of the two seeds averaged, executed- and imagined-movement accuracy was 69.4% and 68.1% for the baseline and 75.0% and 75.0% with cross-subject pretraining, a paired gain of +5.6 and +6.9 points. Three of the four subjects improved in each mode, and the seed-to-seed variability was mixed. With four subjects and about 18 trials each, the paired standard errors are roughly 6 and 5 points, so the result is suggestive rather than conclusive. The ten-subject Task A run below extends it.

Cross-subject pretraining on ten subjects (Task A). We extended the pilot to all ten subjects of Task A (Table VI). TCFormer and EEGNet were each pretrained once on 30 other subjects (S011–S040, every second window, never an evaluated subject). Each was then trained per subject with three seeds, whose softmax outputs were averaged, on the same trial-level split (18 held-out trials per subject). TCFormer reached 74.4% (ME) and 70.0% (MI), EEGNet 75.0% and 61.7%, and the equal-weight average of the two 75.6% and 69.4%. Against the single-run baseline of Table III this is +8.8 and +10.0 points for TCFormer. Two single runs of the same code already differ by up to 6.7 points, however, so we measure the effect of pretraining against a same-protocol baseline in Table VIII (+8.3 points in both modes, not significant). Seed averaging does not explain the gain: it moved group means by only 0.8–1.7 points (mean single-seed accuracy: TCFormer 75.2% and 69.1%, EEGNet 73.3% and 63.3%). On the pilot's four subjects this run gave 68.1% (ME) and 81.9% (MI), against 75.0% and 75.0% in the pilot (30 versus 20 pretraining subjects, three versus two seeds). That is another reminder of the run-to-run spread. TCFormer beat EEGNet by 8.3 points on MI (paired t-test p = 0.048, Wilcoxon p = 0.078; better for 6, equal for 3 and worse for 1 of 10 subjects) and matched it on ME (−0.6 points, p = 0.88). The ensemble did not improve on TCFormer alone (+1.1 and −0.6 points). Three subjects (S005, S006, S009) are not above chance on MI by an exact binomial test (at least 10 of 18 trials are needed), while all ten are above chance on ME. Per-subject ME and MI accuracies are uncorrelated in this task (r = 0.02, n = 10, so only a rough indication). Task B follows in Table VII.

TABLE VI
TASK A, CROSS-SUBJECT PRETRAINING, THREE-SEED AVERAGING: MAJORITY-VOTE ACCURACY (%), TEN SUBJECTS

Model / mode	Mean	Std.	Min	Max	Subjects ≥ 85%
TCFormer ME	74.4	12.2	55.6	94.4	2

Model / mode	Mean	Std.	Min	Max	Subjects ≥ 85%
TCFormer MI	70.0	17.1	38.9	88.9	2
EEGNet ME	75.0	13.9	50.0	94.4	3
EEGNet MI	61.7	19.6	27.8	94.4	1
Ensemble ME	75.6	13.0	50.0	94.4	3
Ensemble MI	69.4	16.7	44.4	88.9	1

Cross-subject pretraining on ten subjects (Task B). We ran the same recipe on Task B (Table VII). TCFormer reached 86.7% (ME) and 71.1% (MI), EEGNet 78.9% and 65.0%, and the equal-weight average of the two 88.9% and 70.0%. Against the single-run baselines of Table III (70.0% and 59.4%) this looks like +16.7 and +11.7 points for TCFormer. The same-protocol baseline of Table VIII (78.9% and 71.1%) shows that most of that apparent gain was run-to-run variation: the real gain is +7.8 points on ME and none on MI. The 95% confidence interval of the TCFormer executed-movement mean is ±9.4 points across the ten subjects, so a true mean below the 85% target is not ruled out. All ten subjects are above chance on ME and eight of ten on MI. Seed averaging again changed group means by at most 0.6 points (mean single-seed accuracy: TCFormer 86.5% and 70.9%, EEGNet 78.3% and 65.0%). TCFormer beat EEGNet by 7.8 points on ME (paired t-test $p = 0.010$, Wilcoxon $p = 0.016$; better for 7 and equal for 3 of 10 subjects) and by 6.1 points on MI ($p = 0.21$, not significant). The ensemble was not reliably better than TCFormer alone (+2.2 points on ME, $p = 0.27$; −1.1 on MI). Per-subject ME and MI accuracies are moderately correlated in this task ($r = 0.55$, $n = 10$). Subjects S006 and S009 were at or below chance on MI in both tasks, but S009 reached 94.4% and 88.9% on ME. That suggests a weakness specific to imagery rather than a generally poor responder.

TABLE VII
TASK B, CROSS-SUBJECT PRETRAINING, THREE-SEED AVERAGING: MAJORITY-VOTE ACCURACY (%), TEN SUBJECTS

Model / mode	Mean	Std.	Min	Max	Subjects ≥ 85%
TCFormer ME	86.7	12.5	61.1	100.0	7
TCFormer MI	71.1	21.2	33.3	94.4	4
EEGNet ME	78.9	12.9	61.1	100.0	3
EEGNet MI	65.0	18.8	27.8	94.4	1
Ensemble ME	88.9	12.9	55.6	100.0	8
Ensemble MI	70.0	21.5	38.9	94.4	3

Same-protocol baseline (effect of cross-subject pretraining). To see what cross-subject pretraining adds, we retrained TCFormer without it (notebook v6) on the same ten subjects, with the same code, the same three seeds and the same 18 held-out trials per subject and mode (the split is deterministic). We then compared the seed-averaged results subject by subject with the pretrained runs of Tables VI and VII (Table VIII). The two arms ran in separate sessions, so GPU nondeterminism cannot be ruled out. On Task B executed movement, pretraining raised accuracy from 78.9% to 86.7% (+7.8 points). It helped 9 of 10 subjects, tied for 1 and hurt none (paired t-test $p = 0.003$, Wilcoxon $p = 0.004$), and the result survives a Bonferroni correction for the four comparisons (threshold 0.0125). On Task A the group mean rose by 8.3 points in both modes, but individual differences ranged from −16.7 to +44.4 points, and neither gain is significant with ten subjects ($p = 0.12$ and 0.11). On Task B imagined movement there was no gain (0.0 points, $p = 1.0$). The three-seed baseline sits 0.5 and 1.7 points above the single-run baselines of Table III on Task A, but 8.9 and 11.7 points above them on Task B. So about half of the +16.7 points on executed movement, and all of the +11.7 points on imagined movement, that we saw against Table III came from run-to-run variation.

Seed averaging raised the baseline by 4.1–5.2 points, but the pretrained models by at most 0.9 points (mean single-seed accuracy for Task A ME, A MI, B ME and B MI: baseline 61.9%, 56.5%, 74.4% and 67.0%; pretrained 75.2%, 69.1%, 86.5% and 70.9%). One pretrained seed is therefore about as good as the three-seed average, while single baseline runs are lower and less stable. Compared with single seeds, pretraining gains 12.0–13.3 points on the first three conditions (paired $p = 0.009$–0.033) and 3.9 points on Task B imagined movement ($p = 0.26$).

TABLE VIII
EFFECT OF CROSS-SUBJECT PRETRAINING ON TCFORMER: THREE-SEED MAJORITY-VOTE ACCURACY (%), MEAN ± STD OVER TEN SUBJECTS

Task / mode	No pretraining	Pretrained	Δ (pts)	Better / tie / worse	Paired t p
Task A – ME	66.1 ± 12.3	74.4 ± 12.2	+8.3	5 / 3 / 2	0.120
Task A – MI	61.7 ± 18.8	70.0 ± 17.1	+8.3	7 / 1 / 2	0.105
Task B – ME	78.9 ± 13.6	86.7 ± 12.5	+7.8	9 / 1 / 0	0.003
Task B – MI	71.1 ± 14.2	71.1 ± 21.2	0.0	5 / 2 / 3	1.000

Best-case subjects. The software demo uses the flagship models of S007 for Task A and S002 for Task B, trained with seed 0 and without cross-subject pretraining. On their 18 held-out trials, S007 reaches 83.3% (15 of 18) on executed and 100% (18 of 18) on imagined movement, with per-window accuracy of 72.4% and 77.8%. S002 reaches 100% (18 of 18) on executed and 88.9% (16 of 18) on imagined movement, with per-window accuracy of 84.9% and 63.1%. The three Task A executed-movement errors were two rest trials and one left-fist trial, all labelled right fist. The two Task B imagined-movement errors were one both-feet trial labelled rest and one rest trial labelled both-fists. These are best-case results for single subjects, chosen on the evaluation data, so they are optimistic. They are also not directly comparable with the base paper's group-level finger-decoding accuracies (two-finger 81.10% executed and 80.56% imagined; three-finger 60.11% and 60.61%) [1], because the task granularity, subject selection and evaluation protocol all differ.

Finger-level pilot (subject S01). We ran the finger notebook on subject S01 of the base paper's dataset [7] for two fingers (thumb versus pinky) and three fingers (thumb, index, pinky), with TCFormer and EEGNet and three seeds averaged. The split is chronological, by whole trial and by session. The model is pretrained on the subject's own earlier sessions of both modes (no other subjects), fine-tuned on the first 30% of the trials of the last session, and evaluated on the remaining, later trials of

that session (448 trials for two fingers, 336 for three; Table IX). For two fingers TCFormer reached 79.9% on executed movement (Wilson 95% interval [29], 76.0–83.4%) and 71.4% on imagined movement (67.1–75.4%), against 76.1% and 65.4% for EEGNet. The three TCFormer seeds agreed within 1.8 points on ME and 3.8 on MI, while the EEGNet seeds spread over 6.5 and 5.6 points. For three fingers TCFormer reached 44.6% (ME) and 43.2% (MI), and EEGNet 46.7% and 37.2%. All of these are above the 33.3% chance level except EEGNet on imagined movement ($p = 0.075$, exact binomial test). The equal-weight ensemble stayed within 2.1 points of the better single model and was ahead of it only for three-finger ME (+0.9).

TABLE IX
FINGER-LEVEL PILOT, SUBJECT S01: MAJORITY-VOTE ACCURACY (%), THREE SEEDS AVERAGED, NO CROSS-SUBJECT PRETRAINING

Config. / mode	Trials	Chance	TCFormer	EEGNet	Ensemble
2-finger – ME	448	50.0	79.9	76.1	78.8
2-finger – MI	448	50.0	71.4	65.4	69.9
3-finger – ME	336	33.3	44.6	46.7	47.6
3-finger – MI	336	33.3	43.2	37.2	41.1

These results come from one subject, so they say nothing about differences between people. The intervals treat trials as independent even though they come from one subject and a few sessions, so they are optimistic. We also cannot test the architecture differences without per-trial predictions. Our two-finger executed-movement accuracy is close to the base paper's 81.10% [1], and our imagined-movement accuracy is about 9 points below its 80.56%. Our three-finger accuracies are 15 to 17 points below its 60.11% and 60.61%. The base paper reports means over 21 subjects with online fine-tuning, so this comparison is only a rough guide.

8. SOFTWARE SYSTEM AND DEPLOYMENT

8.1 Architecture

The trained models are deployed as the three-tier application shown in Fig. 2. *Tier 1 (presentation)* is a browser-based Decode Console. It shows the decoded command for each window, the class probabilities and a three-dimensional bionic-limb model. *Tier 2 (application and ML logic)* is a FastAPI server. Its endpoints are /api/health, /api/models, /api/tasks, /api/predict, /api/replay/log/{task}, /ws/replay/{task}, /api/upload/edf, /api/upload/csv and /api/sample/*. It runs the preprocessing of Section 5.1 and one ONNX Runtime model per task and mode, and turns window predictions into a trial label by majority vote. The band-pass filter is stored as fixed taps that match the MNE filter used in training (maximum difference 4×10^{-14} on test data), so the server sees the same input that the models saw during training. *Tier 3 (data and storage)* holds the EEG data, the ONNX model files with a manifest that records each model's task, mode, label order and held-out accuracy, and the replay logs. The Decode Console talks to the server over REST; it does not use the WebSocket replay endpoint.

The system is software-only by design. The Decode Console is hosted on Vercel, the FastAPI back end runs as a Docker Space on Hugging Face, and everything also runs locally on a laptop. No physical robotic hardware is targeted, and the pipeline calls no external LLM or third-party inference API. The server never invents output. If no model is loaded for a task and mode, it returns an error. Ground truth is shown only when the data contain it (the T0/T1/T2 annotations of an EDF file, or the flagged block design of a synthetic session), and files without the 64 PhysioNet channels are rejected. The server has 65 automated tests: 47 use small synthetic ONNX models and the stored replay logs, 10 run the four exported TCFormer models themselves, 3 check the web page, and 5 cover the finger replays. Section 8.4 gives the public addresses.



Fig. 6. Finger replay view for subject S01 (executed movement, held-out trials of the 25-epoch single-seed models): (a) two-finger model, thumb window; (b) two-finger model, pinky window; (c) three-finger model, index window; (d) three-finger model, thumb window. The close-up hand highlights the decoded finger, and the EEG window below the robot shows the three stored channels for the same window (BioSemi D19, A1 and B22, standing in for C3, CZ and C4). The robot stands in the background only.

8.2 Front End

Fig. 4 shows the Decode Console. For each window of a replayed or uploaded session it shows the decoded command with its confidence, the ground-truth label when there is one, and a match flag. It also drives a three-dimensional virtual bionic-limb model in the browser that moves the arms, the legs or both, depending on the decoded class. The limbs are a software visualization only, and no physical hardware is involved. Below the model the console shows a six-channel EEG window with playback controls, the softmax class probabilities and the task selector. Fig. 5 shows the other views: the Task B replay with the legs extended (a), a finger-kinematics test with manual sliders (b), the session analytics

with a confusion matrix (c), and the Custom Data Lab for uploading EDF or CSV recordings or generating a synthetic session (d). The finger test is a manual demonstration. A separate finger view shows a close-up of the right hand and flexes the decoded finger (thumb, index or pinky). It replays held-out trials of finger models for subject S01, each trained for 25 epochs with one seed (majority-vote accuracy 77.5% and 69.4% for two fingers, executed and imagined, and 54.2% and 43.5% for three). These are not the three-seed results of Table IX. Fig. 6 shows this view. For the finger replays, the EEG window below the robot shows three stored channels (BioSemi electrodes D19, A1 and B22, the nearest electrodes of the 128-channel layout to C3, Cz and C4, so these names are approximate) for the same window (Fig. 6). Without a replay the view plays a labelled simulated sequence. A Composite Demo button plays short stored blocks from the Task A, Task B and finger replays back to back. Each block comes from a different model, so it is a visual composite and not one decoded session, and the console reports no accuracy for it. The hand model has five articulated digits, but the finger-level dataset covers thumb, index, middle and pinky, and the deployed models decode whole-limb commands. A decoded limb command therefore curls the whole hand, not single fingers. The Signal tab shows the stored channels at the full rate of the replay (six channels at 160 Hz for the limb tasks, three at 100 Hz for the fingers) together with their relative band power (theta, mu, beta and low gamma, each as a share of the 4–40 Hz power of the 1 s window), which was computed once from the full-rate windows and is stored in the replay log (Fig. 7). RMS and peak-to-peak are given in z-score units, because every window is z-scored, and no signal-to-noise ratio is computed. A notebook added the traces and band power to the replay logs by rebuilding the held-out windows and attaching a signal to a stored window only when the exported model reproduces that window's stored probabilities. The finger logs hold fewer windows per trial than the rebuilt data, so there every stored window was matched to a window of the same trial, with probabilities agreeing within 5×10^{-7}. Rows and colors are built from the label order of the loaded task, so the same interface serves both tasks.



Fig. 7. Signal tab of the Decode Console for the Task A replay of subject S007 (executed movement): the stored C3 trace at 160 Hz, its relative band power (theta, mu, beta, low gamma), and RMS and peak-to-peak in z-score units for the selected window. Delta lies outside the 4–40 Hz filter, and no signal-to-noise ratio is computed.

8.3 Test Cases

Table X lists the checks made on the system. T1–T7, T9 and T10 are part of the automated suite (65 tests, all passing), and T8 was checked by hand in the front end. Most of the suite uses small synthetic ONNX models, so it tests the server logic. T9 and T10 check that the real exported files load and agree with their manifest and replay logs; they do not measure accuracy on new data.

TABLE X
FUNCTIONAL TEST CASES

T1	/api/health	Backend reports its status, the loaded models and any load errors	Pass
T2	/api/tasks	Both tasks are listed with labels, models and replays	Pass
T3	/api/replay/log/{task}	Stored replay log, with its provenance, returned for each task	Pass
T4	/ws/replay/{task}	Per-window predictions stream over WebSocket	Pass
T5	/api/predict	Probabilities sum to 1, label order follows the manifest, wrong shapes are rejected	Pass
T6	/api/upload/*	Ground truth only from real annotations; files without 64 channels or over the size limit are rejected	Pass
T7	Preprocessing	4–40 Hz FIR output equals the MNE training filter	Pass
T8	Decode Console	Rows and colors built from the loaded log's label order (Task A and B)	Pass (manual)
T9	Exported models	Four ONNX models load and match PyTorch (1e-5)	Pass
T10	Replay logs	Replay logs match the manifest	Pass




Fig. 4. Decode Console, 3D Limb Decoder view (screenshot of the deployed build running locally), replaying the held-out trials of the exported S007 executed-movement model (Task A) at one right-fist window: decoded command with confidence and a match flag against the ground-truth label, the humanoid model with the right arm and hand actuated, softmax class probabilities, the task selector, and the six-channel EEG window with playback controls.




Fig. 5. Other views of the front end: (a) Task B replay with both feet decoded and the bionic legs extended; (b) finger-kinematics test with manual sliders, not driven by EEG (five digits are modelled; the finger dataset covers thumb, index, middle and pinky); (c) session analytics, per-window accuracy and confusion matrix of the loaded log; (d) Custom Data Lab for EDF/CSV upload and synthetic sessions.

8.4 Availability

The code, trained models, notebooks and this report are on GitHub at https://github.com/SaiPhaniAnirudh/NeuroBot. The Decode Console is hosted on Vercel at https://neurobot-ui.vercel.app/, and its FastAPI back end runs as a Docker Space on Hugging Face at https://huggingface.co/spaces/EnergyVenom/neurobot. Both use free plans, so the first request after an idle period can be slow while the Space wakes up.

9. Limitations

- Evaluation sets are small: about 18 trials per subject and mode, so per-subject accuracy moves in steps of about 5.6 points, and individual values such as 100% rest on only 18 trials.
- The trial-level results of Table III are single, unseeded runs. Two runs of the same code differ by up to about 7 points in group mean (Section 7). The cross-subject comparison (Tables VI–VIII) averages three seeds in both arms, but each arm is one session per task, and the two arms ran in separate sessions.
- Differences between subjects are large and persist across every architecture and protocol we tried. A few subjects (e.g., S002, S004, S007) did better than the rest in earlier runs, which may point to a physiological ceiling for weak responders rather than a methodological limit. In the cross-subject runs, however, executed- and imagined-movement

accuracies were uncorrelated across subjects in Task A ($r = 0.02$) and moderately correlated in Task B ($r = 0.55$; $n = 10$ each). Only S006 and S009 were at or below chance on imagined movement in both tasks, and S009 reached 88.9–94.4% on executed movement, so the weakness may be specific to imagery.

- Motor imagery (MI) underperforms movement execution (ME) in every configuration we tested, which is consistent with the weaker and more variable cortical signal of imagined movement.
- Group-mean accuracy passes our 85% target only for Task B executed movement (TCFormer 86.7%, 95% interval ±9.4 points, which includes values below 85%; the baseline without pretraining reached 78.9%). The other three conditions reach 70–74% with cross-subject pretraining, and imagined movement is still far from the target.
- The window-length ablation (v9) covered only four subjects of Task A and was inconclusive. Cross-subject pretraining is significant in only one of four conditions (Task B executed movement, +7.8 points, $p = 0.003$). On Task A its +8.3 points in both modes cannot be told apart from zero with ten subjects of about 18 trials each ($p = 0.12$ and 0.11), and Task B imagined movement shows no gain (Section 7).
- The finger-level results come from a single subject (S01), so they say nothing about differences between people, and their intervals (±3.7 points for two-finger executed movement) treat trials from one subject as independent. They were obtained offline, without the real-time, closed-loop neurofeedback that the base paper reports as improving subject performance during acquisition. That may be part of why our three-finger accuracy (44.6% executed) is below the base paper's 60.11%.
- The exploratory four-finger configuration could not be evaluated under the session-held-out protocol, because the middle finger was recorded only in the offline session (Section 4.2).
- The web demo serves the baseline flagship models rather than the pretrained versions, and its finger models are single-seed, 25-epoch runs on subject S01 only. The Signal tab shows only stored traces and band power. The finger traces come from the BioSemi electrodes nearest to C3, Cz and C4, so their names are approximate, and no signal-quality measure is computed. Because the hosting plans are free, the first request after an idle period can be slow.

10. Future Work

- Extend the finger-level track beyond subject S01 (more subjects, with cross-subject pretraining); a four-finger evaluation would need a different protocol, for example a held-out part of the offline session.
- Repeat the window-length ablation on more subjects (the four-subject pilot was inconclusive).
- Evaluate more subjects and held-out trials per condition so that the Task A pretraining gain (+8.3 points in both modes, Section 7) can be confirmed or excluded, and test whether per-run channel standardization or a sensorimotor channel subset helps the weakest subjects.
- Check the electrode correspondence of the finger recordings (BioSemi D19, A1 and B22 for C3, Cz and C4) against the dataset documentation, and show more channels.
- Support multiple, flexible EEG input methods and data sources.
- Revisit guardrail and observability mechanisms (confidence thresholds, structured output validation, decode logging) appropriate to a software-only deployment.

11. Conclusion

NeuroBot shows that we can build and train an EEG decoding pipeline ourselves, without an external API, and that it decodes coarse limb-level motor intention well above chance. With cross-subject pretraining the group-mean trial-level accuracy is 70–87% (chance 33%), and individual subjects reach 100%. Without pretraining, under the same protocol, it is 62–79%, and the gain is significant only for Task B executed movement. A single-subject finger-level pilot reaches 79.9% for two fingers and 44.6% for three fingers on executed movement. The development history matters as much as the final numbers: each iteration in Section 6 answered a specific problem in the one before, and each architectural change, above all the TCFormer pooling correction, was tested before we adopted it. The trained models are served by a software-only, three-tier application that runs on free hosting. Next we want to bring the same care to the finger-level task and to a more complete software product.

Acknowledgment

The authors used an AI assistant (Anthropic's Claude) to help draft and edit text, write and review code, and format this report. The authors designed the experiments, ran all training on Kaggle, and checked the results, references and claims, and take full responsibility for the content.

References

[1] Y. Ding, C. Udompanyawit, Y. Zhang, and B. He, "EEG-based brain-computer interface enables real-time robotic hand control at individual finger level," *Nature Communications*, vol. 16, p. 5401, 2025, doi: 10.1038/s41467-025-61064-x.

[2] A. L. Goldberger *et al.*, "PhysioBank, PhysioToolkit, and PhysioNet: Components of a new research resource for complex physiologic signals," *Circulation*, vol. 101, no. 23, pp. e215–e220, 2000.

[3] G. Schalk, D. J. McFarland, T. Hinterberger, N. Birbaumer, and J. R. Wolpaw, "BCI2000: A general-purpose brain-computer interface (BCI) system," *IEEE Trans. Biomed. Eng.*, vol. 51, no. 6, pp. 1034–1043, Jun. 2004, doi: 10.1109/TBME.2004.827072.

[4] V. J. Lawhern, A. J. Solon, N. R. Waytowich, S. M. Gordon, C. P. Hung, and B. J. Lance, "EEGNet: A compact convolutional neural network for EEG-based brain-computer interfaces," *J. Neural Eng.*, vol. 15, no. 5, p. 056013, 2018, doi: 10.1088/1741-2552/aace8c.

[5] H. Altaheri, F. Karray, and A.-H. Karimi, “Temporal convolutional transformer for EEG based motor imagery decoding,” *Scientific Reports*, vol. 15, Art. no. 32959, 2025, doi: 10.1038/s41598-025-16219-7.

[6] B. Aristimunha *et al.*, “Braindecode: Toolbox for decoding raw electrophysiological brain data with deep learning models,” Zenodo, 2025, doi: 10.5281/zenodo.17699192.

[7] Y. Ding, C. Udompanyawit, Y. Zhang, and B. He, “EEG-BCI dataset for real-time robotic hand control at individual finger level,” KiltHub, Carnegie Mellon University, 2025, doi: 10.1184/R1/29104040.

[8] J. R. Wolpaw, N. Birbaumer, D. J. McFarland, G. Pfurtscheller, and T. M. Vaughan, “Brain–computer interfaces for communication and control,” *Clin. Neurophysiol.*, vol. 113, no. 6, pp. 767–791, 2002.

[9] G. Pfurtscheller and F. H. Lopes da Silva, “Event-related EEG/MEG synchronization and desynchronization: Basic principles,” *Clin. Neurophysiol.*, vol. 110, no. 11, pp. 1842–1857, 1999.

[10] G. Pfurtscheller and C. Neuper, “Motor imagery and direct brain–computer communication,” *Proc. IEEE*, vol. 89, no. 7, pp. 1123–1134, Jul. 2001.

[11] F. Lotte *et al.*, “A review of classification algorithms for EEG-based brain–computer interfaces: A 10 year update,” *J. Neural Eng.*, vol. 15, no. 3, Art. no. 031005, 2018.

[12] Y. Roy, H. Banville, I. Albuquerque, A. Gramfort, T. H. Falk, and J. Faubert, “Deep learning-based electroencephalography analysis: A systematic review,” *J. Neural Eng.*, vol. 16, no. 5, Art. no. 051001, 2019.

[13] A. Craik, Y. He, and J. L. Contreras-Vidal, “Deep learning for electroencephalogram (EEG) classification tasks: A review,” *J. Neural Eng.*, vol. 16, no. 3, Art. no. 031001, 2019.

[14] R. T. Schirrmeister *et al.*, “Deep learning with convolutional neural networks for EEG decoding and visualization,” *Human Brain Mapping*, vol. 38, no. 11, pp. 5391–5420, 2017.

[15] A. Vaswani *et al.*, “Attention is all you need,” in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017, pp. 5998–6008.

[16] Y. Song, Q. Zheng, B. Liu, and X. Gao, “EEG Conformer: Convolutional transformer for EEG decoding and visualization,” *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 31, pp. 710–719, 2023, doi: 10.1109/TNSRE.2022.3230250.

[17] J. Ainslie *et al.*, “GQA: Training generalized multi-query transformer models from multi-head checkpoints,” arXiv:2305.13245, 2023.

[18] J. Su, M. Ahmed, Y. Lu, S. Pan, W. Bo, and Y. Liu, “RoFormer: Enhanced transformer with rotary position embedding,” *Neurocomputing*, vol. 568, Art. no. 127063, 2024.

[19] S. Bai, J. Z. Kolter, and V. Koltun, “An empirical evaluation of generic convolutional and recurrent networks for sequence modeling,” arXiv:1803.01271, 2018.

[20] B. J. Edelman *et al.*, “Noninvasive neuroimaging enhances continuous neural tracking for robotic device control,” *Sci. Robot.*, vol. 4, no. 31, Art. no. eaaw6844, 2019.

[21] D. P. Kingma and J. Ba, “Adam: A method for stochastic optimization,” in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2015.

[22] I. Loshchilov and F. Hutter, “Decoupled weight decay regularization,” in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019.

[23] I. Loshchilov and F. Hutter, “SGDR: Stochastic gradient descent with warm restarts,” in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2017.

[24] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, “Rethinking the Inception architecture for computer vision,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2016, pp. 2818–2826.

[25] A. Paszke *et al.*, “PyTorch: An imperative style, high-performance deep learning library,” in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 32, 2019, pp. 8024–8035.

[26] A. Gramfort *et al.*, “MEG and EEG data analysis with MNE-Python,” *Front. Neurosci.*, vol. 7, Art. no. 267, 2013.

[27] K. Zhang, G. Xu, X. Zheng, H. Li, S. Zhang, Y. Yu, and R. Liang, “Application of transfer learning in EEG decoding based on brain–computer interfaces: A review,” *Sensors*, vol. 20, no. 21, Art. no. 6321, 2020, doi: 10.3390/s20216321.

[28] G. Brookshire *et al.*, “Data leakage in deep learning studies of translational EEG,” *Front. Neurosci.*, vol. 18, Art. no. 1373515, 2024, doi: 10.3389/fnins.2024.1373515.

[29] E. B. Wilson, “Probable inference, the law of succession, and statistical inference,” *J. Amer. Statist. Assoc.*, vol. 22, no. 158, pp. 209–212, 1927, doi: 10.1080/01621459.1927.10502953.

[30] Z. Shuqfa, A. Lakas, and A. N. Belkacem, “Increasing accessibility to a large brain–computer interface dataset: Curation of PhysioNet EEG motor movement/imagery dataset for decoding and classification,” *Data in Brief*, vol. 54, Art. no. 110181, 2024, doi: 10.1016/j.dib.2024.110181.