

Name: SaiPraveen Marni

USN: 1BM19CS138

Dept: CSE

Section: C

Course Name: Database Management Systems

Lab_batch: C-3

PROGRAM 1: INSURANCE DATABASE

Consider the Insurance database given below. The data types are specified.

PERSON (driver_id: String, name: String, address: String)

CAR (reg_num: String, model: String, year: int)

ACCIDENT (report_num: int, accident_date: date, location: String)

OWNS (driver_id: String, reg_num: String)

PARTICIPATED (driver_id: String, reg_num: String, report_num: int, damage_amount: int)

- i) Create the above tables by properly specifying the primary keys and the foreign keys.
- ii) Enter at least five tuples for each relation.
- iii) Demonstrate how you
 - a. Update the damage amount to 2500 for the car with a specific reg-num(KA37) for which the accident report number was 12.
 - b. Add a new accident to the database.
- iv) Find the total number of people who owned cars that involved in accidents in 2008.

v) Find the number of accidents in which cars belonging to a specific model (MARUTI) were involved.

```
create database ins;

use ins;

create table person(
driver_id varchar(30) primary key,
nam varchar(30),
address varchar(30)
);

create table accident(
report_number int primary key,
dat date,
location varchar(30)
);

create table car(
regno varchar(30),
model varchar(30),
yea int
);

alter table car
add primary key(regno);

create table owns(
driver_id varchar(30),
regno varchar(30),
foreign key(driver_id) references person(driver_id) on delete set null on update cascade,
foreign key(regno) references car(regno) on delete set null on update cascade
);
```

```



















create table participated(
driver_id varchar(30),
regno varchar(30),
report_number int,
dam int,
foreign key(driver_id) references person(driver_id) on update cascade on delete set null,
foreign key(regno) references car(regno) on update cascade on delete set null,
foreign key(report_number) references accident(report_number) on update cascade on delete set null
);

```

```

insert into person(driver_id,nam,address)
values('A01','Praveen','Karnataka'),('A02','Saquib','Jharkhand'),('A03','Vihari','Andhra Pradesh'),('A04','Karthik','Tamil Nadu'),('A05','Bumrah','Gujarat'),('A06','Hari','Karnataka');

```

				driver_id	nam	address
<input type="checkbox"/>		Edit		Copy		Delete
				A01	Praveen	Karnataka
<input type="checkbox"/>		Edit		Copy		Delete
				A02	Saquib	Jharkhand
<input type="checkbox"/>		Edit		Copy		Delete
				A03	Vihari	Andhra Pradesh
<input type="checkbox"/>		Edit		Copy		Delete
				A04	Karthik	Tamil Nadu
<input type="checkbox"/>		Edit		Copy		Delete
				A05	Bumrah	Gujarat
<input type="checkbox"/>		Edit		Copy		Delete
				A06	Hari	Karnataka

```

insert into car(regno,model,yea)
values('KA37','MAHINDRA',2008),('KA35','SKODA',2008),('KA36','MARUTI',2009),('KA39','RENAULT',2010),('KA38','Honda',2012),('KA30','HYUNDAI',2014);

```

				regno	model	yea
<input type="checkbox"/>		Edit		Copy		Delete
				KA30	HYUNDAI	2014
<input type="checkbox"/>		Edit		Copy		Delete
				KA35	SKODA	2008
<input type="checkbox"/>		Edit		Copy		Delete
				KA36	MARUTI	2009
<input type="checkbox"/>		Edit		Copy		Delete
				KA37	MAHINDRA	2008
<input type="checkbox"/>		Edit		Copy		Delete
				KA38	Honda	2012
<input type="checkbox"/>		Edit		Copy		Delete
				KA39	RENAULT	2010

```
insert into accident(report_number,dat,location) values(12,'2008-10-11','Koppal'),(13,'2008-11-19','Hubli'),(14,'2008-08-11','Kolkata'),(15,'2008-08-08','Delhi'),(16,'2008-07-07','Bengaluru'),(17,'2008-06-05','Mumbai');
```

				report_number	dat	location
<input type="checkbox"/>		Edit		Copy		Delete
				12	2008-10-11	Koppal
<input type="checkbox"/>		Edit		Copy		Delete
				13	2008-11-19	Hubli
<input type="checkbox"/>		Edit		Copy		Delete
				14	2008-08-11	Kolkata
<input type="checkbox"/>		Edit		Copy		Delete
				15	2008-08-08	Delhi
<input type="checkbox"/>		Edit		Copy		Delete
				16	2008-07-07	Bengaluru
<input type="checkbox"/>		Edit		Copy		Delete
				17	2008-06-05	Mumbai

```
insert into owns(driver_id,regno)
values('A01','KA37'),('A02','KA35'),('A03','KA36'),('A0','KA39'),('A05','KA38'),('A06','KA30');
```

driver_id	regno
A01	KA37
A02	KA35
A03	KA36
A04	KA39
A05	KA38
A06	KA30

```
insert into participated(driver_id,regno,report_number,dam)
values('A01','KA37',12,2000),('A02','KA35',13,1500),('A03','KA36',14,2000),('A0','KA39',15,2500),('A05','KA38',16,3000),('A06','KA30',17,4000);
```

driver_id	regno	report_number	dam
A01	KA37	12	2000
A02	KA35	13	1500
A03	KA36	14	2000
A04	KA39	15	2500
A05	KA38	16	3000
A06	KA30	17	4000

select * from person;

select * from car;

select * from accident;

select * from owns;

select * from participated;

update participated






















set dam=2500

where report_number=12 and regno='KA37';























driver_id	regno	report_number	dam
A01	KA37	12	2500
A02	KA35	13	1500
A03	KA36	14	2000
A04	KA39	15	2500
A05	KA38	16	3000
A06	KA30	17	4000
A09	KA31	12	2000

insert into accident(report_number,dat,location) values(18,'2008-11-19','Koppal');























insert into accident(report_number,dat,location) values(19,'2000-11-19','Koppal');

		report_number	dat	location
<input type="checkbox"/>	 Edit  Copy  Delete	12	2008-10-11	Koppal
<input type="checkbox"/>	 Edit  Copy  Delete	13	2008-11-19	Hubli
<input type="checkbox"/>	 Edit  Copy  Delete	14	2008-08-11	Kolkata
<input type="checkbox"/>	 Edit  Copy  Delete	15	2008-08-08	Delhi
<input type="checkbox"/>	 Edit  Copy  Delete	16	2008-07-07	Bengaluru
<input type="checkbox"/>	 Edit  Copy  Delete	17	2008-06-05	Mumbai
<input type="checkbox"/>	 Edit  Copy  Delete	18	2008-11-19	Koppal
<input type="checkbox"/>	 Edit  Copy  Delete	19	2000-11-19	Koppal

insert into person(driver_id,nam,address) values('A09','Hari K','Karnataka');

		driver_id	nam	address
<input type="checkbox"/>	 Edit  Copy  Delete	A01	Praveen	Karnataka
<input type="checkbox"/>	 Edit  Copy  Delete	A02	Saquib	Jharkhand
<input type="checkbox"/>	 Edit  Copy  Delete	A03	Vihari	Andhra Pradesh
<input type="checkbox"/>	 Edit  Copy  Delete	A04	Karthik	Tamil Nadu
<input type="checkbox"/>	 Edit  Copy  Delete	A05	Bumrah	Gujarat
<input type="checkbox"/>	 Edit  Copy  Delete	A06	Hari	Karnataka
<input type="checkbox"/>	 Edit  Copy  Delete	A09	Hari K	Karnataka

insert into car(regno,model,yea) values('KA31','MARUTI',2008);

		regno	model	yea
<input type="checkbox"/>	 Edit  Copy  Delete	KA30	HYUNDAI	2014
<input type="checkbox"/>	 Edit  Copy  Delete	KA31	MARUTI	2008
<input type="checkbox"/>	 Edit  Copy  Delete	KA35	SKODA	2008
<input type="checkbox"/>	 Edit  Copy  Delete	KA36	MARUTI	2009
<input type="checkbox"/>	 Edit  Copy  Delete	KA37	MAHINDRA	2008
<input type="checkbox"/>	 Edit  Copy  Delete	KA38	Honda	2012
<input type="checkbox"/>	 Edit  Copy  Delete	KA39	RENAULT	2010

insert into participated(driver_id,regno,report_number,dam) values('A09','KA31',12,2000);

driver_id	regno	report_number	dam
A01	KA37	12	2500
A02	KA35	13	1500
A03	KA36	14	2000
A04	KA39	15	2500
A05	KA38	16	3000
A06	KA30	17	4000
A09	KA31	12	2000

select count(distinct driver_id) cnt from participated a,accident b where
b.report_number=b.report_number and b.dat like '%08';

```
select count(distinct driver_id) cnt from participated a,accident b where b.report_number=b.report_number and b.dat like '%08'
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#)

☐ Show all | Number of rows: Filter rows:

+ Options

cnt
7

select count(distinct report_number) cn from car x,participated y where y.regno=x.regno
and x.model='MARUTI';

```
select count(distinct report_number) cn from car x,participated y where y.regno=x.regno and x.model='MARUTI'
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#)

☐ Show all | Number of rows: Filter rows:

+ Options

cn
2

select * from participated order by dam desc;

select avg(dam) av from participated;

SET SQL_SAFE_UPDATES=0;

delete from participated

where dam<=2500;

```
select nam from person p ,participated q where p.driver_id=q.driver_id and dam>2500;
```

```
select nam,dam from person p ,participated q where p.driver_id=q.driver_id and dam>2500;
```


PROGRAM 2: BANKING ENTERPRISE

Consider the following database for a banking enterprise.

Branch (branch-name: String, branch-city: String, assets: real)

BankAccount(accno: int, branch-name: String, balance: real)

BankCustomer (customer-name: String, customer-street: String, customer-city: String)

Depositer(customer-name: String, accno: int)

Loan (loan-number: int, branch-name: String, amount: real)

- i. Create the above tables by properly specifying the primary keys and the foreign keys.
- ii. Enter at least five tuples for each relation.
- iii. Find all the customers who have at least two accounts at the Main branch (ex. SBI_ResidencyRoad).
- iv. Find all the customers who have an account at all the branches located in a specific city (Ex. Delhi).
- v. Demonstrate how you delete all account tuples at every branch located in a specific city (Ex. Bombay).

```
create database bank;
```

```
use bank;
```

```
create table branch(
```

```
branch_name varchar(30) primary key,
```

```
branch_city varchar(30),
```

```
assests decimal(6,2)
```

```
);
```

```
drop table accounts;
```

```
create table accounts(
```

```
accno int primary key,
```

```
branch_name varchar(30),
```

```
balance decimal(7,2),
```

```
foreign key(branch_name) references branch(branch_name)
```

```
);
```

```
create table depositor(
```

```
customer_name varchar(30),
```

```
customer_street varchar(30),
```

```
customer_city varchar(30)
```

```
);
```

```
alter table depositor
```

```
add column accno int;
```

```
alter table depositor
```

```
add constraint fori
```

```
foreign key(accno) references accounts(accno);
```

```
alter table depositor
```

```
drop foreign key fori;
```

```
create table loan(
```

```
loan_number int primary key,  
branch_name varchar(30),  
amt decimal(7,2)  
);
```

```
alter table loan  
add constraint fk_1  
foreign key(branch_name) references branch(branch_name);
```

```
create table borrower(  
customer_name varchar(30),  
loan_number int,  
foreign key(loan_number) references loan(loan_number)  
);
```

```
desc branch;  
desc accounts;  
desc depositor;  
desc loan;  
desc borrower;
```

```
truncate table depositor;
```

```
insert into branch(branch_name,branch_city,assests) values('SBH  
RAICHUR','RAICHUR',1234.56),('SBI HOSPET','HOSPET',4567.89),('SBI  
BANGLORE','BANGLORE RURAL',9687.25),('SBI GAGAG','GADAG',1000.25),('SBI  
RAICHUR','RAICHUR',2000.24);
```

				branch_name	branch_city	assests
<input type="checkbox"/>				SBH RAICHUR	RAICHUR	1234.56
<input type="checkbox"/>				SBI BANGLORE	BANGLORE RURAL	9687.25
<input type="checkbox"/>				SBI GADAG	GADAG	1000.25
<input type="checkbox"/>				SBI HOSPET	HOSPET	4567.89
<input type="checkbox"/>				SBI RAICHUR	RAICHUR	2000.24

insert into accounts(accno,branch_name,balance) values(1234,'SBH RAICHUR',40000.00),(4567,'SBI BANGLORE',50000.00),(2345,'SBI BANGLORE',60000.00),(1000,'SBI GADAG',70000.00),(1024,'SBI RAICHUR',10000.00);

				accno	branch_name	balance
<input type="checkbox"/>				1000	SBI GADAG	70000.00
<input type="checkbox"/>				1024	SBI RAICHUR	10000.00
<input type="checkbox"/>				1234	SBH RAICHUR	40000.00
<input type="checkbox"/>				2345	SBI BANGLORE	60000.00
<input type="checkbox"/>				4567	SBI BANGLORE	50000.00

insert into depositor(customer_name,customer_street,customer_city,accno) values('Hari','ALMERI','KOPPAL',1234),('Saquib','BTM LAYOUT','BANGLORE',4567),('Praveen','SINDHNUR',' RAICHUR',2345),('Subhas','CHAMRAJPET','BIJAPUR',1000),('Balaji','MUDIRABAD','KOLAR',1024);

customer_name	customer_street	customer_city	accno
Hari	ALMERI	KOPPAL	1234
Saquib	BTM LAYOUT	BANGLORE	4567
Praveen	SINDHNUR	RAICHUR	2345
Subhas	CHAMRAJPET	BIJAPUR	1000
BalaJi	MUDIRABAD	KOLAR	1024
Pramod	Vasavi Nagar	Sindhanur	1233
Pramod	Vasavi Nagar	RAICHUR	1232
Hari	GADAG ROAD	RAICHUR	1220
Hari	GADAG ROAD	RAICHUR	1221
Arya	MANNUR ROAD	RAICHUR	1220
Arya	MANNUR ROAD	RAICHUR	1220

insert into loan(loan_number,branch_name,amt) values(1,'SBI GADAG',10000.00),(2,'SBI RAICHUR',15000.00),(3,'SBH RAICHUR,20000.00),(4,'SBI BANGLORE',25000.00),(5,'SBI BANGLORE',24000.00);

	loan_number	branch_name	amt
<input type="checkbox"/> Edit Copy Delete	1	SBI GADAG	10000.00
<input type="checkbox"/> Edit Copy Delete	2	SBI RAICHUR	15000.00
<input type="checkbox"/> Edit Copy Delete	3	SBH RAICHUR	20000.00
<input type="checkbox"/> Edit Copy Delete	4	SBI BANGLORE	25000.00
<input type="checkbox"/> Edit Copy Delete	5	SBI BANGLORE	24000.00

```
insert into borrower(customer_name,loan_number)
values('Mayur',1),('Pooja',2),('Gagan',3),('Sufail',4),('Akash',5);
```

customer_name	loan_number
Mayur	1
Pooja	2
Gagan	3
Sufail	4
Akash	5

```
insert into branch(branch_name,branch_city,assests) values('SBI
KOPPAL','KOPPAL',1234.56);
```

```
insert into accounts(accno,branch_name,balance) values(1233,'SBH KOPPAL',40000.00);
```

```
insert into accounts(accno,branch_name,balance) values(1232,'SBI KOPPAL',40000.00);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Pramod','Vasavi Nagar','Sindhanur',1233);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Pramod','Vasavi Nagar',' RAICHUR ',1232);
```

```
insert into accounts(accno,branch_name,balance) values(1220,'SBH KOPPAL',40000.00);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Hari','GADAG ROAD',' RAICHUR ',1220);
```

```
insert into accounts(accno,branch_name,balance) values(1221,'SBH KOPPAL',40000.00);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Hari','GADAG ROAD',' RAICHUR ',1221);
```

```
insert into accounts(accno,branch_name,balance) values(1120,'SBH KOPPAL',40000.00);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Arya','MANNUR ROAD',' RAICHUR ',1220);
```

```
insert into accounts(accno,branch_name,balance) values(1128,'SBH KOPPAL',40000.00);
```

```
insert into depositor(customer_name,customer_street,customer_city,accno)
values('Arya','MANNUR ROAD',' RAICHUR ',1220);
```

customer_name	customer_street	customer_city	accno
Hari	ALMERI	KOPPAL	1234
Saquib	BTM LAYOUT	BANGLORE	4567
Praveen	SINDHNUR	RAICHUR	2345
Subhas	CHAMRAJPET	BIJAPUR	1000
BalaJi	MUDIRABAD	KOLAR	1024
Pramod	Vasavi Nagar	Sindhanur	1233
Pramod	Vasavi Nagar	RAICHUR	1232
Hari	GADAG ROAD	RAICHUR	1220
Hari	GADAG ROAD	RAICHUR	1221
Arya	MANNUR ROAD	RAICHUR	1220
Arya	MANNUR ROAD	RAICHUR	1220

```
select * from branch;
```

```
select * from accounts;
```

```
select * from depositor;
```

```
select * from loan;
```

```
select * from borrower;
```

```
select c.customer_name,a.branch_name from depositor c join accounts a on
c.accno=a.accno group by c.customer_name having count(*)>1;
```

```
create table joined as(
```

```
select br.branch_city,acn.branch_name from branch br left join accounts acn on
br.branch_name=acn.branch_name
```

```
);
```

```
create table final as(
```

```
select bran.branch_name,anc.accno from branch bran join accounts anc on  
bran.branch_name=anc.branch_name
```

```
);
```

```
select * from final;
```

```
select * from joined;
```

```
select dpt.customer_name from depositor dpt left join joined jn on  
dpt.branch_name=jn.branch_name where jn.branch_city='RAICHUR';
```

branch_city	branch_name
RAICHUR	SBH RAICHUR
RAICHUR	SBH RAICHUR
RAICHUR	SBH RAICHUR
RAICHUR	SBH RAICHUR
RAICHUR	SBH RAICHUR
BANGLORE RURAL	NULL
GADAG	NULL
HOSPET	NULL
RAICHUR	SBI RAICHUR

```
create table f_join as(
```

```
select fl.branch_name,fl.accno,bc.branch_city from final fl join branch bc on  
fl.branch_name=bc.branch_name
```

```
);
```

```
select * from f_join;
```

```
select distinct customer_name,branch_city from depositor f,f_join fn where  
f.accno=fn.accno and fn.branch_city='RAICHUR';
```

branch_name	accno	branch_city
SBH RAICHUR	1120	RAICHUR
SBH RAICHUR	1128	RAICHUR
SBH RAICHUR	1220	RAICHUR
SBH RAICHUR	1221	RAICHUR
SBH RAICHUR	1233	RAICHUR
SBI RAICHUR	1232	RAICHUR

```
SET SQL_SAFE_UPDATES=0;
```

```
delete from accounts
```

```
where branch_name in(
```

```
select branch_name from branch where branch_city='RAICHUR'
```

```
);
```

✓ 2 rows affected. (Query took 0.1337 seconds.)

```
delete from accounts where branch_name in( select branch_name from branch where branch_city='RAICHUR' )
```

[\[Edit inline\]](#) [\[Edit \]](#) [\[Create PHP code \]](#)

PROGRAM 3: SUPPLIER DATABASE

Consider the following schema:

SUPPLIERS (sid: integer, sname: string, address: string)

PARTS (pid: integer, pname: string, color: string)

CATALOG (sid: integer, pid: integer, cost: real)

The Catalog relation lists the prices charged for parts by Suppliers.

Write the following queries in SQL:

- i. Find the pnames of parts for which there is some supplier.
- ii. Find the snames of suppliers who supply every part.
- iii. Find the snames of suppliers who supply every red part.
- iv. Find the pnames of parts supplied by Acme Widget Suppliers and by no one else.
- v. Find the sids of suppliers who charge more for some part than the average cost of that part (averaged over all the suppliers who supply that part).
- vi. For each part, find the sname of the supplier who charges the most for that part.

```
create database supplier;  
use supplier;  
create table suppliers(  
sid int primary key,  
sname varchar(30),  
address varchar(30)  
);
```

```
create table parts(  
pid int primary key,  
pname varchar(30),
```

```
color varchar(30)
```

```
);
```

```
create table catalog(
```

```
sid int,
```

```
pid int,
```

```
cost int,
```

```
constraint fk_1
```

```
foreign key(sid) references suppliers(sid) on update cascade on delete set null,
```

```
constraint fk_2
```

```
foreign key(pid) references parts(pid) on update cascade on delete set null
```

```
);
```













```
select * from suppliers;
```

```
select * from parts;
```

```
select * from catalog;
```

```
insert into suppliers values (10001,'Acme
```

```
Widget','Bangalore'),(10002,'Johns','Kolkata'),(10003,'Vimal','Mumbai'),(10004,'Reliance','D  
elhi');
```

				sid	sname	address
<input type="checkbox"/>				10001	Acme Widget	Bangalore
<input type="checkbox"/>				10002	Johns	Kolkata
<input type="checkbox"/>				10003	Vimal	Mumbai
<input type="checkbox"/>				10004	Reliance	Delhi

```
insert into parts values
```

```
(20001,'Book','Red'),(20002,'Pen','Red'),(20003,'Pencil','Green'),(20004,'Mobile','Green'),(20  
005,'Charger','Black');
```

				pid	pname	color
<input type="checkbox"/>		Edit		Copy		Delete
				20001	Book	Red
<input type="checkbox"/>		Edit		Copy		Delete
				20002	Pen	Red
<input type="checkbox"/>		Edit		Copy		Delete
				20003	Pencil	Green
<input type="checkbox"/>		Edit		Copy		Delete
				20004	Mobile	Green
<input type="checkbox"/>		Edit		Copy		Delete
				20005	Charger	Black

insert into catalog

values(10001,20001,10),(10001,20002,10),(10001,20003,30),(10001,20004,10),(10001,20005,10),(10002,20001,10),(10002,20002,20),(10003,20003,30),(10004,20003,40);

sid	pid	cost
10001	20001	10
10002	20001	10
10002	20002	20
10004	20003	40
10001	20004	10
10001	20005	10

select suppliers.sname from suppliers where suppliers.sid in(select catalog.sid from catalog inner join parts on catalog.pid=parts.pid group by catalog.sid having count(*)=(select count(parts.pid) from parts)); #2

Showing rows 0 - 0 (1 total, Query took 0.0078 seconds.)

```
select suppliers.sname from suppliers where suppliers.sid in(select catalog.sid from catalog inner join parts on catalog.pid=parts.pid group by catalog.sid having count(*)=(select count(parts.pid) from parts))
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all | Number of rows: | Filter rows:

+ Options

	sname
<input type="checkbox"/>	Edit Copy Delete Acme Widget

select suppliers.sname from suppliers where suppliers.sid in (select catalog.sid from catalog inner join parts on catalog.pid=parts.pid where catalog.pid in (select parts.pid from parts where parts.color='Red') group by catalog.sid having count(*)=(select count(parts.color) from parts where parts.color='Red')); #3

Showing rows 0 - 1 (2 total, Query took 0.0113 seconds.)

```
select suppliers.sname from suppliers where suppliers.sid in (select catalog.sid from catalog inner join parts on catalog.pid=parts.pid where catalog.pid in (select parts.pid from parts where parts.color='Red') group by catalog.sid having count(*)=(select count(parts.color) from parts where parts.color='Red'))
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all | Number of rows: 25 | Filter rows: Sort by key:

+ Options

	sname
<input type="checkbox"/> Edit Copy Delete	Acme Widget
<input type="checkbox"/> Edit Copy Delete	Johns

select parts.pname from parts where parts.pid in (select catalog.pid from catalog inner join parts on catalog.pid=parts.pid where catalog.sid in (select suppliers.sid from suppliers where suppliers.sname ='Acme Widget')); #4

Showing rows 0 - 4 (5 total, Query took 0.0087 seconds.)

```
select parts.pname from parts where parts.pid in (select catalog.pid from catalog inner join parts on catalog.pid=parts.pid where catalog.sid in (select suppliers.sid from suppliers where suppliers.sname ='Acme Widget'))
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all | Number of rows: 25 | Filter rows: Sort by key:

+ Options

	pname
<input type="checkbox"/> Edit Copy Delete	Book
<input type="checkbox"/> Edit Copy Delete	Pen
<input type="checkbox"/> Edit Copy Delete	Pencil
<input type="checkbox"/> Edit Copy Delete	Mobile
<input type="checkbox"/> Edit Copy Delete	Charger

select pname from parts where parts.pid in (select catalog.pid from catalog group by catalog.pid); #1

	pname
<input type="checkbox"/> Edit Copy Delete	Book
<input type="checkbox"/> Edit Copy Delete	Pen
<input type="checkbox"/> Edit Copy Delete	Pencil
<input type="checkbox"/> Edit Copy Delete	Mobile
<input type="checkbox"/> Edit Copy Delete	Charger

select catalog.pid,avg(catalog.cost) from catalog group by catalog.pid;

select * from catalog ou where ou.cost >= (select avg(inn.cost) from catalog inn where inn.pid=ou.pid) order by pid; #5

✓ Showing rows 0 - 5 (6 total, Query took 0.0075 seconds.)

```
select * from catalog ou where ou.cost >= ( select avg(inn.cost) from catalog inn where inn.pid=ou.pid) order by pid
```

☐ Profiling [\[Edit inline\]](#) [\[Edit \]](#) [\[Explain SQL \]](#) [\[Create PHP code \]](#) [\[Refresh \]](#)

☐ Show all | Number of rows: Filter rows: Sort by key:

+ Options

sid	pid	cost
10001	20001	10
10002	20001	10
10002	20002	20
10004	20003	40
10001	20004	10
10001	20005	10

create table ref as(select * from catalog ou where ou.cost = (select max(inn.cost) from catalog inn where inn.pid=ou.pid) order by pid); #ref Table For Query 6

select ref.sid,suppliers.sname,ref.pid,ref.cost from suppliers inner join ref on suppliers.sid=ref.sid order by ref.pid;#6

✓ Showing rows 0 - 5 (6 total, Query took 0.0146 seconds.) [pid: 20001... - 20005...]

```
select ref.sid,suppliers.sname,ref.pid,ref.cost from suppliers inner join ref on suppliers.sid=ref.sid order by ref.pid
```

☐ Profiling [\[Edit inline\]](#) [\[Edit \]](#) [\[Explain SQL \]](#) [\[Create PHP code \]](#) [\[Refresh \]](#)

☐ Show all | Number of rows: Filter rows: Sort by key:

+ Options

sid	sname	pid	cost
10002	Johns	20001	10
10001	Acme Widget	20001	10
10002	Johns	20002	20
10004	Reliance	20003	40
10001	Acme Widget	20004	10
10001	Acme Widget	20005	10

PROGRAM 4: STUDENT_FACULTY DATABASE

Consider the following database for student enrolment for course:

STUDENT (snum: integer, sname: string, major: string, level: string, age: integer)

CLASS (name: string, meets at: time, room: string, fid: integer)

ENROLLED (snum: integer, cname: string)

FACULTY (fid: integer, fname: string, deptid: integer)

The meaning of these relations is straightforward; for example, Enrolled has one record per student-class such that the student is enrolled in the class.

Level is a two character code with 4 different values (example: Junior: JR etc)

Write the following queries in SQL. No duplicates should be printed in any of the answers.

- i. Find the names of all Juniors (level = JR) who are enrolled in a class taught by
- ii. Find the names of all classes that either meet in room R128 or have five or more Students enrolled.
- iii. Find the names of all students who are enrolled in two classes that meet at the same time.
- iv. Find the names of faculty members who teach in every room in which some class is taught.
- v. Find the names of faculty members for whom the combined enrolment of the courses that they teach is less than five.
- vi. Find the names of students who are not enrolled in any class.
- vii. For each age value that appears in Students, find the level value that appears most often. For example, if there are more FR level students aged 18 than SR, JR, or SO students aged 18, you should print the pair (18, FR)

```
create database student_faculty;
```

```
use student_faculty;
```

```
create table student(
```

```
snum int primary key,
```

```
sname varchar(30),
```

```
major varchar(30),  
lvl varchar(30),  
age int  
);
```



















```
create table faculty(  
fid int primary key,  
fname varchar(30),  
dept_id int  
);
```

```
create table class(  
cname varchar(30) primary key,  
meets_at varchar(30),  
room varchar(30),  
fid int,  
constraint fk_1  
foreign key(fid) references faculty(fid)  
);
```

```
create table enrolled(  
snum int ,  
cname varchar(30),  
constraint fk_2  
foreign key(snum) references student(snum),  
constraint fk_3  
foreign key(cname) references class(cname)  
);
```

insert into student values

(1,'Jhon','CS','SR',19),(2,'Smith','CS','JR',17),(3,'Jacob','CV','FR',20),(4,'Tom','CS','FR',25),(5,'Rahul','CS','JR',20),(6,'RANA','CS','FR',21);

<div>← T →</div>				snum	sname	major	lvl	age
<input type="checkbox"/>	 Edit	 Copy	 Delete	1	Jhon	CS	SR	19
<input type="checkbox"/>	 Edit	 Copy	 Delete	2	Smith	CS	JR	17
<input type="checkbox"/>	 Edit	 Copy	 Delete	3	Jacob	CV	FR	20
<input type="checkbox"/>	 Edit	 Copy	 Delete	4	Tom	CS	FR	25
<input type="checkbox"/>	 Edit	 Copy	 Delete	5	Rahul	CS	JR	20
<input type="checkbox"/>	 Edit	 Copy	 Delete	6	Rana	CS	FR	21

insert into faculty values

(11,'Harish',1000),(12,'MV',1000),(13,'Mira',1001),(14,'Shiva',1002),(15,'Nupur',1000);

				fid	fname	dept_id
<input type="checkbox"/>				11	Harish	1000
<input type="checkbox"/>				12	MV	1000
<input type="checkbox"/>				13	Mira	1001
<input type="checkbox"/>				14	Shiva	1002
<input type="checkbox"/>				15	Nupur	1000

insert into class values ('class1','12/11/15 10:15:16','R1',14),('class10','12/11/15 10:15:16','R128',14),('class2','12/11/15 10:15:20','R2',12),('class3','12/11/15 10:15:25','R3',11),('class4','12/11/15 20:15:20','R4',14),('class5','12/11/15 20:15:20','R3',15),('class6','12/11/15 13:20:20','R128',14),('class7','12/11/15 10:10:10','R3',14);

				cname	meets_at	room	fid
<input type="checkbox"/>				class1	12/11/15 10:15:16	R1	14
<input type="checkbox"/>				class10	12/11/15 10:15:16	R128	14
<input type="checkbox"/>				class2	12/11/15 10:15:20	R2	12
<input type="checkbox"/>				class3	12/11/15 10:15:25	R3	11
<input type="checkbox"/>				class4	12/11/15 20:15:20	R4	14
<input type="checkbox"/>				class5	12/11/15 20:15:20	R3	15
<input type="checkbox"/>				class6	12/11/15 13:20:20	R128	14
<input type="checkbox"/>				class7	12/11/15 10:10:10	R3	14

insert into enrolled values

(1,'class1'),(2,'class1'),(3,'class3'),(4,'class3'),(5,'class4'),(1,'class5'),(2,'class5'),(3,'class5'),(4,'class5'),(5,'class5');

snum	cname
1	class1
2	class1
3	class3
4	class3
5	class4
1	class5
2	class5
3	class5
4	class5
5	class5

select student.sname from student where student.snum in (select enrolled.snum from enrolled where enrolled.cname in (select class.cname from class where class.fid in (select f.fid from faculty f where f.fname='Harish')))) and student.lv1='Jr'; #1

Showing rows 0 - 0 (1 total, Query took 0.0098 seconds.)

```
select student.sname from student where student.snum in (select enrolled.snum from enrolled where enrolled.cname in (select class.cname from class where class.fid in (select f.fid from faculty f where f.fname='Harish')))) and student.lv1='Jr'
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all | Number of rows: 25 | Filter rows:

+ Options

	sname
<input type="checkbox"/> Edit Copy Delete	Tom

select class.cname from class where class.cname in (select enrolled.cname from enrolled group by enrolled.cname having count(*)>=5) or class.room='R128'; #2

Showing rows 0 - 2 (3 total, Query took 0.0513 seconds.)

```
select class.cname from class where class.cname in (select enrolled.cname from enrolled group by enrolled.cname having count(*)>=5) or class.room='R128'
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all | Number of rows: 25 | Filter rows: Sort by key: None

+ Options

	cname
<input type="checkbox"/> Edit Copy Delete	class10
<input type="checkbox"/> Edit Copy Delete	class5
<input type="checkbox"/> Edit Copy Delete	class6

create table ref as(

select ou.cname,ou.meets_at from class ou where exists (select inn.cname from class inn where inn.meets_at=ou.meets_at having count(*)>1)

); #3

create table ref1 as(

select enrolled.snum,enrolled.cname,ref.meets_at from enrolled inner join ref on
enrolled.cname=ref.cname

); #3

select student.sname from student where student.snum in (select ou.snum from ref1 ou,
ref1 inn where ou.snum=inn.snum AND ou.cname!=inn.cname and
ou.meets_at=inn.meets_at group by ou.snum); #3

Showing rows 0 - 0 (1 total, Query took 0.0103 seconds.)

#3 select student.sname from student where student.snum in (select ou.snum from ref1 ou, ref1 inn where ou.snum=inn.snum AND ou.cname!=inn.cname and ou.meets_at=inn.meets_at group by ou.snum)

[Edit inline] [Edit] [Create PHP code]

☐ Show all | Number of rows: 25 Filter rows: Search this table

+ Options

← T → sname

☐ Edit Copy Delete Rahul

create table ref1 as(

select count(distinct(class.room))as c from class where class.cname in (select
distinct(enrolled.cname) from enrolled)

); #4

select faculty.fname from faculty where faculty.fid in (select (class.fid) from class where
class.room in(select distinct(class.room) from class where class.cname in (select
distinct(enrolled.cname) from enrolled)) group by class.fid having count(*)=(select ref1.c
from ref1)); #4

select distinct f.fname from faculty f where not exists ((select c.room from class c) MINUS
(select c1.room from class c1 where c1.fid=f.fid));

Showing rows 0 - 0 (1 total, Query took 0.0129 seconds.)

select faculty.fname from faculty where faculty.fid in (select (class.fid) from class where class.room in(select distinct(class.room) from class where class.cname in (select distinct(enrolled.cname) from enrolled)) group by class.fid having count(*)=(select refer.c from refer))

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 Filter rows: Search this table

+ Options

← T → fname

☐ Edit Copy Delete Shiva

select faculty.fname from faculty where faculty.fid in (select class.fid from class where class.cname not in (select enrolled.cname from enrolled group by enrolled.cname having count(*)>=5)); #5

Showing rows 0 - 2 (3 total, Query took 0.0066 seconds.)

```
select faculty.fname from faculty where faculty.fid in (select class.fid from class where class.cname not in (select enrolled.cname from enrolled group by enrolled.cname having count(*)>=5))
```

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

+ Options

	fname
<input type="checkbox"/> Edit Copy Delete	Harish
<input type="checkbox"/> Edit Copy Delete	MV
<input type="checkbox"/> Edit Copy Delete	Shiva

select student.sname from student where student.snum not in (select distinct(enrolled.snum) from enrolled); #6

Showing rows 0 - 0 (1 total, Query took 0.0352 seconds.)

```
select student.sname from student where student.snum not in (select distinct(enrolled.snum) from enrolled)
```

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

	sname
<input type="checkbox"/> Edit Copy Delete	Rana

SELECT s.age, s.lvl FROM student s GROUP BY s.age, s.lvl HAVING s.lvl IN (SELECT s1.lvl FROM student

s1 WHERE s1.age=s.age GROUP BY s1.age, s1.lvl HAVING COUNT(*) >= ALL (SELECT COUNT(*) FROM

student s2 WHERE s1.age=s2.age GROUP BY s2.lvl, s2.age)) ORDER BY s.age; #7

Showing rows 0 - 4 (5 total, Query took 0.0148 seconds.) [age: 17... - 25...]

```
SELECT s.age, s.lvl FROM student s GROUP BY s.age, s.lvl HAVING s.lvl IN (SELECT s1.lvl FROM student s1 WHERE s1.age=s.age GROUP BY s1.age, s1.lvl HAVING COUNT(*) >= ALL (SELECT COUNT(*) FROM student s2 WHERE s1.age=s2.age GROUP BY s2.lvl, s2.age)) ORDER BY s.age
```

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

+ Options

	age	lvl
<input type="checkbox"/> Edit Copy Delete	17	JR
<input type="checkbox"/> Edit Copy Delete	19	SR
<input type="checkbox"/> Edit Copy Delete	20	JR
<input type="checkbox"/> Edit Copy Delete	21	FR
<input type="checkbox"/> Edit Copy Delete	25	FR

PROGRAM 5: AIRLINE FLIGHT DATABASE

Consider the following database that keeps track of airline flight information:
FLIGHTS (flno: integer, from: string, to: string, distance: integer, departs: time, arrives: time, price: integer)

AIRCRAFT (aid: integer, aname: string, cruisingrange: integer) CERTIFIED (eid: integer, aid: integer)

EMPLOYEE (eid: integer, ename: string, salary: integer)

Note that the Employees relation describes pilots and other kinds of employees as well; Every pilot is certified for some aircraft, and only pilots are certified to fly. Write each of the following queries in SQL.

- i. Find the names of aircraft such that all pilots certified to operate them have salaries more than Rs.80,000.
- ii. For each pilot who is certified for more than three aircrafts, find the eid and the maximum cruising range of the aircraft for which she or he is certified.
- iii. Find the names of pilots whose salary is less than the price of the cheapest route from Bengaluru to Frankfurt.
- iv. For all aircraft with cruising range over 1000 Kms, find the name of the aircraft and the average salary of all pilots certified for this aircraft.
- v. Find the aids of all aircraft that can be used on routes from Bengaluru to New Delhi.
- vi. A customer wants to travel from Madison to New York with no more than two changes of flight. List the choice of departure times from Madison if the customer wants to arrive in New York by 6 p.m.
- vii. Print the name and salary of every non-pilot whose salary is more than the average salary for pilots.

```
CREATE DATABASE AIRLINE;
```

```
USE AIRLINE;
```

```
CREATE TABLE FLIGHTS(
```

```
FL_ID INT, FROM_PLACE VARCHAR(20),
```

```
TO_PLACE VARCHAR(20),  
DISTANCE INT,  
DEPARTS TIME,  
ARRIVES TIME,  
PRICE INT,  
PRIMARY KEY(FL_ID));
```

```
CREATE TABLE AIRCRAFT(  
A_ID INT,  
A_NAME VARCHAR(10),  
CRUISING_RANGE INT,  
PRIMARY KEY(A_ID));
```

```
CREATE TABLE EMPLOYEE(  
E_ID INT,  
E_NAME VARCHAR(10),  
SALARY INT,  
PRIMARY KEY(E_ID));
```

```
CREATE TABLE CERTIFIED(  
E_ID INT,  
A_ID INT,  
FOREIGN KEY(E_ID) REFERENCES EMPLOYEE(E_ID),  
FOREIGN KEY(A_ID) REFERENCES AIRCRAFT(A_ID));
```

```
INSERT INTO FLIGHTS VALUES(111,'BENGALURU','FRANKFURT',1000,'09:30','16:00',10000);  
INSERT INTO FLIGHTS VALUES(222,'MANDISON','BENGALURU',1020,'01:30','7:00',9000);  
INSERT INTO FLIGHTS VALUES(333,'BENGALURU','FRANKFURT',1000,'01:40','12:00',9500);  
INSERT INTO FLIGHTS VALUES(555,'NEW DELHI','NEW YORK',5000,'13:30','17:00',15000);
```

INSERT INTO FLIGHTS VALUES(444,'BENGALURU','NEW DELHI',550,'08:00','13:00',5000);

INSERT INTO FLIGHTS VALUES(666,'MANDISION','NEW YORK',12000,'16:30','19:00',20000);

		FL_ID	FROM_PLACE	TO_PLACE	DISTANCE	DEPARTS	ARRIVES	PRICE
<input type="checkbox"/>	Edit Copy Delete	111	BENGALURU	FRANKFURT	1000	09:30:00	16:00:00	10000
<input type="checkbox"/>	Edit Copy Delete	222	MANDISION	BENGALURU	1020	01:30:00	07:00:00	9000
<input type="checkbox"/>	Edit Copy Delete	333	BENGALURU	FRANKFURT	1000	01:40:00	12:00:00	9500
<input type="checkbox"/>	Edit Copy Delete	444	BENGALURU	NEW DELHI	550	08:00:00	13:00:00	5000
<input type="checkbox"/>	Edit Copy Delete	555	NEW DELHI	NEW YORK	5000	13:30:00	17:00:00	15000
<input type="checkbox"/>	Edit Copy Delete	666	MANDISION	NEW YORK	12000	16:30:00	19:00:00	20000

SELECT * FROM FLIGHTS;

INSERT INTO AIRCRAFT VALUES(10,'AIR ASIA',12000);

INSERT INTO AIRCRAFT VALUES(20,'GO AIR',2000);

INSERT INTO AIRCRAFT VALUES(30,'AIR ASIA',600);

INSERT INTO AIRCRAFT VALUES(40,'INDIGO',5000);

INSERT INTO AIRCRAFT VALUES(50,'SPICE JET',900);

INSERT INTO AIRCRAFT VALUES(60,'SPICE JET',12500);

		A_ID	A_NAME	CRUISING_RANGE
<input type="checkbox"/>	Edit Copy Delete	10	AIR ASIA	12000
<input type="checkbox"/>	Edit Copy Delete	20	GO AIR	2000
<input type="checkbox"/>	Edit Copy Delete	30	AIR ASIA	600
<input type="checkbox"/>	Edit Copy Delete	40	INDIGO	5000
<input type="checkbox"/>	Edit Copy Delete	50	SPICE JET	900
<input type="checkbox"/>	Edit Copy Delete	60	SPICE JET	12500

SELECT * FROM AIRCRAFT;

INSERT INTO EMPLOYEE VALUES(3,'SHAAN',60000);




















INSERT INTO EMPLOYEE VALUES(2,'TANYA',15000);

INSERT INTO EMPLOYEE VALUES(4,'RAJATH',81000);

INSERT INTO EMPLOYEE VALUES(1,'SAM',82000);

INSERT INTO EMPLOYEE VALUES(6,'AYMAN',70000);

INSERT INTO EMPLOYEE VALUES(5,'SAAKSHI',9000);

	E_ID	E_NAME	SALARY
<input type="checkbox"/>  Edit  Copy  Delete	1	SAM	82000
<input type="checkbox"/>  Edit  Copy  Delete	2	TANYA	15000
<input type="checkbox"/>  Edit  Copy  Delete	3	SHAAN	60000
<input type="checkbox"/>  Edit  Copy  Delete	4	RAJATH	81000
<input type="checkbox"/>  Edit  Copy  Delete	5	SAAKSHI	9000
<input type="checkbox"/>  Edit  Copy  Delete	6	AYMAN	70000

SELECT * FROM EMPLOYEE;

INSERT INTO CERTIFIED VALUES(1,10);

INSERT INTO CERTIFIED VALUES(4,10);

INSERT INTO CERTIFIED VALUES(3,40);

INSERT INTO CERTIFIED VALUES(5,30);

INSERT INTO CERTIFIED VALUES(5,50);

INSERT INTO CERTIFIED VALUES(4,50);

INSERT INTO CERTIFIED VALUES(4,20);

INSERT INTO CERTIFIED VALUES(4,30);

E_ID	A_ID
1	10
4	10
3	40
5	30
5	50
4	50
4	20
4	30

SELECT * FROM CERTIFIED;

SELECT DISTINCT A.A_NAME FROM AIRCRAFT A WHERE A.A_ID IN (SELECT C.A_ID FROM CERTIFIED C, EMPLOYEE E WHERE C.E_ID = E.E_ID AND NOT EXISTS (SELECT * FROM EMPLOYEE E1 WHERE E1.E_ID = E.E_ID AND E1.SALARY <80000)); #1

✓ Showing rows 0 - 2 (3 total, Query took 0.0118 seconds.)

```
SELECT DISTINCT A.A_NAME FROM AIRCRAFT A WHERE A.A_ID IN (SELECT C.A_ID FROM CERTIFIED C, EMPLOYEE E WHERE C.E_ID = E.E_ID AND NOT EXISTS ( SELECT * FROM EMPLOYEE E1 WHERE E1.E_ID = E.E_ID AND E1.SALARY <80000 ))
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

+ Options

	A_NAME
<input type="checkbox"/> Edit Copy Delete	AIR ASIA
<input type="checkbox"/> Edit Copy Delete	GO AIR
<input type="checkbox"/> Edit Copy Delete	SPICE JET

SELECT C.E_ID,MAX(A.CRUSING_RANGE) AS MAX_CRUSING_RANGE FROM CERTIFIED C,AIRCRAFT A WHERE C.A_ID=A.A_ID AND C.E_ID=(SELECT E_ID FROM CERTIFIED GROUP BY E_ID HAVING COUNT(*)>3); #2

✓ Showing rows 0 - 0 (1 total, Query took 0.0137 seconds.)

```
SELECT C.E_ID,MAX(A.CRUSING_RANGE) AS MAX_CRUSING_RANGE FROM CERTIFIED C,AIRCRAFT A WHERE C.A_ID=A.A_ID AND C.E_ID=(SELECT E_ID FROM CERTIFIED GROUP BY E_ID HAVING COUNT(*)>3)
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

E_ID	MAX_CRUSING_RANGE
4	12000

SELECT E_NAME FROM EMPLOYEE WHERE E_ID IN (SELECT E_ID FROM CERTIFIED) AND SALARY<(SELECT MIN(PRICE) FROM FLIGHTS WHERE FROM_PLACE='BENGALURU' AND TO_PLACE='FRANKFURT'); #3

✓ Showing rows 0 - 0 (1 total, Query took 0.0048 seconds.)

```
SELECT E_NAME FROM EMPLOYEE WHERE E_ID IN (SELECT E_ID FROM CERTIFIED) AND SALARY<(SELECT MIN(PRICE) FROM FLIGHTS WHERE FROM_PLACE='BENGALURU' AND TO_PLACE='FRANKFURT')
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

E_NAME
SAAKSHI

SELECT C.A_ID,AVG(E.SALARY) AS AVERAGE_SALARY FROM EMPLOYEE E,CERTIFIED C WHERE E.E_ID=C.E_ID AND C.A_ID IN (SELECT A_ID FROM AIRCRAFT WHERE CRUSING_RANGE>1000) GROUP BY C.A_ID; #4

✓ Showing rows 0 - 2 (3 total, Query took 0.0057 seconds.)

```
SELECT C.A_ID,AVG(E.SALARY) AS AVERAGE_SALARY FROM EMPLOYEE E,CERTIFIED C WHERE E.E_ID=C.E_ID AND C.A_ID IN (SELECT A_ID FROM AIRCRAFT WHERE CRUISING_RANGE>1000) GROUP BY C.A_ID
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

A_ID	AVERAGE_SALARY
10	81500.0000
20	81000.0000
40	60000.0000

SELECT A_ID FROM AIRCRAFT WHERE CRUISING_RANGE>(SELECT DISTANCE FROM FLIGHTS WHERE FROM_PLACE='BENGALURU' AND TO_PLACE='NEW DELHI'); #5

✓ Showing rows 0 - 5 (6 total, Query took 0.0039 seconds.)

```
SELECT A_ID FROM AIRCRAFT WHERE CRUISING_RANGE>(SELECT DISTANCE FROM FLIGHTS WHERE FROM_PLACE='BENGALURU' AND TO_PLACE='NEW DELHI')
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

+ Options

	A_ID
<input type="checkbox"/> Edit Copy Delete	10
<input type="checkbox"/> Edit Copy Delete	20
<input type="checkbox"/> Edit Copy Delete	30
<input type="checkbox"/> Edit Copy Delete	40
<input type="checkbox"/> Edit Copy Delete	50
<input type="checkbox"/> Edit Copy Delete	60

SELECT F.DEPARTS FROM FLIGHTS F WHERE F.FL_ID IN ((SELECT F0.FL_ID FROM FLIGHTS F0 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE = 'NEW YORK'

AND EXTRACT(HOUR FROM F0.ARRIVES) < 18) UNION (SELECT F0.FL_ID FROM FLIGHTS F0, FLIGHTS F1 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE <> 'NEW YORK'

AND F0.TO_PLACE = F1.FROM_PLACE AND F1.TO_PLACE = 'NEW YORK' AND F1.DEPARTS > F0.ARRIVES AND EXTRACT(HOUR FROM F1.ARRIVES) < 18)

UNION(SELECT F0.FL_ID FROM FLIGHTS F0, FLIGHTS F1, FLIGHTS F2 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE = F1.FROM_PLACE AND F1.TO_PLACE = F2.FROM_PLACE

AND F2.TO_PLACE = 'NEW YORK' AND F0.TO_PLACE <> 'NEW YORK' AND F1.TO_PLACE <> 'NEW YORK' AND F1.DEPARTS > F0.ARRIVES AND F2.DEPARTS > F1.ARRIVES

AND EXTRACT(HOUR FROM F2.ARRIVES) < 18)); #6

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0511 seconds.)

```
SELECT F.DEPARTS FROM FLIGHTS F WHERE F.FL_ID IN ( ( SELECT F0.FL_ID FROM FLIGHTS F0 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE = 'NEW YORK' AND EXTRACT(HOUR FROM F0.ARRIVES) < 18 ) UNION ( SELECT F0.FL_ID FROM FLIGHTS F0, FLIGHTS F1 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE <> 'NEW YORK' AND F0.TO_PLACE = F1.FROM_PLACE AND F1.TO_PLACE = 'NEW YORK' AND F1.DEPARTS > F0.ARRIVES AND EXTRACT(HOUR FROM F1.ARRIVES) < 18 ) UNION( SELECT F0.FL_ID FROM FLIGHTS F0, FLIGHTS F1, FLIGHTS F2 WHERE F0.FROM_PLACE = 'MANDISION' AND F0.TO_PLACE = F1.FROM_PLACE AND F1.TO_PLACE = F2.FROM_PLACE AND F2.TO_PLACE = 'NEW YORK' AND F0.TO_PLACE <> 'NEW YORK' AND F1.TO_PLACE <> 'NEW YORK' AND F1.DEPARTS > F0.ARRIVES AND F2.DEPARTS > F1.ARRIVES AND EXTRACT(HOUR FROM F2.ARRIVES) < 18 ))
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

DEPARTS

SELECT E_NAME,SALARY FROM EMPLOYEE WHERE E_ID NOT IN(SELECT E_ID FROM CERTIFIED) AND SALARY>(SELECT AVG(SALARY) FROM EMPLOYEE WHERE E_ID IN (SELECT E_ID FROM CERTIFIED)); #7

✓ Showing rows 0 - 0 (1 total, Query took 0.0064 seconds.)

```
SELECT E_NAME,SALARY FROM EMPLOYEE WHERE E_ID NOT IN(SELECT E_ID FROM CERTIFIED) AND SALARY>(SELECT AVG(SALARY) FROM EMPLOYEE WHERE E_ID IN (SELECT E_ID FROM CERTIFIED))
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

	E_NAME	SALARY
<input type="checkbox"/> Edit Copy Delete	AYMAN	70000

