



```
In [1]: import numpy as np
import matplotlib.pyplot as plt
from sklearn import tree
from sklearn.datasets import load_iris
from itertools import combinations
```

```
In [2]: iris = load_iris()
X = iris.data
y = iris.target
feature_names = iris.feature_names
target_names = iris.target_names
```

```
In [3]: print("Feature names:", feature_names)
print("Target names:", target_names)
print("\nFirst 5 samples:\n", X[:5])
print("\nFirst 5 labels:\n", y[:5])
```

Feature names: ['sepal length (cm)', 'sepal width (cm)', 'petal length (cm)', 'petal width (cm)']

Target names: ['setosa' 'versicolor' 'virginica']

First 5 samples:

```
[[5.1 3.5 1.4 0.2]
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]]
```

First 5 labels:

```
[0 0 0 0 0]
```

```
In [4]: plot_colors = "ryb"
plot_step = 0.02
```

```
In [5]: plt.figure(figsize=(12, 10))
pair_index = 1
```

<Figure size 1200x1000 with 0 Axes>

```
In [8]: pair_index = 1
for pair in combinations(range(4), 2):
    X_pair = X[:, pair]
    clf = tree.DecisionTreeClassifier(criterion='entropy', max_depth=4, random
    clf.fit(X_pair, y)

    x_min, x_max = X_pair[:, 0].min() - 1, X_pair[:, 0].max() + 1
    y_min, y_max = X_pair[:, 1].min() - 1, X_pair[:, 1].max() + 1
    xx, yy = np.meshgrid(np.arange(x_min, x_max, plot_step), np.arange(y_min,

    plt.subplot(2, 3, pair_index)
    Z = clf.predict(np.c_[xx.ravel(), yy.ravel()])
    Z = Z.reshape(xx.shape)
    cs = plt.contourf(xx, yy, Z, cmap=plt.cm.RdYlBu)
```

```

plt.xlabel(feature_names[pair[0]])
plt.ylabel(feature_names[pair[1]])


for i, color in zip(range(len(target_names)), plot_colors):
    idx = np.where(y == i)
    plt.scatter(X_pair[idx, 0], X_pair[idx, 1], c=y[idx], label=target_names[i])

plt.title('Decision Surface of Decision Tree')
plt.legend()
plt.tight_layout()
pair_index += 1


plt.show()

```

Decision Surface of Decision Tree Decision Surface of Decision Tree Decision Surface of Decision Tree



Decision Surface of Decision Tree Decision Surface of Decision Tree Decision Surface of Decision Tree



```

In [10]: x_min, x_max = X_pair[:, 0].min() - 1, X_pair[:, 0].max() + 1
          y_min, y_max = X_pair[:, 1].min() - 1, X_pair[:, 1].max() + 1
          xx, yy = np.meshgrid(np.arange(x_min, x_max, plot_step),
                               np.arange(y_min, y_max, plot_step))

```

```

In [11]: Z = clf.predict(np.c_[xx.ravel(), yy.ravel()])
          Z = Z.reshape(xx.shape)

```

```

In [14]: plt.figure(figsize=(12, 10))

          for pair_index, pair in enumerate(combinations(range(4), 2), start=1):
              X_pair = X[:, pair]
              clf = tree.DecisionTreeClassifier(criterion='entropy', max_depth=4, random

```

```

clf.fit(X_pair, y)

x_min, x_max = X_pair[:, 0].min() - 1, X_pair[:, 0].max() + 1
y_min, y_max = X_pair[:, 1].min() - 1, X_pair[:, 1].max() + 1
xx, yy = np.meshgrid(np.arange(x_min, x_max, 0.02),
                     np.arange(y_min, y_max, 0.02))
Z = clf.predict(np.c_[xx.ravel(), yy.ravel()]).reshape(xx.shape)

plt.subplot(3, 2, pair_index)
plt.contourf(xx, yy, Z, alpha=0.3, cmap=plt.cm.RdYlBu)

plot_colors = "ryb"
for i, color in zip(range(3), plot_colors):
    plt.scatter(X_pair[y == i, 0], X_pair[y == i, 1],
                c=color, label=target_names[i], edgecolor='k', s=30)

plt.xlabel(feature_names[pair[0]])
plt.ylabel(feature_names[pair[1]])
plt.title(f"Decision Boundary ({feature_names[pair[0]]} vs {feature_names[pair[1]]})")
plt.legend()

plt.tight_layout()
plt.show()

```

