



```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.datasets import load_iris
from sklearn.preprocessing import StandardScaler
from sklearn.cluster import KMeans
from sklearn.metrics import silhouette_score
```

```
In [3]: iris = load_iris()
X = iris.data
y_true = iris.target # true labels for comparison
```

```
In [4]: scaler = StandardScaler()
X_scaled = scaler.fit_transform(X)
```

```
In [5]: silhouette_scores = []
K_range = range(2, 11)
```


```
In [7]: for k in K_range:
    kmeans = KMeans(n_clusters=k, random_state=42, n_init=10)
    kmeans.fit(X_scaled)
    score = silhouette_score(X_scaled, kmeans.labels_)
    silhouette_scores.append(score)
    print(f"k = {k}, Silhouette Score = {score:.4f}")
```

```
k = 2, Silhouette Score = 0.5818
k = 3, Silhouette Score = 0.4599
k = 4, Silhouette Score = 0.3869
k = 5, Silhouette Score = 0.3459
k = 6, Silhouette Score = 0.3171
k = 7, Silhouette Score = 0.3202
k = 8, Silhouette Score = 0.3387
k = 9, Silhouette Score = 0.3424
k = 10, Silhouette Score = 0.3518
```

```
In [8]: best_k = K_range[np.argmax(silhouette_scores)]
print(f"\nBest number of clusters (k) = {best_k}")
```

Best number of clusters (k) = 2

```
In [9]: kmeans_final = KMeans(n_clusters=best_k, random_state=42, n_init=10)
kmeans_final.fit(X_scaled)
```

```
Out[9]: 
KMeans(n_clusters=2, n_init=10, random_state=42)
```

```
In [10]: labels = kmeans_final.labels_
centers = kmeans_final.cluster_centers_

cluster_sizes = pd.Series(labels).value_counts().sort_index()
print("\nCluster Sizes:")
```

```
print(cluster_sizes)

print("\nCluster Centers (Standardized Feature Space):")
print(pd.DataFrame(centers, columns=iris.feature_names))
```

Cluster Sizes:

```
0    100
1     50
```

Name: count, dtype: int64

Cluster Centers (Standardized Feature Space):


	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)
0	0.507289	-0.426631	0.652494	0.627447
1	-1.014579	0.853263	-1.304987	-1.254893

```
In [11]: comparison = pd.crosstab(labels, y_true, rownames=['Cluster'], colnames=['True Species'])
print("\nMapping of Clusters to True Species:")
print(comparison)
```

Mapping of Clusters to True Species:

True Species	0	1	2
Cluster			
0	0	50	50
1	50	0	0

```
In [12]: plt.figure(figsize=(8, 6))
plt.scatter(X_scaled[:, 0], X_scaled[:, 1], c=labels, cmap='viridis', s=50)
plt.scatter(centers[:, 0], centers[:, 1], c='red', marker='X', s=200, label='Centers')
plt.xlabel('Standardized Sepal Length')
plt.ylabel('Standardized Sepal Width')
plt.title(f'K-Means Clustering (k={best_k}) on Iris Dataset')
plt.legend()
plt.grid(True)
plt.show()
```



```
In [13]: print("\nCluster Analysis Complete.")
```

Cluster Analysis Complete.