

Aim:

Write a program to implement stack using **linked lists**.

Sample Input and Output:

```

1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 1
Enter element : 33
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 1
Enter element : 22
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 1
Enter element : 55
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 1
Enter element : 66
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 3
Elements of the stack are : 66 55 22 33
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 2
Popped value = 66
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 2
Popped value = 55
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 3
Elements of the stack are : 22 33
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 5
Peek value = 22
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 4
Stack is not empty.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option : 6

```

Source Code:

StackUsingLList.c

```

#include<stdio.h>
#include<stdlib.h>
void display();
void peek();
void isEmpty();
int main() {

```

```
int op,x;
while(1) {
    printf("1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit\n");
    printf("Enter your option : ");
    scanf("%d",&op);
    switch(op) {
        case 1:
            printf("Enter element : ");
            scanf("%d",&x);
            push(x);
            break;
        case 2:
            pop();
            break;
        case 3:
            display();
            break;
        case 4:
            isEmpty();
            break;
        case 5:
            peek();
            break;
        case 6:
            exit(0);
    }
}
}
struct stack {
    int data;
    struct stack *next;
};
typedef struct stack *stk;
stk top = NULL;
void push(int x) {
    stk temp;
    temp = (stk)malloc(sizeof(struct stack));
    if(temp == NULL)
        printf("Stack is overflow.\n");
    else {
        temp->data=x;
        temp->next=top;
        top=temp;
        printf("Successfully pushed.\n");
    }
}
void display() {
    if(top==NULL)
        printf("Stack is empty.\n");
    else {
        printf("Elements of the stack are : ");
        stk temp=top;
        while(temp!=NULL) {
            printf("%d ",temp->data);
            temp=temp->next;
        }
    }
}
```

```

        printf("\n");
    }
}
void pop() {
    if(top==NULL)
        printf("Stack is underflow.\n");
    else {
        printf("Popped value = ");
        stk temp = top;
        top = top->next;
        printf("%d\n",temp->data);
        free(temp);
    }
}
void peek() {
    if(top==NULL)
        printf("Stack is underflow.\n");
    else {
        printf("Peek value = ");
        stk temp = top;
        printf("%d\n",temp->data);
    }
}
void isEmpty() {
    if(top==NULL)
        printf("Stack is empty.\n");
    else
        printf("Stack is not empty.\n");
}
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 33
Successfully pushed. 1
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 22
Successfully pushed. 1
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 55
Successfully pushed. 1
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 66
Successfully pushed. 3
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 3
Enter your option : 3
Elements of the stack are : 66 55 22 33 2

1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2
Popped value = 66 2
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2
Popped value = 55 3
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 3
Enter your option : 3
Elements of the stack are : 22 33 5
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 5
Enter your option : 5
Peek value = 22 4
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 4
Enter your option : 4
Stack is not empty. 6
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 6
Enter your option : 6

Test Case - 2
User Output
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2
Stack is underflow. 3
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 3
Enter your option : 3
Stack is empty. 5
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 5
Enter your option : 5
Stack is underflow. 4
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 4
Enter your option : 4
Stack is empty. 1
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 23
Successfully pushed. 1
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 1
Enter your option : 1
Enter element : 24
Successfully pushed. 3
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 3
Enter your option : 3
Elements of the stack are : 24 23 5
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 5
Enter your option : 5
Peek value = 24 2
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2
Popped value = 24 2
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2

Popped value = 23 2
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 2
Enter your option : 2
Stack is underflow. 4
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 4
Enter your option : 4
Stack is empty. 6
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit 6
Enter your option : 6