In [2]:
```
import pandas as pd
from sklearn.datasets import load_iris
iris = load_iris()
```

In [3]:
```
dir(iris)
```

Out[3]:
```
['DESCR',
 'data',
 'data_module',
 'feature_names',
 'filename',
 'frame',
 'target',
 'target_names']
```

In [4]:
```
iris.feature_names
```

Out[4]:
```
['sepal length (cm)',
 'sepal width (cm)',
 'petal length (cm)',
 'petal width (cm)']
```

In [5]:
```
iris.target_names
```

Out[5]:
```
array(['setosa', 'versicolor', 'virginica'], dtype='<U10')
```

In [6]:
```
df = pd.DataFrame(iris.data,columns=iris.feature_names)
```

In [7]:
```
df.head()
```

Out[7]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)
0	5.1	3.5	1.4	0.2
1	4.9	3.0	1.4	0.2
2	4.7	3.2	1.3	0.2
3	4.6	3.1	1.5	0.2
4	5.0	3.6	1.4	0.2

In [8]:
```
df['target'] = iris.target
df.head()
```

Out[8]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	target
0	5.1	3.5	1.4	0.2	0
1	4.9	3.0	1.4	0.2	0
2	4.7	3.2	1.3	0.2	0
3	4.6	3.1	1.5	0.2	0
4	5.0	3.6	1.4	0.2	0

In [9]:
```
df[df.target==1].head()
```

Out[9]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	target
50	7.0	3.2	4.7	1.4	1
51	6.4	3.2	4.5	1.5	1
52	6.9	3.1	4.9	1.5	1
53	5.5	2.3	4.0	1.3	1
54	6.5	2.8	4.6	1.5	1

In [10]:
```
df[df.target==2].head()
```

Out[10]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	target
100	6.3	3.3	6.0	2.5	2
101	5.8	2.7	5.1	1.9	2
102	7.1	3.0	5.9	2.1	2
103	6.3	2.9	5.6	1.8	2
104	6.5	3.0	5.8	2.2	2

In [11]:
```
df['flower_name']=df.target.apply(lambda x: iris.target_names[x])
df.head()
```

Out[11]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	target	flower_name
0	5.1	3.5	1.4	0.2	0	setosa
1	4.9	3.0	1.4	0.2	0	setosa
2	4.7	3.2	1.3	0.2	0	setosa
3	4.6	3.1	1.5	0.2	0	setosa
4	5.0	3.6	1.4	0.2	0	setosa

In [12]:
```
df[45:55]
```

Out[12]:

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	target	flower_name
45	4.8	3.0	1.4	0.3	0	setosa
46	5.1	3.8	1.6	0.2	0	setosa
47	4.6	3.2	1.4	0.2	0	setosa
48	5.3	3.7	1.5	0.2	0	setosa
49	5.0	3.3	1.4	0.2	0	setosa
50	7.0	3.2	4.7	1.4	1	versicolor
51	6.4	3.2	4.5	1.5	1	versicolor
52	6.9	3.1	4.9	1.5	1	versicolor
53	5.5	2.3	4.0	1.3	1	versicolor
54	6.5	2.8	4.6	1.5	1	versicolor

In [13]:
```
df0 = df[:50]
df1 = df[50:100]
df2 = df[100:]
```

In [14]:
```
import matplotlib.pyplot as plt
%matplotlib inline
```

In [15]:
```
plt.xlabel('Sepal Length')
plt.ylabel('Sepal Width')
plt.scatter(df0['sepal length (cm)'], df0['sepal width (cm)'],color='green',marker='+')
plt.scatter(df1['sepal length (cm)'], df1['sepal width (cm)'],color='blue',marker='.')
plt.show()
```



In [16]:
```
plt.xlabel('Petal Length')
plt.ylabel('Petal Width')
plt.scatter(df0['petal length (cm)'], df0['petal width (cm)'],color='green',marker='+')
plt.scatter(df1['petal length (cm)'], df1['petal width (cm)'],color='blue',marker='.')
plt.show()
```



In [17]:
```
from sklearn.model_selection import train_test_split
```

In [18]:
```
x = df.drop(['target','flower_name'],axis='columns')
y = df.target
```

In [19]:
```
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2)
```

In [20]:
```
len(x_train)
```

Out[20]:
```
120
```

In [21]:
```
len(x_test)
```

Out[21]:
```
30
```

In [22]:
```
from sklearn.svm import SVC
model = SVC()
```

In [23]:
```
model.fit(x_train, y_train)
```

Out[23]:
```
SVC()
```

In [24]:
```
model.score(x_test, y_test)
```

Out[24]:
```
0.9666666666666667
```

In [25]:
```
model.predict([[4.8,3.0,1.5,0.3]])
```

```
C:\Users\Sai Sushma Iska\anaconda3\Lib\site-packages\sklearn\base.py:493: UserWarning: X does not have valid feature names, but SVC was fitted with feature names
  warnings.warn(
```

Out[25]:
```
array([0])
```

In [26]:
```
model.predict([[5.3,3.7,1.5,0.2]])
```

```
C:\Users\Sai Sushma Iska\anaconda3\Lib\site-packages\sklearn\base.py:493: UserWarning: X does not have valid feature names, but SVC was fitted with feature names
  warnings.warn(
```

Out[26]:
```
array([0])
```

In [27]:
```
model.predict([[6.5,2.8,4.6,1.5]])
```

```
C:\Users\Sai Sushma Iska\anaconda3\Lib\site-packages\sklearn\base.py:493: UserWarning: X does not have valid feature names, but SVC was fitted with feature names
  warnings.warn(
```

Out[27]:
```
array([1])
```

In [28]:
```
model_C = SVC(C=1)
model_C.fit(x_train, y_train)
model_C.score(x_test, y_test)
```

Out[28]:
```
0.9666666666666667
```

In [29]:
```
model_C = SVC(C=10)
model_C.fit(x_train, y_train)
model_C.score(x_test, y_test)
```

Out[29]:
```
1.0
```