Conflicting Appointments (medium)

Problem Statement

Given an array of intervals representing 'N' appointments, find out if a person can **attend all the appointments**.

Example 1:

```
Appointments: [[1,4], [2,5], [7,9]]
Output: false
Explanation: Since [1,4] and [2,5] overlap, a person cannot attend both of these appointments.
```

Example 2:

```
Appointments: [[6,7], [2,4], [8,12]]
Output: true
Explanation: None of the appointments overlap, therefore a person can attend all of them.
```

Example 3:

```
Appointments: [[4,5], [2,3], [3,6]]
Output: false
Explanation: Since [4,5] and [3,6] overlap, a person cannot attend both of these appointments.
```

Try it yourself

Try solving this question here:

Java

```
import java.util.*;

/*class Interval {
  int start;
  int end;

  public Interval(int start, int end) {
    this.start = start;
    this.end = end;
  }
```

```
11   };*/
12
13   class Solution {
14
15     public static boolean canAttendAllAppointments(Interval[] intervals) {
16       // TODO: Write your code here
17       return false;
18     }
19   }
20
```

Test Case | Run Code Result | Stdout

```
[[1, 4], [2, 5], [7, 9]]
```

Use Example Testcases | Run | Submit

← Previous

Solution: Intervals Intersection

Next →

Solution: Conflicting Appointments

Mark as Completed