Solution: Problem Challenge 3: Find the First K Missing Positive Numbers

Problem Statement

Given an unsorted array containing numbers and a number ‘k’, find the first ‘k’ missing positive numbers in the array.

Example 1:

```
Input: [3, -1, 4, 5, 5], k=3
Output: [1, 2, 6]
Explanation: The smallest missing positive numbers are 1, 2 and 6.
```

Example 2:

```
Input: [2, 3, 4], k=3
Output: [1, 5, 6]
Explanation: The smallest missing positive numbers are 1, 5 and 6.
```

Example 3:

```
Input: [-2, -3, 4], k=2
Output: [1, 2]
Explanation: The smallest missing positive numbers are 1 and 2.
```

Solution

This problem follows the **Cyclic Sort** pattern and shares similarities with `Find the Smallest Missing Positive Number`. The only difference is that, in this problem, we need to find the first ‘k’ missing numbers compared to only the first missing number.

We will follow a similar approach as discussed in `Find the Smallest Missing Positive Number` to place the numbers on their correct indices and ignore all numbers that are out of the range of the array. Once we are done with the cyclic sort we will iterate through the array to find indices that do not have the correct numbers.

If we are not able to find ‘k’ missing numbers from the array, we need to add additional numbers to the output array. To find these additional numbers we will use the length of the array. For example, if the length of the array is 4, the next missing numbers will be 4, 5, 6 and so on. One tricky aspect is that any of these additional numbers could be part of the array. Remember, while sorting, we ignored all numbers that are greater than or equal to the length of the array. So all indices that have the missing numbers could possibly have these additional numbers. To handle this, we must keep track of all numbers from those indices that have missing numbers. Let’s understand this with an example:

```
    nums: [2, 1, 3, 6, 5], k =2
```

After the cyclic sort our array will look like:

```
nums: [1, 2, 3, 6, 5]
```

From the sorted array we can see that the first missing number is ‘4’ (as we have ‘6’ on the fourth index) but to find the second missing number we need to remember that the array does contain ‘6’. Hence, the next missing number is ‘7’.

Code

Here is what our algorithm will look like:

Java

```java
import java.util.*;

class Solution {

  public List<Integer> findNumbers(int[] nums, int k) {
    int i = 0;

    // Step 1: Rearrange elements in the array to their correct positions
    while (i < nums.length) {
      if (nums[i] > 0 && nums[i] <= nums.length && nums[i] != nums[nums[i] - 1])
        swap(nums, i, nums[i] - 1);
      else
        i++;
    }

    List<Integer> missingNumbers = new ArrayList<>();
    Set<Integer> extraNumbers = new HashSet<>();

    // Step 2: Find missing numbers up to 'k' by comparing each element to its position
    for (i = 0; i < nums.length && missingNumbers.size() < k; i++)
      if (nums[i] != i + 1) {
        missingNumbers.add(i + 1);
        extraNumbers.add(nums[i]);
```

Run Code Result | Stdout

You must run your code first

Execute

Time Complexity

The time complexity of the above algorithm is $O(n + k)$, as the last two for loops will run for O(n) and O(k) times respectively.

Space Complexity

The algorithm needs O(k) space to store the extraNumbers.

← Previous

Problem Challenge 3: Find The First K Missing Positive Numbers (Hard)

Next →

Introduction To In-Place Reversal Of A Linked List Pattern

Mark as Completed