Problem 5: Zigzag Iterator

Problem Statement

Given two `1d` vectors, implement an iterator to return their elements alternately.

For example, given two `1d` vectors:

```
v1 = [1, 2]
v2 = [3, 4, 5, 6]
```

By calling `next()` repeatedly until `hasNext()` returns `false`, the order of elements returned by next should be: [1, 3, 2, 4, 5, 6].

Example 1:

```
i = ZigzagIterator([1, 2], [3, 4, 5, 6])
print(i.next())  # returns 1
print(i.next())  # returns 3
print(i.next())  # returns 2
print(i.next())  # returns 4
print(i.next())  # returns 5
print(i.next())  # returns 6
print(i.hasNext())  # returns False
```

Example 2:


```
i = ZigzagIterator([1, 2, 3, 4], [5, 6])
print(i.next())  # returns 1
print(i.next())  # returns 5
print(i.next())  # returns 2
print(i.next())  # returns 6
print(i.next())  # returns 3
print(i.next())  # returns 4
print(i.hasNext())  # returns False
```

Example 3:

```
i = ZigzagIterator([1, 2], [])
print(i.next())  # returns 1
print(i.next())  # returns 2
print(i.hasNext())  # returns False
```

Try it yourself

Try solving this question here:



← Previous

Solution: Palindrome Check Using Queue

Next →

Solution: Zigzag Iterator

Mark as Completed