Problem 2: Implement Stack using Queues

Problem Statement

Implement a stack using two queues. The stack should support standard operations like push (add an element to the top of the stack) and pop (remove an element from the top of the stack). **Examples**:

1. **Input**: Push operations: [1, 2, 3], Pop operations: 2

   Output: [1]

   Explanation: After pushing 1, 2, 3 the stack looks like [1, 2, 3]. Then we perform 2 pop operations, removing 3 and 2, so the output is [1].

2. **Input**: Push operations: [9, 8], Pop operations: 1

   Output: [9]

   Explanation: After pushing 9, 8 the stack looks like [9, 8]. Then we perform 1 pop operation, removing 8, so the output is [9].

3. **Input**: Push operations: [5, 6, 7, 8], Pop operations: 4

   Output: []

   Explanation: After pushing 5, 6, 7, 8 the stack looks like [5, 6, 7, 8]. After performing 4 pop operations we are left with zero elements in the stack [].

Try it yourself


Try solving this question here:

Java

```java
import java.util.LinkedList;
import java.util.Queue;

public class Solution {
    public void push(int x) {
        // ToDo: Write Your Code Here.
    }

    public int pop() {
        // ToDo: Write Your Code Here.
        return -1;
    }
}
```



← Previous

Solution: Reverse A Queue

Next →

Solution: Implement Stack Using Queues

Mark as Completed