Problem 1: Reverse Linked List (easy)

Problem Statement:

Given the head of a singly linked list, your task is to reverse the list and return its head. The singly linked list has nodes, and each node contains an integer and a pointer to the next node. The last node in the list points to `null`, indicating the end of the list.

Examples

Example 1:

- **Input**: `[3, 5, 2]`
- **Expected Output**: `[2, 5, 3]`
- **Justification**: Reversing the list `[3, 5, 2]` gives us `[2, 5, 3]`.

Example 2:

- **Input**: `[7]`
- **Expected Output**: `[7]`
- **Justification**: Since there is only one element in the list, the reversed list remains the same.

Example 3:

- **Input**: `[-1, 0, 1]`
- **Expected Output**: `[1, 0, -1]`
- **Justification**: The list is reversed, so the elements are in the order `[1, 0, -1]`.

Try it yourself

Try solving this question here:

Java

```java
// class ListNode {
//     int val;
//     ListNode next;
//     ListNode(int x) { val = x; }
// }

class Solution {
    public ListNode reverseList(ListNode head) {
        // TODO: Write your code here
        return head;
    }
}

```

Test Case | Run Code Result | Stdout

```
[3, 5, 2]
```

Use Example Testcases | Run | Submit

← Previous

Operations On Doubly Linked List

Next →

Solution: Reverse Linked List (Easy)

Mark as Completed