Types of Indexes

Database indexes are designed to improve the speed and efficiency of data retrieval operations. They function by maintaining a separate structure that points to the rows in a table, allowing the database to look up data more quickly without scanning the entire table.

There are various types of database indexes, each with its unique characteristics and use cases. Understanding these different index types is crucial for optimizing the performance of database systems and ensuring efficient data retrieval.

In this section, we will explore several common types of database indexes, including clustered, non-clustered, unique, partial, filtered, full-text, and spatial indexes, along with examples to illustrate their applications.

1. Clustered Indexes

Clustered indexes determine the physical order of data storage in a table. The table's data is sorted and stored based on the columns specified in the clustered index. Since the order of the data is the same as the index, there can only be one clustered index per table. Clustered indexes are highly efficient for range queries, as the data is stored in a contiguous manner.

Example: In a table with a clustered index on the 'DateOfBirth' column, the rows would be stored in the order of the 'DateOfBirth' values.

2. Non-Clustered Indexes

Non-clustered indexes do not affect the physical order of data storage in a table. Instead, they maintain a separate data structure that points to the rows in the table. Multiple non-clustered indexes can be created for a table, and they can be used to optimize specific queries or access patterns.

Example: In a table with a non-clustered index on the 'LastName' column, the index would store pointers to the rows sorted by the 'LastName' values, while the actual table data remains unordered.

3. Unique Indexes

A unique index ensures that the indexed columns do not contain duplicate values. This constraint helps maintain data integrity and can be used to enforce uniqueness across one or more columns in a table.

Example: In a table with a unique index on the 'Email' column, no two rows can have the same email address.

4. Partial Indexes

A partial index includes only a subset of rows in a table based on a specified filter condition. This type of index is useful when a large table has a relatively small number of rows that are frequently queried, reducing the size and maintenance overhead of the index.

Example: In a table with a partial index on the 'Status' column where the condition is "Status = 'Active'", only rows with an 'Active' status would be included in the index.

5. Filtered Indexes

Similar to partial indexes, filtered indexes include only a subset of rows based on a specified filter condition. However, filtered indexes are specific to Microsoft SQL Server and provide additional optimization options for queries with specific predicates.

Example: In a table with a filtered index on the 'ProductID' column where the condition is "Price > 100", only rows with a price greater than 100 would be included in the index.

6. Full-Text Indexes

Full-text indexes are designed to support complex text-based searches, such as natural language queries or pattern matching. This type of index enables searching for words or phrases within large text fields or documents, offering more advanced search capabilities compared to traditional indexes.

Example: In a table with a full-text index on the 'Description' column, users can search for rows containing specific words or phrases in the 'Description' field.

7. Spatial Indexes

Spatial indexes are used to optimize queries involving spatial data types, such as geometry or geography data. They enable efficient processing of spatial queries, such as finding objects within a specific area or calculating distances between objects.

Example: In a table containing location information, a spatial index on the 'GeoCoordinates' column would enable fast retrieval of nearby locations based on latitude and longitude coordinates.

← Previous

What Are Indexes?

Next →

Introduction To Bloom Filters