Buddy Strings (easy)

Problem Statement

Given two strings `a` and `b`, return `true` if they can be considered "buddy strings". Otherwise, return `false`.

Two strings are `buddy strings` if you can `swap` any two letters in one string to make it `equal` to the other string.

Examples

- **Example 1**:
  - **Input**: `a = "xy", b = "yx"`
  - **Expected Output**: true
  - **Justification**: Swapping 'x' and 'y' in string `a` results in "yx", which matches string `b`.
- **Example 2**:
  - **Input**: `a = "ab", b = "cd"`
  - **Expected Output**: false
  - **Justification**: There are differences at every position, and swapping any characters in `a` cannot make it equal to `b`.
- **Example 3**:
  - **Input**: `a = "abcde", b = "acbde"`
  - **Expected Output**: true
  - **Justification**: Swapping 'b' and 'c' in string `a` results in "acbde", which matches string `b`.

Try it yourself

Try solving this question here:



Java

```java
public class Solution {
    // Method to check if two strings are buddy strings
    public boolean buddyStrings(String a, String b) {
            // ToDo: Write Your Code Here.
            return false;
        }
}

```

Test Case | Run Code Result | Stdout

"xy"
"yx"

Use Example Testcases | Run | Submit

← Previous

Who Should Take This Course?

Next →

Solution: Buddy Strings

Mark as Completed