Decode String (Medium)

Problem Statement

You have a string that represents encodings of substrings, where each encoding is of the form `k[encoded_string]`, where `k` is a positive integer, and `encoded_string` is a string that contains letters only.

Your task is to decode this string by repeating the `encoded_string` `k` times and return it. It is given that `k` is always a positive integer.

Examples

1.
   - **Input**: `"3[a3[c]]"`
   - **Expected Output**: `"acccacccaccc"`
   - **Justification**: The inner `3[c]` is decoded as `ccc`, and then `a` is appended to the front, forming `acc`. This is then repeated 3 times to form `acccacccaccc`.

2.
   - **Input**: `"2[b3[d]]"`
   - **Expected Output**: `"bdddbddd"`
   - **Justification**: The inner `3[d]` is decoded as `ddd`, and then `b` is appended to the front, forming `bddd`. This is then repeated 2 times to form `bddd bddd`.

3.
   - **Input**: `"4[z]"`
   - **Expected Output**: `"zzzz"`
   - **Justification**: The `4[z]` is decoded as `z` repeated 4 times, forming `zzzz`.

Try it yourself

Try solving this question here:

Java

```java
import java.util.Stack;

public class Solution {
    public String decodeString(String s) {
        // ToDo: Write Your Code Here.
        return "";
    }
}

```

Test Case | Run Code Result | Stdout

"3[a]2[bc]"

Use Example Testcases | Run | Submit