Min Cost Climbing Stairs (easy)

Problem Statement

Given an array of integers `cost` , where `cost[i]` represents the cost of the ith step on a staircase, determine the minimum total cost to reach the top of the staircase.

It is given that once you pay the cost, you can climb the stairs by either taking `one step` or `two steps` at a time. You can start stepping either from the `0` or `1` index.

Examples

1. **Example 1**:
   - **Input**: `[2, 7, 9, 3, 1]`
   - **Expected Output**: 10
   - **Justification**: The minimum cost path starts on the second step (cost=7), then jumps two steps to the fourth step (cost=3), and finally reaches the end, totaling a cost of 10.
2. **Example 2**:
   - **Input**: `[3, 2, 10, 1]`
   - **Expected Output**: 3
   - **Justification**: The minimum cost path is starting on the second step (cost=2) and then jumping two steps to the last step (cost=1), totaling a cost of 3.
3. **Example 3**:
   - **Input**: `[5, 10, 5, 15, 10, 5, 20]`
   - **Expected Output**: 25
   - **Justification**: The optimal path involves taking the first step (cost=5), skipping to the third step (cost=5), then to the fifth step (cost=10), and finally to the sixth step (cost=5), totaling a cost of 25.

Try it yourself

Try solving this question here:

Java

```java
public class Solution {
    public int minCostClimbingStairs(int[] cost) {
        // ToDo: Write Yoru code Here.
        return 0;
    }
}
```

Test Case | Run Code Result | Stdout

[5,10,5,15,10,5,20]

Use Example Testcases | Run | Submit