Problem Challenge 1: Reconstructing a Sequence (hard)

Problem Statement

Given a sequence `originalSeq` and an array of sequences, write a method to find if `originalSeq` can be **uniquely** reconstructed from the array of sequences.

Unique reconstruction means that we need to find if `originalSeq` is the **only sequence** such that all sequences in the array are subsequences of it.

Example 1:

```
Input: originalSeq: [1, 2, 3, 4], seqs: [[1, 2], [2, 3], [3, 4]]
Output: true
Explanation: The sequences [1, 2], [2, 3], and [3, 4] can uniquely reconstruct
[1, 2, 3, 4], in other words, all the given sequences uniquely define the order of
numbers
in the 'originalSeq'.
```

Example 2:

```
Input: originalSeq: [1, 2, 3, 4], seqs: [[1, 2], [2, 3], [2, 4]]
Output: false
Explanation: The sequences [1, 2], [2, 3], and [2, 4] cannot uniquely reconstruct
[1, 2, 3, 4]. There are two possible sequences we can construct from the given
sequences:
1) [1, 2, 3, 4]
2) [1, 2, 4, 3]
```

Example 3:

```
Input: originalSeq: [3, 1, 4, 2, 5], seqs: [[3, 1, 5], [1, 4, 2, 5]]
Output: true
Explanation: The sequences [3, 1, 5] and [1, 4, 2, 5] can uniquely reconstruct
[3, 1, 4, 2, 5].
```

Try it yourself

Try solving this question here:

Java

```java
import java.util.*;

class Solution {
  public boolean canConstruct(int[] originalSeq, int[][] sequences) {
    // TODO: Write your code here
    return false;
  }
}

```

Test Case | Run Code Result | Stdout

```
[1, 2, 3, 4]
[[1, 2], [2, 3], [3, 4]]
```

Use Example Testcases | Run | Submit

← Previous

Solution: Alien Dictionary

Next →

Solution: Problem Challenge 1: Reconstructing A Sequence

Mark as Completed