Tasks Scheduling (medium)

Problem Statement

There are ‘N’ tasks, labeled from ‘0’ to ‘N-1’. Each task can have some prerequisite tasks which need to be completed before it can be scheduled. Given the number of tasks and a list of prerequisite pairs, find out if it is possible to schedule all the tasks.

Example 1:

```
Input: Tasks=3, Prerequisites=[0, 1], [1, 2]
Output: true
Explanation: To execute task '1', task '0' needs to finish first. Similarly, task
'1' needs
to finish before '2' can be scheduled. One possible scheduling of tasks is: [0, 1,
2]
```

Example 2:

```
Input: Tasks=3, Prerequisites=[0, 1], [1, 2], [2, 0]
Output: false
Explanation: The tasks have a cyclic dependency, therefore they cannot be
scheduled.
```

Example 3:

```
Input: Tasks=6, Prerequisites=[2, 5], [0, 5], [0, 4], [1, 4], [3, 2], [1, 3]
Output: true
Explanation: A possible scheduling of tasks is: [0 1 4 3 2 5]
```

Try it yourself

Try solving this question here:

Java

```
import java.util.*;

class Solution {
  public boolean isSchedulingPossible(int tasks, int[][] prerequisites) {
    // TODO: Write your code here
    return false;
  }
```

```
8    }
9
```

Test Case | Run Code Result | Stdout

```
3
[[0,1],[1,2]]
```

Use Example Testcases | Run | Submit

← Previous

Solution: Topological Sort

Next →

Solution: Tasks Scheduling

Mark as Completed