
Solution: Reverse Level Order Traversal

Problem Statement

Given a binary tree, populate an array to represent its level-by-level traversal in reverse order, i.e., the **lowest level comes first.** You should populate the values of all nodes in each level from left to right in separate sub-arrays.


Example 1:

Reverse Level Order Traversal: [[4,5,6,7], [2,3], [1]]



Example 2:

Reverse Level Order Traversal: [[9,10,5], [7,1], [12]]





Solution


This problem follows the `Binary Tree Level Order Traversal` pattern. We can follow the same **BFS** approach. The only difference will be that instead of appending the current level at the end, we will


append the current level at the beginning of the result list.


Here is the visual representation of the algorithm:



Level Size: 1
Queue:
12
1
Insert
12
7
1
9
10
5


Level Size: 2
Queue:
12
7
1
1
Current Level:
12
2
Insert
12
7
1
9
10
5


Level Size: 2
Queue:
7
1
Level:1
12
12
7
1
9
10
5


Level Size: 2
Queue:
7
1
9
1
Current Level:
7
Level: 1
12
2
Insert
12
7
1
9
10
5


Level Size: 3




Reverse Level Order Traversal

Code

Please note that, for **Java** and **C#**, we will use a `LinkedList` instead of an `ArrayList` for our result list. As in the case of `ArrayList`, appending an element at the beginning means shifting all the existing

elements. Since we need to append the level array at the beginning of the result list, a `LinkedList` will be better, as this shifting of elements is not required in a `LinkedList`. Similarly, we will use a double-ended queue (deque) for **Python**, **C++**, and **JavaScript**. Here is the code for this algorithm:



Time Complexity

The time complexity of the above algorithm is O(N), where 'N' is the total number of nodes in the tree. This is due to the fact that we traverse each node once.

Space Complexity

The space complexity of the above algorithm will be O(N) as we need to return a list containing the level order traversal. We will also need O(N) space for the queue. Since we can have a maximum of N/2 nodes at any level (this could happen only at the lowest level), therefore we will need O(N) space to store them in the queue.