Encode and Decode Strings

Problem Statement

Given a list of strings, your task is to develop two functions: one that encodes the list of strings into a single string, and another that decodes the resulting single string back into the original list of strings. It is crucial that the decoded list is identical to the original one.

It is given that you can use any encoding technique to encode list of string into the single string.

Examples

1. **Example 1**:
   - **Input**: ["apple", "banana"]
   - **Expected Output**: ["apple", "banana"]
   - **Justification**: When we encode the input strings ["apple", "banana"], we get a single encoded string. Decoding this encoded string should give us the original list ["apple", "banana"].
2. **Example 2**:
   - **Input**: ["sun", "moon", "stars"]
   - **Expected Output**: ["sun", "moon", "stars"]
   - **Justification**: After encoding the input list, decoding it should bring back the original list.
3. **Example 3**:
   - **Input**: ["Hello123", "&*^%"]
   - **Expected Output**: ["Hello123", "&*^%"]
   - **Justification**: Regardless of the content of the string (special characters, numbers, etc.), decoding the encoded list should reproduce the original list.

Try it yourself

Try solving this question here:

Java

```java
import java.util.*;

public class Solution {

    // Function to encode list of strings to a single string
    public String encode(List<String> strs) {
        StringBuilder sb = new StringBuilder();
        // ToDo: Write Your Code Here.
        return sb.toString();
    }

    // Function to decode the encoded string back to the list of strings
    public List<String> decode(String s) {
        List<String> res = new ArrayList<>();
        // ToDo: Write Your Code Here.
        return res;
    }
}
```

Test Case | Run Code Result | Stdout

["apple","banana"]

Use Example Testcases | Run | Submit

← Previous
Solution: Meeting Rooms II

Next →
Solution: Encode And Decode Strings

Mark as Completed