Minimum Deletions & Insertions to Transform a String into another

Problem Statement

Given strings s1 and s2, we need to transform s1 into s2 by deleting and inserting characters. Write a function to calculate the count of the minimum number of deletion and insertion operations.

Example 1:

```
Input: s1 = "abc"
       s2 = "fbc"
Output: 1 deletion and 1 insertion.
Explanation: We need to delete {'a'} and insert {'f'} to s1 to transform
it into s2.
```

Example 2:

```
Input: s1 = "abdca"
       s2 = "cbda"
Output: 2 deletions and 1 insertion.
Explanation: We need to delete {'a', 'c'} and insert {'c'} to s1 to
transform it into s2.
```

Example 3:

```
Input: s1 = "passport"
       s2 = "ppsspt"
Output: 3 deletions and 1 insertion
Explanation: We need to delete {'a', 'o', 'r'} and insert {'p'} to s1 to
transform it into s2.
```

Try it yourself

Try solving this question here:

Java

```java

class Solution {

  public List<Integer> findMDI(String s1, String s2) {
    List<Integer> result = new ArrayList<>();
    // TODO: Write your code here
    return result;
  }
}

```

Test Case | Run Code Result | Stdout

"abc"
"fbc"

Use Example Testcases | Run | Submit

← Previous

Solution: Longest Common Subsequence

Next →

Solution: Minimum Deletions & Insertions To Transform A String Into Another

Mark as Completed