Solution: Problem Challenge 1: Next Interval

Problem Statement

Given an array of intervals, find the next interval of each interval. In a list of intervals, for an interval 'i' its next interval 'j' will have the smallest 'start' greater than or equal to the 'end' of 'i'.

Write a function to return an array containing indices of the next interval of each input interval. If there is no next interval of a given interval, return -1. It is given that none of the intervals have the same start point.

Example 1:

> **Input:** Intervals [[2,3], [3,4], [5,6]]
> **Output:** [1, 2, -1]
> **Explanation:** The next interval of [2,3] is [3,4] having index '1'. Similarly, the next interval of [3,4] is [5,6] having index '2'. There is no next interval for [5,6] hence we have '-1'.

Example 2:

> **Input:** Intervals [[3,4], [1,5], [4,6]]
> **Output:** [2, -1, -1]
> **Explanation:** The next interval of [3,4] is [4,6] which has index '2'. There is no next interval for [1,5] and [4,6].

Solution

A brute force solution could be to take one interval at a time and go through all the other intervals to find the next interval. This algorithm will take $O(N^2)$ where 'N' is the total number of intervals. Can we do better than that?

We can utilize the **Two Heaps** approach. We can push all intervals into two heaps: one heap to sort the intervals on maximum start time (let's call it `maxStartHeap`) and the other on maximum end time (let's

call it `maxEndHeap`). We can then iterate through all intervals of the 'maxEndHeap' to find their next interval. Our algorithm will have the following steps:

1. Take out the top (having highest end) interval from the `maxEndHeap1` to find its next interval. Let's call this interval `topEnd`.
2. Find an interval in the `maxStartHeap` with the closest start greater than or equal to the start of `topEnd`. Since `maxStartHeap` is sorted by 'start' of intervals, it is easy to find the interval with the highest 'start'. Let's call this interval `topStart`.
3. Add the index of `topStart` in the result array as the next interval of `topEnd`. If we can't find the next interval, add '-1' in the result array.
4. Put the `topStart` back in the `maxStartHeap`, as it could be the next interval of other intervals.
5. Repeat the steps 1-4 until we have no intervals left in `maxEndHeap`.

Code

Here is what our algorithm will look like:

Java

```
import java.util.*;

// class Interval {
//   int start = 0;
//   int end = 0;

//   Interval(int start, int end) {
//     this.start = start;
//     this.end = end;
//   }
// }

class Solution {
  public int[] findNextInterval(Interval[] intervals) {
    int n = intervals.length;
    // heap for finding the maximum start
    PriorityQueue<Integer> maxStartHeap =
        new PriorityQueue<>(n, (i1, i2) -> intervals[i2].start - intervals[i1].start);
    // heap for finding the minimum end
    PriorityQueue<Integer> maxEndHeap =
        new PriorityQueue<>(n, (i1, i2) -> intervals[i2].end - intervals[i1].end);
    int[] result = new int[n];
    for (int i = 0; i < intervals.length; i++) {
      maxStartHeap.offer(i);
```

Run Code Result | Stdout

You must run your code first

Execute

Time Complexity

The time complexity of our algorithm will be O(NlogN), where 'N' is the total number of intervals.

Space Complexity

The space complexity will be O(N) because we will be storing all the intervals in the heaps.

← Previous

Problem Challenge 1: Next Interval (Hard)

Next →

Introduction To Subsets Pattern

Mark as Completed