Solution: Minimum Coin Change

Introduction

Given an infinite supply of ‘n’ coin denominations and a total money amount, we are asked to find the minimum number of coins needed to make up that amount.

Example 1:

```
Denominations: {1,2,3}
Total amount: 5
Output: 2
Explanation: We need a minimum of two coins {2,3} to make a total of '5'
```

Example 2:

```
Denominations: {1,2,3}
Total amount: 11
Output: 4
Explanation: We need a minimum of four coins {2,3,3,3} to make a total of '11'
```

Problem Statement

Given a number array to represent different coin denominations and a total amount 'T', we need to find the minimum number of coins needed to make a change for 'T'. We can assume an infinite supply of coins, therefore, each coin can be chosen multiple times.

This problem follows the `"Unbounded Knapsack"` pattern.

Basic Solution


A basic brute-force solution could be to try all combinations of the given coins to select the ones that give a total sum of 'T'. This is what our algorithm will look like:

```
for each coin 'c'
  create a new set which includes one quantity of coin 'c' if it does not exceed 'T', and
     recursively call to process all coins
```

```
    create a new set without coin 'c', and recursively call to process the remaining coins
  return the count of coins from the above two sets with a smaller number of coins
```

Code

Here is the code for the brute-force solution:




The time complexity of the above algorithm is exponential $O(2^{C+T})$, where 'C' represents total coin denominations and 'T' is the total amount that we want to make change. The space complexity will be $O(C+T)$.

Let's try to find a better solution.

Top-down Dynamic Programming with Memoization

We can use memoization to overcome the overlapping sub-problems. We will be using a two-dimensional array to store the results of solved sub-problems. As mentioned above, we need to store

results for every coin combination and for every possible sum:



Bottom-up Dynamic Programming

Let's try to populate our array `dp[TotalDenominations][Total+1]` for every possible total with a minimum number of coins needed.

So for every possible total 't' (0<= t <= Total) and for every possible coin index (0 <= index < denominations.length), we have two options:

- Exclude the coin: In this case, we will take the minimum coin count from the previous set => `dp[index-1][t]`
- Include the coin if its value is not more than 't': In this case, we will take the minimum count needed to get the remaining total, plus include '1' for the current coin => `dp[index][t-denominations[index]] + 1`


Finally, we will take the minimum of the above two values for our solution:

```
dp[index][t] = min(dp[index-1][t], dp[index][t-denominations[index]] + 1)
```


Let's draw this visually with the following example:

```
Denominations: [1, 2, 3]
Total: 7
```


Let's start with our base case of zero total:




We don't need any coin to make zero total




Total:1, Index:0 => dp[Index][Total-denominations[Index] + 1, we didn't consider dp[Index-1][Total] as Index = 0




Total:2, Index:0 => dp[Index][Total-denominations[Index] + 1, we didn't consider dp[Index-1][Total] as Index = 0




Total:3-7, Index:0 => dp[Index][Total-denominations[Index] + 1, we didn't consider dp[Index-1][Total] as Index = 0




Total:1, Index:1 => dp[Index-1][t], we didn't consider dp[Index][Total-denominations[Index] as Total < denominations[Index]




Total:2, Index:1 => min(dp[Index-1][Total], dp[Index][Total-denominations[Index] + 1)



Total:3, Index:1 => min(dp[Index-1][Total], dp[Index][Total-denominations[Index] + 1)



Total:4-7, Index:1 => min(dp[Index-1][Total], dp[Index][Total-denominations[Index] + 1)



Total:7, Index:2 => min(dp[Index-1][Total], dp[Index][Total-denominations[Index] + 1)

Code

Here is the code for our bottom-up dynamic programming approach:

Java

```
import java.util.Arrays;

class Solution {

  public int countChange(int[] denominations, int total)
  {
    int n = denominations.length;
    int[][] dp = new int[n][total + 1];

    for(int i=0; i < n; i++)
      for(int j=0; j <= total; j++)
        dp[i][j] = Integer.MAX_VALUE;

    // populate the total=0 columns, as we don't need any coin to make zero total
    for(int i=0; i < n; i++)
      dp[i][0] = 0;

    for(int i=0; i < n; i++) {
      for(int t=1; t <= total; t++) {
        if(i > 0)
          dp[i][t] = dp[i-1][t]; //exclude the coin
        if(t >= denominations[i]) {
          if(dp[i][t-denominations[i]] != Integer.MAX_VALUE)
```

Run Code Result | Stdout

You must run your code first

Execute

The above solution has time and space complexity of $O(C * T)$, where 'C' represents total coin denominations and 'T' is the total amount that we want to make change.

← Previous

Minimum Coin Change

Next →

Maximum Ribbon Cut

Mark as Completed