Solution: Maximum Sum Increasing Subsequence

Problem Statement

Given a number sequence, find the increasing subsequence with the highest sum. Write a method that returns the highest sum.

Example 1:

```
Input: {4,1,2,6,10,1,12}
Output: 32
Explanation: The increaseing sequence is {4,6,10,12}.
Please note the difference, as the LIS is {1,2,6,10,12} which has a sum of '31'.
```

Example 2:

```
Input: {-4,10,3,7,15}
Output: 25
Explanation: The increaseing sequences are {10, 15} and {3,7,15}.
```

Basic Solution

The problem is quite similar to the `"Longest Increasing Subsequence"`. The only difference is that, instead of finding the increasing subsequence with the maximum length, we need to find an increasing sequence with the maximum sum.

A basic brute-force solution could be to try all the subsequences of the given array. We can process one number at a time, so we have two options at any step:

1. If the current number is greater than the previous number that we included, we include that number in a running sum and make a recursive call for the remaining array.
2. We can skip the current number to make a recursive call for the remaining array.

The highest sum of any increasing subsequence would be the max value returned by the two recurse calls from the above two options.

Code

Here is the code:

```java
class Solution {

  public int findMSIS(int[] nums) {
      return findMSISRecursive(nums, 0, -1, 0);
  }

  private int findMSISRecursive(int[] nums, int currentIndex, int previousIndex, int sum) {
    if(currentIndex == nums.length)
      return sum;

    // include nums[currentIndex] if it is larger than the last included number
    int s1 = sum;
    if(previousIndex == -1 || nums[currentIndex] > nums[previousIndex])
      s1 = findMSISRecursive(nums, currentIndex+1, currentIndex, sum + nums[currentIndex]);

    // excluding the number at currentIndex
    int s2 = findMSISRecursive(nums, currentIndex+1, previousIndex, sum);

    return Math.max(s1, s2);
  }

  public static void main(String[] args) {
```

Run Code Result | Stdout

You must run your code first

Execute

The time complexity of the above algorithm is exponential $O(2^n)$, where 'n' is the lengths of the input array. The space complexity is $O(n)$ which is used to store the recursion stack.

Top-down Dynamic Programming with Memoization

We can use memoization to overcome the overlapping subproblems.

The three changing values for our recursive function are the current index, the previous index, and the sum. An efficient way of storing the results of the subproblems could be a hash-table whose key would be a string (currentIndex + "|" + previousIndex + "|" + sum).

Here is the code:

```java
import java.util.HashMap;
import java.util.Map;

class Solution {
```

```
6
7     public int findMSIS(int[] nums) {
8       Map<String, Integer> dp = new HashMap<>();
9       return findMSISRecursive(dp, nums, 0, -1, 0);
10    }
11
12    private int findMSISRecursive(Map<String, Integer> dp, int[] nums, int currentIndex, int previousIndex,
13      if(currentIndex == nums.length)
14        return sum;
15
16      String subProblemKey = currentIndex + "-" + previousIndex + "-" + sum;
17      if(!dp.containsKey(subProblemKey)) {
18        // include nums[currentIndex] if it is larger than the last included number
19        int s1 = sum;
20        if(previousIndex == -1 || nums[currentIndex] > nums[previousIndex])
21          s1 = findMSISRecursive(dp, nums, currentIndex+1, currentIndex, sum + nums[currentIndex]);
22
23        // excluding the number at currentIndex
24        int s2 = findMSISRecursive(dp, nums, currentIndex+1, previousIndex, sum);
```

Run Code Result | Stdout

You must run your code first

Execute

Bottom-up Dynamic Programming

The above algorithm tells us two things:


1. If the number at the current index is bigger than the number at the previous index, we include that number in the sum for an increasing sequence up to the current index.
2. But if there is a maximum sum increasing subsequence (MSIS), without including the number at the current index, we take that.

So we need to find all the increasing subsequences for a number at index `i`, from all the previous numbers (i.e. numbers till index `i-1`), to find MSIS.


If `i` represents the currentIndex and 'j' represents the previousIndex, our recursive formula would look like:

```
    if num[i] > num[j] => dp[i] = dp[j] + num[i] if there is no bigger MSIS for 'i'
```


Let's draw this visually for {-4,10,3,7,15}. Start with a subsequence of length '1', as every number can represent an MSIS:




Every number is a LIS of length '1'




i:1, j:0 => Since num[i] > num[j] but dp[i] > dp[j]+ nums[i], therefore no update




i:2, j:0 => Since num[i] > num[j] but dp[i] > dp[j]+ nums[i], therefore no update




i:2, j:1 => Since num[i] < num[j], therefore no update




i:3, j:0 => Since num[i] > num[j] but dp[i] > dp[j]+ nums[i], therefore no update




i:3, j:1 => Since num[i] < num[j], therefore no update




i:3, j:2 => Since num[i] > num[j] and dp[i] < dp[j] + num[i], therefore dp[i] = dp[j] + num[i]




i:4, j:0 => Since num[i] > num[j] but dp[i] > dp[j]+ nums[i], therefore no update



i:4, j:1 => Since num[i] > num[j] and dp[i] < dp[j] + num[i], therefore dp[i] = dp[j] + num[i]



i:4, j:2 => Since num[i] > num[j] but dp[i] > dp[j]+ nums[i], therefore no update



i:4, j:3 => Since num[i] > num[j] but dp[i] == dp[j]+ nums[i], therefore no update

From the above visualization, we can clearly see that the maximum sum of any increasing subsequence is '25' -- as shown by `dp[4]`.

Here is the code for our bottom-up dynamic programming approach:

Java

```
class Solution {

  public int findMSIS(int[] nums) {
    int[] dp = new int[nums.length];
    dp[0] = nums[0];

    int maxSum = nums[0];
    for (int i=1; i<nums.length; i++) {
      dp[i] = nums[i];
      for (int j=0; j<i; j++) {
        if (nums[i] > nums[j] && dp[i] < dp[j] + nums[i])
          dp[i] = dp[j] + nums[i];
```

```
14          }
15          maxSum = Math.max(maxSum, dp[i]);
16        }
17
18        return maxSum;
19      }
20
21      public static void main(String[] args) {
22        Solution msis = new Solution();
23        int[] nums = {4,1,2,6,10,1,12};
24        System.out.println(msis.findMSIS(nums));
```

Run Code Result | Stdout

You must run your code first

Execute

The time complexity of the above algorithm is $O(n^2)$ and the space complexity is $O(n)$.

← Previous

Maximum Sum Increasing Subsequence

Next →

Shortest Common Super-Sequence

Mark as Completed