Nested List Weight Sum (medium)

Problem Statement

You are given a `nestedList`. Each element of the `nestedList` contains either integers or other such nested lists.

The depth level is determined by how many levels of nested lists the integer is within. For example, each element of the list `[1, 1, [2], [2, [3]]]` represents the depth of itself.

Return the `sum of all integers` of the list after `multiplying` each integer with its `depth level`.

2. Example Generation

- **Example 1**:
  - Input: `[[2, [3, 4]], [5, 6], 7]`
  - Expected Output: `54`
  - Justification: The sum is calculated as 4 (2 at depth 2) + 9 (3 at depth 3) + 12 (4 at depth 3) + 10 (5 at depth 2) + 12 (6 at depth 2) + 7 (7 at depth 1).
- **Example 2**:
  - Input: `[1, [4, [6]]]`
  - Expected Output: `27`
  - Justification: The sum is 1 (depth 1) + 8 (4 at depth 2) + 18 (6 at depth 3).
- **Example 3**:
  - Input: `[5, [2, [3, [4]]], 1]`
  - Expected Output: `50`
  - Justification: The calculation is 5 (depth 1) + 4 (2 at depth 2) + 9 (3 at depth 3) + 16 (4 at depth 4) + 1 (depth 1).

Try it yourself

Try solving this question here:

Java

```java
import java.util.ArrayList;
import java.util.List;

// NestedInteger class represents either a single integer or a nested list of integers
// class NestedInteger {
//     private Integer value;
//     private List<NestedInteger> list;
//     private boolean isSingleInteger;

//     // Constructor for a single integer
//     public NestedInteger(int value) {
//         this.value = value;
//         this.isSingleInteger = true;
//     }

//     // Constructor for an empty nested list
//     public NestedInteger() {
//         this.list = new ArrayList<>();
//         this.isSingleInteger = false;
//     }

//     // Returns true if this NestedInteger holds a single integer
//     public boolean isInteger() {
```

Run Code Result | Stdout

You must run your code first

Execute

← Previous

Solution: Basic Calculator II

Next →

Solution: Nested List Weight Sum

Mark as Completed