Solution: Problem Challenge 3: Rotation Count


Problem Statement

Given an array of numbers which is sorted in ascending order and is rotated ‘k’ times around a pivot, find ‘k’.

You can assume that the array does not have any duplicates.


Example 1:

```
Input: [10, 15, 1, 3, 8]
Output: 2
Explanation: The array has been rotated 2 times.
```



Example 2:

```
Input: [4, 5, 7, 9, 10, -1, 2]
Output: 5
Explanation: The array has been rotated 5 times.
```



Example 3:

```
Input: [1, 3, 8, 10]
Output: 0
Explanation: The array has not been rotated.
```

Solution

This problem follows the **Binary Search pattern**. We can use a similar strategy as discussed in `Search in Rotated Array`.

In this problem, actually, we are asked to find the index of the minimum element. The number of times the minimum element is moved to the right will be equal to the number of rotations. An interesting fact about the minimum element is that it is the only element in the given array which is smaller than its previous element. Since the array is sorted in ascending order, all other elements are bigger than their previous element.

After calculating the `middle`, we can compare the number at index `middle` with its previous and next number. This will give us two options:


1. If `arr[middle] > arr[middle + 1]`, then the element at `middle + 1` is the smallest.
2. If `arr[middle - 1] > arr[middle]`, then the element at `middle` is the smallest.

To adjust the ranges we can follow the same approach as discussed in `Search in Rotated Array`. Comparing the numbers at indices `start` and `middle` will give us two options:

1. If `arr[start] < arr[middle]`, the numbers from start to middle are sorted.
2. Else, the numbers from `middle + 1` to end are sorted.

Code

Here is what our algorithm will look like:



You must run your code first

Execute

Time Complexity

Since we are reducing the search range by half at every step, this means that the time complexity of our algorithm will be O(logN) where 'N' is the total elements in the given array.

Space Complexity

The algorithm runs in constant space O(1).

Similar Problems


Problem 1

How do we find the rotation count of a sorted and rotated array that has duplicates too?

The above code will fail on the following example!


Example 1:

```
Input: [3, 3, 7, 3]
Output: 3
Explanation: The array has been rotated 3 times.
```



Solution

We can follow the same approach as discussed in `Search in Rotated Array`. The only difference is that before incrementing `start` or decrementing `end`, we will check if either of them is the smallest number.



Time & Space Complexities

This algorithm will run in O(logN) most of the times, but since we only skip two numbers in case of duplicates instead of the half of the numbers, therefore the worst case time complexity will become O(N). The algorithm runs in constant space O(1).

← Previous

Problem Challenge 3: Rotation Count (Medium)

Next →

Introduction To Bitwise XOR Pattern

Mark as Completed