Meeting Rooms II (medium)

Problem Statement

Given a list of time intervals during which meetings are scheduled, determine the minimum number of meeting rooms that are required to ensure that none of the meetings overlap in time.

Examples

1. **Example 1:**
   - **Input:** `[[10, 15], [20, 25], [30, 35]]`
   - **Expected Output:** `1`
   - **Justification:** There are no overlapping intervals in the given list. So, only 1 meeting room is enough for all the meetings.
2. **Example 2:**
   - **Input:** `[[10, 20], [15, 25], [24, 30]]`
   - **Expected Output:** `2`
   - **Justification:** The first and second intervals overlap, and the second and third intervals overlap as well. So, we need 2 rooms.
3. **Example 3:**
   - **Input:** `[[10, 20], [20, 30]]`
   - **Expected Output:** `1`
   - **Justification:** The end time of the first meeting is the same as the start time of the second meeting. So, one meeting can be scheduled right after the other in the same room.

Try it yourself

Try solving this question here:



```
2   import java.util.PriorityQueue;
3
4   public class Solution {
5       public int minMeetingRooms(int[][] intervals) {
6           // ToDo: Write Your Code Here.
7           return 0;
8       }
9   }
10
```

Test Case | Run Code Result | Stdout

```
[[0,30],[5,10],[15,20]]
```

Use Example Testcases | Run | Submit

← Previous

Solution: Longest Consecutive Sequence

Next →

Solution: Meeting Rooms II

Mark as Completed