Design Chess

Let's design a system to play online chess.

Chess is a two-player strategy board game played on a chessboard, which is a checkered gameboard with 64 squares arranged in an 8×8 grid. There are a few versions of game types that people play all over the world. In this design problem, we are going to focus on designing a two-player online chess game.



System Requirements

We'll focus on the following set of requirements while designing the game of chess:

1. The system should support two online players to play a game of chess.
2. All rules of international chess will be followed.
3. Each player will be randomly assigned a side, black or white.
4. Both players will play their moves one after the other. The white side plays the first move.
5. Players can't cancel or roll back their moves.
6. The system should maintain a log of all moves by both players.
7. Each side will start with 8 pawns, 2 rooks, 2 bishops, 2 knights, 1 queen, and 1 king.
8. The game can finish either in a checkmate from one side, forfeit or stalemate (a draw), or resignation.


Use case diagram

We have two actors in our system:

- **Player**: A registered account in the system, who will play the game. The player will play chess moves.
- **Admin**: To ban/modify players.

Here are the top use cases for chess:

- **Player moves a piece**: To make a valid move of any chess piece.
- **Resign or forfeit a game**: A player resigns from/forfeits the game.
- **Register new account/Cancel membership**: To add a new member or cancel an existing member.
- **Update game log**: To add a move to the game log.





Class diagram

Here are the main classes for chess:

- **Player**: Player class represents one of the participants playing the game. It keeps track of which side (black or white) the player is playing.
- **Account**: We'll have two types of accounts in the system: one will be a player, and the other will be an admin.


- **Game**: This class controls the flow of a game. It keeps track of all the game moves, which player has the current turn, and the final result of the game.
- **Box**: A box represents one block of the 8x8 grid and an optional piece.
- **Board**: Board is an 8x8 set of boxes containing all active chess pieces.
- **Piece**: The basic building block of the system, every piece will be placed on a box. This class contains the color the piece represents and the status of the piece (that is, if the piece is currently in play or not). This would be an abstract class and all game pieces will extend it.
- **Move**: Represents a game move, containing the starting and ending box. The Move class will also keep track of the player who made the move, if it is a castling move, or if the move resulted in the capture of a piece.
- **GameController**: Player class uses GameController to make moves.
- **GameView**: Game class updates the GameView to show changes to the players.



<<dataType>>
Address
streetAddress: string
city: string
state: string
zipcode: string
country: string
<<dataType>>
Person
name: string
address: Address
email: string
phone: string
<<enumeration>>
GameStatus
Active
BlackWin
WhiteWin
Forfeit
Stalemate
Resignation
<<enumeration>>
AccountStatus
Active
Closed
Canceled
Blacklisted
None
Move
startBox: Box
endingBox: Box
pieceKilled: Piece
player: Player
isCastlingMove: bool
setCastlingMove(): void
Box
x: int
y: int
getX(): int
getY(): int
made by
64
1
Board
creationDate: date
getPieces(): list<Piece>
resetBoard(): void
GameController
validateMove(): bool
manipulates
Game
movesPlayed: list<Move>
currentTurn: Player
status: GameStatus
isOver(): bool
playerMove(): bool
makeMove(): bool
uses
updates
Piece
killed: bool
isWhite(): bool
isKilled(): bool
canMove(): bool
0..1
Extends
GameView
makeMove(): bool
Sees
Player
person: Person
totalGamesPlayed: int
whiteSide: bool
isWhiteSide(): bool
isChecked(): bool
King
castlingDone: bool
canMove(): bool
Queen
canMove(): bool
Knight
canMove(): bool
Bishop
canMove(): bool
Rook
canMove(): bool
Pawn
canMove(): bool
Admin
blockUser(): bool
Extends
Extends
Account
id: int
password: string
status: AccountStatus
resetPassword(): bool



Activity diagrams

Make move: Any Player can perform this activity. Here are the set of steps to make a move:


Player moves a piece from Box b1 to Box b2
Is this a valid move?
[no]
[yes]
Will the player be under check after the move?
[yes]
[no]
Show message, not a valid move
Does b2 contain a piece?
[yes]
Capture piece at b2
[no]
Is the piece moved a pawn and is b2 a back rank?
[yes]
Promote the pawn to either a queen, a bishop, a knight or a rock.
[no]
Is this a castling move?
[yes]
Set the correct position of rock
[no]



Code

Here is the code for the top use cases.

Enums, DataTypes, Constants: Here are the required enums, data types, and constants:

```java
public enum GameStatus {
  ACTIVE, BLACK_WIN, WHITE_WIN, FORFEIT, STALEMATE, RESIGNATION
  }

  public enum AccountStatus {
  ACTIVE, CLOSED, CANCELED, BLACKLISTED, NONE
  }

  public class Address {
  private String streetAddress;
  private String city;
  private String state;
  private String zipCode;
  private String country;
  }

  public class Person {
  private String name;
  private Address address;
  private String email;
  private String phone;
  }

```

Box: To encapsulate a cell on the chess board:

```java
public class Box {
    private Piece piece;
    private int x;
    private int y;

    public Box(int x, int y, Piece piece) {
      this.setPiece(piece);
```

```
        this.setX(x);
        this.setY(y);
      }

      public Piece getPiece() {
        return this.piece;
      }

      public void setPiece(Piece p) {
        this.piece = p;
      }

      public int getX() {
        return this.x;
      }

      public void setX(int x) {
```

Piece: An abstract class to encapsulate common functionality of all chess pieces:

```java
public abstract class Piece {

  private boolean killed = false;
  private boolean white = false;

  public Piece(boolean white) {
    this.setWhite(white);
  }

  public boolean isWhite() {
    return this.white == true;
  }

  public void setWhite(boolean white) {
    this.white = white;
  }

  public boolean isKilled() {
    return this.killed == true;
  }

  public void setKilled(boolean killed) {
    this.killed = killed;
  }
```

King: To encapsulate King as a chess piece:

```java
public class King extends Piece {
    private boolean castlingDone = false;

    public King(boolean white) {
      super(white);
    }

    public boolean isCastlingDone() {
      return this.castlingDone == true;
    }

    public void setCastlingDone(boolean castlingDone) {
      this.castlingDone = castlingDone;
    }

    @Override
    public boolean canMove(Board board, Box start, Box end) {
      // we can't move the piece to a box that has a piece of the same color
```

```
        if(end.getPiece().isWhite() == this.isWhite()) {
          return false;
        }

        int x = Math.abs(start.getX() - end.getX());
        int y = Math.abs(start.getY() - end.getY());
```

Knight: To encapsulate Knight as a chess piece:

```java
public class Knight extends Piece {
    public Knight(boolean white) {
      super(white);
    }

    @Override
    public boolean canMove(Board board, Box start, Box end) {

      // we can't move the piece to a box that has a piece of the same color
      if(end.getPiece().isWhite() == this.isWhite()) {
        return false;
      }

      int x = Math.abs(start.getX() - end.getX());
      int y = Math.abs(start.getY() - end.getY());
      return x * y == 2;
    }
  }

```

Board: To encapsulate a chess board:

```java
public class Board {
    Box[][] boxes;

    public Board() {
      this.resetBoard();
    }

    public Box getBox(int x, int y) {

      if (x < 0 || x > 7 || y < 0 || y > 7) {
        throw new Exception("Index out of bound");
      }

      return boxes[x][y];
    }

    public void resetBoard() {
      // initialize white pieces
      boxes[0][0] = new Box(new Rook(true), 0, 0);
      boxes[0][1] = new Box(new Knight(true), 0, 1);
      boxes[0][2] = new Box(new Bishop(true), 0, 2);
      //...
      boxes[1][0] = new Box(new Pawn(true), 1, 0);
      boxes[1][1] = new Box(new Pawn(true), 1, 1);
```

Player: To encapsulate a chess player:

```java
public class Player extends Account{
  private Person person;
  private boolean whiteSide = false;

  public Player(Person person, boolean whiteSide){
  this.person = person;
  this.whiteSide = whiteSide;
  }

  public boolean isWhiteSide() {
  return this.whiteSide == true;
  }
  }

```

Move: To encapsulate a chess move:

```java
public class Move {
  private Player player;
  private Box start;
  private Box end;
  private Piece pieceMoved;
  private Piece pieceKilled;
  private boolean castlingMove = false;

  public Move(Player player, Box start, Box end){
    this.player = player;
    this.start = start;
    this.end = end;
    this.pieceMoved = start.getPiece();
  }

  public boolean isCastlingMove() {
    return this.castlingMove == true;
  }

  public void setCastlingMove(boolean castlingMove) {
    this.castlingMove = castlingMove;
  }
  }

```

Game: To encapsulate a chess game:

```java
public class Game {
    private Player[] players;
    private Board board;
    private Player currentTurn;
    private GameStatus status;
    private List<Move> movesPlayed;

    private void initialize(Player p1, Player p2) {
      players[0] = p1;
      players[1] = p2;
```

```
11
12          board.resetBoard();
13
14          if(p1.isWhiteSide()) {
15            this.currentTurn = p1;
16          } else {
17            this.currentTurn = p2;
18          }
19
20          movesPlayed.clear();
21        }
22
23        public boolean isEnd() {
24          return this.getStatus() != GameStatus.ACTIVE;
```

← Previous

Design A Restaurant Management System

Next →

Design An Online Stock Brokerage System

Mark as Completed