Solution: Subset Sum

Problem Statement

Given a set of positive numbers, determine if a subset exists whose sum is equal to a given number ‘S’.

Example 1:

```
Input: {1, 2, 3, 7}, S=6
Output: True
The given set has a subset whose sum is '6': {1, 2, 3}
```

Example 2:

```
Input: {1, 2, 7, 1, 5}, S=10
Output: True
The given set has a subset whose sum is '10': {1, 2, 7}
```

Example 3:

```
Input: {1, 3, 4, 8}, S=6
Output: False
The given set does not have any subset whose sum is equal to '6'.
```

Basic Solution

This problem follows the **0/1 Knapsack pattern** and is quite similar to `Equal Subset Sum Partition`. A basic brute-force solution could be to try all subsets of the given numbers to see if any set has a sum equal to ‘S’.

So our brute-force algorithm will look like:

```
for each number 'i'
  create a new set which INCLUDES number 'i' if it does not exceed 'S', and recursively
     process the remaining numbers
  create a new set WITHOUT number 'i', and recursively process the remaining numbers
return true if any of the above two sets has a sum equal to 'S', otherwise return false
```

Since this problem is quite similar to `Equal Subset Sum Partition`, let's jump directly to the bottom-up dynamic programming solution.

Bottom-up Dynamic Programming


We'll try to find if we can make all possible sums with every subset to populate the array `dp[TotalNumbers][S+1]`.


For every possible sum 's' (where 0 <= s <= S), we have two options:


1. Exclude the number. In this case, we will see if we can get the sum 's' from the subset excluding this number => `dp[index-1][s]`
2. Include the number if its value is not more than 's'. In this case, we will see if we can find a subset to get the remaining sum => `dp[index-1][s-num[index]]`


If either of the above two scenarios returns true, we can find a subset with a sum equal to 's'.


Let's draw this visually, with the example input {1, 2, 3, 7}, and start with our base case of size zero:









num\sum
0 1 2 3 4 5 6
1
T T F F F F F
{1, 2}
T T
{1,2,3}
T
{1,2,3,7}
T



num\sum
0 1 2 3 4 5 6
1
T T F F F F F
{1, 2}
T T T
{1,2,3}
T
{1,2,3,7}
T



num\sum
0 1 2 3 4 5 6
1
T T F F F F F
{1, 2}
T T T T
{1,2,3}
T
{1,2,3,7}
T


num\sum
0 1 2 3 4 5 6
1
T T F F F F F
{1, 2}
T T T T F F F
{1,2,3}
T
{1,2,3,7}
T









Code

Here is the code for our bottom-up dynamic programming approach:

Java

```
class Solution {

  public boolean canPartition(int[] num, int sum) {
```

```
    int n = num.length;
    boolean[][] dp = new boolean[n][sum + 1];

    // populate the sum=0 columns, as we can always form '0' sum with an empty set
    for (int i = 0; i < n; i++)
      dp[i][0] = true;

    // with only one number, we can form a subset only when the required sum is
    // equal to its value
    for (int s = 1; s <= sum; s++) {
      dp[0][s] = (num[0] == s ? true : false);
    }

    // process all subsets for all sums
    for (int i = 1; i < num.length; i++) {
      for (int s = 1; s <= sum; s++) {
        // if we can get the sum 's' without the number at index 'i'
        if (dp[i - 1][s]) {
          dp[i][s] = dp[i - 1][s];
        } else if (s >= num[i]) {
```

Run Code Result | Stdout

You must run your code first

Execute

Time and Space Complexity

The above solution has the time and space complexity of O(N*S), where ‘N’ represents total numbers and ‘S’ is the required sum.

Challenge

Can we improve our bottom-up DP solution even further? Can you find an algorithm that has O(S) space complexity?

Java

```
class Solution {

  public boolean canPartition(int[] num, int sum) {
    int n = num.length;
    boolean[] dp = new boolean[sum + 1];

    // handle sum=0, as we can always have '0' sum with an empty set
    dp[0] = true;

    // with only one number, we can have a subset only when the required sum is equal to
    // its value
    for (int s = 1; s <= sum; s++) {
      dp[s] = (num[0] == s ? true : false);
    }
```

```
15
16        // process all subsets for all sums
17        for (int i = 1; i < n; i++) {
18          for (int s = sum; s >= 0; s--) {
19            // if dp[s]==true, this means we can get the sum 's' without num[i], hence we
20            // can move on to the next number else we can include num[i] and see if we can
21            // find a subset to get the remaining sum
22            if (!dp[s] && s >= num[i]) {
23              dp[s] = dp[s - num[i]];
24            }
```

Run Code Result | Stdout

You must run your code first

Execute

← Previous

Subset Sum (Medium)

Next →

Minimum Subset Sum Difference (Hard)

Mark as Completed