Problem Challenge 3: Employee Free Time (hard)

Problem Statement

For 'K' employees, we are given a list of intervals representing each employee's working hours. Our goal is to determine if there is a **free interval which is common to all employees**. You can assume that each list of employee working hours is sorted on the start time.

Example 1:

```
Input: Employee Working Hours=[[[1,3], [5,6]], [[2,3], [6,8]]]
Output: [3,5]
Explanation: All the employees are free between [3,5].
```

Example 2:

```
Input: Employee Working Hours=[[[1,3], [9,12]], [[2,4]], [[6,8]]]
Output: [4,6], [8,9]
Explanation: All employees are free between [4,6] and [8,9].
```

Example 3:

```
Input: Employee Working Hours=[[[1,3]], [[2,4]], [[3,5], [7,9]]]
Output: [5,7]
Explanation: All employees are free between [5,7].
```

Try it yourself

Try solving this question here:

Java

```java
import java.util.*;

/*class Interval {
    int start;
    int end;

    public Interval(int start, int end) {
      this.start = start;
      this.end = end;
    }
  };*/


class EmployeeInterval {
  Interval interval; // interval representing employee's working hours
  int employeeIndex; // index of the list containing working hours of this employee
  int intervalIndex; // index of the interval in the employee list

  public EmployeeInterval(Interval interval, int employeeIndex, int intervalIndex) {
    this.interval = interval;
    this.employeeIndex = employeeIndex;
```

Test Case | Run Code Result | Stdout

[[[1, 3], [5, 6]], [[2, 3], [6, 8]]]

Use Example Testcases | Run | Submit

← Previous

Solution: Problem Challenge 2: Maximum CPU Load

Next →

Solution: Problem Challenge 3: Employee Free Time

Mark as Completed