Introductory Lecture Topics: basics,resources,stl,bitwise tricks,gdb

League of Programmers

IIT Kanpur

September 30, 2011

Aim of the Discussion Series

Aim of the Discussion Series

 Discussion camp not a lecture series. You need to show motivation.

Aim of the Discussion Series

- Discussion camp not a lecture series. You need to show motivation.
- To help you code better and faster, introduce you to new tricks mostly to help you do well in programming contests.

Language Issues

• Language We stress on: C++

Language Issues

- Language We stress on: C++
- Slower languages like java and python time out on many judges.

Language Issues

- Language We stress on: C++
- Slower languages like java and python time out on many judges.
- C has too restrictive and does not support stl/ templates / classes.

Compete against Indian coders in live contests Codechef

- Compete against Indian coders in live contests Codechef
- As problem archive Codeforces/Spoj/UVA/Topcoder/Project Euler

- Compete against Indian coders in live contests Codechef
- As problem archive Codeforces/Spoj/UVA/Topcoder/Project Euler
- Short Programming Contests Codeforces/Topcoder

- Compete against Indian coders in live contests Codechef
- As problem archive Codeforces/Spoj/UVA/Topcoder/Project Euler
- Short Programming Contests Codeforces/Topcoder
- Tougher Problems acm.sgu.ru/Codechef Monthly challenge/IOI/ACM ICPC previous years archive/Topcoder level 3

Popular Contests to participate in

 India: ACM ICPC/ IOPC/ Shastra OPC/ Codecraft/ Codechef Monthly Challenge/ Codechef Cook off

Popular Contests to participate in

- India: ACM ICPC/ IOPC/ Shastra OPC/ Codecraft/ Codechef Monthly Challenge/ Codechef Cook off
- World: Topcode SRMs/ Codeforces/ Facebook Hacker Cup/ Google Code Jam

Overflow

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)
- Comparing Doubles

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)
- ullet Comparing Doubles Solution: Always keep cushion of a small ϵ .

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)
- ullet Comparing Doubles Solution: Always keep cushion of a small ϵ .
- Segmentation faults

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)
- ullet Comparing Doubles Solution: Always keep cushion of a small ϵ .
- Segmentation faults
 Solution: Use gdb \(\langle gdb \) tutorial \(\rangle \)

- Overflow Use data type of appropriate size. Choose data type of every variable carefully based on the constraints of the problem
- Passing Multi Dimensional Arrays
 Solution: either use vector stl(convenient) or global arrays of large enough size(faster)
- ullet Comparing Doubles Solution: Always keep cushion of a small ϵ .
- Segmentation faults
 Solution: Use gdb \(\langle gdb \tautorial \rangle \)
- From Your side



• Understand what the program is expected to do.

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations
- x MB $\approx x/4 * 10^6$ sized int arrays

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations
- x MB $\approx x/4 * 10^6$ sized int arrays Not all operations are equally fast:

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations
- x MB $\approx x/4 * 10^6$ sized int arrays Not all operations are equally fast: operations on unsigned ints/long long are faster

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations
- x MB \approx x/4 * 10⁶ sized int arrays Not all operations are equally fast: operations on unsigned ints/long long are faster bitwise operators and shift operators (&| \wedge >><<)

- Understand what the program is expected to do.
- Understand the Input/Output format and use exactly that format
- Meaning of constraints
- What do time limit and memory limit mean??
- 1 sec $\approx (1-2)*10^8$ operations
- x MB \approx x/4 * 10⁶ sized int arrays Not all operations are equally fast: operations on unsigned ints/long long are faster bitwise operators and shift operators (&| \land >><<) Using too much memory (> 10 MB) slows down programmes

Website: http://www.cplusplus.com/reference

• what is template ?

Website: http://www.cplusplus.com/reference

- what is template ?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations

Website: http://www.cplusplus.com/reference

- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.

Problem:spoj.pl/problems/WEIRDFN

Problem:http://www.spoj.pl/problems/HOMO/

Problem:spoj.pl/problems/HISTOGRA

Website: http://www.cplusplus.com/reference

- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 - Problem:http://www.spoj.pl/problems/HOMO/
 - Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set
 - Problem:spoj.pl/problems/SUBSEQ

- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 Problem:http://www.spoj.pl/problems/HOMO/
 Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set Problem:spoj.pl/problems/SUBSEQ
- string class and stringstream to parse strings useful mostly for topcoder SRM problems

- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 Problem:http://www.spoj.pl/problems/HOMO/
 Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set Problem:spoj.pl/problems/SUBSEQ
- string class and stringstream to parse strings useful mostly for topcoder SRM problems
- memset/fill: initialize arrays



- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 Problem:http://www.spoj.pl/problems/HOMO/
 Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set Problem:spoj.pl/problems/SUBSEQ
- string class and stringstream to parse strings useful mostly for topcoder SRM problems
- memset/fill: initialize arrays
- Queue can be use as queue and stack



- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 - Problem:http://www.spoj.pl/problems/HOMO/
 - Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set Problem:spoj.pl/problems/SUBSEQ
- string class and stringstream to parse strings useful mostly for topcoder SRM problems
- memset/fill: initialize arrays
- Queue can be use as queue and stack
- bitset(next section)



- what is template?
- Vector: Dynamic size arrays with insertion/deletion to/from arbitrary locations
- Set: Just like a mathematical set.
 Problem:spoj.pl/problems/WEIRDFN
 - Problem:http://www.spoj.pl/problems/HOMO/
 - Problem:spoj.pl/problems/HISTOGRA
- Map: Advanced set Problem:spoj.pl/problems/SUBSEQ
- string class and stringstream to parse strings useful mostly for topcoder SRM problems
- memset/fill: initialize arrays
- Queue can be use as queue and stack
- bitset(next section)



 Numbers are stored in binary and processing on bits is way faster

- Numbers are stored in binary and processing on bits is way faster
- Our weapons:

```
<< (left shift), >> (right shift), &(bitwise and), |(bitwise or), ^(bitwise xor) ~(bitwise not)
```

- Numbers are stored in binary and processing on bits is way faster
- Our weapons:

```
<< (left shift), >> (right shift), &(bitwise and), |(bitwise or), ^(bitwise xor) ~(bitwise not)
```

speed up the code by upto 100 times.

- Numbers are stored in binary and processing on bits is way faster
- Our weapons:

```
<< (left shift), >> (right shift), &(bitwise and), |(bitwise or), ^(bitwise xor) ~(bitwise not)
```

 speed up the code by upto 100 times. caution: try to use bitwise operations on unsigned integers only

• Example:

Any subset of $\{0,1\dots31\}$ is a single int Do set union/intersection/complement in one operation increment /decrement all elements by x in one operation

• Example:

Any subset of $\{0,1\dots31\}$ is a single int Do set union/intersection/complement in one operation increment /decrement all elements by x in one operation

• Even more:

Find if $x \in S$. Generate all subsets of S in $2^{|S|}$ time

Generate all subsets of $\{1..n\}$ changing one bit at a time Generate all subsets of S which have exactly t elements Count the number of elements of elements in a set SRemove smallest element from S

check if |S| = 1

• Example:

Any subset of $\{0,1\dots31\}$ is a single int Do set union/intersection/complement in one operation increment /decrement all elements by x in one operation

• Even more:

Find if $x \in S$.

Generate all subsets of S in $2^{|S|}$ time Generate all subsets of $\{1..n\}$ changing one bit at a time Generate all subsets of S which have exactly t elements Count the number of elements of elements in a set S Remove smallest element from S check if |S|=1

Never multiply or divide or take remainder modulo power of 2



Practice Probems

```
More tricks: graphics.stanford.edu/~seander/bithacks.html
lab.polygonal.de/2007/05/10/bitwise-gems-fast-integer-math
bits.stephan-brumme.com
Problems:
codechef.com/problems/TEAMSEL
spoj.pl/problems/PIZZALOC
acm.sgu.ru/problem.php?contest=0&problem=249
codechef.com/problems/SEQUENCE
spoj.pl/problems/NGM2
spoj.pl/problems/VILLAGES
bitwise dp:
community.topcoder.com/stat?c=problem_statement&pm=6725&rd=101
community.topcoder.com/stat?c=problem_statement&pm=6095&rd=991
community.topcoder.com/stat?c=problem_statement&pm=6400&rd=100
```