13) Implement your own ping program.

Aim:

To implement your own ping program

procedure

To write the ping code

```
import os
import platform
import subprocess

def ping(host = "google.com", count = 4):
    param = "-n" if platform.system().lower()
        = "windows" else "-c"
    command = ["ping", param, str(count), host]
try:
    output = subprocess.check_output(comman
            universal_newlines = True).
    print(output)
except Exception as e:
    print("f ping failed : {e}")
if __name__ == "__main__":
```

REDMI 13C 5G 19/10/2026 18:32

ping ('8.8.8.8").

output:

pinging 8.8.8.8 with 32 bytes of data:

Reply from 8.8.8.8 bytes = 32 time = 6ms TTL=119

Reply from 8.8.8.8: bytes = 32 times = 9ms TTL=119

Reply from 8.8.8.8 bytes = 32 times time = 5ms TTL=

Reply from 8.8.8.8: bytes = 32, time = 9ms TTL=119

Ping statistics for 8.8.8.8:

packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate route trip times in milli-seconds:

Minimum = 5ms, Maximum = 9ms, Average = 7ms

Result:

Therefore, the Implement your own ping program executed successfully.

REDMI 13C 5G 19/10/2026 18:33