Presentation

Of

C Language

Prepared

By

M.SAQIB NOOR

Saqibnoor123@gmail.com

2nd Application:

AGE CALCULATOR APP IN DATATYPE INT:

```
#include <stdio.h>
main () {
int age , agem, agew, aged , ageh, agemi , ages;

      age = 1;
        agem = age * 12;
        agew = agem * 4;
        aged = agew * 7;
        ageh = aged * 24;
        agemi = ageh * 60;
        ages = agemi * 60;
        printf("\n\n\t\t\t Age Calculator");
        printf("\n Age in Years : %d " , age);
        printf("\n Age in Months : %d " , agem);
        printf("\n Age in Weeks : %d " , agew);
        printf("\n Age in Days : %d " , aged);
        printf("\n Age in Hours : %d " , ageh);
        printf("\n Age in Mins : %d " , agemi);
        printf("\n Age in Seconds : %d " , ages);

}
```

3rd Application:

APP IN DATATYPE INT:

```
#include <stdio.h>
main () {

	int table ;

	table = 15;

	printf("\n\n\t\t\t Table of %d " , table);
	printf("\n %d * 1 = %d " , table , table * 1);
	printf("\n %d * 2 = %d " , table , table * 2);
	printf("\n %d * 3 = %d " , table , table * 3);
	printf("\n %d * 4 = %d " , table , table * 4);
	printf("\n %d * 5 = %d " , table , table * 5);
	printf("\n %d * 6 = %d " , table , table * 6);
	printf("\n %d * 7 = %d " , table , table * 7);
	printf("\n %d * 8 = %d " , table , table * 8);
	printf("\n %d * 9 = %d " , table , table * 9);
	printf("\n %d * 10 = %d " , table , table * 10);

}
```