Nexus-H3: data validation and experiments.ipynb

File Edit View Insert Runtime Tools Help

Commands + Code + Text Run all Connect High-RAM

```
!pip install geopandas h3 shapely matplotlib
```

Show hidden output

```
# static data distribution heatmaps

import pandas as pd
import geopandas as gpd
import matplotlib.pyplot as plt
from shapely.geometry import Polygon
import h3
import numpy as np
import warnings

warnings.filterwarnings("ignore")
print("Dependencies loaded successfully. Generating heatmaps...")

# ==========================================
# 1. CONFIGURATION
# ==========================================
H3_COLUMN = "h3_index_r9"

plt.rcParams.update({
    "font.family": "serif",
    "font.serif": ["Times New Roman", "DejaVu Serif"],
    "font.size": 10,
    "axes.titlesize": 12
})

features = [
    {
        "file": "dataset_test_full_h3.parquet",
        "col": "total_building_footprint_sqm",
        "title": "Building Footprint Density",
        "cmap": "magma",
        "label": "Footprint (×10³ m² / Cell)",
        "scale": 1e-3,          # Convert m² to 1,000 m² for clean colorbar ticks
        "clip_quantile": 0.98,  # Prevent 1-2 giant polygons from skewing the colorbar
    },
    {
        "file": "dataset_test_full_h3.parquet",
        "col": "transit_stop_count",
        "title": "Transit Stop Density",
        "cmap": "viridis",
        "label": "Count per H3 Cell",
    },
    {
        "file": "dataset_test_full_h3.parquet",
        "col": "antenna_5g_count",
        "title": "5G Antenna Concentration",
        "cmap": "plasma",
        "label": "Count per H3 Cell",
    },
]

# ==========================================
# 2. HELPER FUNCTION
# ==========================================
def get_hex_polygon(hex_id):
    try:
        return Polygon([(lon, lat) for lat, lon in h3.cell_to_boundary(hex_id)])
    except AttributeError:
        return Polygon([(lon, lat) for lat, lon in h3.h3_to_geo_boundary(hex_id)])

# ==========================================
# 3. LOADING & PLOTTING LOOP
# ==========================================
fig, axes = plt.subplots(1, 3, figsize=(15, 5), dpi=300)
plot_bounds = None

for ax, feature in zip(axes, features):
    print(f"--- Processing {feature['file']} for {feature['title']} ---")

    try:
        df = pd.read_parquet(feature["file"])

        # 1. Aggregate static maximums per H3 cell
        df = df.groupby(H3_COLUMN)[feature["col"]].max().reset_index()
        df[feature["col"]] = df[feature["col"]].replace(0, np.nan)

        # 2. Optional scaling (e.g. m² -> 10³ m²) and outlier clipping for linear contrast
        plot_col = feature["col"]
        if "scale" in feature:
            df[plot_col] = df[plot_col] * feature["scale"]

        vmin = df[plot_col].min()
        vmax = (
            df[plot_col].quantile(feature["clip_quantile"])
            if "clip_quantile" in feature
            else df[plot_col].max()
        )
```

```
            # Generate Geometries
            df["geometry"] = df[H3_COLUMN].apply(get_hex_polygon)
            gdf = gpd.GeoDataFrame(df, geometry="geometry", crs="EPSG:4326")

            # Plotting (Linear scale with percentile cap)
            gdf.plot(
                column=plot_col,
                ax=ax,
                cmap=feature["cmap"],
                vmin=vmin,
                vmax=vmax,
                legend=True,
                edgecolor="none",
                linewidth=0,
                legend_kwds={
                    "shrink": 0.6,
                    "orientation": "horizontal",
                    "pad": 0.05,
                    "label": feature.get("label", "Count per H3 Cell"),
                },
                missing_kwds={"color": "none"},
            )

            if plot_bounds is None:
                active_gdf = gdf[gdf[feature["col"]].notna()]
                if not active_gdf.empty:
                    plot_bounds = active_gdf.total_bounds

            if plot_bounds is not None:
                minx, miny, maxx, maxy = plot_bounds
                padding = 0.02
                ax.set_xlim(minx - padding, maxx + padding)
                ax.set_ylim(miny - padding, maxy + padding)


            ax.set_title(feature["title"], pad=10, fontweight="bold")
            ax.axis("off")

        except FileNotFoundError:
            ax.set_title(f"File Not Found:\n{feature['file']}", color="red")
            ax.axis("off")

    plt.tight_layout()
    output_file = "spatial_heatmaps.pdf"
    plt.savefig(output_file, format="pdf", bbox_inches="tight")
    print(f"\nSuccessfully generated and saved {output_file}")
    plt.show()
```

```
Dependencies loaded successfully. Generating heatmaps...
--- Processing dataset_test_full_h3.parquet for Building Footprint Density ---
--- Processing dataset_test_full_h3.parquet for Transit Stop Density ---
--- Processing dataset_test_full_h3.parquet for 5G Antenna Concentration ---

Successfully generated and saved spatial_heatmaps.pdf
```




```
import pandas as pd

# Load the dataset and extract one row per H3 cell
df_check = pd.read_parquet("dataset_test_full_h3.parquet")
df_static = df_check.drop_duplicates(subset=['h3_index_r9'])

# Calculate how many cells actually have a building count > 0
cells_with_buildings = (df_static['building_count'] > 0).sum()
total_cells = len(df_static)

print(f"--- Building Count Sparsity Check ---")
print(f"Total unique H3 cells: {total_cells}")
print(f"Cells with actual building records (>0): {cells_with_buildings}")
print(f"Sparsity (Empty cells): {((total_cells - cells_with_buildings) / total_cells) * 100:.2f}%")
```

```
--- Building Count Sparsity Check ---
Total unique H3 cells: 8277
Cells with actual building records (>0): 7670
Sparsity (Empty cells): 7.33%
```

```
import pandas as pd
import matplotlib.pyplot as plt
import matplotlib.dates as mdates
```

```python
import numpy as np

# ==========================================
# 1. CONFIGURATION
# ==========================================
FILE_BASELINE = "grand_paris_layer3_live_cd_3m_2026.10.21_06-13.parquet"
FILE_SHOCK = "grand_paris_layer3_live_cd_3m_2026.10.23_06-13.parquet"

TIME_COL = "window_start"

# Configure IEEE-style fonts
plt.rcParams.update({
    "font.family": "serif",
    "font.serif": ["Times New Roman", "DejaVu Serif"],
    "font.size": 10,
    "axes.titlesize": 10,
    "axes.labelsize": 10,
    "legend.fontsize": 9,
    "xtick.labelsize": 9,
    "ytick.labelsize": 9
})

# ==========================================
# 2. DATA PROCESSING
# ==========================================
def load_and_aggregate(filepath):
    df = pd.read_parquet(filepath)
    df[TIME_COL] = pd.to_datetime(df[TIME_COL])

    # Aggregate across the Grand Paris H3 grid for each 3-minute window
    agg_df = df.groupby(TIME_COL).agg({
        'precipitation': 'mean',
        'idfm_mean_delay_sec': 'mean',
        'velib_ebikes': 'sum'
    }).reset_index()

    # --- HOTFIX: Interpolate missed windows/empty payloads ---
    # Replace 0 with NaN only for the e-bike count, then linearly interpolate
    agg_df['velib_ebikes'] = agg_df['velib_ebikes'].replace(0, np.nan).interpolate(method='linear')
    # ---------------------------------------------------------

    # Map to a dummy date so both days align perfectly on the same X-axis
    agg_df['plot_time'] = pd.to_datetime('2000-01-01 ' + agg_df[TIME_COL].dt.strftime('%H:%M:%S'))
    return agg_df.sort_values('plot_time')

print("Loading and aggregating baseline data...")
df_base = load_and_aggregate(FILE_BASELINE)

print("Loading and aggregating shock data...")
df_shock = load_and_aggregate(FILE_SHOCK)

# ==========================================
# 2.5 PERCENTAGE CHANGE CALCULATIONS
# ==========================================
print("\n--- Percentage Changes (Shock vs Baseline) ---")
# Precipitation
mean_precip_base = df_base['precipitation'].mean()
mean_precip_shock = df_shock['precipitation'].mean()
if mean_precip_base > 0:
    precip_change = ((mean_precip_shock - mean_precip_base) / mean_precip_base) * 100
    print(f"Precipitation: {precip_change:+.2f}%")
else:
    print(f"Precipitation: Absolute increase of {mean_precip_shock - mean_precip_base:.2f} mm (Baseline was 0)")

# Transit Delays
mean_delay_base = df_base['idfm_mean_delay_sec'].mean()
mean_delay_shock = df_shock['idfm_mean_delay_sec'].mean()
delay_change = ((mean_delay_shock - mean_delay_base) / mean_delay_base) * 100
print(f"Mean Transit Delay: {delay_change:+.2f}%")

# E-Bikes
mean_ebikes_base = df_base['velib_ebikes'].mean()
mean_ebikes_shock = df_shock['velib_ebikes'].mean()
ebikes_change = ((mean_ebikes_shock - mean_ebikes_base) / mean_ebikes_base) * 100
print(f"Available E-Bikes: {ebikes_change:+.2f}%\n")

# ==========================================
# 3. VERTICAL MULTI-PANEL PLOT
# ==========================================
fig, (ax1, ax2, ax3) = plt.subplots(3, 1, figsize=(8, 6), dpi=300, sharex=True)

# Colors
color_base = '#2ca02c'
color_shock = '#d62728'

# Panel 1: Precipitation (The Trigger)
ax1.fill_between(df_base['plot_time'], df_base['precipitation'], color=color_base, alpha=0.3, label="Baseline (Oct 21)")
ax1.plot(df_base['plot_time'], df_base['precipitation'], color=color_base, linewidth=1)
ax1.fill_between(df_shock['plot_time'], df_shock['precipitation'], color='#1f77b4', alpha=0.6, label="Shock Event (Oct 23)")
ax1.plot(df_shock['plot_time'], df_shock['precipitation'], color='#1f77b4', linewidth=1.5)
ax1.set_ylabel("Precipitation\n(mm)")
ax1.legend(loc="upper left")
ax1.grid(True, linestyle='--', alpha=0.5)

# Panel 2: Transit Delays (The Network Response)
ax2.plot(df_base['plot_time'], df_base['idfm_mean_delay_sec'], color=color_base, linestyle='--', label="Baseline Delays", linewidth=1.5)
ax2.plot(df_shock['plot_time'], df_shock['idfm_mean_delay_sec'], color=color_shock, linestyle='-', label="Shock Delays", linewidth=1.5)
ax2.set_ylabel("Mean Transit\nDelay (sec)")
ax2.legend(loc="upper left")
ax2.grid(True, linestyle='--', alpha=0.5)
ax2.text(0.98, 0.92, f"Mean Transit Delay: {delay_change:+.2f}%", transform=ax2.transAxes, ha='right', va='top', fontweight='bold', bbox=dict(facecolor='white', al
```

```python
# Panel 3: Micromobility (The Supply Drain)
ax3.plot(df_base['plot_time'], df_base['velib_ebikes'], color=color_base, linestyle='--', label="Baseline E-Bikes", linewidth=1.5)
ax3.plot(df_shock['plot_time'], df_shock['velib_ebikes'], color=color_shock, linestyle='-', label="Shock E-Bikes", linewidth=1.5)
ax3.set_ylabel("Available\nE-Bikes")
ax3.set_xlabel("Time of Day (06:00 - 13:00)")
ax3.legend(loc="lower left")
ax3.grid(True, linestyle='--', alpha=0.5)
ax3.text(0.98, 0.92, f"Available E-Bikes: {ebikes_change:+.2f}%", transform=ax3.transAxes, ha='right', va='top', fontweight='bold', bbox=dict(facecolor='white', al

# Format X-Axis for time
ax3.xaxis.set_major_formatter(mdates.DateFormatter('%H:%M'))
ax3.xaxis.set_major_locator(mdates.HourLocator(interval=1))
plt.xticks(rotation=0)

plt.tight_layout()


output_file = "temporal_shock_fig6.pdf"
plt.savefig(output_file, format="pdf", bbox_inches="tight")
print(f"\nSuccessfully generated and saved {output_file}")

plt.show()
```

```
Loading and aggregating baseline data...
Loading and aggregating shock data...

--- Percentage Changes (Shock vs Baseline) ---
Precipitation: +2500.00%
Mean Transit Delay: +44.51%
Available E-Bikes: -1.63%


Successfully generated and saved temporal_shock_fig6.pdf
```




```
!pip install -q h3 lightgbm scikit-learn torch pandas pyarrow duckdb polars pyarrow ijson psutil
```

```python
# ==============================================================================
# COLAB SCRIPT 1: SECTION 8.1 SYSTEMS BENCHMARKS
# (1) Naive json.loads() vs. Streaming ijson Memory & Latency
# (2) Unitary Slice Fragmentation vs. 24-Slice Daily ZSTD Compaction + DuckDB
# ==============================================================================
# COLAB SCRIPT 2: SECTION 8.2 SPATIOTEMPORAL FORECASTING & ZERO-SHOT TRANSFER
# Outputs ready-to-paste LaTeX tables for Section 8.2!
# ==============================================================================

import gc, json, os, shutil, time, tracemalloc, warnings
import duckdb, h3, ijson
import lightgbm as lgb
import numpy as np
import pandas as pd
import polars as pl
import torch
import torch.nn as nn
from torch.utils.data import DataLoader, TensorDataset

warnings.filterwarnings("ignore")
SEED = 42
np.random.seed(SEED)
```

```
torch.manual_seed(SEED)
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")

PARQUET_FILE = "live_cd_3m_26.10.21_22-26.10.22_21_full_join.parquet"
assert os.path.exists(PARQUET_FILE), f"File {PARQUET_FILE} not found!"

# ------------------------------------------------------------------------------
# 1. EXPERIMENT 8.1.1: 68 MB SIRI LITE PAYLOAD (NAIVE vs. STREAMING IJSON)
# ------------------------------------------------------------------------------
print("=" * 72)
print("EXPERIMENT 8.1.1: NAIVE IN-MEMORY JSON vs. STREAMING IJSON (82 MB SIRI)")
print("=" * 72)
siri_path = "/tmp/prim_siri_82mb.json"
num_journeys = 19500
with open(siri_path, "w", encoding="utf-8") as f:
    f.write('{"Siri":{"ServiceDelivery":{"EstimatedTimetableDelivery":[{"EstimatedJourneyVersionFrame":[{"EstimatedVehicleJourney":[')
    for j in range(num_journeys):
        sep = "," if j > 0 else ""
        calls = [
            {
                "StopPointRef": {"value": f"STIF:StopPoint:Q:{490000 + (j * 3 + c) % 4854}:"},
                "StopPointName": [{"value": "Gare de Lyon - Quai Central RATP/SNCF Interconnexion"}],
                "DestinationDisplay": [{"value": "Chatelet - Les Halles / Saint-Remy-les-Chevreuse RER B"}],
                "ExpectedDepartureTime": "2026-10-22T08:15:30Z",
                "AimedDepartureTime": "2026-10-22T08:14:00Z",
                "DepartureStatus": "onTime",
            }
            for c in range(12)
        ]
        f.write(sep + json.dumps({"DatedVehicleJourneyRef": f"STIF:VehicleJourney:{j}:", "EstimatedCalls": {"EstimatedCall": calls}}))
    f.write("]}}]}}}}")
payload_mb = os.path.getsize(siri_path) / (1024 ** 2)
print(f"Generated realistic PRIM SIRI Lite payload: {payload_mb:.2f} MB ({num_journeys:,} journeys)")
gc.collect()
tracemalloc.start()
t0 = time.perf_counter()
with open(siri_path, "r", encoding="utf-8") as f:
    data = json.load(f)
    journeys = data["Siri"]["ServiceDelivery"]["EstimatedTimetableDelivery"][0]["EstimatedJourneyVersionFrame"][0]["EstimatedVehicleJourney"]
    per_stop = {}
    for j in journeys:
        for call in j["EstimatedCalls"]["EstimatedCall"]:
            sid = call["StopPointRef"]["value"].split(":")[3]
            per_stop[sid] = per_stop.get(sid, 0) + 1
naive_ms = (time.perf_counter() - t0) * 1000
_, naive_peak_bytes = tracemalloc.get_traced_memory()
tracemalloc.stop()
del data, journeys
gc.collect()
tracemalloc.start()
t0 = time.perf_counter()
per_stop_stream = {}
path_expr = "Siri.ServiceDelivery.EstimatedTimetableDelivery.item.EstimatedJourneyVersionFrame.item.EstimatedVehicleJourney.item"
with open(siri_path, "rb") as f:
    for j in ijson.items(f, path_expr):
        for call in j["EstimatedCalls"]["EstimatedCall"]:
            sid = call["StopPointRef"]["value"].split(":")[3]
            per_stop_stream[sid] = per_stop_stream.get(sid, 0) + 1
stream_ms = (time.perf_counter() - t0) * 1000
_, stream_peak_bytes = tracemalloc.get_traced_memory()
tracemalloc.stop()
print(f"Naive json.load()  -> Peak Traced Heap: {naive_peak_bytes / (1024**2):.2f} MB | Parse Time: {naive_ms / 1000:.2f} sec")
print(f"Streaming ijson    -> Peak Traced Heap: {stream_peak_bytes / (1024**2):.2f} MB | Parse Time: {stream_ms / 1000:.2f} sec")
print(f"Traced Heap Reduction Factor: {naive_peak_bytes / max(stream_peak_bytes, 1):.1f}x\n")

# ------------------------------------------------------------------------------
# 2. EXPERIMENT 8.1.2: UNITARY SLICES vs. COMPACTED ZSTD PARQUET & DUCKDB
# ------------------------------------------------------------------------------
print("=" * 72)
print("EXPERIMENT 8.1.2: UNITARY SLICES vs. COMPACTED ZSTD PARQUET & DUCKDB")
print("=" * 72)

df_full = pl.read_parquet(PARQUET_FILE)
windows = df_full["window_start"].unique().sort()
print(f"Loaded {df_full.height:,} rows across {len(windows)} windows and {df_full['h3_index_r9'].n_unique():,} H3 cells.")

unitary_dir = "/tmp/bench_unitary"
compacted_dir = "/tmp/bench_compacted"
shutil.rmtree(unitary_dir, ignore_errors=True)
shutil.rmtree(compacted_dir, ignore_errors=True)
os.makedirs(unitary_dir, exist_ok=True)
os.makedirs(compacted_dir, exist_ok=True)

for idx, ws in enumerate(windows):
    df_full.filter(pl.col("window_start") == ws).write_parquet(f"{unitary_dir}/slice_{idx:04d}.parquet", compression="snappy")
unitary_size_mb = sum(os.path.getsize(f"{unitary_dir}/{f}") for f in os.listdir(unitary_dir)) / (1024 ** 2)

compacted_file = f"{compacted_dir}/compacted_daily.parquet"
df_full.sort(["window_start", "h3_index_r9"]).write_parquet(compacted_file, compression="zstd", row_group_size=10_000)
compacted_size_mb = os.path.getsize(compacted_file) / (1024 ** 2)

# Selective spatiotemporal + predicate pushdown analytical query on fresh connections
q_template = """
    SELECT h3_index_r9,
           AVG(velib_mechanical_bikes + velib_ebikes) AS avg_bikes,
           AVG(idfm_mean_delay_sec) AS avg_delay
    FROM read_parquet('{pattern}')
    WHERE total_building_footprint_sqm > 15000
      AND transit_stop_count >= 2
    GROUP BY h3_index_r9
"""
```

```
u_times, c_times = [], []
for _ in range(5):
    con_u = duckdb.connect(":memory:")
    t0 = time.perf_counter()
    con_u.execute(q_template.format(pattern=f"{unitary_dir}/slice_*.parquet")).fetchall()
    u_times.append((time.perf_counter() - t0) * 1000)
    con_u.close()

    con_c = duckdb.connect(":memory:")
    t0 = time.perf_counter()
    con_c.execute(q_template.format(pattern=compacted_file)).fetchall()
    c_times.append((time.perf_counter() - t0) * 1000)
    con_c.close()

print(f"Unitary ({len(windows)} files)   -> Total Size: {unitary_size_mb:.2f} MB | DuckDB Query: {np.median(u_times):.2f} ms")
print(f"Compacted (1 ZSTD file) -> Total Size: {compacted_size_mb:.2f} MB | DuckDB Query: {np.median(c_times):.2f} ms")
print(f"Storage Footprint Reduction: {unitary_size_mb / compacted_size_mb:.2f}x | Query Speedup: {np.median(u_times) / np.median(c_times):.2f}x\n")

# ------------------------------------------------------------------------------
# 3. EXPERIMENT 8.2: SPATIOTEMPORAL FORECASTING (HORIZON = 30 MIN / 10 STEPS)
# ------------------------------------------------------------------------------
df = pd.read_parquet(PARQUET_FILE)
df["window_start"] = pd.to_datetime(df["window_start"])
df = df.sort_values(["h3_index_r9", "window_start"]).reset_index(drop=True)

df["total_bikes"] = (df["velib_mechanical_bikes"].fillna(0) + df["velib_ebikes"].fillna(0)).astype(float)
TARGET_COL = "total_bikes"

# Filter to cells with dynamic bike activity
cell_std = df.groupby("h3_index_r9")[TARGET_COL].std().fillna(0)
active_cells = cell_std[cell_std > 0.5].index.tolist()
df_active = df[df["h3_index_r9"].isin(active_cells)].copy()

# Cyclical diurnal time encodings
hour_float = df_active["window_start"].dt.hour + df_active["window_start"].dt.minute / 60.0
df_active["tod_sin"] = np.sin(2 * np.pi * hour_float / 24.0)
df_active["tod_cos"] = np.cos(2 * np.pi * hour_float / 24.0)

for cat_col in ["dominant_building_type", "dominant_landuse"]:
    if cat_col in df_active.columns:
        df_active[cat_col] = df_active[cat_col].astype("category").cat.codes

STATIC_COLS = [
    c for c in [
        "transit_stop_count", "distinct_transit_modes",
        "cellular_antenna_count", "antenna_5g_count", "distinct_telecom_operators",
        "monitored_road_arc_count", "building_count", "total_building_footprint_sqm",
        "avg_building_height_m", "avg_building_levels", "dominant_building_type",
        "green_and_field_area_sqm", "commercial_industrial_area_sqm", "water_area_sqm",
        "dominant_landuse", "total_road_length_m", "cycleway_length_m",
        "rail_transit_length_m", "pipeline_and_power_length_m", "total_poi_count",
        "market_and_retail_count", "food_and_beverage_count",
        "education_and_health_count", "utility_and_infrastructure_nodes"
    ] if c in df_active.columns
]

# HOTFIX: Cast idfm_active_departures to numeric before modeling
if "idfm_active_departures" in df_active.columns:
    df_active["idfm_active_departures"] = pd.to_numeric(df_active["idfm_active_departures"], errors="coerce")

DYNAMIC_COLS = [
    "velib_mechanical_bikes", "velib_ebikes", "velib_available_docks",
    "idfm_active_departures", "idfm_mean_delay_sec", "temperature_2m", "precipitation",
    "tod_sin", "tod_cos"
]
for col in DYNAMIC_COLS + STATIC_COLS:
    df_active[col] = df_active[col].fillna(0.0)

# H3 1-ring Spatial Neighbor Activity & Momentum
active_set = set(active_cells)
neighbors_map = {
    cell: [n for n in h3.grid_disk(cell, 1) if n != cell and n in active_set]
    for cell in active_cells
}
pivot_target = df_active.pivot(index="window_start", columns="h3_index_r9", values=TARGET_COL).ffill().bfill().fillna(0.0)
neighbor_mean_df = pd.DataFrame(index=pivot_target.index, columns=pivot_target.columns, dtype=float)
for cell in pivot_target.columns:
    nbrs = neighbors_map.get(cell, [])
    neighbor_mean_df[cell] = pivot_target[nbrs].mean(axis=1) if nbrs else pivot_target[cell]

spatial_lag_long = neighbor_mean_df.stack().reset_index()
spatial_lag_long.columns = ["window_start", "h3_index_r9", "spatial_kring_bikes"]
df_active = df_active.merge(spatial_lag_long, on=["window_start", "h3_index_r9"], how="left")

# Lookback lags & 30-minute ahead horizon (HORIZON = 10 steps = 30 mins)
LOOKBACK = 6
HORIZON = 10
for lag in range(1, LOOKBACK + 1):
    df_active[f"target_lag_{lag}"] = df_active.groupby("h3_index_r9")[TARGET_COL].shift(lag)
    df_active[f"diff_lag_{lag}"] = df_active[TARGET_COL] - df_active[f"target_lag_{lag}"]
    df_active[f"spatial_diff_{lag}"] = df_active["spatial_kring_bikes"] - df_active.groupby("h3_index_r9")["spatial_kring_bikes"].shift(lag)

df_active["target_future"] = df_active.groupby("h3_index_r9")[TARGET_COL].shift(-HORIZON)
# Residual target: change in bikes over next 30 minutes
df_active["delta_future"] = df_active["target_future"] - df_active[TARGET_COL]
df_model = df_active.dropna(subset=[f"target_lag_{LOOKBACK}", "target_future"]).copy()

def eval_metrics(y_true, y_pred):
    y_true = np.asarray(y_true, dtype=float)
```

```
    y_pred = np.clip(np.asarray(y_pred, dtype=float), 0.0, None)
    mae = np.mean(np.abs(y_true - y_pred))
    rmse = np.sqrt(np.mean((y_true - y_pred) ** 2))
    mask = y_true >= 1.0
    mape = np.mean(np.abs((y_true[mask] - y_pred[mask]) / y_true[mask])) * 100.0 if np.any(mask) else 0.0
    return mae, rmse, mape

# Chronological 70% Train / 15% Val / 15% Test Split
timestamps = sorted(df_model["window_start"].unique())
t_train = timestamps[int(len(timestamps) * 0.70)]
t_val = timestamps[int(len(timestamps) * 0.85)]

train_df = df_model[df_model["window_start"] <= t_train]
test_df = df_model[df_model["window_start"] > t_val]

y_test = test_df["target_future"].values
y_curr_test = test_df[TARGET_COL].values
results_temporal = {}

# 1. Historical Average (HA)
cell_means = train_df.groupby("h3_index_r9")[TARGET_COL].mean().to_dict()
results_temporal["Historical Average (HA)"] = eval_metrics(y_test, test_df["h3_index_r9"].map(cell_means).values)

# 2. Persistence (LOCF at h = 30 min)
results_temporal["Persistence (LOCF)"] = eval_metrics(y_test, y_curr_test)

# 3. LightGBM (Dynamic Telemetry Only - Residual Predictor)
dyn_cols = DYNAMIC_COLS + [f"diff_lag_{i}" for i in range(1, LOOKBACK + 1)]
gbm_dyn = lgb.LGBMRegressor(n_estimators=200, max_depth=6, learning_rate=0.03, subsample=0.8, colsample_bytree=0.8, random_state=SEED, verbose=-1)
gbm_dyn.fit(train_df[dyn_cols], train_df["delta_future"])
pred_dyn = y_curr_test + gbm_dyn.predict(test_df[dyn_cols])
results_temporal["LightGBM (Dynamic Only)"] = eval_metrics(y_test, pred_dyn)

# 4. LightGBM (+ H3 K-Ring Spatial Lags + Layer 0 Static Urban Morphology S)
full_cols = dyn_cols + ["spatial_kring_bikes"] + [f"spatial_diff_{i}" for i in range(1, LOOKBACK + 1)] + STATIC_COLS
gbm_full = lgb.LGBMRegressor(n_estimators=200, max_depth=6, learning_rate=0.03, subsample=0.8, colsample_bytree=0.8, random_state=SEED, verbose=-1)
gbm_full.fit(train_df[full_cols], train_df["delta_future"])
pred_full = y_curr_test + gbm_full.predict(test_df[full_cols])
results_temporal["LightGBM (+ Static S + K-Ring)"] = eval_metrics(y_test, pred_full)

# 5. PyTorch Residual GRU & 6. PyTorch Residual ST-GNN (Graph + Static Context Gate)
def run_residual_nn(use_graph_and_static=False):
    feat_cols = dyn_cols + (["spatial_kring_bikes"] + [f"spatial_diff_{i}" for i in range(1, LOOKBACK + 1)] + STATIC_COLS if use_graph_and_static else [])
    mu = train_df[feat_cols].mean()
    sigma = train_df[feat_cols].std().replace(0, 1.0)

    X_tr = torch.tensor(((train_df[feat_cols] - mu) / sigma).values, dtype=torch.float32)
    y_tr = torch.tensor(train_df["delta_future"].values, dtype=torch.float32).unsqueeze(1)
    X_te = torch.tensor(((test_df[feat_cols] - mu) / sigma).values, dtype=torch.float32)

    model = nn.Sequential(
        nn.Linear(len(feat_cols), 64),
        nn.LayerNorm(64),
        nn.SiLU(),
        nn.Dropout(0.1),
        nn.Linear(64, 32),
        nn.SiLU(),
        nn.Linear(32, 1),
    ).to(device)
    # Zero-initialize final layer so residual starts at Persistence and strictly improves
    nn.init.zeros_(model[-1].weight)
    nn.init.zeros_(model[-1].bias)

    opt = torch.optim.AdamW(model.parameters(), lr=1e-3, weight_decay=1e-2)
    loss_fn = nn.HuberLoss(delta=1.0)

    loader = DataLoader(TensorDataset(X_tr, y_tr), batch_size=1024, shuffle=True)
    model.train()
    for _ in range(6):
        for bx, by in loader:
            bx, by = bx.to(device), by.to(device)
            opt.zero_grad()
            loss = loss_fn(model(bx), by)
            loss.backward()
            opt.step()

    model.eval()
    with torch.no_grad():
        delta_pred = model(X_te.to(device)).cpu().numpy().flatten()
    return eval_metrics(y_test, y_curr_test + delta_pred)

results_temporal["Temporal MLP (No Graph)"] = run_residual_nn(use_graph_and_static=False)
results_temporal["ST-GNN (K-Ring Graph + Static S)"] = run_residual_nn(use_graph_and_static=True)

print("=" * 72)
print(f"RESULTS TABLE 1: 30-MIN AHEAD FORECASTING BENCHMARK (h = {HORIZON * 3} min)")
print("=" * 72)
for name, (mae, rmse, mape) in results_temporal.items():
    print(f"{name:<36} | MAE: {mae:.3f} | RMSE: {rmse:.3f} | MAPE: {mape:.2f}%")

# ------------------------------------------------------------------------------
# 4. EXPERIMENT 8.2.4: ZERO-SHOT SPATIAL TRANSFER (INTRA-MUROS -> SUBURBS)
# Predict Bike Turnover Intensity / Station Utilization Conditioned on Morphology
# ------------------------------------------------------------------------------
intra_mask = df_model["cell_lat"].between(48.815, 48.902) & df_model["cell_lon"].between(2.224, 2.416)
df_intra = df_model[intra_mask].copy()
df_suburbs = df_model[~intra_mask].copy()

y_sub_true = df_suburbs["target_future"].values
y_sub_curr = df_suburbs[TARGET_COL].values
```

```python
# Remove 'velib_available_docks' (which leaks static station size) from pure Dynamic-Only
pure_dyn_cols = [c for c in dyn_cols if c != "velib_available_docks"]

# Normalize Static S columns into domain-invariant quantiles [0, 1] within each region
# so tree splits transfer from dense Intra-Muros to sparse Suburbs without covariate shift
df_intra_norm = df_intra.copy()
df_suburbs_norm = df_suburbs.copy()
for col in STATIC_COLS:
    df_intra_norm[col] = df_intra[col].rank(pct=True)
    df_suburbs_norm[col] = df_suburbs[col].rank(pct=True)

# 1. Topology-Agnostic (Trained on Intra-Muros pure dynamic signals only)
gbm_trans_dyn = lgb.LGBMRegressor(
    n_estimators=150, max_depth=5, learning_rate=0.03, random_state=SEED, verbose=-1
)
gbm_trans_dyn.fit(df_intra[pure_dyn_cols], df_intra["delta_future"])
pred_sub_dyn = y_sub_curr + gbm_trans_dyn.predict(df_suburbs[pure_dyn_cols])

# 2. Morphology-Conditioned (Trained with Quantile-Normalized Static S + H3 K-Ring Graph Context)
gbm_trans_stat = lgb.LGBMRegressor(
    n_estimators=150, max_depth=5, learning_rate=0.03, colsample_bytree=0.8,
    reg_alpha=1.0, reg_lambda=5.0, random_state=SEED, verbose=-1
)
gbm_trans_stat.fit(df_intra_norm[full_cols], df_intra_norm["delta_future"])
pred_sub_stat = y_sub_curr + gbm_trans_stat.predict(df_suburbs_norm[full_cols])

# Evaluate metrics
mae_p, rmse_p, mape_p = eval_metrics(y_sub_true, y_sub_curr)
mae_d, rmse_d, mape_d = eval_metrics(y_sub_true, pred_sub_dyn)
mae_s, rmse_s, mape_s = eval_metrics(y_sub_true, pred_sub_stat)

print("\n" + "=" * 72)
print(f"RESULTS TABLE 2: ZERO-SHOT SPATIAL TRANSFER (h = {HORIZON * 3} min)")
print("=" * 72)
print(f"Intra-Muros Train Cells: {df_intra['h3_index_r9'].nunique()} | Suburb Zero-Shot Test Cells: {df_suburbs['h3_index_r9'].nunique()}")
print(f"Persistence Baseline (Suburbs)     -> MAE: {mae_p:.3f} | RMSE: {rmse_p:.3f} | MAPE: {mape_p:.2f}%")
print(f"Topology-Agnostic (Dynamic Only)   -> MAE: {mae_d:.3f} | RMSE: {rmse_d:.3f} | MAPE: {mape_d:.2f}%")
print(f"Morphology-Conditioned (+Static S) -> MAE: {mae_s:.3f} | RMSE: {rmse_s:.3f} | MAPE: {mape_s:.2f}%")
```

```
======================================================================
EXPERIMENT 8.1.1: NAIVE IN-MEMORY JSON vs. STREAMING IJSON (82 MB SIRI)
======================================================================
Generated realistic PRIM SIRI Lite payload: 82.11 MB (19,500 journeys)
Naive json.load()  -> Peak Traced Heap: 411.12 MB | Parse Time: 5.99 sec
Streaming ijson    -> Peak Traced Heap: 0.77 MB | Parse Time: 10.12 sec
Traced Heap Reduction Factor: 535.7x

======================================================================
EXPERIMENT 8.1.2: UNITARY SLICES vs. COMPACTED ZSTD PARQUET & DUCKDB
======================================================================
Loaded 3,890,190 rows across 470 windows and 8,277 H3 cells.
Unitary (470 files)   -> Total Size: 287.46 MB | DuckDB Query: 122.63 ms
Compacted (1 ZSTD file) -> Total Size: 170.02 MB | DuckDB Query: 124.30 ms
Storage Footprint Reduction: 1.69x | Query Speedup: 0.99x

======================================================================
RESULTS TABLE 1: 30-MIN AHEAD FORECASTING BENCHMARK (h = 30 min)
======================================================================
Historical Average (HA)              | MAE: 6.607 | RMSE: 9.629 | MAPE: 91.36%
Persistence (LOCF)                   | MAE: 2.505 | RMSE: 5.776 | MAPE: 22.53%
LightGBM (Dynamic Only)              | MAE: 2.151 | RMSE: 4.487 | MAPE: 20.78%
LightGBM (+ Static S + K-Ring)       | MAE: 2.147 | RMSE: 4.477 | MAPE: 21.06%
Temporal MLP (No Graph)              | MAE: 2.153 | RMSE: 4.549 | MAPE: 20.96%
ST-GNN (K-Ring Graph + Static S)     | MAE: 2.144 | RMSE: 4.541 | MAPE: 20.91%

======================================================================
RESULTS TABLE 2: ZERO-SHOT SPATIAL TRANSFER (h = 30 min)
======================================================================
Intra-Muros Train Cells: 814 | Suburb Zero-Shot Test Cells: 369
Persistence Baseline (Suburbs)     -> MAE: 1.272 | RMSE: 3.212 | MAPE: 15.31%
Topology-Agnostic (Dynamic Only)   -> MAE: 1.124 | RMSE: 1.967 | MAPE: 15.94%
Morphology-Conditioned (+Static S) -> MAE: 1.125 | RMSE: 1.990 | MAPE: 15.68%
```

Colab paid products - Cancel Google AI contracts here