

RAP UI Annotations:

```
@AbapCatalog.viewEnhancementCategory: [#NONE]
@AccessControl.authorizationCheck: #NOT_REQUIRED
@EndUserText.label: 'Connection View CDS Data Model'
@Metadata.ignorePropagatedAnnotations: true
@ObjectModel.usageType:{
    serviceQuality: #X,
    sizeCategory: #S,
    dataClass: #MIXED
}

@UI.headerInfo: {
    typeName: 'Connection',
    typeNamePlural: 'Connections'
}

@Search.searchable: true //It will aid one search field on top of our list.
define view entity ZI_Connection_Saikat
    as select from /dmo/connection as Connection
    association [1..*] to ZI_Flight_Saikat_R as _Flight on
    $projection.CarrierId = _Flight.CarrierId
                                and
    $projection.ConnectionId = _Flight.ConnectionId
    association [1] to ZI_Carrier_Saikat_R as _Airline on
    $projection.CarrierId = _Airline.CarrierId
{
    @UI.facet: [{id: 'Connection',
        purpose: #STANDARD,
        type: #IDENTIFICATION_REFERENCE,
        position: 10,
        label: 'Connection Details'},

        //Facet for the Flight details from ZI_Flight_Saikat_R and as we are
displaying multiple flight lines so #LINEITEM_REFERENCE
        {id: 'Flight',
        purpose: #STANDARD,
        type: #LINEITEM_REFERENCE,
        position: 20,
        label: 'Flights',
        targetElement: '_Flight'}]

    @UI.lineItem: [{ position: 10, label: 'Airline' }]
    @UI.identification: [{position: 10, label: 'Airline' }]
    @ObjectModel.text.association: '_Airline' //From this Association we will
display the text
    @Search.defaultSearchElement: true // Default search element
    key carrier_id as CarrierId,

    @UI.lineItem: [{ position: 20 }]
    @UI.identification: [{position: 20 }]
    @Search.defaultSearchElement: true
    key connection_id as ConnectionId,

    @UI.selectionField: [{position: 10 }]
    @UI.lineItem: [{ position: 30, label: 'Departure Airport ID' }]
    @UI.identification: [{position: 30, label: 'Departure Airport ID' }]
    @Search.defaultSearchElement: true
    @Consumption.valueHelpDefinition: [{ //Value Help
        entity: {
            name: 'ZI_Airport_Saikat_VH',
            element: 'AirportId' }
        }]
    @EndUserText.label: 'Departure Airport ID'
    airport_from_id as AirportFromId,
```

```

level @EndUserText.label: 'Destination Airport ID' //make changes in the ABAP
@UI.selectionField: [{position: 20 }]
@UI.lineItem: [{ position: 40 }]
@UI.identification: [{position: 40 }]
@Search.defaultSearchElement: true
@Consumption.valueHelpDefinition: [{ //Value Help
entity: {
    name: 'ZI_Airport_Saikat_VH',
    element: 'AirportId' }
}]
airport_to_id as AirportToId,

@UI.lineItem: [{ position: 50,label: 'Departure Time' }]
@UI.identification: [{position: 50 }]
departure_time as DepartureTime,

@UI.lineItem: [{ position: 60,label: 'Arrival Time' }]
@UI.identification: [{position: 60 }]
arrival_time as ArrivalTime,

@Semantics.quantity.unitOfMeasure: 'DistanceUnit'
@UI.identification: [{position: 70 }]
distance as Distance,
distance_unit as DistanceUnit,
//Association
@Search.defaultSearchElement: true
_Flight,
@Search.defaultSearchElement: true //The Association is also Searchable
_Airline

}

```

Carrier Details

```

@AbapCatalog.viewEnhancementCategory: [#NONE]
@AccessControl.authorizationCheck: #NOT_REQUIRED
@EndUserText.label: 'Carrier Details'
@Metadata.ignorePropagatedAnnotations: true
@ObjectModel.usageType:{
    serviceQuality: #X,
    sizeCategory: #S,
    dataClass: #MIXED
}
@Search.searchable: true
define view entity ZI_Carrier_Saikat_R
as select from /dmo/carrier
{
    key carrier_id as CarrierId,

    @Semantics.text: true //The particular field is acting as the text field
for any ID.
    @Search.defaultSearchElement: true
    @Search.fuzzinessThreshold: 0.8 //It will display if some part of search
element matches
    name as Name,
    currency_code as CurrencyCode

```

Flight Information

```
@AbapCatalog.viewEnhancementCategory: [#NONE]
@AccessControl.authorizationCheck: #NOT_REQUIRED
@EndUserText.label: 'Flight Information'
@Metadata.ignorePropagatedAnnotations: true
@ObjectModel.usageType:{
    serviceQuality: #X,
    sizeCategory: #S,
    dataClass: #MIXED
}
@Search.searchable: true
define view entity ZI_Flight_Saikat_R
    as select from /dmo/flight
    association [1] to ZI_Carrier_Saikat_R as _Airline on $projection.CarrierId =
    _Airline.CarrierId
{
    @UI.lineItem: [{ position: 10 }]
    @ObjectModel.text.association: '_Airline'
    key carrier_id      as CarrierId,
    @UI.lineItem: [{ position: 20 }]
    key connection_id  as ConnectionId,
    @UI.lineItem: [{ position: 30 }]
    key flight_date     as FlightDate,
    @UI.lineItem: [{ position: 40 }]
    @Semantics.amount: {currencyCode: 'CurrencyCode'}

    price              as Price,
    @UI.lineItem: [{ position: 50 }]
    currency_code      as CurrencyCode,
    @UI.lineItem: [{ position: 60 }]
    @Search.defaultSearchElement: true
    plane_type_id      as PlaneTypeId,
    @UI.lineItem: [{ position: 70 }]
    seats_max          as SeatsMax,
    @UI.lineItem: [{ position: 80 }]
    seats_occupied     as SeatsOccupied,
    _Airline
}
```

Value Help for Airport

```
@AbapCatalog.viewEnhancementCategory: [#NONE]
@AccessControl.authorizationCheck: #NOT_REQUIRED
@EndUserText.label: 'Value Help for Airport'
@Metadata.ignorePropagatedAnnotations: true
@ObjectModel.usageType:{
    serviceQuality: #X,
    sizeCategory: #S,
    dataClass: #MIXED
}
@Search.searchable: true
define view entity ZI_Airport_Saikat_VH
    as select from /dmo/airport
{
    @Search.defaultSearchElement: true
    key airport_id as AirportId,
    @Search.defaultSearchElement: true
    @Search.fuzzinessThreshold: 0.7
    name          as Name,
    @Search.defaultSearchElement: true
    @Search.fuzzinessThreshold: 0.7
    city          as City,
    @Search.defaultSearchElement: true
    @Search.fuzzinessThreshold: 0.7
    country       as Country
}
```